








11A-Ant1-5240-PASS




11A-Ant1-5745-PASS









8.3 MAXIMUM PEAK POWER DENSITY

8.3.1 Applicable Standard

According to FCC Part 15.407(a)(1) for UNII Band I
According to FCC Part 15.407(a)(2) for UNII Band II-A and UNII Band II-C
According to FCC Part 15.407(a)(3) for UNII Band III
According to 789033 D02 Section II(F)
According to RSS-247

8.3.2 Conformance Limit

FCC Limit:

■ For the band 5.15-5.25 GHz,

(a)(1) (i) For an outdoor access point, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(a) (1) (ii) For an indoor access point, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(a) (1) (iii) For fixed point-to-point access points, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(a) (1) (iv) For client devices, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

■ For the 5.25-5.35 GHz and 5.47-5.725 GHz bands

(b) (2) The maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

■ For the band 5.725-5.85 GHz

(a) (3) The maximum power spectral density shall not exceed 30 dBm in any 500-kHz band provided the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

IC Limit:

- Frequency band 5150-5250 MHz
The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.
- Frequency band 5250-5350 MHz
The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.
- Frequency bands 5470-5600 MHz and 5650-5725 MHz
The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.
- Frequency band 5725-5850 MHz

The output power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications and multiple collocated transmitters transmitting the same information.

8.3.3 Test Configuration

Test according to clause 6.1 radio frequency test setup

8.3.4 Test Procedure

Methods refer to FCC KDB 789033

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:

- a) Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $VBW \geq 3 RBW$.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/RBW)$ to the measured result, whereas $RBW (< 500 \text{ KHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/RBW)$ to the measured result, whereas $RBW (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 KHz for the sections 5.c) and 5.d) above, since $RBW=100 \text{ KHz}$ is available on nearly all spectrum analyzers.



8.3.5 Test Results


Temperature:	25.8°C
Relative Humidity:	49%
ATM Pressure:	1011 mbar

Note: N/A

TestMode	Antenna	Frequency[MHz]	Result [dBm/MHz]	Limit[dBm/MHz]	Verdict
11A	Ant1	5180	2.33	≤11.00	PASS
11A	Ant1	5200	2.27	≤11.00	PASS
11A	Ant1	5240	2.33	≤11.00	PASS
11A	Ant1	5745	1.41	≤30.00	PASS
11A	Ant1	5785	2.76	≤30.00	PASS
11A	Ant1	5825	2.32	≤30.00	PASS
11N20SISO	Ant1	5180	2.63	≤11.00	PASS
11N20SISO	Ant1	5200	2.77	≤11.00	PASS
11N20SISO	Ant1	5240	1.81	≤11.00	PASS
11N20SISO	Ant1	5745	2.69	≤30.00	PASS
11N20SISO	Ant1	5785	2.17	≤30.00	PASS
11N20SISO	Ant1	5825	2.35	≤30.00	PASS

Note: 1.The Result and Limit Unit is dBm/500 kHz in the band 5.725–5.85 GHz.
2.The Duty Cycle Factor and RBW Factor is compensated in the graph.








11A-Ant1-5240-PASS




11A-Ant1-5745-PASS







11N20SISO-Ant1-5180-PASS




11N20SISO-Ant1-5200-PASS




11N20SISO-Ant1-5240-PASS



11N20SISO-Ant1-5745-PASS



11N20SISO-Ant1-5785-PASS



11N20SISO-Ant1-5825-PASS

8.4 UNDESIRABLE RADIATED SPURIOUS EMISSION

8.4.1 Applicable Standard

According to FCC Part 15.407 (b), 15.209, 15.205

According to 789033 D02 SectionII(G)

According to RSS-GEN

8.4.2 Conformance Limit

For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.

Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	24000/F(KHz)	20 log (uV/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

The provisions of §15.205 apply to intentional radiators operating under this section, 15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

Remark: 1. Emission level in dBuV/m=20 log (uV/m)

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

8.4.3 Test Configuration

Test according to clause 6.2 radio frequency test setup

8.4.4 Test Procedure

■ Unwanted Emissions Measurements below 1000 MHz

Compliance shall be demonstrated using CISPR quasi-peak detection; however, peak detection is permitted as an alternative to quasi-peak detection.

The EUT was placed on a turn table which is 0.8m above ground plane.

And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

Repeat above procedures until all frequency measured was complete.

We use software control the EUT, Let EUT hopping on and transmit with highest power, All the modes have been tested and the worst result was reported.

Use the following spectrum analyzer settings:

SetRBW=120kHz for $f < 1$ GHz(30MHz to 1GHz), 200Hz for $f < 150$ KHz(9KHz to 150KHz), 9KHz for < 30 MHz(150KHz to 30KHz).

Set the VBW > RBW.

Detector = Peak.

Trace mode = max hold.

Follow the guidelines in ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Repeat above procedures until all frequency measured was complete.

■ Unwanted Maximumpeak Emissions Measurements above 1000 MHz

Maximum emission levels are measured by setting the analyzer as follows:

RBW = 1 MHz.

VBW $\geq$ 3 MHz.

Detector = Peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweeps to continue until the trace stabilizes. Note that if the transmission is not continuous, the time required for the trace to stabilize will increase by a factor of approximately $1/x$, where x is the duty cycle. For example, at 50 percent duty cycle, the measurement time will increase by a factor of two relative to measurement time for continuous transmission.

■ Unwanted Average Emissions Measurements above 1000 MHz

Method VB (Averaging using reduced video bandwidth): Alternative method.

RBW = 1 MHz.

Video bandwidth. • If the EUT is configured to transmit with duty cycle ≥ 98 percent, set $VBW \leq RBW/100$ (i.e., 10 kHz) but not less than 10 Hz.

• If the EUT duty cycle is < 98 percent, set $VBW \geq 1/T$, where T is defined in section II.B.1.a).

Video bandwidth mode or display mode • The instrument shall be set to ensure that video filtering is applied in the power domain. Typically, this requires setting the detector mode to RMS and setting the Average-VBW Type to Power (RMS).

• As an alternative, the analyzer may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some analyzers require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode.

Detector = Peak.

Sweep time = auto.

Trace mode = max hold.

Allow max hold to run for at least 50 traces if the transmitted signal is continuous or has at least 98 percent duty cycle. For lower duty cycles, increase the minimum number of traces by a factor of 1/x, where x is the duty cycle. For example, use at least 200 traces if the duty cycle is 25 percent. (If a specific emission is demonstrated to be continuous—i.e., 100 percent duty cycle—rather than turning on and off with the transmit cycle, at least 50 traces shall be averaged.)

■ Band edge measurements.

Unwanted band-edge emissions may be measured using either of the special band-edge measurement techniques (the marker-delta or integration methods) described below. Note that the marker-delta method is primarily a radiated measurement technique that requires the 99% occupied bandwidth edge to be within 2 MHz of the authorized band edge, whereas the integration method can be used in either a radiated or conducted measurement without any special requirement with regards to the displacement of the unwanted emission(s) relative to the authorized bandwidth.

Marker-Delta Method.

The marker-delta method, as described in ANSI C63.10, can be used to perform measurements of the radiated unwanted emissions level of emissions provided that the 99% occupied bandwidth of the fundamental is within 2 MHz of the authorized band-edge.

8.4.5 Test Results

Temperature:	25° C
Relative Humidity:	60%
ATM Pressure:	1011 mbar

■ Spurious Emission below 30MHz(9KHz to 30MHz)

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40 \log(\text{Specific distance} / \text{test distance})$ (dB);

Limit line = Specific limits(dBuV) + distance extrapolation factor

■ For Undesirable radiatedSpurious Emission in U-NII - 1

●Undesirable radiated Spurious Emission Above 1GHz(1GHz to 40GHz)

All the antenna(Antenna 1) and modes(802.11a/n) has been tested and the worst(Antenna 1,802.11a) result recorded was report as below:

no any obvious emission were detected from 18 GHz to 40 GHz, so below finaltest was performed with frequency range from 1GHz to 18 GHz.

Test mode:		802.11a		Frequency:	Channel 36: 5180MHz
Freq. (MHz)	Ant.Pol.	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Over(dB)
5817.2834	V	50.32	-44.91	-27	17.91
10658.5682	V	58.57	-36.66	-27	9.66
17994.9997	V	66.78	-28.45	-27	1.45
5906.2886	H	50.40	-44.83	-27	17.83
10650.5677	H	59.33	-35.9	-27	8.9
17607.9769	H	66.06	-29.17	-27	2.17

Test mode:		802.11a		Frequency:	Channel 40: 5200MHz
Freq. (MHz)	Ant.Pol.	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Over(dB)
5810.283	V	49.70	-45.53	-27	18.53
10700.5706	V	57.98	-37.25	-27	10.25
17994.9997	V	66.10	-29.13	-27	2.13
5740.2788	H	49.63	-45.6	-27	18.6
10002.5296	H	58.44	-36.79	-27	9.79
17979.9988	H	65.21	-30.02	-27	3.02


Test mode:		802.11a		Frequency:	Channel 48: 5240MHz
Freq. (MHz)	Ant.Pol.	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Over(dB)
5808.2828	V	49.45	-45.78	-27	18.78
10173.5396	V	58.65	-36.58	-27	9.58
17978.9988	V	65.45	-29.78	-27	2.78
5930.29	H	50.04	-45.19	-27	18.19
10671.5689	H	58.14	-37.09	-27	10.09
17992.9996	H	65.38	-29.85	-27	2.85

Note: (1) All Readings are Peak Value (VBW=3MHz) and Average Value(VBW=10Hz).
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 (3)EIRP[dBm] = E[dBμV/m] + 20 log(d[meters]) - 104.77
 d is the measurement distance in 3 meters

Test mode: 802.11a

Frequency:

Channel 36: 5180MHz




Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5817.2834	50.32	-6.54	74.00	23.68	PK	Vertical
2	10658.5682	58.57	4.22	74.00	15.43	PK	Vertical
3	17994.9997	66.78	11.07	74.00	7.22	PK	Vertical

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	5817.2834	36.07	54.00	17.93	AV	Vertical
2	10658.5682	43.00	54.00	11.00	AV	Vertical
3	17994.9997	46.69	54.00	7.31	AV	Vertical



Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5906.2886	50.40	-6.56	74.00	23.60	PK	Horizontal
2	10650.5677	59.33	4.00	74.00	14.67	PK	Horizontal
3	17607.9769	66.06	11.04	74.00	7.94	PK	Horizontal


AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	5906.2886	36.22	54.00	17.78	AV	Horizontal
2	10650.5677	42.98	54.00	11.02	AV	Horizontal
3	17607.9769	46.68	54.00	7.32	AV	Horizontal

Test mode: 802.11a

Frequency:

Channel 40: 5200MHz




Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5810.283	49.70	-6.54	74.00	24.30	PK	Vertical
2	10700.5706	57.98	5.36	74.00	16.02	PK	Vertical
3	17994.9997	66.10	11.07	74.00	7.90	PK	Vertical

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	5810.283	36.42	54.00	17.58	AV	Vertical
2	10700.5706	43.83	54.00	10.17	AV	Vertical
3	17994.9997	46.75	54.00	7.25	AV	Vertical



Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5740.2788	49.63	-6.87	74.00	24.37	PK	Horizontal
2	10002.5296	58.44	2.29	74.00	15.56	PK	Horizontal
3	17979.9988	65.21	10.62	74.00	8.79	PK	Horizontal


AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	5740.2788	35.29	54.00	18.71	AV	Horizontal
2	10002.5296	40.98	54.00	13.02	AV	Horizontal
3	17979.9988	45.93	54.00	8.07	AV	Horizontal

Test mode: 802.11a

Frequency:

Channel 48: 5240MHz




Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5808.2828	49.45	-6.54	74.00	24.55	PK	Vertical
2	10173.5396	58.65	2.45	74.00	15.35	PK	Vertical
3	17978.9988	65.45	10.59	74.00	8.55	PK	Vertical

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	5808.2828	36.20	54.00	17.80	AV	Vertical
2	10173.5396	40.69	54.00	13.31	AV	Vertical
3	17978.9988	45.92	54.00	8.08	AV	Vertical



Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5930.29	50.04	-6.46	74.00	23.96	PK	Horizontal
2	10671.5689	58.14	4.58	74.00	15.86	PK	Horizontal
3	17992.9996	65.38	11.01	74.00	8.62	PK	Horizontal

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	5930.29	35.67	54.00	18.33	AV	Horizontal
2	10671.5689	43.22	54.00	10.78	AV	Horizontal
3	17992.9996	46.24	54.00	7.76	AV	Horizontal

●Undesirable radiated Undesirable radiatedSpurious Emission in Band Edge

All the antenna(Antenna 1) and modes(802.11a/n) has been tested and the worst(Antenna 1,802.11a) result recorded was report as below:

Test mode: 802.11a		Frequency: Channel 36: 5180MHz			
Freq. (MHz)	Ant.Pol.	Field Strength (RBW=100KHz) (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Verdict
5049.575	H	54.47	-40.76	-27	Pass
5147.6438	V	54.33	-40.9	-27	Pass


Test mode: 802.11a		Frequency: Channel 48: 5240MHz			
Freq. (MHz)	Ant.Pol.	Field Strength (RBW=100KHz) (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Verdict
5353.1763	H	53.69	-41.54	-27	Pass
5352.4612	V	53.60	-41.63	-27	Pass

Note:

- (1) All Readings are Peak Value (VBW=3MHz) and Average Value(VBW=10Hz).
- (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
- (3)EIRP[dBm] = E[dBμV/m] + 20 log(d[meters]) - 104.77

d is the measurement distance in 3 meters


U-NII - 1				
Test Model	Undesirable radiated	Undesirable radiated	Spurious Emission in Band Edge	
	802.11a	Channel 36: 5180MHz	Ant.Pol	H



Suspected Data List							
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5049.575	54.47	37.78	74.00	19.53	PK	Horizontal

AV Final Data List						
NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	5049.575	43.89	54.00	10.11	AV	Horizontal

Test Model U-NII - 1
Undesirable radiated Undesirable radiatedSpurious Emission in Band Edge
802.11a Channel 36: 5180MHz Ant.Pol V




Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5147.6438	54.33	37.78	74.00	19.67	PK	Vertical

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	5147.6438	43.99	54.00	10.01	AV	Vertical


U-NII - 1				
Test Model	Undesirable radiated	Undesirable radiated	Spurious Emission in Band Edge	
	802.11a	Channel 48: 5240MHz	Ant.Pol	H



Suspected Data List							
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5353.1763	53.69	37.99	74.00	20.31	PK	Horizontal

AV Final Data List						
NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	5353.1763	44.51	54.00	9.49	AV	Horizontal

U-NII - 1				
Test Model	Undesirable radiated	Undesirable radiated	Spurious Emission in Band Edge	
	802.11a	Channel 48: 5240MHz	Ant.Pol	V



Suspected Data List							
NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5352.4612	53.60	37.98	74.00	20.40	PK	Vertical

AV Final Data List						
NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	5352.4612	44.21	54.00	9.79	AV	Vertical

■ For Undesirable radiated Spurious Emission in U-NII -3

● Undesirable radiated Spurious Emission Above 1GHz(1GHz to 40GHz)

All the antenna(Antenna 1) and modes(802.11a/n) has been tested and the worst(Antenna 1,802.11a) result recorded was report as below:

no any obvious emission were detected from 18 GHz to 40 GHz, so below finaltest was performed with frequency range from 1GHz to 18 GHz.

Test mode: 802.11a Frequency: Channel 149: 5745MHz

Freq. (MHz)	Ant.Pol.	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Over(dB)
.2771	V	50.07	-45.16	-27	18.16
10000.5294	V	57.64	-37.59	-27	10.59
17997.9999	V	65.47	-29.76	-27	2.76
5804.2826	H	50.46	-44.77	-27	17.77
10557.5622	H	58.01	-37.22	-27	10.22
17608.977	H	65.16	-30.07	-27	3.07

Test mode: 802.11a Frequency: Channel 157: 5785MHz

Freq. (MHz)	Ant.Pol.	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Over(dB)
5648.2734	V	50.07	-45.16	-27	18.16
10048.5323	V	58.11	-37.12	-27	10.12
17988.9994	V	65.38	-29.85	-27	2.85
5809.2829	H	49.45	-45.78	-27	18.78
10056.5327	H	57.99	-37.24	-27	10.24
17980.9989	H	64.86	-30.37	-27	3.37

Test mode: 802.11a Frequency: Channel 165: 5825MHz


Freq. (MHz)	Ant.Pol.	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Over(dB)
5896.288	V	50.61	-44.62	-27	17.62
10648.5676	V	57.94	-37.29	-27	10.29
17929.9959	V	65.33	-29.9	-27	2.9
5771.2807	H	50.02	-45.21	-27	18.21
10187.5404	H	59.28	-35.95	-27	8.95
17992.9996	H	65.12	-30.11	-27	3.11

Note: (1) All Readings are Peak Value (VBW=3MHz) and Average Value(VBW=10Hz).
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 (3)EIRP[dBm] = E[dBuV/m] + 20 log(d[meters]) - 104.77
 d is the measurement distance in 3 meters

Test mode: 802.11a

Frequency:

Channel 149: 5745MHz




Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	.2771	50.07	-7.03	74.00	23.93	PK	Vertical
2	10000.5294	57.64	2.28	74.00	16.36	PK	Vertical
3	17997.9999	65.47	11.16	74.00	8.53	PK	Vertical

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	5710.2771	35.64	54.00	18.36	AV	Vertical
2	10000.5294	40.51	54.00	13.49	AV	Vertical
3	17997.9999	46.37	54.00	7.63	AV	Vertical



Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5804.2826	50.46	-6.55	74.00	23.54	PK	Horizontal
2	10557.5622	58.01	2.47	74.00	15.99	PK	Horizontal
3	17608.977	65.16	11.03	74.00	8.84	PK	Horizontal


AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	5804.2826	36.12	54.00	17.88	AV	Horizontal
2	10557.5622	41.01	54.00	12.99	AV	Horizontal
3	17608.977	46.26	54.00	7.74	AV	Horizontal

Test mode: 802.11a

Frequency:

Channel 157: 5785MHz




Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5648.2734	50.07	-7.20	74.00	23.93	PK	Vertical
2	10048.5323	58.11	2.50	74.00	15.89	PK	Vertical
3	17988.9994	65.38	10.89	74.00	8.62	PK	Vertical

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	5648.2734	35.16	54.00	18.84	AV	Vertical
2	10048.5323	40.62	54.00	13.38	AV	Vertical
3	17988.9994	46.53	54.00	7.47	AV	Vertical



Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5809.2829	49.45	-6.54	74.00	24.55	PK	Horizontal
2	10056.5327	57.99	2.54	74.00	16.01	PK	Horizontal
3	17980.9989	64.86	10.65	74.00	9.14	PK	Horizontal


AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	5809.2829	35.59	54.00	18.41	AV	Horizontal
2	10056.5327	40.96	54.00	13.04	AV	Horizontal
3	17980.9989	45.93	54.00	8.07	AV	Horizontal

Test mode:: 802.11a

Frequency:

Channel 165: 5825MHz




Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5896.288	50.61	-6.58	74.00	23.39	PK	Vertical
2	10648.5676	57.94	3.94	74.00	16.06	PK	Vertical
3	17929.9959	65.33	9.12	74.00	8.67	PK	Vertical

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	5896.288	35.84	54.00	18.16	AV	Vertical
2	10648.5676	42.18	54.00	11.82	AV	Vertical
3	17929.9959	44.24	54.00	9.76	AV	Vertical



Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5771.2807	50.02	-6.70	74.00	23.98	PK	Horizontal
2	10187.5404	59.28	2.39	74.00	14.72	PK	Horizontal
3	17992.9996	65.12	11.01	74.00	8.88	PK	Horizontal

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	5771.2807	35.55	54.00	18.45	AV	Horizontal
2	10187.5404	40.93	54.00	13.07	AV	Horizontal
3	17992.9996	46.32	54.00	7.68	AV	Horizontal

●Undesirable radiated Undesirable radiatedSpurious Emission in Band Edge

All the antenna(Antenna 1) and modes(802.11a/n) has been tested and the worst(Antenna 1,802.11a) result recorded was report as below:


Test mode: 802.11a		Frequency: Channel 149: 5745MHz			
Freq. (MHz)	Ant.Pol.	Field Strength (RBW=100KHz) (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Verdict
5724.9375	H	66.08	-29.15	26.86	Pass
5724.9375	V	69.35	-25.88	26.86	Pass

Test mode: 802.11a		Frequency: Channel 165: 5825MHz			
Freq. (MHz)	Ant.Pol.	Field Strength (RBW=100KHz) (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Verdict
5850.0625	H	61.35	-33.88	26.86	Pass
5853.8769	V	62.67	-32.56	18.16	Pass

Note: (1) All Readings are Peak Value (VBW=3MHz) and Average Value(VBW=10Hz).
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 (3) $EIRP[dBm] = E[dB\mu V/m] + 20 \log(d[meters]) - 104.77$
 d is the measurement distance in 3 meters

U-NII-3


Test Model	Undesirable radiated	Undesirable radiated	Spurious Emission in Band Edge	
	802.11a	Channel 149: 5745MHz	Ant.Pol	H



Suspected Data List							
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5724.9375	66.08	39.04	122.16	56.08	PK	Horizontal


U-NII-3

Test Model	Undesirable radiated	Undesirable radiated	Spurious Emission in Band Edge	
	802.11a	Channel 149: 5745MHz	Ant.Pol	V




Suspected Data List							
NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5724.9375	69.35	39.04	122.16	52.81	PK	Vertical

Test Model U-NII-3
Undesirable radiated Undesirable radiatedSpurious Emission in Band Edge
802.11a Channel 165: 5825MHz Ant.Pol H



Suspected Data List							
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5850.0625	61.35	39.37	122.16	60.81	PK	Horizontal


Test Model U-NII-3
Undesirable radiated 802.11a Undesirable radiated Channel 165: 5825MHz Spurious Emission in Band Edge Ant.Pol V



Suspected Data List							
NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5853.8769	62.67	39.37	113.46	50.79	PK	Vertical


- Undesirable radiated Spurious Emission below 1GHz (30MHz to 1GHz)
All the antenna(Antenna 1) and modes(802.11a/n) has been tested and the worst(Antenna 1,802.11a) result recorded was report as below:

Mode:	11A 5180
-------	----------



Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	36.7968	37.59	-12.75	24.84	PK	40.00	15.16	Vertical
2	58.1582	37.54	-11.77	25.77	PK	40.00	14.23	Vertical
3	63.013	44.65	-12.45	32.20	PK	40.00	7.80	Vertical
4	70.7808	42.10	-13.58	28.52	PK	40.00	11.48	Vertical
5	274.684	41.92	-9.59	32.33	PK	46.00	13.67	Vertical
6	599.96	30.84	-0.27	30.57	PK	46.00	15.43	Vertical

Final Data List					
NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	36.7968	-12.75	23.76	40.00	16.24
2	58.1582	-11.77	24.69	40.00	15.31
3	63.013	-12.45	30.80	40.00	9.20
4	70.7808	-13.58	27.12	40.00	12.88
5	274.6847	-9.59	31.11	46.00	14.89
6	599.96	-0.27	29.35	46.00	16.65




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	66.8969	39.94	-13.01	26.93	PK	40.00	13.07	Horizontal
2	192.152	41.69	-12.67	29.02	PK	43.50	14.48	Horizontal
3	226.136	40.26	-10.87	29.39	PK	46.00	16.61	Horizontal
4	277.597	47.57	-9.44	38.13	PK	46.00	7.87	Horizontal
5	314.494	39.20	-8.02	31.18	PK	46.00	14.82	Horizontal
6	599.96	33.12	-0.27	32.85	PK	46.00	13.15	Horizontal

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	66.8969	-13.01	25.46	40.00	14.54
2	192.1522	-12.67	27.73	43.50	15.77
3	226.1361	-10.87	28.10	46.00	17.90
4	277.5976	-9.44	37.02	46.00	8.98
5	314.4945	-8.02	30.07	46.00	15.93
6	599.96	-0.27	31.65	46.00	14.35

Mode:	11A 5200
-------	----------




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	36.7968	37.82	-12.75	25.07	PK	40.00	14.93	Vertical
2	58.1582	38.65	-11.77	26.88	PK	40.00	13.12	Vertical
3	63.984	45.13	-12.59	32.54	PK	40.00	7.46	Vertical
4	70.7808	42.17	-13.58	28.59	PK	40.00	11.41	Vertical
5	271.771	41.64	-9.73	31.91	PK	46.00	14.09	Vertical
6	333.913	37.37	-7.00	30.37	PK	46.00	15.63	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	36.7968	-12.75	23.94	40.00	16.06
2	58.1582	-11.77	25.43	40.00	14.57
3	63.984	-12.59	31.09	40.00	8.91
4	70.7808	-13.58	27.56	40.00	12.44
5	271.7718	-9.73	30.88	46.00	15.12
6	333.9139	-7.00	29.02	46.00	16.98




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	66.8969	39.47	-13.01	26.46	PK	40.00	13.54	Horizontal
2	222.252	40.75	-11.00	29.75	PK	46.00	16.25	Horizontal
3	277.597	47.38	-9.44	37.94	PK	46.00	8.06	Horizontal
4	360.130	39.95	-6.63	33.32	PK	46.00	12.68	Horizontal
5	599.96	32.86	-0.27	32.59	PK	46.00	13.41	Horizontal
6	680.550	30.32	-1.01	29.31	PK	46.00	16.69	Horizontal

Final Data List


NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	66.8969	-13.01	25.35	40.00	14.65
2	222.2523	-11.00	28.64	46.00	17.36
3	277.5976	-9.44	36.50	46.00	9.50
4	360.1301	-6.63	32.30	46.00	13.70
5	599.96	-0.27	31.57	46.00	14.43
6	680.5506	-1.01	28.29	46.00	17.71

Mode:	11A 5240
-------	----------



Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	36.7968	37.79	-12.75	25.04	PK	40.00	14.96	Vertical
2	49.4194	35.23	-10.75	24.48	PK	40.00	15.52	Vertical
3	51.3614	37.21	-10.85	26.36	PK	40.00	13.64	Vertical
4	66.8969	45.34	-13.01	32.33	PK	40.00	7.67	Vertical
5	70.7808	42.16	-13.58	28.58	PK	40.00	11.42	Vertical
6	274.684	40.95	-9.59	31.36	PK	46.00	14.64	Vertical

Final Data List					
NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	36.7968	-12.75	23.64	40.00	16.36
2	49.4194	-10.75	23.25	40.00	16.75
3	51.3614	-10.85	25.05	40.00	14.95
4	66.8969	-13.01	31.02	40.00	8.98
5	70.7808	-13.58	27.27	40.00	12.73
6	274.6847	-9.59	30.23	46.00	15.77




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	64.955	39.06	-12.73	26.33	PK	40.00	13.67	Horizontal
2	191.181	41.29	-12.71	28.58	PK	43.50	14.92	Horizontal
3	262.062	38.87	-10.24	28.63	PK	46.00	17.37	Horizontal
4	274.684	47.97	-9.59	38.38	PK	46.00	7.62	Horizontal
5	317.407	39.74	-8.01	31.73	PK	46.00	14.27	Horizontal
6	599.96	32.80	-0.27	32.53	PK	46.00	13.47	Horizontal

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	64.955	-12.73	24.99	40.00	15.01
2	191.1812	-12.71	27.24	43.50	16.26
3	262.0621	-10.24	27.47	46.00	18.53
4	274.6847	-9.59	37.22	46.00	8.78
5	317.4074	-8.01	30.49	46.00	15.51
6	599.96	-0.27	31.29	46.00	14.71

Mode:	11A 5745
-------	----------



Suspected Data List								
NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	36.7968	38.04	-12.75	25.29	PK	40.00	14.71	Vertical
2	58.1582	39.59	-11.77	27.82	PK	40.00	12.18	Vertical
3	66.8969	45.38	-13.01	32.37	PK	40.00	7.63	Vertical
4	70.7808	42.36	-13.58	28.78	PK	40.00	11.22	Vertical
5	274.684	41.40	-9.59	31.81	PK	46.00	14.19	Vertical
6	333.913	37.26	-7.00	30.26	PK	46.00	15.74	Vertical

Final Data List					
NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	36.7968	-12.75	23.81	40.00	16.19
2	58.1582	-11.77	26.52	40.00	13.48
3	66.8969	-13.01	31.07	40.00	8.93
4	70.7808	-13.58	27.40	40.00	12.60
5	274.6847	-9.59	30.43	46.00	15.57
6	333.9139	-7.00	28.88	46.00	17.12