





Date: 26.MAY.2026 09:37:03

11N40SISO-Ant1-5190-PASS




Date: 26.MAY.2026 09:43:51

11N40SISO-Ant1-5230-PASS



Date: 26.MAY.2026 09:46:34

11N40SISO-Ant1-5755-PASS



Date: 26.MAY.2026 09:51:52

11N40SISO-Ant1-5795-PASS

8.4 UNDESIRABLE RADIATED SPURIOUS EMISSION

8.4.1 Applicable Standard

According to FCC Part 15.407 (b), 15.209, 15.205

According to 789033 D02 SectionII(G)

According to RSS-GEN

8.4.2 Conformance Limit

For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.

Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log (uV/m)	300
0.490-1.705	24000/F(KHz)	20 log (uV/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

The provisions of §15.205 apply to intentional radiators operating under this section, 15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

Remark: 1. Emission level in dBuV/m=20 log (uV/m)

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

8.4.3 Test Configuration

Test according to clause 6.2 radio frequency test setup

8.4.4 Test Procedure

■ Unwanted Emissions Measurements below 1000 MHz

Compliance shall be demonstrated using CISPR quasi-peak detection; however, peak detection is permitted as an alternative to quasi-peak detection.

The EUT was placed on a turn table which is 0.8m above ground plane.

And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

Repeat above procedures until all frequency measured was complete.

We use software control the EUT, Let EUT hopping on and transmit with highest power, All the modes have been tested and the worst result was reported.

Use the following spectrum analyzer settings:

SetRBW=120kHz for $f < 1$ GHz(30MHz to 1GHz), 200Hz for $f < 150$ KHz(9KHz to 150KHz), 9KHz for < 30 MHz(150KHz to 30KHz).

Set the VBW > RBW.

Detector = Peak.

Trace mode = max hold.

Follow the guidelines in ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Repeat above procedures until all frequency measured was complete.

■ Unwanted Maximumpeak Emissions Measurements above 1000 MHz

Maximum emission levels are measured by setting the analyzer as follows:

RBW = 1 MHz.

VBW $\geq$ 3 MHz.

Detector = Peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweeps to continue until the trace stabilizes. Note that if the transmission is not continuous, the time required for the trace to stabilize will increase by a factor of approximately $1/x$, where x is the duty cycle. For example, at 50 percent duty cycle, the measurement time will increase by a factor of two relative to measurement time for continuous transmission.

■ Unwanted Average Emissions Measurements above 1000 MHz

Method VB (Averaging using reduced video bandwidth): Alternative method.

RBW = 1 MHz.

Video bandwidth. • If the EUT is configured to transmit with duty cycle $\geq$ 98 percent, set $VBW \leq RBW/100$ (i.e., 10 kHz) but not less than 10 Hz.

• If the EUT duty cycle is < 98 percent, set $VBW \geq 1/T$, where T is defined in section II.B.1.a).

Video bandwidth mode or display mode • The instrument shall be set to ensure that video filtering is applied in the power domain. Typically, this requires setting the detector mode to RMS and setting the Average-VBW Type to Power (RMS).

• As an alternative, the analyzer may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some analyzers require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode.

Detector = Peak.

Sweep time = auto.

Trace mode = max hold.

Allow max hold to run for at least 50 traces if the transmitted signal is continuous or has at least 98 percent duty cycle. For lower duty cycles, increase the minimum number of traces by a factor of 1/x, where x is the duty cycle. For example, use at least 200 traces if the duty cycle is 25 percent. (If a specific emission is demonstrated to be continuous—i.e., 100 percent duty cycle—rather than turning on and off with the transmit cycle, at least 50 traces shall be averaged.)

■ Band edge measurements.

Unwanted band-edge emissions may be measured using either of the special band-edge measurement techniques (the marker-delta or integration methods) described below. Note that the marker-delta method is primarily a radiated measurement technique that requires the 99% occupied bandwidth edge to be within 2 MHz of the authorized band edge, whereas the integration method can be used in either a radiated or conducted measurement without any special requirement with regards to the displacement of the unwanted emission(s) relative to the authorized bandwidth.

Marker-Delta Method.

The marker-delta method, as described in ANSI C63.10, can be used to perform measurements of the radiated unwanted emissions level of emissions provided that the 99% occupied bandwidth of the fundamental is within 2 MHz of the authorized band-edge.

8.4.5 Test Results

Temperature:	25° C
Relative Humidity:	60%
ATM Pressure:	1011 mbar

■ Spurious Emission below 30MHz(9KHz to 30MHz)

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40 \log(\text{Specific distance} / \text{test distance})$ (dB);

Limit line = Specific limits(dBuV) + distance extrapolation factor

■ For Undesirable radiatedSpurious Emission in U-NII - 1

●Undesirable radiated Spurious Emission Above 1GHz(1GHz to 40GHz)

All the antenna(Antenna 1) and modes(802.11a/n) has been tested and the worst(Antenna 1,802.11a) result recorded was report as below:

no any obvious emission were detected from 18 GHz to 40 GHz, so below finaltest was performed with frequency range from 1GHz to 18 GHz.

Test mode: 802.11a Frequency: Channel 36: 5180MHz

Freq. (MHz)	Ant.Pol.	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Over(dB)
3590.152	V	39.31	-55.92	-27	28.92
10611.56	V	53.00	-42.23	-27	15.23
17985.99	V	55.63	-39.6	-27	12.6
4302.194	H	41.55	-53.68	-27	26.68
11572.62	H	52.60	-42.63	-27	15.63
17987.99	H	56.25	-38.98	-27	11.98

Test mode: 802.11a Frequency: Channel 40: 5200MHz

Freq. (MHz)	Ant.Pol.	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Over(dB)
3988.175	V	39.75	-55.48	-27	28.48
7635.390	V	49.32	-45.91	-27	18.91
17989.99	V	57.08	-38.15	-27	11.15
2962.115	H	38.94	-56.29	-27	29.29
5626.272	H	44.43	-50.8	-27	23.8
17973.99	H	55.96	-39.27	-27	12.27

Test mode: 802.11a Frequency: Channel 48: 5240MHz


Freq. (MHz)	Ant.Pol.	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Over(dB)
3875.169	V	39.67	-55.56	-27	28.56
7674.392	V	47.86	-47.37	-27	20.37
17972.99	V	56.22	-39.01	-27	12.01
3669.157	H	40.11	-55.12	-27	28.12
7557.385	H	47.72	-47.51	-27	20.51
17998.99	H	56.00	-39.23	-27	12.23

Note: (1) All Readings are Peak Value (VBW=3MHz) and Average Value(VBW=10Hz).
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 (3)EIRP[dBm] = E[dBμV/m] + 20 log(d[meters]) - 104.77
 d is the measurement distance in 3 meters

Test mode: 802.11a

Frequency:

Channel 36: 5180MHz




Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3590.1524	39.31	-20.21	74.00	34.69	PK	Vertical
2	10611.5654	53.00	-3.99	74.00	21.00	PK	Vertical
3	17985.9992	55.63	0.44	74.00	18.37	PK	Vertical

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	3590.1524	22.21	54.00	31.79	AV	Vertical
2	10611.5654	34.37	54.00	19.63	AV	Vertical
3	17985.9992	35.95	54.00	18.05	AV	Vertical



Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4302.1942	41.55	-18.35	74.00	32.45	PK	Horizontal
2	11572.6219	52.60	-4.40	74.00	21.40	PK	Horizontal
3	17987.9993	56.25	0.51	74.00	17.75	PK	Horizontal


AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	4302.1942	24.46	54.00	29.54	AV	Horizontal
2	11572.6219	34.07	54.00	19.93	AV	Horizontal
3	17987.9993	35.92	54.00	18.08	AV	Horizontal

Test mode: 802.11a

Frequency:

Channel 40: 5200MHz




Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3988.1758	39.75	-19.22	74.00	34.25	PK	Vertical
2	7635.3903	49.32	-10.50	74.00	24.68	PK	Vertical
3	17989.9994	57.08	0.56	74.00	16.92	PK	Vertical

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	3988.1758	23.29	54.00	30.71	AV	Vertical
2	7635.3903	27.97	54.00	26.03	AV	Vertical
3	17989.9994	36.22	54.00	17.78	AV	Vertical



Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2962.1154	38.94	-20.97	74.00	35.06	PK	Horizontal
2	5626.2721	44.43	-14.75	74.00	29.57	PK	Horizontal
3	17973.9985	55.96	0.10	74.00	18.04	PK	Horizontal


AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	2962.1154	21.67	54.00	32.33	AV	Horizontal
2	5626.2721	23.72	54.00	30.28	AV	Horizontal
3	17973.9985	35.39	54.00	18.61	AV	Horizontal

Test mode: 802.11a

Frequency:

Channel 48: 5240MHz




Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3875.1691	39.67	-19.60	74.00	34.33	PK	Vertical
2	7674.3926	47.86	-10.51	74.00	26.14	PK	Vertical
3	17972.9984	56.22	0.08	74.00	17.78	PK	Vertical

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	3875.1691	22.04	54.00	31.96	AV	Vertical
2	7674.3926	27.34	54.00	26.66	AV	Vertical
3	17972.9984	34.87	54.00	19.13	AV	Vertical



Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3669.157	40.11	-20.09	74.00	33.89	PK	Horizontal
2	7557.3857	47.72	-10.56	74.00	26.28	PK	Horizontal
3	17998.9999	56.00	0.82	74.00	18.00	PK	Horizontal

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	3669.157	21.90	54.00	32.10	AV	Horizontal
2	7557.3857	28.00	54.00	26.00	AV	Horizontal
3	17998.9999	36.06	54.00	17.94	AV	Horizontal

●Undesirable radiated Undesirable radiatedSpurious Emission in Band Edge


All the antenna(Antenna 1) and modes(802.11a/n) has been tested and the worst(Antenna 1,802.11a) result recorded was report as below:

Test mode: 802.11a		Frequency:		Channel 36: 5180MHz	
Freq. (MHz)	Ant.Pol.	Field Strength (RBW=100KHz) (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Verdict
5143.09	H	52.78	-42.45	-27	Pass
5105.39	V	52.74	-42.49	-27	Pass

Test mode: 802.11a		Frequency:		Channel 48: 5240MHz	
Freq. (MHz)	Ant.Pol.	Field Strength (RBW=100KHz) (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Verdict
5358.03	H	52.58	-42.65	-27	Pass
5354.60	V	52.04	-43.19	-27	Pass

Note: (1) All Readings are Peak Value (VBW=3MHz) and Average Value(VBW=10Hz).
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 (3)EIRP[dBm] = E[dBμV/m] + 20 log(d[meters]) - 104.77
 d is the measurement distance in 3 meters


U-NII - 1				
Test Model	Undesirable radiated	Undesirable radiated	Spurious Emission in Band Edge	
	802.11a	Channel 36: 5180MHz	Ant.Pol	H



Suspected Data List							
NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5105.3938	52.74	36.73	74.00	21.26	PK	Vertical

AV Final Data List						
NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	5105.3938	44.32	54.00	9.68	AV	Vertical

U-NII - 1				
Test Model	Undesirable radiated	Undesirable radiated	Spurious Emission in Band Edge	
	802.11a	Channel 36: 5180MHz	Ant.Pol	V




Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5143.0938	52.78	36.74	74.00	21.22	PK	Horizontal

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	5143.0938	42.97	54.00	11.03	AV	Horizontal


U-NII - 1				
Test Model	Undesirable radiated	Undesirable radiated	Spurious Emission in Band Edge	
	802.11a	Channel 48: 5240MHz	Ant.Pol	H



Suspected Data List							
NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5358.03	52.58	36.93	74.00	21.42	PK	Horizontal

AV Final Data List						
NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	5358.03	43.59	54.00	10.41	AV	Horizontal

U-NII - 1				
Test Model	Undesirable radiated	Undesirable radiated	Spurious Emission in Band Edge	
	802.11a	Channel 48: 5240MHz	Ant.Pol	V



Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	5354.6062	52.04	36.92	74.00	21.96	PK	Vertical

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	5354.6062	44.06	54.00	9.94	AV	Vertical

■ For Undesirable radiated Spurious Emission in U-NII -3

● Undesirable radiated Spurious Emission Above 1GHz(1GHz to 40GHz)

All the antenna(Antenna 1) and modes(802.11a/n) has been tested and the worst(Antenna 1,802.11a) result recorded was report as below:

no any obvious emission were detected from 18 GHz to 40 GHz, so below finaltest was performed with frequency range from 1GHz to 18 GHz.

Test mode: 802.11a Frequency: Channel 149: 5745MHz

Freq. (MHz)	Ant.Pol.	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Over(dB)
3988.1758	V	39.71	-55.52	-27	28.52
7658.3917	V	47.74	-47.49	-27	20.49
17970.9983	V	55.82	-39.41	-27	12.41
4223.1896	H	41.17	-54.06	-27	27.06
8767.4569	H	50.13	-45.1	-27	18.1
17962.9978	H	55.93	-39.3	-27	12.3

Test mode: 802.11a Frequency: Channel 157: 5785MHz

Freq. (MHz)	Ant.Pol.	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Over(dB)
4341.1965	V	40.48	-54.75	-27	27.75
8850.4618	V	50.21	-45.02	-27	18.02
17982.999	V	55.98	-39.25	-27	12.25
4280.193	H	41.21	-54.02	-27	27.02
8853.462	H	49.90	-45.33	-27	18.33
17983.9991	H	56.13	-39.1	-27	12.1

Test mode: 802.11a Frequency: Channel 165: 5825MHz


Freq. (MHz)	Ant.Pol.	Field Strength (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Over(dB)
4230.19	V	40.47	-54.76	-27	27.76
8862.4625	V	51.19	-44.04	-27	17.04
17980.9989	V	56.45	-38.78	-27	11.78
4345.1968	H	40.87	-54.36	-27	27.36
8853.462	H	50.10	-45.13	-27	18.13
17985.9992	H	55.15	-40.08	-27	13.08

Note: (1) All Readings are Peak Value (VBW=3MHz) and Average Value(VBW=10Hz).
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 (3) EIRP[dBm] = E[dBuV/m] + 20 log(d[meters]) - 104.77
 d is the measurement distance in 3 meters

Test mode: 802.11a

Frequency:

Channel 149: 5745MHz




Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3988.1758	39.71	-19.22	74.00	34.29	PK	Vertical
2	7658.3917	47.74	-10.50	74.00	26.26	PK	Vertical
3	17970.9983	55.82	0.01	74.00	18.18	PK	Vertical

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	3988.1758	23.19	54.00	30.81	AV	Vertical
2	7658.3917	28.18	54.00	25.82	AV	Vertical
3	17970.9983	35.30	54.00	18.70	AV	Vertical



Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4223.1896	41.17	-18.59	74.00	32.83	PK	Horizontal
2	8767.4569	50.13	-8.15	74.00	23.87	PK	Horizontal
3	17962.9978	55.93	-0.21	74.00	18.07	PK	Horizontal


AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	4223.1896	23.09	54.00	30.91	AV	Horizontal
2	8767.4569	30.00	54.00	24.00	AV	Horizontal
3	17962.9978	35.17	54.00	18.83	AV	Horizontal

Test mode: 802.11a

Frequency:

Channel 157: 5785MHz




Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4341.1965	40.48	-18.22	74.00	33.52	PK	Vertical
2	8850.4618	50.21	-7.46	74.00	23.79	PK	Vertical
3	17982.999	55.98	0.36	74.00	18.02	PK	Vertical

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	4341.1965	24.15	54.00	29.85	AV	Vertical
2	8850.4618	30.18	54.00	23.82	AV	Vertical
3	17982.999	35.59	54.00	18.41	AV	Vertical



Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4280.193	41.21	-18.41	74.00	32.79	PK	Horizontal
2	8853.462	49.90	-7.44	74.00	24.10	PK	Horizontal
3	17983.9991	56.13	0.39	74.00	17.87	PK	Horizontal


AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	4280.193	24.06	54.00	29.94	AV	Horizontal
2	8853.462	30.94	54.00	23.06	AV	Horizontal
3	17983.9991	35.78	54.00	18.22	AV	Horizontal

Test mode:: 802.11a

Frequency:

Channel 165: 5825MHz




Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor[dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4230.19	40.47	-18.57	74.00	33.53	PK	Vertical
2	8862.4625	51.19	-7.36	74.00	22.81	PK	Vertical
3	17980.9989	56.45	0.30	74.00	17.55	PK	Vertical

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	4230.19	23.20	54.00	30.80	AV	Vertical
2	8862.4625	30.25	54.00	23.75	AV	Vertical
3	17980.9989	35.36	54.00	18.64	AV	Vertical



Suspected Data List

NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4345.1968	40.87	-18.20	74.00	33.13	PK	Horizontal
2	8853.462	50.10	-7.44	74.00	23.90	PK	Horizontal
3	17985.9992	55.15	0.44	74.00	18.85	PK	Horizontal

AV Final Data List

NO.	Freq. [MHz]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Detector	Polarity
1	4345.1968	24.16	54.00	29.84	AV	Horizontal
2	8853.462	30.55	54.00	23.45	AV	Horizontal
3	17985.9992	35.07	54.00	18.93	AV	Horizontal

●Undesirable radiated Undesirable radiatedSpurious Emission in Band Edge


All the antenna(Antenna 1) and modes(802.11a/n) has been tested and the worst(Antenna 1,802.11a) result recorded was report as below:

Test mode: 802.11a		Frequency:		Channel 149: 5745MHz	
Freq. (MHz)	Ant.Pol.	Field Strength (RBW=100KHz) (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Verdict
5718.6843	H	52.59	-42.64	15.23	Pass
5722.5613	V	52.64	-42.59	21.44	Pass


Test mode: 802.11a		Frequency:		Channel 165: 5825MHz	
Freq. (MHz)	Ant.Pol.	Field Strength (RBW=100KHz) (dBuV/m)	E.I.R.P (dBm)	Limit (dBm)	Verdict
5851.6258	H	52.37	-42.86	23.29	Pass
5856.8784	V	52.37	-42.86	15.07	Pass

Note: (1) All Readings are Peak Value (VBW=3MHz) and Average Value(VBW=10Hz).
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 (3) $EIRP[dBm] = E[dB\mu V/m] + 20 \log(d[meters]) - 104.77$
 d is the measurement distance in 3 meters


U-NII-3				
Test Model	Undesirable radiated	Undesirable radiated	Spurious Emission in Band Edge	
	802.11a	Channel 149: 5745MHz	Ant.Pol	H




U-NII-3				
Test Model	Undesirable radiated	Undesirable radiated	Spurious Emission in Band Edge	
	802.11a	Channel 149: 5745MHz	Ant.Pol	V



U-NII-3				
Test Model	Undesirable radiated	Undesirable radiated	Spurious Emission in Band Edge	
	802.11a	Channel 165: 5825MHz	Ant.Pol	H




U-NII-3				
Test Model	Undesirable radiated	Undesirable radiated	Spurious Emission in Band Edge	
	802.11a	Channel 165: 5825MHz	Ant.Pol	V



- Undesirable radiated Spurious Emission below 1GHz (30MHz to 1GHz)
All the antenna(Antenna 1) and modes(802.11a/n) has been tested and the worst(Antenna 1,802.11a) result recorded was report as below:

Mode:	11A 5180
-------	----------




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	53.3033	38.44	-16.73	21.71	PK	40.00	18.29	Vertical
2	61.0711	41.93	-17.73	24.20	PK	40.00	15.80	Vertical
3	84.3744	39.13	-19.81	19.32	PK	40.00	20.68	Vertical
4	180.500	45.04	-18.96	26.08	PK	43.50	17.42	Vertical
5	385.375	36.15	-11.61	24.54	PK	46.00	21.46	Vertical
6	924.264	27.91	-3.13	24.78	PK	46.00	21.22	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	53.3033	-16.73	20.65	40.00	19.35
2	61.0711	-17.73	22.98	40.00	17.02
3	84.3744	-19.81	18.10	40.00	21.90
4	180.5005	-18.96	24.22	43.50	19.28
5	385.3754	-11.61	23.51	46.00	22.49
6	924.2643	-3.13	23.75	46.00	22.25




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	181.4715	47.41	-18.92	28.49	PK	43.50	15.01	Horizontal
2	261.0911	40.78	-16.00	24.78	PK	46.00	21.22	Horizontal
3	273.7137	42.94	-15.46	27.48	PK	46.00	18.52	Horizontal
4	355.2753	42.48	-12.37	30.11	PK	46.00	15.89	Horizontal
5	370.8108	41.29	-12.01	29.28	PK	46.00	16.72	Horizontal
6	807.7477	31.33	-5.14	26.19	PK	46.00	19.81	Horizontal

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	181.4715	-18.92	26.72	43.50	16.78
2	261.0911	-16.00	23.37	46.00	22.63
3	273.7137	-15.46	26.07	46.00	19.93
4	355.2753	-12.37	29.06	46.00	16.94
5	370.8108	-12.01	28.23	46.00	17.77
6	807.7477	-5.14	24.97	46.00	21.03

Mode:	11A 5200
-------	----------




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	58.1582	35.99	-17.36	18.63	PK	40.00	21.37	Vertical
2	62.042	41.60	-17.87	23.73	PK	40.00	16.27	Vertical
3	84.3744	39.56	-19.81	19.75	PK	40.00	20.25	Vertical
4	179.529	44.95	-19.00	25.95	PK	43.50	17.55	Vertical
5	389.259	36.64	-11.52	25.12	PK	46.00	20.88	Vertical
6	958.248	27.76	-2.75	25.01	PK	46.00	20.99	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	58.1582	-17.36	16.96	40.00	23.04
2	62.042	-17.87	22.06	40.00	17.94
3	84.3744	-19.81	17.92	40.00	22.08
4	179.5295	-19.00	24.48	43.50	19.02
5	389.2593	-11.52	23.65	46.00	22.35
6	958.2482	-2.75	23.54	46.00	22.46




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	180.500	46.71	-18.96	27.75	PK	43.50	15.75	Horizontal
2	254.294	40.98	-16.06	24.92	PK	46.00	21.08	Horizontal
3	272.742	43.61	-15.51	28.10	PK	46.00	17.90	Horizontal
4	359.159	42.38	-12.36	30.02	PK	46.00	15.98	Horizontal
5	369.839	41.51	-12.03	29.48	PK	46.00	16.52	Horizontal
6	804.834	31.55	-5.22	26.33	PK	46.00	19.67	Horizontal

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	180.5005	-18.96	25.76	43.50	17.74
2	254.2943	-16.06	23.28	46.00	22.72
3	272.7427	-15.51	26.46	46.00	19.54
4	359.1592	-12.36	28.74	46.00	17.26
5	369.8398	-12.03	28.04	46.00	17.96
6	804.8348	-5.22	24.89	46.00	21.11

Mode:	11A 5240
-------	----------




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	52.3323	35.11	-16.61	18.50	PK	40.00	21.50	Vertical
2	61.0711	40.21	-17.73	22.48	PK	40.00	17.52	Vertical
3	85.3453	38.38	-19.67	18.71	PK	40.00	21.29	Vertical
4	179.529	45.20	-19.00	26.20	PK	43.50	17.30	Vertical
5	387.317	36.25	-11.56	24.69	PK	46.00	21.31	Vertical
6	872.802	27.71	-3.70	24.01	PK	46.00	21.99	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	52.3323	-16.61	16.81	40.00	23.19
2	61.0711	-17.73	20.79	40.00	19.21
3	85.3453	-19.67	17.38	40.00	22.62
4	179.5295	-19.00	24.87	43.50	18.63
5	387.3173	-11.56	23.19	46.00	22.81
6	872.8028	-3.70	22.51	46.00	23.49




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	181.4715	46.99	-18.92	28.07	PK	43.50	15.43	Horizontal
2	262.0621	41.28	-15.96	25.32	PK	46.00	20.68	Horizontal
3	269.8298	43.32	-15.65	27.67	PK	46.00	18.33	Horizontal
4	352.3624	43.11	-12.38	30.73	PK	46.00	15.27	Horizontal
5	370.8108	41.46	-12.01	29.45	PK	46.00	16.55	Horizontal
6	810.6607	31.16	-5.08	26.08	PK	46.00	19.92	Horizontal

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	181.4715	-18.92	26.62	43.50	16.88
2	262.0621	-15.96	23.87	46.00	22.13
3	269.8298	-15.65	26.06	46.00	19.94
4	352.3624	-12.38	29.12	46.00	16.88
5	370.8108	-12.01	27.84	46.00	18.16
6	810.6607	-5.08	24.83	46.00	21.17

Mode:	11A 5745
-------	----------




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	36.7968	36.36	-18.27	18.09	PK	40.00	21.91	Vertical
2	53.3033	37.94	-16.73	21.21	PK	40.00	18.79	Vertical
3	62.042	40.10	-17.87	22.23	PK	40.00	17.77	Vertical
4	83.4034	39.25	-19.95	19.30	PK	40.00	20.70	Vertical
5	177.587	45.21	-19.08	26.13	PK	43.50	17.37	Vertical
6	392.172	35.17	-11.45	23.72	PK	46.00	22.28	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	36.7968	-18.27	16.96	40.00	23.04
2	53.3033	-16.73	19.44	40.00	20.56
3	62.042	-17.87	20.82	40.00	19.18
4	83.4034	-19.95	17.89	40.00	22.11
5	177.5876	-19.08	24.72	43.50	18.78
6	392.1722	-11.45	22.14	46.00	23.86




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	182.442	46.94	-18.87	28.07	PK	43.50	15.43	Horizontal
2	259.149	41.41	-16.05	25.36	PK	46.00	20.64	Horizontal
3	270.800	42.25	-15.60	26.65	PK	46.00	19.35	Horizontal
4	353.333	43.18	-12.38	30.80	PK	46.00	15.20	Horizontal
5	368.868	41.55	-12.06	29.49	PK	46.00	16.51	Horizontal
6	813.573	29.69	-5.05	24.64	PK	46.00	21.36	Horizontal

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	182.4424	-18.87	26.94	43.50	16.56
2	259.1491	-16.05	24.23	46.00	21.77
3	270.8008	-15.60	24.88	46.00	21.12
4	353.3333	-12.38	28.86	46.00	17.14
5	368.8689	-12.06	27.55	46.00	18.45
6	813.5736	-5.05	22.70	46.00	23.30

Mode:	11A 5785
-------	----------




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	53.3033	37.21	-16.73	20.48	PK	40.00	19.52	Vertical
2	60.1001	41.05	-17.61	23.44	PK	40.00	16.56	Vertical
3	81.4615	38.06	-20.23	17.83	PK	40.00	22.17	Vertical
4	84.3744	39.39	-19.81	19.58	PK	40.00	20.42	Vertical
5	180.500	45.46	-18.96	26.50	PK	43.50	17.00	Vertical
6	372.752	35.45	-11.95	23.50	PK	46.00	22.50	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	53.3033	-16.73	19.03	40.00	20.97
2	60.1001	-17.61	21.99	40.00	18.01
3	81.4615	-20.23	16.21	40.00	23.79
4	84.3744	-19.81	18.32	40.00	21.68
5	180.5005	-18.96	25.24	43.50	18.26
6	372.7528	-11.95	22.24	46.00	23.76




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	180.500	47.61	-18.96	28.65	PK	43.50	14.85	Horizontal
2	260.120	41.66	-16.03	25.63	PK	46.00	20.37	Horizontal
3	274.684	41.69	-15.41	26.28	PK	46.00	19.72	Horizontal
4	359.159	42.54	-12.36	30.18	PK	46.00	15.82	Horizontal
5	372.752	41.24	-11.95	29.29	PK	46.00	16.71	Horizontal
6	796.096	31.32	-5.64	25.68	PK	46.00	20.32	Horizontal

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	180.5005	-18.96	27.07	43.50	16.43
2	260.1201	-16.03	24.41	46.00	21.59
3	274.6847	-15.41	25.06	46.00	20.94
4	359.1592	-12.36	28.79	46.00	17.21
5	372.7528	-11.95	27.90	46.00	18.10
6	796.0961	-5.64	24.65	46.00	21.35

Mode:	11A 5825
-------	----------




Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	53.3033	37.05	-16.73	20.32	PK	40.00	19.68	Vertical
2	60.1001	40.74	-17.61	23.13	PK	40.00	16.87	Vertical
3	83.4034	39.85	-19.95	19.90	PK	40.00	20.10	Vertical
4	180.500	45.61	-18.96	26.65	PK	43.50	16.85	Vertical
5	350.420	35.86	-12.39	23.47	PK	46.00	22.53	Vertical
6	385.375	36.13	-11.61	24.52	PK	46.00	21.48	Vertical

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	53.3033	-16.73	19.06	40.00	20.94
2	60.1001	-17.61	21.71	40.00	18.29
3	83.4034	-19.95	18.48	40.00	21.52
4	180.5005	-18.96	25.59	43.50	17.91
5	350.4204	-12.39	22.41	46.00	23.59
6	385.3754	-11.61	22.81	46.00	23.19



Suspected Data List

NO.	Freq. [MHz]	Reading [dBμV]	Factor [dB/m]	Level [dBμV/m]	Detector	Limit [dBμV/m]	Margin [dB]	Polarity
1	182.442	46.85	-18.87	27.98	PK	43.50	15.52	Horizontal
2	258.178	41.29	-16.04	25.25	PK	46.00	20.75	Horizontal
3	272.742	41.47	-15.51	25.96	PK	46.00	20.04	Horizontal
4	353.333	43.03	-12.38	30.65	PK	46.00	15.35	Horizontal
5	369.839	41.14	-12.03	29.11	PK	46.00	16.89	Horizontal
6	813.573	30.75	-5.05	25.70	PK	46.00	20.30	Horizontal

Final Data List

NO.	Freq. [MHz]	Factor [dB/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]
1	182.4424	-18.87	26.20	43.50	17.30
2	258.1782	-16.04	23.47	46.00	22.53
3	272.7427	-15.51	24.54	46.00	21.46
4	353.3333	-12.38	29.58	46.00	16.42
5	369.8398	-12.03	28.04	46.00	17.96
6	813.5736	-5.05	24.47	46.00	21.53

8.5 POWER LINE CONDUCTED EMISSIONS

8.5.1 Applicable Standard

According to FCC Part 15.207(a)

According to IC RSS-Gen 8.8

8.5.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

8.5.3 Test Configuration

Test according to clause 6.3 conducted emission test setup

8.5.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.


Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Repeat above procedures until all frequency measured were complete.

8.5.5 Test Results

Pass

The AC120V &240V voltage have been tested, and the worst result recorded was report as below:



Site Conduction 2#

Phase: L1

Temperature: 24.9

Limit: (CE)FCC PART 15 class B_QP


Power: AC 120V/60Hz

Humidity: 44 %

Mode: WiFi mode

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	0.1820	39.54	10.61	50.15	64.39	-14.24	QP	
2		0.1820	23.40	10.61	34.01	54.39	-20.38	AVG	
3		0.2620	32.33	10.62	42.95	61.37	-18.42	QP	
4		0.2620	15.90	10.62	26.52	51.37	-24.85	AVG	
5		0.3820	30.00	10.62	40.62	58.24	-17.62	QP	
6		0.3820	18.33	10.62	28.95	48.24	-19.29	AVG	
7		0.4420	27.38	10.62	38.00	57.02	-19.02	QP	
8		0.4420	12.26	10.62	22.88	47.02	-24.14	AVG	
9		0.5780	25.89	10.65	36.54	56.00	-19.46	QP	
10		0.5780	12.25	10.65	22.90	46.00	-23.10	AVG	
11		0.7700	25.76	10.66	36.42	56.00	-19.58	QP	
12		0.7700	10.55	10.66	21.21	46.00	-24.79	AVG	



Site Conduction 2#

Phase: **N**

Temperature: 24.9

Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz

Humidity: 44 %

Mode: WiFi mode

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1740	38.65	10.61	49.26	64.77	-15.51	QP	
2		0.1740	21.20	10.61	31.81	54.77	-22.96	AVG	
3		0.4860	25.98	10.63	36.61	56.24	-19.63	QP	
4		0.4860	9.26	10.63	19.89	46.24	-26.35	AVG	
5		0.6820	24.03	10.66	34.69	56.00	-21.31	QP	
6		0.6820	8.39	10.66	19.05	46.00	-26.95	AVG	
7		3.1100	29.00	10.87	39.87	56.00	-16.13	QP	
8		3.1100	13.69	10.87	24.56	46.00	-21.44	AVG	
9		5.5260	27.52	11.04	38.56	60.00	-21.44	QP	
10		5.5260	15.91	11.04	26.95	50.00	-23.05	AVG	
11		12.7180	30.02	11.33	41.35	60.00	-18.65	QP	
12		12.7180	18.35	11.33	29.68	50.00	-20.32	AVG	

8.6 ANTENNA APPLICATION

8.6.1 Antenna Requirement

Standard	Requirement
FCC CRF Part15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
FCC 47 CFR Part15.407(a)	If transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.
RSS-Gen Section 6.8	The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

8.6.2 Result

PASS.

- Note:
- ☒ Antenna use a permanently attached antenna which is not replaceable.
 - ☐ Not using a standard antenna jack or electrical connector for antenna replacement
 - ☐ The antenna has to be professionally installed (please provide method of installation)

Please refer to the attached document Internal Photos to show the antenna connector.

----- END OF REPORT -----

9 APPENDIX PHOTOGRAPHS OF EUT

Please refer to the file of External Photo and Internal Photo.



10 APPENDIX PHOTOGRAPHS OF TEST SETUP

Please refer to the file of Test Setup Photo.



声 明 Statement

1. 本报告无授权批准人签字及“检验检测专用章”无效；

This report is invalid without the signature of the authorized approver and the "special seal for testing".

2. 未经许可本报告不得部分复制；

This report shall not be copied partly without authorization.

3. 本报告的检测结果仅对送测样品有效，委托方对样品的代表性和资料的真实性负责；

The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the samples and the authenticity of the material.

4. 本检测报告中检测项目标注有特殊符号则该项目不在资质认定范围内，仅作为客户委托、科研、教学或内部质量控制等目的使用；

The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.

5. 本检测报告以实测值进行符合性判定，未考虑不确定度所带来的风险，本实验室不承担相关责任，特别约定、标准或规范中有明确规定的除外；

The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards or regulations, EMTEK shall not assume any responsibility.

6. 对本检验报告若有异议，请于收到报告之日起 20 日内提出。

Objections shall be raised within 20 days from the date receiving the report.