

FCC PART 15 SUBPART C TEST REPORT

FCC PART 15.247

Report Reference No...... : **MK25102412P01-R01**

FCC ID..... : **2BEGN-YS-302**

Compiled by
(position+printed name+signature)... : Engineer/ Cindy Zheng

Supervised by
(position+printed name+signature)... : Manager/Haley Wen

Approved by
(position+printed name+signature)... : RF Manager/ Vivian Jiang

Date of issue..... : December 11, 2025

Cindy Zheng
Haley Wen
Vivian Jiang

Testing Laboratory Name..... : **MAXLAB Testing Co.,Ltd.**

Address..... : 1/F, Building B, Xinshidai GR Park, Shiyan Street, Bao'an District, Shenzhen, Guangdong, 518052, People's Republic of China

Applicant's name..... : **Shenzhen Youshid High Technology Co., Ltd**

Address..... : Suite 1801, Building 3C ,Tianan Cloud Park, Bantian Street, Longgang District, Shenzhen, China

Test specification..... :

FCC Part 15.247

Standard..... : **KDB558074 D01 15.247 Meas Guidance v05r02**

ANSI C63.10:2020

MAXLAB Testing Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the MAXLAB Testing Co.,Ltd.is acknowledged as copyright owner and source of the material. MAXLAB Testing Co.,Ltd.takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description..... : **Projector**

Trade Mark..... : N/A

Manufacturer..... : Dongguan Youshida Technology Co., Ltd

Model/Type reference..... : YS-302

Listed Models : YS-300, YS-301, YS-301PLUS, YS-302PLUS, YS-303, YS-304, YS-306, YS-307, YS-308, YS-309, YS-310, YS-311, YS-312, HY-300PRO, HY-360PLUS, HY-360Portable

Modulation Type..... : CCK/ DSSS/ OFDM /OFDMA

Operation Frequency..... : From 2412 - 2462MHz

Rating..... : AC100~240V

Result..... : **PASS**

TEST REPORT

Equipment under Test : **Projector**

Model /Type : **YS-302**

Series Model No. YS-300, YS-301, YS-301PLUS, YS-302PLUS, YS-303, YS-304, YS-306, YS-307, YS-308, YS-309, YS-310, YS-311, YS-312, HY-300PRO, HY-360PLUS, HY-360Portable

Model Declaration : All the models are electrical identical including the same software parameter and hardware design, same mechanical structure and design, the only difference is the model named different.

Applicant : **Shenzhen Youshid High Technology Co., Ltd**

Address : Suite 1801, Building 3C ,Tianan Cloud Park, Bantian Street, Longgang District, Shenzhen, China

Manufacturer : **Dongguan Youshida Technology Co., Ltd**

Address : Room 201,Building 6,NO.155,Jianshe Road,Shima,Tangxia Town,Dongguan, China

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1 TEST STANDARDS	4
2 SUMMARY	5
2.1 General Remarks.....	5
2.2 Product Description.....	5
2.3 Equipment Under Test.....	5
2.4 Short description of the Equipment under Test (EUT).....	5
2.5 EUT operation mode.....	6
2.6 Block Diagram of Test Setup.....	6
2.7 Related Submittal(s) / Grant (s).....	6
2.8 Modifications.....	6
3 TEST ENVIRONMENT	7
3.1 Address of the test laboratory.....	7
3.2 Test Facility.....	7
3.3 Environmental conditions.....	7
3.4 Test Description.....	8
3.5 Statement of the measurement uncertainty.....	8
3.6 Equipments Used during the Test.....	9
4 TEST CONDITIONS AND RESULTS	11
4.1 AC Power Conducted Emission.....	11
4.2 Radiated Emission.....	14
4.3 Maximum Peak Conducted Output Power.....	20
4.4 Power Spectral Density.....	21
4.5 6dB Bandwidth and 99% Bandwidth.....	25
4.6 Out-of-band Emissions.....	33
4.7 Duty Cycle Of Test Signal.....	44
4.8 Antenna Requirement.....	48
5 TEST SETUP PHOTOS OF THE EUT	49
6 PHOTOS OF THE EUT	50

1 TEST STANDARDS

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

ANSI C63.10-2020: American National Standard for Testing Unlicensed Wireless Devices

KDB558074 D01 v05r02: Guidance for Compliance Measurements on Digital Transmission Systems (DTS) ,Frequency Hopping Spread Spectrum System(HFSS), and Hybrid System Devices Operating Under §15.247 of The FCC rules.

2 SUMMARY

2.1 General Remarks

Date of receipt of test sample	:	October 22, 2025
Testing commenced on	:	October 22, 2025
Testing concluded on	:	December 11, 2025

2.2 Product Description

Product Name:	Projector
Model/Type reference:	YS-302
Power supply:	AC100~240V
Adapter information (Auxiliary test supplied by testing Lab)	N/A
testing sample ID:	MK25102412P01-R01-1# (Engineer sample), MK25102412P01-R01-2# (Normal sample)
Hardware version:	WF-4102B
Software version:	V013
WIFI :	
Supported type:	802.11b/g/n20/ax20 802.11n40/ax40
Modulation:	802.11b: DSSS 802.11g/802.11n(HT20)/ 802.11n(HT40): OFDM 802.11ax(HE20)/ 802.11ax(HE40): OFDMA
Operation frequency:	802.11b/802.11g/802.11n(HT20)/802.11ax(HE20): 2412MHz~2462MHz 802.11n(HT40)/802.11ax(HE40): 2422MHz~2452MHz
Channel number:	802.11b/802.11g/802.11n(HT20)/802.11ax(HE20): 11 802.11n(HT40)/802.11ax(HE40):7
Channel separation:	5MHz
Antenna type:	PCB Antenna
Antenna gain:	1.73 dBi

2.3 Equipment Under Test

Power supply system utilised

Power supply voltage	:	☐ 230V / 50 Hz	☒ 120V / 60Hz
		☐ 5 V DC	☐ 24 V DC
		☐ Other (specified in blank below)	

2.4 Short description of the Equipment under Test (EUT)

This is a Projector.

For more details, refer to the user's manual of the EUT.

2.5 EUT operation mode

The application provider specific test software(MP_Kit_RTL11n_FTV_USB_v1.25) to control sample in continuous TX and RX (Duty Cycle >98%) for testing meet KDB558074 test requirement.

IEEE 802.11b/g/n(HT20)/ax(HE20): 11 channels are provided to the EUT.

IEEE 802.11n(HT40)/ax(HE40): 7 channels are provided to the EUT.

IEEE 802.11b/g/n(HT20)/ax(HE20)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432		
6	2437		
7	2442		


IEEE 802.11n(HT40)/ax(HE40)

Channel	Frequency(MHz)		
3	2422		
4	2427		
5	2432		
6	2437		
7	2442		
8	2447		
9	2452		

Test software: MP_Kit_RTL11n_FTV_USB_v1.25

Test mode	Power level	Rating power mW	Date Rate Mbps
B Mode (CH01 CH06 CH11)	40	9	1 Mbps
G Mode (CH01 CH06 CH11)	40	9	6 Mbps
N(HT20) Mode (CH01 CH06 CH11)	40	9	11 Mbps
N(HT40) Mode (CH03 CH06 CH9)	30	3	MCS 8
AX(HE20) Mode (CH01 CH06 CH11)	40	9	MCS 8
AX(HE40) Mode (CH03 CH06 CH9)	30	3	MCS 8

2.6 Block Diagram of Test Setup



2.7 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

2.8 Modifications

No modifications were implemented to meet testing criteria.

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

MAXLAB Testing Co.,Ltd.

1/F, Building B, Xinshidai GR Park, Shiyan Street, Bao'an District, Shenzhen, Guangdong, 518052, People's Republic of China

3.2 Test Facility

FCC-Registration No.: 562200 Designation Number: CN1338

MAXLAB Testing Co.,Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

Industry Canada Registration Number. Is: 11093A CAB identifier: CN0019

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing.

A2LA-Lab Cert. No.: 4707.01

MAXLAB Testing Co.,Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Radiated Emission:

Temperature:	25 ° C
Humidity:	45 %
Atmospheric pressure:	950-1050mbar

Conducted testing:

Temperature:	25 ° C
Humidity:	44 %
Atmospheric pressure:	950-1050mbar

AC Power Conducted Emission

Temperature:	24 ° C
Humidity:	44 %
Atmospheric pressure:	950-1050mbar

3.4 Test Description

FCC PART 15.247		
FCC Part 15.207	AC Power Conducted Emission	PASS
FCC Part 15.247(a)(2)	6dB Bandwidth & 99% Bandwidth	PASS
FCC Part 15.247(d)	Spurious RF Conducted Emission	PASS
FCC Part 15.247(b)	Maximum Peak Conducted Output Power	PASS
FCC Part 15.247(e)	Power Spectral Density	PASS
FCC Part 15.109/ 15.205/ 15.209	Radiated Emissions	PASS
FCC Part 15.247(d)	Band Edge	PASS
FCC Part 15.203/15.247 (b)	Antenna Requirement	PASS

Data Rate Used:

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel
Maximum Peak Conducted Output Power Power Spectral Density 6dB Bandwidth Spurious RF conducted emission Radiated Emission 9KHz~1GHz& Radiated Emission 1GHz~10 th Harmonic	11b/DSSS	1 Mbps	1/6/11
	11g/OFDM	6 Mbps	1/6/11
	11n(HT20)/OFDM	MCS 8	1/6/11
	11n(HT40)/OFDM	MCS 8	3/6/9
	11ax(HE20)/OFDMA	MCS 8	1/6/11
	11ax(HE40)/OFDMA	MCS 8	3/6/9
Band Edge	11b/DSSS	1 Mbps	1/11
	11g/OFDM	6 Mbps	1/11
	11n(HT20)/OFDM	MCS 8	1/11
	11n(HT40)/OFDM	MCS 8	3/9
	11ax(HE20)/OFDMA	MCS 8	1/11
	11ax(HE40)/OFDMA	MCS 8	3/9

3.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the MAXLAB Testing Co.,Ltd.quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for MAXLAB Testing Co.,Ltd.

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	9KHz~30MHz	3.82 dB	(1)
Radiated Emission	30~1000MHz	4.06 dB	(1)
Radiated Emission	1~18GHz	5.14 dB	(1)

Radiated Emission	18-40GHz	5.38 dB	(1)
Conducted Disturbance	0.15~30MHz	2.14 dB	(1)
Transmitter power conducted	1~40GHz	0.57 dB	(1)
Conducted spurious emission	1~40GHz	1.60 dB	(1)
OBW	1~40GHz	25 Hz	(1)
PSD	1~40GHz	0.02 dBm	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.6 Equipments Used during the Test

Conducted Emission					
Test Equipment	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
Shielding Room	ZhongYu Electron	7.3(L)YS-302.1(W)x2.9(H)	MAX252	2025-10-20	2026-10-19
EMI Test Receiver	R&S	ESCI 7	MAX552	2025-10-20	2026-10-19
Coaxial Switch	ANRITSU CORP	MP59B	MAX225	2025-10-20	2026-10-19
ENV216 2-L-V-NETZNACHB.DE	ROHDE&SCHWARZ	ENV216	MAX226	2025-10-20	2026-10-19
Coaxial Cable	MAX	N/A	MAX227	N/A	N/A
EMI Test Software	AUDIX	E3	N/A	N/A	N/A
Thermo meter	KTJ	TA328	MAX233	2025-10-20	2026-10-19
Absorbing clamp	Elektronik-Feinmechanik	MDS21	MAX229	2025-10-20	2026-10-19
LISN	R&S	ENV216	308	2025-10-20	2026-10-19
LISN	R&S	ENV216	314	2025-10-20	2026-10-19

Radiation Test equipment					
Test Equipment	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	MAX250	2025-10-20	2026-10-19
Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	MAX251	N/A	N/A
EMI Test Receiver	Rohde & Schwarz	ESU26	MAX203	2025-10-20	2026-10-19
BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	MAX214	2025-10-20	2026-10-19
Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	MAX208	2025-10-20	2026-10-19
Horn Antenna	ETS-LINDGREN	3160	MAX217	2025-10-20	2026-10-19
EMI Test Software	AUDIX	E3	N/A	N/A	N/A
Coaxial Cable	MAX	N/A	MAX213	2025-10-20	2026-10-19
Coaxial Cable	MAX	N/A	MAX211	2025-10-20	2026-10-19
Coaxial cable	MAX	N/A	MAX210	2025-10-20	2026-10-19
Coaxial Cable	MAX	N/A	MAX212	2025-10-20	2026-10-19
Amplifier(100kHz-3GHz)	HP	8347A	MAX204	2025-10-20	2026-10-19
Amplifier(2GHz-20GHz)	HP	84722A	MAX206	2025-10-20	2026-10-19


Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	MAX218	2025-10-20	2026-10-19
Band filter	Amindeon	82346	MAX219	2025-10-20	2026-10-19
Power Meter	Anritsu	ML2495A	MAX540	2025-10-20	2026-10-19
Power Sensor	Anritsu	MA2411B	MAX541	2025-10-20	2026-10-19
Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	MAX575	2025-10-20	2026-10-19
Splitter	Agilent	11636B	MAX237	2025-10-20	2026-10-19
Loop Antenna	ZHINAN	ZN30900A	MAX534	2025-10-20	2026-10-19
Breitband hornantenne	SCHWARZBECK	BBHA 9170	MAX579	2025-10-20	2026-10-19
Amplifier	TDK	PA-02-02	MAX574	2025-10-20	2026-10-19
Amplifier	TDK	PA-02-03	MAX576	2025-10-20	2026-10-19
PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	MAX578	2025-10-20	2026-10-19

RF Conducted Test:					
Test Equipment	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
MXA Signal Analyzer	Agilent	N9020A	MAX566	2025-10-20	2026-10-19
EMI Test Receiver	R&S	ESCI 7	MAX552	2025-10-20	2026-10-19
Spectrum Analyzer	Agilent	E4440A	MAX533	2025-10-20	2026-10-19
MXG vector Signal Generator	Agilent	N5182A	MAX567	2025-10-20	2026-10-19
ESG Analog Signal Generator	Agilent	E4428C	MAX568	2025-10-20	2026-10-19
USB RF Power Sensor	DARE	RPR3006W	MAX569	2025-10-20	2026-10-19
RF Switch Box	Shongyi	RFSW3003328	MAX571	2025-10-20	2026-10-19
Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	MAX572	2025-10-20	2026-10-19

4 TEST CONDITIONS AND RESULTS

4.1 AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2020.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2020
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2020
- 4 The EUT received power from AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit


For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST RESULTS

Note: 802.11b/802.11g/802.11n (HT20)/ax (HE20)/ 802.11n (HT40)/ax (HE40) Mode all have been tested, only worse case 802.11b 2412Mhz mode is reported.




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1890	18.67	16.73	35.40	64.08	-28.68	QP	P
2	0.2400	14.10	16.72	30.82	52.10	-21.28	AVG	P
3	0.2813	17.25	16.71	33.96	60.78	-26.82	QP	P
4	0.3750	11.99	16.70	28.69	48.39	-19.70	AVG	P
5 *	0.8340	11.02	16.64	27.66	46.00	-18.34	AVG	P
6	1.1408	12.54	16.60	29.14	56.00	-26.86	QP	P
7	1.5405	8.49	16.55	25.04	46.00	-20.96	AVG	P
8	2.7375	0.16	16.38	16.54	46.00	-29.46	AVG	P
9	3.1075	3.07	16.32	19.39	56.00	-36.61	QP	P
10	4.6310	-1.45	16.14	14.69	56.00	-41.31	QP	P
11	4.9740	-4.56	16.10	11.54	46.00	-34.46	AVG	P
12	6.5022	0.67	15.81	16.48	60.00	-43.52	QP	P

Note:1).Level (dBuV)= Reading (dBuV)+ Factor (dB)

2). Factor (dB)=insertion loss of LISN (dB) + Cable loss (dB)

3). Margin(dB) = Limit (dBuV) - Level (dBuV)



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Level (dBμV)	Limit (dBμV)	Margin (dB)	Detector	P/F
1	0.1609	18.87	17.53	36.40	65.42	-29.02	QP	P
2	0.2085	14.20	17.53	31.73	53.26	-21.53	AVG	P
3	0.2637	17.79	17.53	35.32	61.31	-25.99	QP	P
4	0.3120	12.95	17.52	30.47	49.92	-19.45	AVG	P
5	0.4776	15.82	17.52	33.34	56.38	-23.04	QP	P
6 *	0.6045	12.33	17.51	29.84	46.00	-16.16	AVG	P
7	0.9960	9.67	17.51	27.18	46.00	-18.82	AVG	P
8	1.6586	11.53	17.49	29.02	56.00	-26.98	QP	P
9	1.7565	7.12	17.48	24.60	46.00	-21.40	AVG	P
10	3.0795	0.53	17.43	17.96	46.00	-28.04	AVG	P
11	3.1115	7.59	17.43	25.02	56.00	-30.98	QP	P
12	5.1184	6.56	17.38	23.94	60.00	-36.06	QP	P

Note:1).Level (dBμV)= Reading (dBμV)+ Factor (dB)


2). Factor (dB)=insertion loss of LISN (dB) + Cable loss (dB)

3). Margin(dB) = Limit (dBμV) - Level (dBμV)


4.2 Radiated Emission

TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz, Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz, Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz, Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

$$Transd=AF +CL-AG$$

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power.

The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.

Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	$20\log(2400/F(KHz))+40\log(300/3)$	$2400/F(KHz)$
0.49-1.705	3	$20\log(24000/F(KHz))+ 40\log(30/3)$	$24000/F(KHz)$
1.705-30	3	$20\log(30)+ 40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150


216-960	3	46.0	200
Above 960	3	54.0	500


TEST RESULTS

Remark:

1. This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
2. All three channels (lowest/middle/highest) of each mode were measured below 1GHz and recorded worst case at 802.11b low channel.
3. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.
4. The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

For 30MHz-1GHz





For 1GHz to 25GHz

Note: 802.11b/802.11g/802.11n (HT20)/ax (HE20)/ 802.11n (HT40)/ax (HE40) Mode all have been tested, only worse case 802.11b mode is reported **(above 1GHz)**

Frequency(MHz):			2412		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4824.00	56.05	PK	74	17.95	60.41	32.40	5.11	41.87	-4.36
4824.00	45.97	AV	54	8.03	50.33	32.40	5.11	41.87	-4.36
7236.00	55.16	PK	74	18.84	55.79	36.58	6.43	43.64	-0.63
7236.00	45.03	AV	54	8.97	45.66	36.58	6.43	43.64	-0.63

Frequency(MHz):			2412		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4824.00	56.16	PK	74	17.84	60.52	32.40	5.11	41.87	-4.36
4824.00	45.98	AV	54	8.02	50.34	32.40	5.11	41.87	-4.36
7236.00	54.79	PK	74	19.21	55.42	36.58	6.43	43.64	-0.63
7236.00	45.00	AV	54	9.00	45.63	36.58	6.43	43.64	-0.63

Frequency(MHz):			2437		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4874.00	56.90	PK	74	17.10	60.85	32.56	5.34	41.85	-3.95
4874.00	46.69	AV	54	7.31	50.64	32.56	5.34	41.85	-3.95
7311.00	55.18	PK	74	18.82	55.54	36.54	6.81	43.71	-0.36
7311.00	45.25	AV	54	8.75	45.61	36.54	6.81	43.71	-0.36

Frequency(MHz):			2437		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4874.00	56.57	PK	74	17.43	60.52	32.56	5.34	41.85	-3.95
4874.00	46.40	AV	54	7.60	50.35	32.56	5.34	41.85	-3.95
7311.00	55.05	PK	74	18.95	55.41	36.54	6.81	43.71	-0.36
7311.00	44.90	AV	54	9.10	45.26	36.54	6.81	43.71	-0.36

Frequency(MHz):			2462		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4924.00	57.09	PK	74	16.91	60.55	32.73	5.64	41.83	-3.46
4924.00	47.28	AV	54	6.72	50.74	32.73	5.64	41.83	-3.46
7386.00	55.36	PK	74	18.64	55.42	36.50	7.23	43.79	-0.06
7386.00	45.20	PK	54	8.80	45.26	36.50	7.23	43.79	-0.06

Frequency(MHz):			2462		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4924.00	56.78	PK	74	17.22	60.24	32.73	5.64	41.83	-3.46
4924.00	46.88	AV	54	7.12	50.34	32.73	5.64	41.83	-3.46
7386.00	55.06	PK	74	18.94	55.12	36.50	7.23	43.79	-0.06
7386.00	45.20	PK	54	8.80	45.26	36.50	7.23	43.79	-0.06

- 1) Emission level (dBuV/m) = Meter Reading+ antenna Factor+ cable loss- preamp factor.
- 2) Margin value = Limits-Emission level.
- 3) -- Mean the PK detector measured value is below average limit.
- 4) The other emission levels were very low against the limit.
- 5) RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.

Results of Band Edges Test (Radiated)

Note: 802.11b/802.11g/802.11n (HT20)/ax (HE20)/ 802.11n (HT40)/ax (HE40) Mode all have been tested, only worse case 802.11b mode is reported.

Test Frequency(MHz):			Lowest channel		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2310.00	49.92	PK	74	24.08	60.34	27.42	4.31	42.15	-10.42
2310.00	39.84	AV	54	14.16	50.26	27.42	4.31	42.15	-10.42
2390.00	48.12	PK	74	25.88	58.41	27.55	4.35	42.19	-10.29
2390.00	37.97	AV	54	16.03	48.26	27.55	4.35	42.19	-10.29
2400.00	45.43	PK	74	28.57	55.62	27.70	4.39	42.28	-10.19
2400.00	35.33	AV	54	18.67	45.52	27.70	4.39	42.28	-10.19

Test Frequency(MHz):			Lowest channel		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2310.00	48.23	PK	74	25.77	58.65	27.42	4.31	42.15	-10.42
2310.00	37.99	AV	54	16.01	48.41	27.42	4.31	42.15	-10.42
2390.00	45.36	PK	74	28.64	55.65	27.55	4.35	42.19	-10.29
2390.00	34.97	AV	54	19.03	45.26	27.55	4.35	42.19	-10.29
2400.00	43.22	PK	74	30.78	53.41	27.70	4.39	42.28	-10.19
2400.00	33.33	AV	54	20.67	43.52	27.70	4.39	42.28	-10.19

Test Frequency(MHz):			Highest channel		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	44.82	PK	74	29.18	55.45	27.55	4.38	42.56	-10.63
2483.50	35.34	AV	54	18.66	45.97	27.55	4.38	42.56	-10.63
2500.00	42.78	PK	74	31.22	53.51	27.69	4.46	42.88	-10.73
2500.00	32.53	AV	54	21.47	43.26	27.69	4.46	42.88	-10.73

Test Frequency(MHz):			Highest channel		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	42.11	PK	74	31.89	52.74	27.55	4.38	42.56	-10.63
2483.50	32.49	AV	54	21.51	43.12	27.55	4.38	42.56	-10.63
2500.00	39.51	PK	74	34.49	50.24	27.69	4.46	42.88	-10.73
2500.00	30.09	AV	54	23.91	40.82	27.69	4.46	42.88	-10.73

Note:

- 1) Emission level (dBuV/m) = Meter Reading+ antenna Factor+ cable loss- preamp factor.
- 2) Margin value = Limits-Emission level.
- 3) -- Mean the PK detector measured value is below average limit.
- 4) The other emission levels were very low against the limit.
- 5) RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.

4.3 Maximum Peak Conducted Output Power

Limit

The Maximum Peak Output Power Measurement is 30dBm.

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power sensor.

Test Configuration



Test Results

Type	Channel	Output power PK (dBm)	Limit (dBm)	Result
802.11b	01	7.56	30.00	Pass
	06	4.85		
	11	7.63		
802.11g	01	6.85	30.00	Pass
	06	6.45		
	11	6.35		
802.11n(HT20)	01	5.45	30.00	Pass
	06	5.85		
	11	5.61		
802.11n(HT40)	03	4.52	30.00	Pass
	06	4.26		
	09	4.14		
802.11ax (HT20)	01	5.12	30.00	Pass
	06	5.21		
	11	5.34		
802.11ax (HT40)	03	4.05	30.00	Pass
	06	4.21		
	09	4.11		

Note:

- 1) Measured output power at difference data rate for each mode and recorded worst case for each mode.
- 2) Test results including cable loss.
- 3) Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; MCS 8 at IEEE 802.11n HT20; MCS 8 at IEEE 802.11n HT40; MCS 8 at IEEE 802.11ax HE20; MCS 8 at IEEE 802.11ax HE40.
- 4) Duty Cycle Factor : 0dB

4.4 Power Spectral Density

Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW ≥ 3 kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Set the span to 1.5 times the DTS channel bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
11. The resulting peak PSD level must be 8dBm.

Test Configuration



Test Results

Type	Channel	Power Spectral Density (dBm/3KHz)	Limit (dBm/3KHz)	Result
802.11b	01	-21.324	8.00	Pass
	06	-20.973		
	11	-20.178		
802.11g	01	-21.402	8.00	Pass
	06	-20.171		
	11	-19.403		
802.11n(HT20)	01	-18.895	8.00	Pass
	06	-19.242		
	11	-19.428		
802.11n(HT40)	03	-21.999	8.00	Pass
	06	-22.829		
	09	-20.720		
802.11ax (HE20)	01	-18.946	8.00	Pass
	06	-19.038		
	11	-17.446		
802.11ax (HE40)	03	-16.598	8.00	Pass
	06	-18.561		
	09	-18.799		

Note:

- 1) Measured peak power spectrum density at difference data rate for each mode and recorded worst case for each mode.
- 2) Test results including cable loss;
- 3) Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; MCS 8 at IEEE 802.11n HT20; MCS 8 at IEEE 802.11n HT40; MCS 8 at IEEE 802.11ax HE20; MCS 8 at IEEE 802.11ax HE40.

Please refer to following plots;

802.11b



802.11g



CH01




CH01



CH06



CH06




CH11




CH11




802.11n(HT20)




802.11n(HT40)




CH01



CH03



CH06




CH06



CH11

CH09


802.11ax(HE20)



802.11ax(HE40)



CH01




CH03



CH06



CH06



CH11

CH09

4.5 6dB Bandwidth and 99% Bandwidth

Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz

Test Procedure

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot$ RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

6dB

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 300 KHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 300 KHz RBW and 910 KHz VBW for 802.11b/g/n/ax20, 510 KHz RBW and 1.6 MHz VBW for 802.11n/ax40, record the 99% bandwidth.

Test Configuration



Test Results

Type	Channel	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (KHz) 6dB Bandwidth	Result
802.11b	01	10.12	14.977	≥500	Pass
	06	10.11	14.963		
	11	10.11	14.960		
802.11g	01	16.53	16.629	≥500	Pass
	06	16.54	16.683		
	11	16.53	16.611		
802.11n(HT20)	01	17.66	17.739	≥500	Pass
	06	17.67	17.734		
	11	17.65	17.735		
802.11n(HT40)	03	36.43	36.218	≥500	Pass
	06	36.44	36.241		
	09	36.43	36.213		
802.11ax(HE20)	01	17.67	17.719	≥500	Pass
	06	17.67	17.759		
	11	17.66	17.719		
802.11ax(HE40)	03	36.43	36.220	≥500	Pass
	06	36.43	36.285		
	09	36.42	36.169		

Note:

- 1) Measured peak power spectrum density at difference data rate for each mode and recorded worst case for each mode.
- 2) Test results including cable loss;
- 3) Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; MCS 8 at IEEE 802.11n HT20; MCS 8 at IEEE 802.11n HT40; MCS 8 at IEEE 802.11ax HE20; MCS 8 at IEEE 802.11ax HE40.


Please refer to following plots;

6dB Bandwidth

802.11b



802.11g




CH01




CH01



CH06



CH06




CH11




CH11



802.11n(HT20)




802.11n(HT40)




CH01




CH03



CH06




CH06



CH11

CH09


802.11ax(HE20)



802.11ax(HE40)




CH01




CH03



CH06



CH06



CH11


CH09

99% Bandwidth

802.11b



802.11g



CH01



CH01



CH06




CH06




CH11

CH11

802.11n(HT20)



802.11n(HT40)




CH01




CH03



CH06




CH06




CH11

CH09


802.11ax(HE20)




802.11ax(HE40)



CH01




CH03



CH06



CH06



CH11

CH09

4.6 Out-of-band Emissions

Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

Test Procedure

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector, and max hold. Measurements utilizing these setting are made of the in-band reference level, bandedge and out-of-band emissions.

Test Configuration




Test Results

Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandage measurement data. And record the worst data in the report.

Test plot as follows:

Mode	Channel	OOB Emission Frequency (MHz)	OOB Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result
IEEE 802.11b	1	2398.92	-33.896	-18.77	-15.126	PASS
		2400.00	-34.617	-18.77	-15.847	PASS
		24196.0	-24.906	-18.77	-6.136	PASS
	6	21287.0	-25.985	-20.73	-5.255	PASS
	11	2483.50	-37.053	-20.14	-16.913	PASS
		24605.5	-27.690	-20.14	-7.550	PASS
IEEE 802.11g	1	2398.27	-33.417	-23.69	-9.727	PASS
		2400.00	-33.744	-23.69	-10.054	PASS
		24721.0	-25.830	-23.69	-2.140	PASS
	6	21300.7	-26.506	-25.27	-1.236	PASS
	11	2483.50	-37.166	-25.33	-11.836	PASS
		24614.2	-27.319	-25.33	-1.989	PASS
IEEE 802.11n_HT20	1	2400.00	-35.111	-25.37	-9.741	PASS
		21253.9	-27.716	-25.37	-2.346	PASS
	6	24691.6	-27.554	-25.5	-2.054	PASS
	11	2483.50	-37.649	-25.44	-12.209	PASS
		21258.2	-26.110	-25.44	-0.670	PASS
IEEE 802.11n_HT40	3	2400.00	-34.855	-24.8	-10.055	PASS
		24611.1	-27.512	-24.8	-2.712	PASS
	6	21240.8	-26.709	-26.42	-0.289	PASS
	9	2483.50	-37.990	-26.03	-11.960	PASS
		24785.9	-27.727	-26.03	-1.697	PASS
IEEE 802.11ax_HE20	1	2400.00	-35.756	-24.82	-10.936	PASS
		24613.0	-28.193	-24.82	-3.373	PASS
	6	24818.3	-28.510	-24.71	-3.800	PASS
	11	2483.50	-38.804	-23.89	-14.914	PASS
		24652.3	-28.310	-23.89	-4.420	PASS
IEEE 802.11ax_HE40	3	2400.00	-36.930	-28.31	-8.620	PASS
		24935.1	-28.735	-28.31	-0.425	PASS
	6	24129.2	-28.546	-28.05	-0.496	PASS
	9	2483.50	-38.909	-27.87	-11.039	PASS
		24158.5	-28.569	-27.87	-0.698	PASS


IEEE 802.11b_Channel 1




IEEE 802.11b_Channel 6




In-Band Reference Level



In-Band Reference Level



Out Of Band Emission



30.0 MHz - 25000.0 MHz

30.0 MHz - 25000.0 MHz


IEEE 802.11b_Channel 11




IEEE 802.11g_Channel 1




In-Band Reference Level




In-Band Reference Level



Out Of Band Emission




Out Of Band Emission



30.0 MHz - 25000.0 MHz

30.0 MHz - 25000.0 MHz


IEEE 802.11g_Channel 6




IEEE 802.11g_Channel 11



In-Band Reference Level




In-Band Reference Level



30.0 MHz - 25000.0 MHz




Out Of Band Emission



30.0 MHz - 25000.0 MHz


IEEE 802.11n(HT20)_Channel 1




IEEE 802.11n(HT20)_Channel 6




In-Band Reference Level



In-Band Reference Level



Out Of Band Emission



30.0 MHz - 25000.0 MHz

30.0 MHz - 25000.0 MHz


IEEE 802.11n(HT20)_Channel 11




IEEE 802.11n(HT40)_Channel 3




In-Band Reference Level




In-Band Reference Level



Out Of Band Emission



Out Of Band Emission



30.0 MHz - 25000.0 MHz

30.0 MHz - 25000.0 MHz


IEEE 802.11n(HT40)_Channel 6




IEEE 802.11n(HT40)_Channel 9



In-Band Reference Level




In-Band Reference Level



30.0 MHz - 25000.0 MHz



Out Of Band Emission



30.0 MHz - 25000.0 MHz


IEEE 802.11ax(HE20)_Channel 1




IEEE 802.11ax(HE20)_Channel 6




In-Band Reference Level



In-Band Reference Level



Out Of Band Emission




30.0 MHz - 25000.0 MHz

30.0 MHz - 25000.0 MHz


IEEE 802.11ax(HE20)_Channel 11




IEEE 802.11ax(HE40)_Channel 3




In-Band Reference Level




In-Band Reference Level



Out Of Band Emission




Out Of Band Emission




30.0 MHz - 25000.0 MHz

30.0 MHz - 25000.0 MHz


IEEE 802.11ax(HE40)_Channel 6




IEEE 802.11ax(HE40)_Channel 9




In-Band Reference Level



In-Band Reference Level



30.0 MHz - 25000.0 MHz



30.0 MHz - 25000.0 MHz

4.7 Duty Cycle Of Test Signal

Standard Requirement

Pre-analysis Check: While conducting average power measurement, duty cycle of each mode shall be checked to ensure its duty cycle in order to compensate for the loss due to insufficient ratio of duty cycle.

All duty cycle is pre-scanned, and result as obtained below shows only the most representative ones where duty cycle is conducted as the given transmission with given virtual operation that expresses the percentage.

Formula

Duty Cycle = $T_{on} / (T_{on} + T_{off})$

Test Procedure

1. Set span = Zero
2. RBW = 8MHz
3. VBW = 8MHz,
4. Detector = Peak


Test Result

Mode	Data rates	Channel	On Time (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Factor (dB)
IEEE 802.11b	1	1	20.000	20.000	100	0
		6	20.000	20.000	100	0
		11	20.000	20.000	100	0
IEEE 802.11g	6	1	20.000	20.000	100	0
		6	20.000	20.000	100	0
		11	20.000	20.000	100	0
IEEE 802.11n(HT20)	MCS 8	1	20.000	20.000	100	0
		6	20.000	20.000	100	0
		11	20.000	20.000	100	0
IEEE 802.11n(HT40)	MCS 8	3	20.000	20.000	100	0
		6	20.000	20.000	100	0
		9	20.000	20.000	100	0
IEEE 802.11ax(HE20)	MCS 8	1	20.000	20.000	100	0
		6	20.000	20.000	100	0
		11	20.000	20.000	100	0
IEEE 802.11ax(HE40)	MCS 8	3	20.000	20.000	100	0
		6	20.000	20.000	100	0
		9	20.000	20.000	100	0


802.11b




802.11g




CH01




CH01




CH06



CH06




CH11



CH11




802.11n(HT20)





CH01

802.11n(HT40)




CH03



CH06


CH06




CH11

CH09

802.11ax(HE20)



802.11ax(HE40)




CH01




CH03



CH06



CH06



CH11

CH09

4.8 Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Test Result:

The maximum gain of antenna was 1.73 dBi.

Remark: The antenna gain is provided by the customer, if the data provided by the customer is not accurate, MAXLAB Testing Co.,Ltd. does not assume any responsibility.

5 Test Setup Photos of the EUT

Reference to the appendix I for details.

6 Photos of the EUT

Reference to the appendix II for details.

***** End of Report *****