


Test Report

Product name : 3.1.2 Channel Dolby Atmos Sound Bar with Wireless Subwoofer
Trademark : TCL
Model no. : A65K
Series Model(s) : N/A
FCC ID : 2BEHEA65K
Report No : C251107024-RF02
Test Standards : CFR47 FCC Part 15: Subpart C Section 15.247
CFR47 FCC Part 15: Subpart C Section 15.207
CFR47 FCC Part 15: Subpart C Section 15.209
Applicant : TCL OVERSEAS MARKETING LTD.
Address of applicant : Unit 1905, 19/F, Nan Fung Centre, 264-298 Castle Peak Road, Tsuen Wan, New Territories, Hong Kong
Manufacturer : TCL OVERSEAS MARKETING LTD
Manufacturer Address : Unit 1905, 19/F, Nan Fung Centre, 264-298 Castle Peak Road, Tsuen Wan, New Territories, Hong Kong
Date of Test Date : Nov 07, 2025 to Nov 18, 2025
Date of issue : Dec 22, 2025
Test result : Compliance

Prepared By


:



Adil Yang/Engineer

Reviewed By

:



Greg Zhang/Engineer

Approved By

:



Tom Gan/Manager

The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of preparer, reviewer and approver. Any objections must be raised to CSIC within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	Dec 22, 2025	Initial Issue	ALL	Adil Yang

Table of Contents

	Page
1. TEST SUMMARY	4
1.1. TEST DESCRIPTION	4
1.2. TEST FACILITY	5
1.3. MEASUREMENT UNCERTAINTY	5
2. GENERAL INFORMATION	6
2.1. GENERAL DESCRIPTION OF EUT	6
2.2. DESCRIPTION OF TEST MODES AND TEST FREQUENCY	7
2.3. MEASUREMENT INSTRUMENTS LIST	8
2.4. DESCRIPTION OF THE TEST MODES	9
2.5. TEST SOFTWARE AND POWER LEVEL	10
2.6. BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.7. DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS	11
2.8. ENVIRONMENTAL CONDITIONS FOR TESTING	11
3. EMC TEST	12
3.1. CONDUCTED EMISSION ON AC MAINS MEASUREMENT	12
3.2. RADIATED SPURIOUS EMISSION MEASUREMENT	15
3.3. RESTRICTED BANDS MEASUREMENT	25
3.4. CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHz BANDWIDTH MEASUREMENT	28
3.5. CONDUCTED POWER SPECTRAL DENSITY MEASUREMENT	29
3.6. 6dB BANDWIDTH MEASUREMENT	30
3.7. 99% BANDWIDTH MEASUREMENT	31
3.8. MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT	32
3.9. ANTENNA REQUIREMENT	34
4. TEST PHOTOS	35
5. EUT PHOTOS	36

1. TEST SUMMARY

1.1. TEST DESCRIPTION

Test procedures according to the technical standards:

Item	Clause	Result	Note
Conducted Emission on AC Mains	Part 15.207(a)	PASS	
Maximum Conducted Output Power	Part 15.247(b)(3)	PASS	
Radiated Spurious Emission	Part 15.247(c) Part 15.205	PASS	
Conducted Spurious Emissions Measured in 100 kHz Bandwidth	Part 15.247(d)	PASS	
Conducted Power Spectral Density	Part 15.247(e)	PASS	
6dB Bandwidth	Part 15.247(a)(2)	PASS	
Antenna Requirement	Part 15.247(b)(4) Part 15.203	PASS	

Note:

- 1) "N/A" denotes test is not applicable in this Test Report.
- 2) All tests are according to ANSI C63.10-2020.
- 3) The statements of test result on the above are decided by the request of test standard only; the measurement uncertainties are not factored into this compliance determination.
- 4) The information of measurement uncertainty is available upon the customer's request.

1.2. TEST FACILITY

Shenzhen Central Standard International Center Co., Ltd. (CSIC)

Room 201, Building 1, Mogen Fashion Industrial Park, No. 10, Shilongzai Road, Xinshi Community, Dalang Street, Longhua District, Shenzhen.

The test facility is recognized, certified or accredited by the following organizations:

CNAS Registration No.: L11671

FCC Registration No.: 0031378433 Designation Number: CN1317

IC CAB identifier: CN0051

A2LA Lab Cert. No.: 6426.01

1.3. MEASUREMENT UNCERTAINTY

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table.

Below is the best measurement capability for Shenzhen Central Standard International Center Co., Ltd.

Test Items	Measurement Uncertainty	Notes
RF output power, conducted	$\pm 1.06\text{dB}$	(1)
Unwanted Emissions, conducted	$\pm 1.32\text{dB}$	(1)
All emissions, radiated 9KHz-30MHz	$\pm 4.86\text{dB}$	(1)
All emissions, radiated 30-1GHz	$\pm 4.86\text{dB}$	(1)
All emissions, radiated 1G-6GHz	$\pm 5.08\text{dB}$	(1)
All emissions, radiated >6G	$\pm 5.30\text{dB}$	(1)
Conducted Emission (9KHz-150KHz)	$\pm 3.18\text{dB}$	(1)
Conducted Emission (150KHz-30MHz)	$\pm 3.20\text{dB}$	(1)

Note(1): This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

2. GENERAL INFORMATION

2.1. GENERAL DESCRIPTION OF EUT

EUT(Product Specifications)	
Product Name:	3.1.2 Channel Dolby Atmos Sound Bar with Wireless Subwoofer
Model:	A65K
Series Model(s):	N/A
Power supply:	24.0 VDC, 2.5A
Hardware version:	A65K
Software version:	V09
Technical Specification of Bluetooth LE	
Frequency Range:	2402 MHz to 2480 MHz
Type of Modulation:	GFSK
Channel Number:	40 channels
Data Rate:	1 Mbps, 2 Mbps
Channel Separation:	2 MHz
Antenna Type:	FPC Antenna
Antenna Gain:	2.85 dBi.
Technical Specification of SRD	
Frequency Range:	2402 MHz to 2480 MHz
Type of Modulation:	GFSK
Channel Number:	40 channels
Data Rate:	1 Mbps, 2 Mbps
Channel Separation:	2 MHz
Antenna Type:	FPC Antenna
Antenna Gain:	2.92 dBi.
Remark:	

Adapter information	
Product Name:	AC/DC ADAPTER
Model No:	KA65E-2402500P
Input Power:	AC 100-240V 50/60Hz 1.5A max
Output Power:	DC 24.0V 2.5A, 60.0W
Manufacturer:	SHENZHEN KEYU POWER SUPPLY TECHNOLOGY CO., LTD.

Note:

1. For a more detailed features description, please refer to the manufacture's specifications or the user's manual.
2. Full tests were applied to the sample(C251107024-Y01/04) only in this document.

2.2. DESCRIPTION OF TEST MODES AND TEST FREQUENCY

The EUT has been tested under typical operating conditions. The Applicant provides communication tools software to control the EUT for staying in continuous transmitting mode for testing.

Operation Frequency List for Bluetooth Low Energy and SRD:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402.00	10	2422.00
1	2404.00	11	2424.00
2	2406.00	12	2426.00
3	2408.00	13	2428.00
4	2410.00	14	2430.00
5	2412.00	15	2432.00
6	2414.00	16	2434.00
7	2416.00	17	2436.00
8	2418.00	18	2438.00
9	2420.00	19	2440.00
20	2442.00	30	2462.00
21	2444.00	31	2464.00
22	2446.00	32	2466.00
23	2448.00	33	2468.00
24	2450.00	34	2470.00
25	2452.00	35	2472.00
26	2454.00	36	2474.00
27	2456.00	37	2476.00
28	2458.00	38	2478.00
29	2460.00	39	2480.00

For Bluetooth Low Energy and SRD		
Test Channel	EUT Channel	Test Frequency (MHz)
lowest	CH00	2402
middle	CH19	2440
highest	CH39	2480

2.3. MEASUREMENT INSTRUMENTS LIST

RF Connected Test					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	Spectrum Analyzer	Agilent	N9020A	MY50200391	May. 25, 2026
2	Spectrum Analyzer	Agilent	N9020A-526	MY55330012	Apr. 25, 2026
3	Spectrum Analyzer	R&S	FSV40	101401	Mar. 04, 2026
4	Vector Signal Generator	Agilent	N5182A	MY50140130	May. 24, 2026
5	Signal Generator	R&S	SMCV100B	103780	May. 24, 2026
6	Automatic control unit	MW	MW100-RFCB	MY54250020	May. 24, 2026
7	EXTENDED RANGE DC POWER SUPPLY	TAKASAGO	ZX-400LA	428710060166	May. 24, 2026
8	Inverter power supply	AKE	AKE-2003-P2	N/A	May. 24, 2026
9	Programmable constant temperature and humidity chamber	Angui	AG1000L	2304061049	Jul. 24, 2026
10	MTS 8310E	MW	V2.0.0.0		

Radiation Test equipment					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	Spectrum Analyzer	Agilent	N9020A	MY50200391	May. 25, 2026
2	Spectrum Analyzer	R&S	FSV40	101401	Mar. 04, 2026
3	Amplifier	EMCO	EM330	980204	May. 25, 2026
4	Amplifier	COM-MW	DPA8-1000-18000-1012	8220837	Mar. 04, 2026
5	Amplifier	SKET	LNPA_1840-50	SK201801801	Feb. 20, 2026
6	Loop Antenna	Schwarzbeck	FMZB1519B	00023	Oct.20, 2028
7	Bilog Antenna	Sunol Sciences	JB1	n.a.	Jul.10, 2027
8	Horn Antenna	COM-MW	ZAB-1-18G-50	20171109	Jun.03, 2026
9	Horn Antenna	COM-MW	ZLB7-18-40G-777	3231081	Mar.28, 2026
10	Cable 6m-1	XINQY	XQY-CLA520-NJ-SMAJ-6M	25051772	May.23, 2026
11	Cable 1m	JunCoax	JA800-NMSM-1M	N/A	May.23, 2026
12	Cable-005	SUCOFLEX	104PEA4M	N/A	May.23, 2026
13	3M Chamber	Maor	9*6*6	--	Aug.16, 2028
14	EZ-EMC	Farad	V3.1		

Mains Terminal Disturbance Voltage Test equipment					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	EMI Test Receiver	R&S	ESCI3	101413	Mar.04, 2026
2	LISN	R&S	ENV216	100002	Mar.04, 2026
3	LISN	MEB	NNB 42	---	May.25, 2026
4	Cable 1.8m-1	XINQY	XQY-CMR200-NJ-BNCJ-1.8M	---	May.23, 2026
5	Shielding Room	Maor	8*4*3	--	Aug.14, 2028
6	EZ-EMC	Fara	V3.1		

Note:

- 1) The cable loss has calculated in test result which connection between each test instruments.

2.4. DESCRIPTION OF THE TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Worst Mode	Description	Data Rate
Mode 1	TX CH0	1 Mbps
Mode 2	TX CH19	1 Mbps
Mode 3	TX CH39	1 Mbps
Mode 4	TX CH0	2 Mbps
Mode 5	TX CH19	2 Mbps
Mode 6	TX CH39	2 Mbps

Note:

- 1) The measurements are performed at the high, middle, low available channels.
- 2) All the bit rate of transmitter have been tested and found the lowest rate is found to be the worst case and recorded.
- 3) This test was performed with EUT in X, Y, Z position and worst case was found when EUT in X position.
- 4) For radiated emission above 1 GHz test, 1GHz-25GHz have been pre-tested and in this report only recorded the worst case. The remaining spurious points are all below the limit value of 20dB.

For AC Conducted Emission

Test Case	
AC Conducted Emission	Mode7: Working


2.5. TEST SOFTWARE AND POWER LEVEL

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.

Test Software Version	BT FCC Tool V2.24 for Bluetooth		
Frequency	2402MHz	2440MHz	2480MHz
BLE 1M	4	4	4
BLE 2M	4	4	4
Test Software Version	bt_tool_v1.1.2 for SRD		
Frequency	2402MHz	2440MHz	2480MHz
SRD 1M	4	4	4
SRD 2M	4	4	4

2.6. BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

a. Radiated Spurious Emission Test



b. Conducted Emission Test



2.7. DESCRIPTION OF NECESSARY ACCESSORIES AND SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Necessary accessories					
Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
N/A	N/A	N/A	N/A	N/A	N/A

Support units					
Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
E-2	Notebook	DELL	Vostro 3400	N/A	N/A
E-3	Mobile Phone	XiaoMi	Redmi K70	C33018fb	N/A
C-1	USB Cable	N/A	100cm	N/A	N/A
C-2	HDMI Cable	N/A	150cm	N/A	N/A

Note:

- 1) The support equipment was authorized by Declaration of Confirmation.
- 2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.8. ENVIRONMENTAL CONDITIONS FOR TESTING

Test Item	Temperature (°C)	Relative Humidity (%)	Test Voltage	Tested by
Conducted Emission on AC Mains	24.6	54.0	101.2	Sean Chen
Radiated Spurious Emission	26.9	49.0	100.9	Fiona Huang
Conducted Spurious Emissions Measured in 100 kHz Bandwidth	26.9	49.0	100.9	Fiona Huang
Conducted Power Spectral Density	26.9	49.0	100.9	Fiona Huang
99% Bandwidth	26.9	49.0	100.9	Fiona Huang
6dB Bandwidth	26.9	49.0	100.9	Fiona Huang
Maximum Conducted Output Power	26.9	49.0	100.9	Fiona Huang

3. EMC TEST

3.1. Conducted Emission on AC Mains Measurement

Limit

Operating frequency band. In case the emission fall within the restricted band specified on Part 207(a) limit in the table below has to be followed.

FREQUENCY (MHz)	Conducted Emission limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56 *	56 - 46 *
0.5 - 5	56	46
5 - 30	60	50

Note:

- 1) The tighter limit applies at the band edges.
- 2) The limit of “ * ” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
RBW	9 kHz

Test Procedure

- a) The EUT was 0.8 meters from the horizontal ground plane and 0.4 meters from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment's powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d) LISN at least 80 cm from nearest part of EUT chassis.
- e) For the actual test configuration, please refer to the related Item –EUT Test Photos.

Test Setup



Note:

- 1) Support units were connected to second LISN.
- 2) Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

EUT OPERATING CONDITIONS


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

Test Results

Note: All modes have been tested, and the report only reflects the worst mode.


Test Mode :	Working	Test Voltage :	AC 120V/60Hz
-------------	---------	----------------	--------------

L



No.	Frequency (MHz)	QuasiPeak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	QuasiPeak result (dBuV)	Average result (dBuV)	QuasiPeak limit (dBuV)	Average limit (dBuV)	QuasiPeak margin (dB)	Average margin (dB)	Remark
1*	0.3820	33.98	27.54	9.73	43.71	37.27	58.23	48.24	-14.52	-10.97	Pass
2P	0.7180	19.20	8.21	9.71	28.91	17.92	56.00	46.00	-27.09	-28.08	Pass
3P	0.9900	14.20	6.89	9.72	23.92	16.61	56.00	46.00	-32.08	-29.39	Pass
4P	4.4540	19.52	14.59	9.82	29.34	24.41	56.00	46.00	-26.66	-21.59	Pass
5P	13.1380	16.93	11.94	9.86	26.79	21.80	60.00	50.00	-33.21	-28.20	Pass
6P	17.5940	15.04	10.33	9.87	24.91	20.20	60.00	50.00	-35.09	-29.80	Pass

N



No.	Frequency (MHz)	QuasiPeak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	QuasiPeak result (dBuV)	Average result (dBuV)	QuasiPeak limit (dBuV)	Average limit (dBuV)	QuasiPeak margin (dB)	Average margin (dB)	Remark
1P	0.2580	31.88	13.14	9.76	41.64	22.90	61.49	51.50	-19.85	-28.60	Pass
2*	0.3820	35.48	29.36	9.79	45.27	39.15	58.23	48.24	-12.96	-9.09	Pass
3P	0.7140	17.82	11.18	9.81	27.63	20.99	56.00	46.00	-28.37	-25.01	Pass
4P	4.4540	19.20	14.64	10.34	29.54	24.98	56.00	46.00	-26.46	-21.02	Pass
5P	12.9900	17.45	12.24	10.51	27.96	22.75	60.00	50.00	-32.04	-27.25	Pass
6P	28.7500	14.52	10.08	10.72	25.24	20.80	60.00	50.00	-34.76	-29.20	Pass

Correction Factor = insertion loss of LISN + cable loss;

Reading = Reading Amplitude in the instrument;

Result = Correction Factor + Reading;

Margin = Result – Limit

3.2. Radiated Spurious Emission Measurement

Limit

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205 (a)&209(a) limit in the table and according to ANSI C63.10-2013 below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (Below 1GHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- 1) The limit for radiated test was performed according to FCC PART 15C.
- 2) The tighter limit applies at the band edges.
- 3) Emission level (dBuV/m)=20log Emission level (uV/m).

For Radiated Emission	
Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP/AVG
Start Frequency	9 KHz/150KHz(Peak/QP/AVG)
Stop Frequency	150KHz/30MHz(Peak/QP/AVG)
RB / VB (emission in restricted band)	200Hz (From 9kHz to 0.15MHz)/
	9KHz (From 0.15MHz to 30MHz);
	200Hz (From 9kHz to 0.15MHz)/
	9KHz (From 0.15MHz to 30MHz)
Attenuation	Auto
Detector	Peak/QP
Start Frequency	30 MHz(Peak/QP)
Stop Frequency	1000 MHz (Peak/QP)
RB / VB (emission in restricted band)	120 kHz / 300 kHz

Attenuation	Auto
Detector	Peak/AVG
Start Frequency	1000 MHz(Peak/AVG)
Stop Frequency	10th carrier hamonic(Peak/AVG)
RB / VB (emission in restricted band)	1 MHz / 3 MHz(Peak)
	1 MHz/1/T MHz(AVG)

For Restricted band	
Spectrum Parameter	Setting
Detector	Peak/AVG
Start/Stop Frequency	Lower Band Edge: 2310 to 2410 MHz
	Upper Band Edge: 2476 to 2500 MHz
RB / VB	1 MHz / 3 MHz(Peak)
	1 MHz/1/T MHz(AVG)
Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for Peak & AVG
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for Peak & AVG
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

Test Procedure

- The measuring distance of at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz,and above 1GHz.
- The EUT was placed on the top of a rotating table 0.8 meters (above 1GHz is 1.5 m) above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m(above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then QuasiPeak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

DEVIATION FROM TEST STANDARD


No deviation.

Test Setup


1. Radiated Emission Test-Up Frequency Below 30MHz



2. Radiated Emission Test-Up Frequency 30MHz~1GHz



3. Radiated Emission Test-Up Frequency Above 1GHz



EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.5 Unless otherwise a special operating condition is specified in the follows during the testing.


Test Result

Below 1GHz:

All modes have been tested, and the report only reflects the worst mode.


Test Mode: Working

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (deg.)	Height (cm)	Remark
1	92.9973	45.06	-17.46	27.60	43.50	-15.90	---	---	QP
2	170.1887	41.32	-11.85	29.47	43.50	-14.03	---	---	QP
3	185.1625	42.57	-13.30	29.27	43.50	-14.23	---	---	QP
4	270.6161	42.40	-12.08	30.32	46.00	-15.68	---	---	QP
5*	542.6104	38.21	-5.62	32.59	46.00	-13.41	---	---	QP
6	925.6132	30.35	1.26	31.61	46.00	-14.39	---	---	QP

Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correction factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (deg.)	Height (cm)	Remark
1*	34.0450	48.30	-12.37	35.93	40.00	-4.07	---	---	QP
2	56.4662	43.75	-11.96	31.79	40.00	-8.21	---	---	QP
3	91.0574	48.82	-17.79	31.03	43.50	-12.47	---	---	QP
4	286.2653	40.49	-11.70	28.79	46.00	-17.21	---	---	QP
5	350.9721	39.83	-9.75	30.08	46.00	-15.92	---	---	QP
6	624.4696	34.32	-3.50	30.82	46.00	-15.18	---	---	QP

Correction Factor = antenna factor + cable loss – amplifier gain;

Reading = Reading Amplitude in the instrument;

Result = Correction Factor + Reading;

Margin = Result – Limit.

Above 1GHz (BLE):
BLE 1M
GFSK-Low Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6066	56.6	-11.66	44.94	80.72	-35.78	peak
2	6950	55.73	-7.15	48.58	80.72	-32.14	peak
3	8208	56.8	-6.95	49.85	74	-24.15	peak
4	9024	55.96	-6.35	49.61	74	-24.39	peak
5	9602	55.38	-5.85	49.53	80.72	-31.19	peak
6	10078	55.34	-4.47	50.87	80.72	-29.85	peak

GFSK-Low Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6066	57.23	-11.66	45.57	80.72	-35.15	peak
2	6984	55.51	-6.86	48.65	80.72	-32.07	peak
3	8106	56.13	-6.64	49.49	74	-24.51	peak
4	8990	56.24	-6.39	49.85	80.72	-30.87	peak
5	9602	56.03	-5.85	50.18	80.72	-30.54	peak
6	10350	55	-4.09	50.91	80.72	-29.81	peak

GFSK- Middle Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4910	57.53	-14.06	43.47	74	-30.53	peak
2	6066	56.64	-11.66	44.98	80.72	-35.74	peak
3	6950	55.91	-7.15	48.76	80.72	-31.96	peak
4	8072	54.84	-6.53	48.31	74	-25.69	peak
5	8922	55.83	-6.59	49.24	80.72	-31.48	peak
6	9602	55.23	-5.85	49.38	80.72	-31.34	peak

GFSK-Middle Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6542	56.53	-10.38	46.15	80.72	-34.57	peak
2	6950	55.74	-7.15	48.59	80.72	-32.13	peak
3	7732	55.92	-7.56	48.36	74	-25.64	peak
4	8174	55.32	-6.85	48.47	74	-25.53	peak
5	9058	55.92	-6.34	49.58	74	-24.42	peak
6	9772	57.05	-5.23	51.82	80.72	-28.9	peak

GFSK-High Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4740	57.95	-14.22	43.73	74	-30.27	peak
2	5998	57.07	-11.75	45.32	80.72	-35.4	peak
3	6984	55.41	-6.86	48.55	80.72	-32.17	peak
4	7732	56	-7.56	48.44	74	-25.56	peak
5	8242	55.82	-7	48.82	74	-25.18	peak
6	9024	55.97	-6.35	49.62	74	-24.38	peak

GFSK-High Vertical

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5080	58.32	-14.32	44	74	-30	peak
2	6372	57.57	-11.05	46.52	80.72	-34.2	peak
3	6950	56.93	-7.15	49.78	80.72	-30.94	peak
4	8106	57.28	-6.64	50.64	74	-23.36	peak
5	8990	55.84	-6.39	49.45	80.72	-31.27	peak
6	9908	56.75	-4.84	51.91	80.72	-28.81	peak

BLE 2M

GFSK-Low Horizontal

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4706	58.26	-14.27	43.99	74	-30.01	peak
2	6032	57.73	-11.7	46.03	80.72	-34.69	peak
3	6984	56.36	-6.86	49.5	80.72	-31.22	peak
4	8276	56.97	-7.09	49.88	74	-24.12	peak
5	9024	55.68	-6.35	49.33	74	-24.67	peak
6	10078	53.38	-4.47	48.91	80.72	-31.81	peak

GFSK-Low Vertical

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	6984	56.21	-6.86	49.35	80.72	-31.37	peak
2	7732	55.28	-7.56	47.72	74	-26.28	peak
3	8208	56.73	-6.95	49.78	74	-24.22	peak
4	8990	55.91	-6.39	49.52	80.72	-31.2	peak
5	9602	56.16	-5.85	50.31	80.72	-30.41	peak
6	10044	55.15	-4.55	50.6	80.72	-30.12	peak

GFSK- Middle Horizontal

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5964	56.64	-11.89	44.75	80.72	-35.97	peak
2	6950	56.56	-7.15	49.41	80.72	-31.31	peak
3	7732	55.27	-7.56	47.71	74	-26.29	peak
4	8072	55.32	-6.53	48.79	74	-25.21	peak
5	8786	55.7	-6.98	48.72	80.72	-32	peak
6	9568	56.05	-5.95	50.1	80.72	-30.62	peak

GFSK-Middle Vertical

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	5998	56.63	-11.75	44.88	80.72	-35.84	peak
2	6984	56.32	-6.86	49.46	80.72	-31.26	peak
3	7732	55.43	-7.56	47.87	74	-26.13	peak
4	8412	56.17	-7.53	48.64	74	-25.36	peak
5	9024	55.87	-6.35	49.52	74	-24.48	peak
6	9772	56.58	-5.23	51.35	80.72	-29.37	peak

GFSK-High Horizontal

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	4910	58.18	-14.06	44.12	74	-29.88	peak
2	6984	56	-6.86	49.14	80.72	-31.58	peak
3	7732	55.97	-7.56	48.41	74	-25.59	peak
4	8276	56.5	-7.09	49.41	74	-24.59	peak
5	8990	56.08	-6.39	49.69	80.72	-31.03	peak
6	9432	55.48	-6.2	49.28	74	-24.72	peak

GFSK-High Vertical

No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
1	3176	63.94	-18.85	45.09	80.72	-35.63	peak
2	3686	61.13	-16.64	44.49	74	-29.51	peak
3	6950	55.73	-7.15	48.58	80.72	-32.14	peak
4	7936	55.03	-6.57	48.46	80.72	-32.26	peak
5	8990	56.34	-6.39	49.95	80.72	-30.77	peak
6	9738	54.52	-5.36	49.16	80.72	-31.56	peak

Node:

- 1、Testing was carried out within frequency range 9kHz to the tenth harmonics. The measurement results below 30MHz and 18GHz - 26.5GHz were greater than 20dB below the limit, so only the radiated spurious emissions from 30MHz to 18GHz were reported..
- 2、Radiated emissions measured in frequency above 1GHz were made with an instrument using peak/average detector mode.
- 3、Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4、Margin (dB), result in dBuV/m – limit in dBuV/m.
- 5、According to section part 15.247(d), frequencies other than those required by part 15.205(a) are limited to the level of the intended emission (min. 100.72 dBuV/m = $P_{min}(dBm) + 95.2$, where $P_{min}(dBm)$ is Restrict Band(This value(5.521dBm) comes from the image Restrict Band NVNT BLE 2M 2480MHz Peak) of Appendix A) minus 20dB.

**Above 1GHz (SRD):
SRD 1M**
GFSK-Low Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6338	56.88	-11.13	45.75	77.90	-32.15	peak
2	6984	55.55	-6.86	48.69	77.90	-29.21	peak
3	7596	55.64	-8.22	47.42	74	-26.58	peak
4	8072	55.35	-6.53	48.82	74	-25.18	peak
5	8990	56.24	-6.39	49.85	77.90	-28.05	peak
6	9398	55	-6.22	48.78	74	-25.22	peak

GFSK-Low Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4804.048	63.42	-14.22	49.2	54	-4.8	AVG
2	4808	65.87	-14.21	51.66	74	-22.34	peak
3	6984	55.67	-6.86	48.81	77.90	-29.09	peak
4	7936	54.83	-6.57	48.26	77.90	-29.64	peak
5	8344	55.95	-7.31	48.64	74	-25.36	peak
6	9024	56.13	-6.35	49.78	74	-24.22	peak
7	9398	55.2	-6.22	48.98	74	-25.02	peak

GFSK- Middle Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6984	55.81	-6.86	48.95	77.90	-28.95	peak
2	8106	55.8	-6.64	49.16	74	-24.84	peak
3	8276	56	-7.09	48.91	74	-25.09	peak
4	8990	56.02	-6.39	49.63	77.90	-28.27	peak
5	9738	54.58	-5.36	49.22	77.90	-28.68	peak
6	10350	54.44	-4.09	50.35	77.90	-27.55	peak

GFSK-Middle Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4876	65.97	-14.09	51.88	74	-22.12	peak
2	6950	55.96	-7.15	48.81	77.90	-29.09	peak
3	7732	55.33	-7.56	47.77	74	-26.23	peak
4	8242	55.67	-7	48.67	74	-25.33	peak
5	9058	56.59	-6.34	50.25	74	-23.75	peak
6	9670	54.09	-5.64	48.45	77.90	-29.45	peak

GFSK-High Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6712	55.35	-9.05	46.3	77.90	-31.6	peak
2	6984	55.15	-6.86	48.29	77.90	-29.61	peak
3	7902	54.5	-6.78	47.72	77.90	-30.18	peak
4	8548	56.46	-7.68	48.78	77.90	-29.12	peak
5	8820	55.69	-6.88	48.81	77.90	-29.09	peak

6	9364	54.68	-6.24	48.44	74	-25.56	peak
---	------	-------	-------	-------	----	--------	------

GFSK-High Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6950	55.95	-7.15	48.8	77.90	-29.1	peak
2	7426	56	-8.4	47.6	74	-26.4	peak
3	8276	55.5	-7.09	48.41	74	-25.59	peak
4	9024	55.8	-6.35	49.45	74	-24.55	peak
5	9398	55.02	-6.22	48.8	74	-25.2	peak
6	10044	54.05	-4.55	49.5	77.90	-28.4	peak

SRD 2M

GFSK-Low Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6916	56	-7.44	48.56	77.90	-29.34	peak
2	7732	55.38	-7.56	47.82	74	-26.18	peak
3	8174	55.45	-6.85	48.6	74	-25.4	peak
4	8412	55.61	-7.53	48.08	74	-25.92	peak
5	8990	56.61	-6.39	50.22	77.90	-27.68	peak
6	9364	54.84	-6.24	48.6	74	-25.4	peak

GFSK-Low Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4808	65.81	-14.21	51.6	74	-22.4	peak
2	6950	56	-7.15	48.85	77.90	-29.05	peak
3	7732	55.19	-7.56	47.63	74	-26.37	peak
4	8378	56.5	-7.42	49.08	74	-24.92	peak
5	8990	55.8	-6.39	49.41	77.90	-28.49	peak
6	9738	54.08	-5.36	48.72	77.90	-29.18	peak

GFSK- Middle Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6984	55.79	-6.86	48.93	77.90	-28.97	peak
2	8072	56.11	-6.53	49.58	74	-24.42	peak
3	8378	56.19	-7.42	48.77	74	-25.23	peak
4	9024	56.46	-6.35	50.11	74	-23.89	peak
5	9398	54.94	-6.22	48.72	74	-25.28	peak
6	10044	54.25	-4.55	49.7	77.90	-28.2	peak

GFSK-Middle Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4876	64.96	-14.09	50.87	74	-23.13	peak
2	6950	56.49	-7.15	49.34	77.90	-28.56	peak
3	8106	55.37	-6.64	48.73	74	-25.27	peak
4	8786	55.72	-6.98	48.74	77.90	-29.16	peak
5	9024	55.91	-6.35	49.56	74	-24.44	peak

6	9738	54.23	-5.36	48.87	77.90	-29.03	peak
---	------	-------	-------	-------	-------	--------	------

GFSK-High Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6984	55.68	-6.86	48.82	77.90	-29.08	peak
2	7494	56.02	-8.76	47.26	74	-26.74	peak
3	8106	55.91	-6.64	49.27	74	-24.73	peak
4	9058	55.63	-6.34	49.29	74	-24.71	peak
5	9364	55.92	-6.24	49.68	74	-24.32	peak
6	9806	54.26	-5.13	49.13	77.90	-28.77	peak

GFSK-High Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4944	65.38	-14.01	51.37	74	-22.63	peak
2	6984	56.31	-6.86	49.45	77.90	-28.45	peak
3	7732	55.11	-7.56	47.55	74	-26.45	peak
4	8208	56.15	-6.95	49.2	74	-24.8	peak
5	9058	55.76	-6.34	49.42	74	-24.58	peak
6	9364	55.09	-6.24	48.85	74	-25.15	peak

Node:

- 1、Testing was carried out within frequency range 9kHz to the tenth harmonics. The measurement results below 30MHz and 18GHz - 26.5GHz were greater than 20dB below the limit, so only the radiated spurious emissions from 30MHz to 18GHz were reported..
- 2、Radiated emissions measured in frequency above 1GHz were made with an instrument using peak/average detector mode.
- 3、Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4、Margin (dB), result in dBuV/m – limit in dBuV/m.
- 5、According to section part 15.247(d), frequencies other than those required by part 15.205(a) are limited to the level of the intended emission (min. 97.90dBuV/m = $P_{min}(dBm) + 95.2$, where $P_{min}(dBm)$ is Restrict Band(This value(2.700dBm) comes from the image Restrict Band NVNT SRD 2M 2480MHz Ant1 Peak) of Appendix A) minus 20dB.

3.3. Restricted Bands Measurement

Limit

For FCC:

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

Restricted Frequency Band (MHz)	Distance Meters(at 3m)	
	Peak (dBuV/m)	Average (dBuV/m)
2310 to 2390	74	54
2483.5 to 2500	74	54
	Peak (dBm) ^{Note1}	Average (dBm) ^{Note1}
2310 to 2390	-21.20	-41.20
2483.5 to 2500	-21.20	-41.20

Note:

1. $E = \text{EIRP} - 20 \log d + 104.8$

Where, E is the electric field strength in dBuV/m; EIRP is the equivalent isotropically radiated power in dBm; d is the specified measurement distance in m.

2. According the ANSI C63.10 11.12.2 antenna-port conducted measurements may also be used as an alternative to radiated measurements for determining compliance in the restricted frequency bands requirements. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case emissions is required.

Test Procedure

Radiated measurement
1. Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
3. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.

4. The Peak Value and average value both need to comply with applicable limit above 1 GHz.
5. Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
6. For the actual test configuration, please see the test setup photo.

Conducted measurement

1. Measure the conducted output power (in dBm) using the detector specified by the appropriate regulatory agency (see 11.12.2.3 through 11.12.2.5 for guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
2. Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP (see 11.12.2.6 for guidance on determining the applicable antenna gain).
3. Add the appropriate maximum ground reflection factor to the EIRP (6 dB for frequencies ≤ 30 MHz; 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive; and 0 dB for frequencies > 1000 MHz).
4. For MIMO devices, measure the power of each chain and sum the EIRP of all chains in linear terms (i.e., watts and mW).
5. Convert the resultant EIRP to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20 \log d + 104.8$$

Where,

E is the electric field strength in dBuV/m.


EIRP is the equivalent isotropically radiated power in dBm.

d is the specified measurement distance in m.

6. Compare the resultant electric field strength level with the applicable regulatory limit.

7. Perform the radiated spurious emission test.

Test Configuration



The EUT is connected to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

Test Results

Pass

Please refer to Appendix A.

Remark: The test uses antenna-port conducted measurements as an alternative to radiated measurements for determining compliance in the restricted frequency bands requirements.

3.4. Conducted Spurious Emissions Measured in 100 kHz Bandwidth Measurement

Limit

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

Test Procedure

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold
For Band edge	
Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2327 – 2427 MHz
	Upper Band Edge: 2447 – 2547 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

Test Configuration



The EUT is connected to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.5 Unless otherwise a special operating condition is specified in the follows during the testing.

Test Results

Pass

Please refer to Appendix A.

3.5. Conducted Power Spectral Density Measurement

Limits

Test Item	Limit	Frequency Range (MHz)	Result
Power Spectral Density	$\leq 8 \text{ dBm(RBW} \geq 3\text{KHz)}$	2400-2483.5	PASS

Test Procedure

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW to: $100 \text{ kHz} \geq \text{RBW} \geq 3 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP



EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.5 Unless otherwise a special operating condition is specified in the follows during the testing.

Test Results

Pass

Please refer to Appendix A.

3.6. 6dB BANDWIDTH Measurement

Limits

Test Item	Limit	Frequency Range (MHz)	Result
Bandwidth	≥500KHz	2400-2483.5	PASS

Test Procedure

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW- 3RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be- 6 dB.

TEST SETUP



EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.5 Unless otherwise a special operating condition is specified in the follows during the testing.

Test Results

Pass

Please refer to Appendix A.

3.7. 99% BANDWIDTH Measurement

Limits

Section	Test Item	Limit	Frequency Range (MHz)
RSS-Gen 6.7	99% Bandwidth	--	2400-2483.5

Test Procedure

The EUT was operating in Bluetooth mode and controlled its channel. Printed out the test result from the

spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 1%-5% OBW(43KHz).

Set the video bandwidth (VBW) =130 kHz.

Set Span=4MHz

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

Allow the trace to stabilize.

Use the 99 % power bandwidth function of the instrument.

Measure the maximum width of the emission.

Measure and record the results in the test report.

TEST SETUP



EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.5 Unless otherwise a special operating condition is specified in the follows during the testing.

Test Results

Pass

Please refer to Appendix A.

3.8. Maximum Conducted Output Power Measurement

Limits

Section	Test Item	Limit	Frequency Range (MHz)
15.247 (b)(3)	Output Power	1 watt or 30dBm	2400-2483.5
RSS-247 5.4(d) RSS-Gen 6.12	EIRP	36dBm	2400-2483.5

Test Procedure

Some regulatory agencies permit the maximum conducted (average) output power to be measured as an alternative to the maximum peak conducted output power for determining compliance to the limit. When this option is exercised, the measured power is to be referenced to the OBW rather than to the DTS bandwidth (see 11.2 for definitions and 6.9.2 for measurement guidance).

When using a spectrum analyzer or EMI receiver to perform these measurements, it shall be capable of utilizing a number of measurement points in each sweep that is greater than or equal to twice the span / RBW, to set a bin-to-bin spacing of $\leq \text{RBW} / 2$ so that narrowband signals are not lost between frequency bins. If possible, configure or modify the operation of the EUT so that it transmits continuously at its maximum power control level (see 11.6).

The intent is to test at 100% duty cycle; however, a small reduction in duty cycle (to no lower than 98%) is permitted, if required by the EUT for amplitude control purposes. Manufacturers are expected to provide software to the test laboratory to permit such continuous operation.

If continuous transmission (or at least 98% duty cycle) cannot be achieved because of hardware limitations (e.g., overheating), the EUT shall be operated at its maximum power control level, with the transmit duration as long as possible, and the duty cycle as high as possible during which sweep triggering/signal gating techniques may be used to perform the measurement over the transmission duration.

Measurement using a power meter (PM):

1. Method AVGPM:

Method AVGPM is a measurement using an RF average power meter, as follows:

a) As an alternative to spectrum analyzer or EMI receiver measurements, measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied:

- 1) The EUT is configured to transmit continuously, or to transmit with a constant duty cycle.
- 2) At all times when the EUT is transmitting, it shall be transmitting at its maximum power control level.
- 3) The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.

b) If the transmitter does not transmit continuously, measure the duty cycle, D, of the transmitter output signal as described in 11.6.

c) Measure the average power of the transmitter. This measurement is an average over both the ON and OFF periods of the transmitter.


d) Adjust the measurement in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle.

2. Method AVGPM-G:

Method AVGPM-G is a measurement using a gated RF average power meter.

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

TEST SETUP



EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.5 Unless otherwise a special operating condition is specified in the follows during the testing.

Test Results

Pass

Please refer to Appendix A.

3.9. ANTENNA REQUIREMENT

STANDARD REQUIREMENT

According to the manufacturer declared, the EUT has FPC Antenna (For Bluetooth and SRD), the directional gain of antenna is antenna Gain: 2.85 dBi for Bluetooth and 2.92 dBi for SRD, and the antenna connector is designed with a reverse polarity socket and does not consider replacement. Therefore, the EUT is considered sufficient to comply with the provision.

EUT ANTENNA

The FPC Antenna for Bluetooth. It complies with the standard requirement.



The FPC Antenna for SRD. It complies with the standard requirement.



4. TEST PHOTOS

Please refer to Appendix D Test Setup.

5. EUT PHOTOS

External Photos Please refer to Appendix B and Internal Photos Please refer to Appendix C.

*****THE END*****