

FCC PART 15E TEST REPORT FOR CERTIFICATION On Behalf of

TCL OVERSEAS MARKETING LTD

1. 11.1.4 Channel Dolby Atmos Sound Bar with Wireless Subwoofer and Satellite Speakers
2. 7.1.2 Channel Dolby Atmos Sound Bar with Wireless Subwoofer
3. 7.1.2 Channel Dolby Atmos Sound Bar with Built-in Subwoofer

Model Number: 1. Q95K; 2. Q85K; 3. Q75K

Additional Model:

1. Q95K-UK, Q95K Pro, Q90K, Q91K, Q92K, Q93K, Q94K, Q9CK, Q91C, Q9CC, Q95KS, Q9*****, (* can be any numerica number "0~9" or alphebtical number "A~Z" or blank)
2. Q85K-UK, Q85K Pro, Q80K, Q81K, Q82K, Q83K, Q84K, Q8CK, Q81C, Q8CC, Q85KS, Q8*****, (* can be any numerica number "0~9" or alphebtical number "A~Z" or blank)
3. Q75K-UK, Q75K Pro, Q70K, Q71K, Q72K, Q73K, Q74K, Q7CK, Q71C, Q7CC, Q75KS, Q7*****, (* can be any numerica number "0~9" or alphebtical number "A~Z" or blank)

FCC ID: 2BEHEQ95K



Applicant:	TCL OVERSEAS MARKETING LTD
Address:	Unit 1905,19/F, Nan Fung Centre, 264-298 Castle Peak Road,
	Tsuen Wan, New Territories,Hong Kong
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan,
	Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2606125
Date of Test:	Apr. 16, 2026 to Jun. 02, 2026
Date of Report:	Jun. 08, 2026

TABLE OF CONTENTS

Description	Page
TEST REPORT VERIFICATION.....	3
1. GENERAL INFORMATION	5
1.1. Description of Device (EUT).....	5
1.2. The antenna information for EUT	6
1.3. Information of RF Cable	6
2. SUMMARY OF TEST	7
2.1. Summary of test result	7
2.2. Test Facilities.....	8
2.3. Measurement uncertainty for EST Technology Co., Ltd.....	9
2.4. Assistant equipment used for test	9
2.5. Block Diagram	9
2.6. Test Mode	10
2.7. Channel List.....	11
2.8. Power Setting of Test Software	12
2.9. Duty Cycle of Test Signal	12
2.10. Test Equipment List.....	13
3. 6dB BANDWIDTH & 26dB BANDWIDTH & 99% OCCUPIED BANDWIDTH	15
3.1. Limit.....	15
3.2. Test Setup.....	15
3.3. Spectrum Analyzer Setting.....	15
3.4. Test Procedure.....	16
3.5. Test Result.....	16
4. MAXIMUM CONDUCTED OUTPUT POWER	17
4.1. Limit.....	17
4.2. Test Setup.....	17
4.3. Spectrum Analyzer Setting.....	17
4.4. Test Procedure.....	18
4.5. Test Result.....	18
5. PEAK POWER SPECTRAL DENSITY	19
5.1. Limit.....	19
5.2. Test Setup.....	19
5.3. Spectrum Analyzer Setting.....	19
5.4. Test Procedure.....	19
5.5. Test Result.....	19
6. UNWANTED EMISSIONS AND BAND EDGE	20
6.1. Limit.....	20
6.2. Test Setup.....	21
6.3. Spectrum Analyzer Setting.....	22
6.4. Test Procedure.....	23
6.5. Test Result.....	24
7. FREQUENCY STABILITY	63
7.1. Limit.....	63
7.2. Test Setup.....	63

7.3. Spectrum Analyzer Setting.....	63
7.4. Test Procedure.....	64
7.5. Test Result.....	64
8. AC POWER LINE CONDUCTED EMISSIONS	65
8.1. Limit.....	65
8.2. Test Setup.....	65
8.3. Spectrum Analyzer Setting.....	65
8.4. Test Procedure.....	65
8.5. Test Result.....	66
9. ANTENNA REQUIREMENTS.....	68
9.1. Limit.....	68
9.2. Test Result.....	68
10. TEST SETUP PHOTO.....	69
11. EUT PHOTO	72

Applicant:	TCL OVERSEAS MARKETING LTD		
Address:	Unit 1905,19/F, Nan Fung Centre, 264-298 Castle Peak Road, Tsuen Wan, New Territories,Hong Kong		
Manufacturer:	TCL OVERSEAS MARKETING LTD		
Address:	Unit 1905,19/F, Nan Fung Centre, 264-298 Castle Peak Road, Tsuen Wan, New Territories,Hong Kong		
E.U.T:	1. 11.1.4 Channel Dolby Atmos Sound Bar with Wireless Subwoofer and Satellite Speakers 2. 7.1.2 Channel Dolby Atmos Sound Bar with Wireless Subwoofer 3. 7.1.2 Channel Dolby Atmos Sound Bar with Built-in Subwoofer		
Model Number:	1. Q95K; 2. Q85K; 3. Q75K		
Additional Model:	1. Q95K-UK, Q95K Pro, Q90K, Q91K, Q92K, Q93K, Q94K, Q9CK, Q91C, Q9CC, Q95KS, Q9***** (* can be any numerica number "0~9" or alphebtical number "A~Z" or blank) 2. Q85K-UK, Q85K Pro, Q80K, Q81K, Q82K, Q83K, Q84K, Q8CK, Q81C, Q8CC, Q85KS, Q8***** (* can be any numerica number "0~9" or alphebtical number "A~Z" or blank) 3. Q75K-UK, Q75K Pro, Q70K, Q71K, Q72K, Q73K, Q74K, Q7CK, Q71C, Q7CC, Q75KS, Q7***** (* can be any numerica number "0~9" or alphebtical number "A~Z" or blank)		
Power Supply:	AC 100-240V ,50/60Hz		
Trade Name:	TCL	Serial No.:	-----
Date of Receipt:	Apr. 16, 2026	Date of Test:	Apr. 16, 2026 to Jun. 02, 2026
Test Specification:	FCC Part 15 Subpart E 15.407 ANSI C63.10:2020 FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01 FCC KDB 662911 D01 Multiple Transmitter Output v02r01		
Test Result:	The device described above is tested by EST Technology Co., Ltd. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the FCC Rules and Regulations Part 15 Subpart E requirements. This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd.		
Prepared by:	Reviewed by:	Date: Jun. 08, 2026	
 Ring Yang / Assistant	 Seven Wang / Engineer	 Iceman Hu / Manager	
Other Aspects:	None.		
Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested			
This test report is based on a single evaluation of one sample of above mentioned products, It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd. The statement of compliance in this report is based on the limit in the test standard, the measurement uncertainty is not considered.			

1.GENERAL INFORMATION

1.1.Description of Device (EUT)

FCC ID	:	2BEHEQ95K
Product Name	:	11.1.4 Channel Dolby Atmos Soundbar with Wireless Subwoofer and Satellite Speakers
Model Number	:	Q95K
Software Version	:	N/A
Hardware Version	:	N/A
Operation frequency	:	U-NII-1: 5150 MHz~5250 MHz U-NII-2A: 5250 MHz~5350 MHz U-NII-2C: 5470 MHz~5725 MHz U-NII-3: 5725 MHz~5850 MHz
Number of channel	:	U-NII-1: IEEE 802.11a/ ax HE20: 4 Channels U-NII-2A: IEEE 802.11a / ax HE20: 4 Channels; U-NII-2C: IEEE 802.11a / ax HE20: 12 Channels; U-NII-3: IEEE 802.11a / ax HE20: 6 Channels
Modulation	:	OFDM
Transmit Data Rate	:	IEEE 802.11a: 54, 48, 36, 24, 18, 12, 9, 6Mbps; IEEE 802.11ax: up to 57.8Mbps;
Channels Spacing	:	IEEE 802.11a: 20MHz; IEEE 802.11ax HE20: 20MHz
Transmit Power	:	U-NII-1 IEEE 802.11a: 16.18dBm IEEE 802.11ax HE20: 17.16dBm
	:	U-NII-2A IEEE 802.11a: 19.76dBm IEEE 802.11ax HE20: 19.58dBm
	:	U-NII-2C IEEE 802.11a: 19.60dBm IEEE 802.11ax HE20: 19.03dBm
	:	U-NII-3 IEEE 802.11a: 20.50dBm IEEE 802.11ax HE20: 20.17dBm
Sample Type	:	Prototype production
Note: The product information is provided by the manufacturer. The laboratory is not responsible for this data.		

1.2.The antenna information for EUT

Ant No.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	-	-	FPC	-	4.42

Note:

- 1.The antenna gain is declared by the customer and the laboratory is not responsible for the accuracy of the antenna gain.
2. The test results of this report only apply to the sample as received.

1.3.Information of RF Cable

Cable Loss(dB)	Provided by
1.0	TCL OVERSEAS MARKETING LTD

Note:

- 1.The customer declared the loss value of the RF Cable. and the test results of this report only apply to the sample as received.
- 2.The laboratory is not responsible for the accuracy of the cable loss.

2.SUMMARY OF TEST

2.1.Summary of test result

No.	Description of Test Item	FCC Standard Section	Results
1	6dB Bandwidth & 26dB Bandwidth & 99% Occupied Bandwidth	15.407(a) 15.407(e)	PASS
2	Maximum Conducted Output Power	15.407(a)	PASS
3	Peak Power Spectral Density	15.407(a)	PASS
4	Unwanted Emissions and Band Edge	15.205 15.209 15.407(b)	PASS
5	Frequency Stability	15.407(g)	PASS
6	AC Power Line Conducted Emissions	15.207 15.407(b)(9)	PASS
7	Antenna Requirement	15.203	PASS

Note:“N/A” denotes test is not applicable in this test report.

2.2.Test Facilities

EMC Lab : Accredited by CNAS, CHINA
Registration No.: L5288
This Accreditation is valid until: November 12, 2029

Recognized by FCC, USA
Designation Number: CN1215
This Recognition is valid until: January 31, 2028

Accredited by A2LA, USA
Registration No.: 4366.01
This Accreditation is valid until: January 31, 2028

Recognized by Industry Canada
CAB identifier No.: CN0035
This Recognition is valid until: January 31, 2028

Recognized by VCCI, Japan
Registration No.:C-14103; T-20073; R-13663;
R-20103; G-20097
Date of registration: Apr. 20, 2026
This Recognition is valid until: Apr. 19, 2029

Recognized by TUV Rheinland, Germany
Registration No.: UA 50413872 0001
Date of registration: July 31, 2018

Recognized by Intertek
Registration No.: 2011-RTL-L2-64
Date of registration: November 08, 2018

Name of Firm : EST Technology Co., Ltd.

Site Location : Chilingxiang, Qishantou, Santun, Houjie, Dongguan,
Guangdong, China

2.3.Measurement uncertainty for EST Technology Co., Ltd.

Test Item	Uncertainty
Uncertainty for Conduction emission test	2.54dB
Uncertainty for spurious emissions test (Below 30MHz)	± 1.62 dB
Uncertainty for Radiation Emission test (30MHz-1GHz)	3.62
Uncertainty for Radiation Emission test (1GHz to 18GHz)	4.86
Uncertainty for spurious emissions test (18GHz to 40GHz)	4.67
Uncertainty for radio frequency	7×10^{-8}
Uncertainty for conducted RF Power	1.08dB
Uncertainty for Power density test	0.26dB
Temperature	$\pm 0.6^{\circ}\text{C}$
Humidity	± 4.0 %
Volatage DC	$\pm 1.0\%$
Volatage (AC, <10KHz)	$\pm 1.5\%$

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.


2.4.Assistant equipment used for test

Item	Equipment	Brand	Model Name/Type No.	FCC ID	Series No.
-	-	-	-	-	-

Item	Shielded Type	Ferrite Core	Length	Note
1	NO	NO	1.5m	AC Cable

2.5.Block Diagram

For radiated emissions test: EUT was placed on a turn table, which is 0.8 (or 1.5) meter high above ground.



(EUT: 11.1.4 Channel Dolby Atmos Sound Bar with Wireless Subwoofer and Satellite Speakers)

2.6.Test Mode

Pre-scan has been combined all possible modulations and data rates to determine the worst case test mode,the worst case test mode was selected for the final test as listed below.

Test Item	Test Mode	Channel	Modulation	Data rate
6dB Bandwidth	IEEE 802.11a	149/157/165	OFDM	6Mbps
	IEEE 802.11ax HE20	149/157/165	OFDM	MCS0
26dB Bandwidth	IEEE 802.11a	36/40/48/52/60/64/100/116/140/144/149/157/165	OFDM	6Mbps
	IEEE 802.11ax HE20	36/40/48/52/60/64/100/116/140/144/149/157/165	OFDM	MCS0
99% Occupied Bandwidth	IEEE 802.11a	36/40/48/52/60/64/100/116/140/144/149/157/165	OFDM	6Mbps
	IEEE 802.11ax HE20	36/40/48/52/60/64/100/116/140/144/149/157/165	OFDM	MCS0
Maximum Conducted Output Power	IEEE 802.11a	36/40/48/52/60/64/100/116/140/144/149/157/165	OFDM	6Mbps
	IEEE 802.11ax HE20	36/40/48/52/60/64/100/116/140/144/149/157/165	OFDM	MCS0
Peak Power Spectral Density	IEEE 802.11a	36/40/48/52/60/64/100/116/140/144/149/157/165	OFDM	6Mbps
	IEEE 802.11ax HE20	36/40/48/52/60/64/100/116/140/144/149/157/165	OFDM	MCS0
Unwanted Emissions and Band Edge (Above 1GHz)	IEEE 802.11a	36/40/48/52/60/64/100/116/140/144/149/157/165	OFDM	6Mbps
	IEEE 802.11ax HE20	36/40/48/52/60/64/100/116/140/144/149/157/165	OFDM	MCS0
Unwanted Emissions Below 1GHz	IEEE 802.11a	36	OFDM	6Mbps
Frequency Stability	Unmodulation	36/52/100/149	N/A	N/A
AC Power Line Conducted Emissions	IEEE 802.11a	36	OFDM	6Mbps

Note: In radiated measurement,the EUT had been pre-scan on the positioned of each 3 axis(X,Y,Z), the worst case was found when positioned on **X-plane**.

2.7.Channel List

Band	Mode	Channel	Frequency (MHz)
U-NII-1	IEEE 802.11a & ax HE20	36	5180
		40	5200
		44	5220
		48	5240
U-NII-2A	IEEE 802.11a & ax HE20	52	5260
		56	5280
		60	5300
		64	5320
U-NII-2C	IEEE 802.11a & ax HE20	100	5500
		104	5520
		108	5540
		112	5560
		116	5580
		120	5600
		124	5620
		128	5640
		132	5660
		136	5680
		140	5700
		144	5720
U-NII-3	IEEE 802.11a & ax HE20	149	5745
		153	5765
		157	5785
		161	5805
		165	5825

2.8.Power Setting of Test Software

Software Name	CMD			
U-NII-1				
Frequency(MHz)	5180	5200		5240
IEEE 802.11a Setting	16	16		16
IEEE 802.11ax HE20 Setting	16	16		16
U-NII-2A				
Frequency(MHz)	5260	5300		5320
IEEE 802.11a Setting	19	19		19
IEEE 802.11ax HE20 Setting	19	19		19
U-NII-2C				
Frequency(MHz)	5500	5580	5700	5720
IEEE 802.11a Setting	19	19	19	19
IEEE 802.11ax HE20 Setting	19	19	19	19
U-NII-3				
Frequency(MHz)	5745	5785		5825
IEEE 802.11a Setting	19	19		19
IEEE 802.11ax HE20 Setting	19	19		19

Note: This information is provided by the applicant.

2.9.Duty Cycle of Test Signal

Refer to Appendix B of Appendix FCC ID 5G Wi-Fi (the test data).

Note:

1. Duty Cycle=On Time/Total Time×100%.
2. Duty Factor=10×LOG(1/Duty Cycle).
3. If duty cycle <98 %, the conducted average output power and average power spectral density should be add duty factor.
4. If duty cycle≥98 %,the EUT is consider to be transmitting continuously,the conducted average output power and average power spectral density no need to add duty factor.
5. The on-time time is transmission duration(T).
6. The VBW Setting is use for RMS measurement in Unwanted Emissions and Band Edge(Above 1GHz) Test.

2.10.Test Equipment List

For conducted emission test

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESRP3	EST-E070	LISAI	June 11,25	June 10,26
Artificial Mains Network	Rohde & Schwarz	ENV216	EST-E048	LISAI	June 11,25	June 10,26
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	EST-E078	LISAI	June 11,25	June 10,26
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A

For radiated emission test(9kHz-30MHz)

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	EST-E047	LISAI	June 11,25	June 10,26
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	EST-E054	LISAI	June 11,25	June 10,26
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
9kHz-30MHz Cable	N/A	EST-001	N/A	N/A	N/A	N/A

For radiated emissions test (30MHz-1000MHz)

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	EST-E047	LISAI	June 11,25	June 10,26
Bilog Antenna	Teseq	CBL 6111D	EST-E034	LISAI	June 11,25	June 10,26
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
30-1000MHz Cable	N/A	EST-002	N/A	N/A	N/A	N/A

For radiated emission test(Above 1000MHz)

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
Horn Antenna	SCHWARZBECK	BBHA9120D	EST-E144	LISAI	June 11,25	June 10,26
Horn Antenna	Com-Power	AHA-840	EST-E133	LISAI	June 11,25	June 10,26
Low Noise Amplifier	RF	TRLA-010180 G45N	EST-E142	LISAI	June 11,25	June 10,26
Spectrum Analyzer	Rohde &Schwarz	FSV40	EST-E069	LISAI	June 11,25	June 10,26
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
Above 1GHz Cable	N/A	EST-003	N/A	N/A	N/A	N/A

For connect EUT antenna terminal test


Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
TS 1120	Tonscend	/	/	/	/	/
Test Software	Tonscend	JS1120-3	3.5.39	/	/	/
RF Control Unit	Tonscend	JS0806-2	EST-E134	LISAI	June 11,25	June 10,26
Signal and Spectrum Analyzer	Keysight	N9010B	EST-E141	LISAI	June 11,25	June 10,26
Temperature controller	GAOXIN	GX-3030-3 A	EST-E101	LISAI	June 11,26	June 10,27
Three-phase voltage stabilizing source	BESTEK	BEST6100 0	EST-E333	LISAI	June 11,26	June 10,27

3.6dB BANDWIDTH & 26dB BANDWIDTH & 99% OCCUPIED BANDWIDTH

3.1.Limit

Band	Frequency (MHz)	Test Item	Limit
U-NII-1	5150-5250	26dB Bandwidth&99% Occupied Bandwidth	N/A
U-NII-2A	5250-5350	26dB Bandwidth&99% Occupied Bandwidth	N/A
U-NII-2C	5470-5725	26dB Bandwidth&99% Occupied Bandwidth	N/A
U-NII-3	5725-5850	6dB Bandwidth&99% Occupied Bandwidth	6dB Bandwidth≥500KHz

3.2.Test Setup



3.3.Spectrum Analyzer Setting

6dB Bandwidth	
Spectrum Parameters	Setting
RBW	100KHz
VBW	300KHz
Span	40MHz(20MHz Bandwidth mode) 60MHz(40MHz Bandwidth mode) 120MHz(80MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

26dB Bandwidth	
Spectrum Parameters	Setting
RBW	approximately 1% of the emission bandwidth
VBW	>RBW
Span	40MHz(20MHz Bandwidth mode) 60MHz(40MHz Bandwidth mode) 120MHz(80MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

99% Occupied Bandwidth	
Spectrum Parameters	Setting
RBW	1% to 5% of the OBW
VBW	approximately three times the RBW
Span	between 1.5 times and 5.0 times the OBW
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

3.4.Test Procedure

For 26dB Bandwidth Measurement :

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 3.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, measure the maximum width of the emission that is 26 dB down from the peak of the emission.Compare this with the RBW setting of the instrument.
Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

For 6dB Bandwidth Measurement :

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 3.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

For 99% Occupied Bandwidth Measurement :

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 3.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, use the 99% power bandwidth function to measure bandwidth.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

3.5.Test Result

Refer to Appendix A1/A2/A3 of Appendix FCC ID 5G Wi-Fi (the test data).


4.MAXIMUM CONDUCTED OUTPUT POWER

4.1.Limit

Band	EUT Type	Limit
U-NII-1	Outdoor Access Point	1W(30dBm) (Max. e.i.r.p $\leq$ 125mW at any elevation angle above 30 degrees as measured from the horizon)
	Indoor Access Point	1W(30dBm)
	Fixed point-to-point Access Point	1W(30dBm)
	Mobile and Portable Client Device	250mW(23.98dBm)
U-NII-2A	All Device	250mW(23.98dBm) or 11dBm+10 log B,Which is lesser. (B is 26dB Bandwidth in MHz)
U-NII-2C	All Device	250mW(23.98dBm) or 11dBm+10 log B,Which is lesser. (B is 26dB Bandwidth in MHz)
U-NII-3	All Device	1W(30dBm)

Note: For the Band U-NII-2A and U-NII-2C,the maximum conducted output power limit calculate result refer to section 3.5.

4.2.Test Setup



4.3.Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	1MHz
VBW	3MHz
Span	40MHz(20MHz Bandwidth mode) 80MHz(40MHz Bandwidth mode) 160MHz(80MHz Bandwidth mode)
Sweep Time	Auto
Detector	RMS
Trace Mode	Max Hold

4.4.Test Procedure

- a. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- b. Spectrum analyzer setting parameters in accordance with section 4.3.
- c. Set the EUT transmit continuously with maximum output power.
- d. Use the channel power function to measure maximum peak output power, allow trace to stabilize, save test pictures.
- e. Repeat above procedures until all modes and channels were measured.
- f. Record the results in the test report.

4.5.Test Result


Refer to Appendix C of Appendix FCC ID 5G Wi-Fi (the test data).

5. PEAK POWER SPECTRAL DENSITY

5.1. Limit

Band	EUT Type	Limit
U-NII-1	Outdoor Access Point	17dBm/MHz
	Indoor Access Point	17dBm/MHz
	Fixed point-to-point Access Point	17dBm/MHz
	Mobile and Portable Client Device	11dBm/MHz
U-NII-2A	All Device	11dBm/MHz
U-NII-2C	All Device	11dBm/MHz
U-NII-3	All Device	30dBm/500KHz

5.2. Test Setup



5.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	1MHz(For U-NII-1&U-NII-2A&U-NII-2C)500KHz(For U-NII-3)
VBW	3MHz(For U-NII-1&U-NII-2A&U-NII-2C)2MHz(For U-NII-3)
Span	encompass the entire 26 dB EBW or 99% OBW of the signal
Sweep Time	Auto
Number of Sweep Point	$\geq 2 \times \text{SPAN} / \text{RBW}$
Detector	RMS(power averaging)
Trace Average	≥ 100 traces

5.4. Test Procedure

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 5.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, use the marker-to-peak function to set the marker to the average of the emission.
- If the duty cycle of test signal $< 98\%$, the result = max measured value + $10 \times \log(1/\text{duty cycle})$;
If the duty cycle of test signal $\geq 98\%$, the result = max measured value.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

5.5. Test Result

Refer to Appendix D of Appendix FCC ID 5G Wi-Fi (the test data).

6.UNWANTED EMISSIONS AND BAND EDGE

6.1.Limit

The maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

The unwanted emissions which fall in Restricted bands shall not exceed the field strength levels specified in the following table:

15.209 Radiated emission limits

Frequency (MHz)	Field Strength(μ V/m)	Distance(m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

Note:

1. $\text{dB}\mu\text{V/m} = 20\text{Log}(\mu\text{V/m})$
2. Above 1GHz the formula is used to convert the EIRP to field strength


$$E[\text{dB}\mu\text{V/m}] = \text{EIRP}[\text{dBm}] - 20 \log(d[\text{m}]) + 104.77$$

where E is field strength and d is distance at which the field strength limit is specified in the applicable requirements.


for example, 3m field strength($\text{dB}\mu\text{V/m}$)= $\text{EIRP} - 20\log(3) + 104.77 = \text{EIRP} + 95.2$

6.2.Test Setup


9kHz~30MHz



30~1000MHz



Above 1GHz



6.3.Spectrum Analyzer Setting

For 9KHz-150KHz

Spectrum Parameters	Setting
RBW	300Hz(for Peak&AVG)/CISPR 200Hz(for QP)
VBW	300Hz(for Peak&AVG)/CISPR 200Hz(for QP)
Start frequency	9KHz
Stop frequency	150KHz
Sweep Time	Auto
Detector	PEAK/QP/AVG
Trace Mode	Max Hold

Note : For 9KHz-90KHz&110KHz-150KHz,the detector is average,other frequency is CISPR QP detector.

For 150KHz-30MHz

Spectrum Parameters	Setting
RBW	9KHz
VBW	9KHz
Start frequency	150KHz
Stop frequency	30MHz
Sweep Time	Auto
Detector	QP
Trace Mode	Max Hold

Note : For 150KHz-490KHz,the detector is average,other frequency is CISPR QP detector.

For 30MHz-1GHz

Spectrum Parameters	Setting
RBW	120KHz
VBW	300KHz
Start frequency	30MHz
Stop frequency	1GHz
Sweep Time	Auto
Detector	QP
Trace Mode	Max Hold

For Above 1GHz

Spectrum Parameters	Setting	
RBW	1MHz	
VBW	PEAK Measurement	AVG Measurement
	3MHz	Duty cycle $\geq$ 98%,VBW=10Hz Duty cycle<98%,VBW $\geq$ 1/T Video bandwidth mode=RMS (power averaging)
Start frequency	1GHz	
Stop frequency	40GHz	

Sweep Time	Auto
Detector	PEAK
Trace Mode	Max Hold

Note: T is the on-time of the duty cycle, when EUT is continuously emitted Maximum output power, in seconds. Refer to Section 2.8 on time.

6.4.Test Procedure

- a. EUT was placed on a turn table, which is 0.8 meter high above ground for below 1GHz test, and which is 1.5 meter high above ground for above 1GHz test.
- b. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower.
- c. Set the EUT transmit continuously with maximum output power.
- d. The turn table can rotate 360 degrees to determine the position of the maximum emission level.
- e. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.
- f. Spectrum analyzer setting parameters in accordance with section 6.3.
- g. Repeat above procedures until all channels were measured.
- h. Record the results in the test report.
- i. IEEE 802.11a and IEEE 802.11ax HE20 all have been tested, only worst case IEEE 802.11ax HE20 is recorded.


6.5.Test Result

Radiated Emissions Below 1GHz

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 1 File: \\EMC-966-2\\test data\\2026\\Report\\RF\\TCL 多媒体\\Q95K-Soundbar-Wireless.EM6 (12)



Site no. : 2# 966 chamber Data no. : 1
Dis. / Ant. : 3m 47018 Ant. pol. : VERTICAL
Limit : FCC PART 15 E(3M)
Env. / Ins. : Temp:24.2°C;Humi:65%;Press:101.3kPa
Engineer : Eric Lin
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : TX Mode
Sample No. : EST-260410010-006
Wireless


	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	37.76	15.90	0.71	11.12	27.73	40.00	12.27	QP
2	364.65	14.64	2.54	6.79	23.97	46.00	22.03	QP
3	564.47	19.86	3.28	1.52	24.66	46.00	21.34	QP
4	745.86	21.36	3.87	2.55	27.78	46.00	18.22	QP
5	799.21	21.88	4.04	3.02	28.94	46.00	17.06	QP
6	881.66	22.50	4.28	2.03	28.81	46.00	17.19	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 2 File: \\EMC-966-2\\test data\\2026\\Report\\RF\\TCL 多媒体\\Q95K-Soundbar-Wireless.EM6 (12)



Site no. : 2# 966 chamber Data no. : 2
Dis. / Ant. : 3m 47018 Ant. pol. : HORIZONTAL
Limit : FCC PART 15 E(3M)
Env. / Ins. : Temp:24.2°C;Humi:65%;Press:101.3kPa
Engineer : Eric Lin
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : TX Mode
Sample No. : EST-260410010-006
Wireless

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	79.47	7.40	1.06	13.86	22.32	40.00	17.68	QP
2	189.08	9.14	1.74	12.66	23.54	43.50	19.96	QP
3	359.80	14.57	2.52	6.30	23.39	46.00	22.61	QP
4	675.05	20.45	3.64	2.14	26.23	46.00	19.77	QP
5	893.30	22.58	4.31	4.58	31.47	46.00	14.53	QP
6	914.64	22.78	4.37	6.04	33.19	46.00	12.81	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

Note:

1. The amplitude of 9KHz to 30MHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.
2. All channels had been pre-test, only the worst case was reported.

Radiated Emissions Above 1G


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 37

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 37
Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aron Zhang
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : IEEE 802.11ax HE20 TX 5180MHz
Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7188.00	37.03	6.70	43.36	42.97	43.34	68.20	24.86	Peak
2	8956.00	38.65	7.05	43.01	41.07	43.76	68.20	24.44	Peak
3	10843.00	39.43	8.67	42.11	39.87	45.86	74.00	28.14	Peak
4	12611.00	40.22	9.23	40.08	37.76	47.13	74.00	26.87	Peak
5	13529.00	41.25	9.85	39.71	36.45	47.84	68.20	20.36	Peak
6	14175.00	41.66	10.36	40.29	37.53	49.26	68.20	18.94	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 38

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 38
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
 Limit : FCCPART 15E PEAK NII
 Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : 11.1.4 Channel Dolby Atmos Sound Bar
 with Wireless Subwoofer and
 Satellite Speakers
 Power : AC 120V/60Hz
 M/N : Q95K
 Test Mode : IEEE 802.11ax HE20 TX 5180MHz
 Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7205.00	37.10	6.70	43.36	42.82	43.26	68.20	24.94	Peak
2	8871.00	38.80	7.04	43.03	40.80	43.61	68.20	24.59	Peak
3	10911.00	39.42	8.71	42.06	40.22	46.29	74.00	27.71	Peak
4	12475.00	40.19	9.16	40.29	38.80	47.86	74.00	26.14	Peak
5	13546.00	41.28	9.86	39.72	37.23	48.65	68.20	19.55	Peak
6	14022.00	42.06	10.23	39.94	36.65	49.00	68.20	19.20	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official
 limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 39

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 39
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
 Limit : FCCPART 15E PEAK NII
 Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : 11.1.4 Channel Dolby Atmos Sound Bar
 with Wireless Subwoofer and
 Satellite Speakers
 Power : AC 120V/60Hz
 M/N : Q95K
 Test Mode : IEEE 802.11ax HE20 TX 5200MHz
 Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7069.00	36.43	6.66	43.39	43.17	42.87	68.20	25.33	Peak
2	8208.00	37.60	6.96	43.16	41.18	42.58	74.00	31.42	Peak
3	8990.00	38.42	7.06	43.00	40.91	43.39	68.20	24.81	Peak
4	9857.00	39.55	7.97	42.74	40.02	44.80	68.20	23.40	Peak
5	10911.00	39.42	8.71	42.06	40.53	46.60	74.00	27.40	Peak
6	11812.00	39.97	8.89	41.19	38.98	46.65	74.00	27.35	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official
 limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 40

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 40
Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aron Zhang
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : IEEE 802.11ax HE20 TX 5200MHz
Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7239.00	36.80	6.71	43.35	42.56	42.72	68.20	25.48	Peak
2	7885.00	37.35	6.90	43.22	41.69	42.72	68.20	25.48	Peak
3	9058.00	38.42	7.11	42.98	40.95	43.50	74.00	30.50	Peak
4	9738.00	40.20	7.84	42.78	39.45	44.71	68.20	23.49	Peak
5	10843.00	39.43	8.67	42.11	40.04	46.03	74.00	27.97	Peak
6	11829.00	39.98	8.89	41.17	39.23	46.93	74.00	27.07	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 41

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 41
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
 Limit : FCCPART 15E PEAK NII
 Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : 11.1.4 Channel Dolby Atmos Sound Bar
 with Wireless Subwoofer and
 Satellite Speakers
 Power : AC 120V/60Hz
 M/N : Q95K
 Test Mode : IEEE 802.11ax HE20 TX 5240MHz
 Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	6525.00	35.98	6.28	43.40	43.27	42.13	68.20	26.07	Peak
2	7188.00	37.03	6.70	43.36	43.28	43.65	68.20	24.55	Peak
3	7970.00	37.97	6.93	43.21	41.25	42.94	68.20	25.26	Peak
4	8871.00	38.80	7.04	43.03	41.31	44.12	68.20	24.08	Peak
5	9670.00	40.10	7.77	42.80	40.31	45.38	68.20	22.82	Peak
6	10520.00	39.49	8.46	42.33	40.07	45.69	68.20	22.51	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official
 limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 42

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 42
Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aron Zhang
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : IEEE 802.11ax HE20 TX 5240MHz
Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7222.00	36.95	6.71	43.36	42.72	43.02	68.20	25.18	Peak
2	8072.00	37.80	6.95	43.19	41.40	42.96	74.00	31.04	Peak
3	9687.00	40.25	7.78	42.79	41.30	46.54	68.20	21.66	Peak
4	10503.00	39.50	8.45	42.34	40.25	45.86	68.20	22.34	Peak
5	11285.00	39.60	8.81	41.71	39.32	46.02	74.00	27.98	Peak
6	13138.00	40.54	9.54	39.55	37.31	47.84	68.20	20.36	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 43

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 43
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
 Limit : FCCPART 15E PEAK NII
 Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : 11.1.4 Channel Dolby Atmos Sound Bar
 with Wireless Subwoofer and
 Satellite Speakers
 Power : AC 120V/60Hz
 M/N : Q95K
 Test Mode : IEEE 802.11ax HE20 TX 5260MHz
 Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7205.00	37.10	6.70	43.36	42.32	42.76	68.20	25.44	Peak
2	8735.00	38.67	7.03	43.05	41.10	43.75	68.20	24.45	Peak
3	10231.00	39.55	8.27	42.53	40.11	45.40	68.20	22.80	Peak
4	11115.00	39.48	8.79	41.88	39.24	45.63	74.00	28.37	Peak
5	12322.00	40.16	9.08	40.52	38.22	46.94	74.00	27.06	Peak
6	13546.00	41.28	9.86	39.72	36.96	48.38	68.20	19.82	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official
 limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 44

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 44
Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aron Zhang
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : IEEE 802.11ax HE20 TX 5260MHz
Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7086.00	36.57	6.67	43.38	43.12	42.98	68.20	25.22	Peak
2	7970.00	37.97	6.93	43.21	42.05	43.74	68.20	24.46	Peak
3	9449.00	39.10	7.53	42.87	41.00	44.76	74.00	29.24	Peak
4	10554.00	39.49	8.48	42.31	40.01	45.67	68.20	22.53	Peak
5	11846.00	39.99	8.90	41.15	38.45	46.19	74.00	27.81	Peak
6	13512.00	41.22	9.83	39.70	37.75	49.10	68.20	19.10	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 45

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 45
Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aron Zhang
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : IEEE 802.11ax HE20 TX 5300MHz
Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7205.00	37.10	6.70	43.36	42.28	42.72	68.20	25.48	Peak
2	8055.00	37.90	6.95	43.19	41.88	43.54	74.00	30.46	Peak
3	9534.00	39.30	7.62	42.84	41.38	45.46	68.20	22.74	Peak
4	10894.00	39.42	8.70	42.07	40.24	46.29	74.00	27.71	Peak
5	12526.00	40.21	9.19	40.21	37.49	46.68	74.00	27.32	Peak
6	13614.00	41.40	9.91	39.74	36.91	48.48	68.20	19.72	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 46

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 46
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
 Limit : FCCPART 15E PEAK NII
 Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : 11.1.4 Channel Dolby Atmos Sound Bar
 with Wireless Subwoofer and
 Satellite Speakers
 Power : AC 120V/60Hz
 M/N : Q95K
 Test Mode : IEEE 802.11ax HE20 TX 5300MHz
 Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7086.00	36.57	6.67	43.38	42.87	42.73	68.20	25.47	Peak
2	7987.00	38.08	6.93	43.20	41.19	43.00	68.20	25.20	Peak
3	8854.00	38.70	7.04	43.03	41.21	43.92	68.20	24.28	Peak
4	10044.00	39.59	8.14	42.66	40.08	45.15	68.20	23.05	Peak
5	11183.00	39.53	8.80	41.81	40.44	46.96	74.00	27.04	Peak
6	12526.00	40.21	9.19	40.21	37.66	46.85	74.00	27.15	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official
 limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 47

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 47
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
 Limit : FCCPART 15E PEAK NII
 Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : 11.1.4 Channel Dolby Atmos Sound Bar
 with Wireless Subwoofer and
 Satellite Speakers
 Power : AC 120V/60Hz
 M/N : Q95K
 Test Mode : IEEE 802.11ax HE20 TX 5320MHz
 Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7290.00	36.35	6.73	43.34	42.87	42.61	74.00	31.39	Peak
2	8140.00	37.60	6.96	43.17	41.89	43.28	74.00	30.72	Peak
3	9568.00	39.40	7.66	42.83	40.98	45.21	68.20	22.99	Peak
4	10809.00	39.44	8.65	42.13	39.81	45.77	74.00	28.23	Peak
5	12509.00	40.20	9.18	40.24	37.71	46.85	74.00	27.15	Peak
6	13988.00	42.07	10.21	39.89	37.58	49.97	68.20	18.23	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official
 limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 48

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 48
Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aron Zhang
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : IEEE 802.11ax HE20 TX 5320MHz
Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7188.00	37.03	6.70	43.36	42.24	42.61	68.20	25.59	Peak
2	9245.00	38.95	7.31	42.93	40.68	44.01	68.20	24.19	Peak
3	10282.00	39.54	8.30	42.50	40.34	45.68	68.20	22.52	Peak
4	11166.00	39.52	8.80	41.83	40.22	46.71	74.00	27.29	Peak
5	12526.00	40.21	9.19	40.21	38.23	47.42	74.00	26.58	Peak
6	14090.00	41.88	10.29	40.09	37.52	49.60	68.20	18.60	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 49

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 49
Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aron Zhang
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : IEEE 802.11ax HE20 TX 5500MHz
Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7171.00	36.97	6.69	43.37	42.40	42.69	68.20	25.51	Peak
2	8038.00	38.00	6.94	43.19	41.86	43.61	74.00	30.39	Peak
3	9551.00	39.35	7.64	42.83	40.78	44.94	68.20	23.26	Peak
4	11336.00	39.64	8.82	41.66	39.78	46.58	74.00	27.42	Peak
5	12407.00	40.18	9.13	40.39	38.01	46.93	74.00	27.07	Peak
6	13937.00	41.98	10.17	39.87	36.76	49.04	68.20	19.16	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 50

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 50
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
 Limit : FCCPART 15E PEAK NII
 Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : 11.1.4 Channel Dolby Atmos Sound Bar
 with Wireless Subwoofer and
 Satellite Speakers
 Power : AC 120V/60Hz
 M/N : Q95K
 Test Mode : IEEE 802.11ax HE20 TX 5500MHz
 Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7205.00	37.10	6.70	43.36	42.30	42.74	68.20	25.46	Peak
2	8769.00	38.53	7.03	43.05	40.82	43.33	68.20	24.87	Peak
3	9772.00	40.00	7.87	42.77	40.03	45.13	68.20	23.07	Peak
4	12118.00	40.12	8.98	40.82	38.24	46.52	74.00	27.48	Peak
5	12917.00	40.28	9.39	39.63	37.87	47.91	68.20	20.29	Peak
6	14073.00	41.92	10.28	40.06	37.84	49.98	68.20	18.22	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official
 limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 51

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 51
Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aron Zhang
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : IEEE 802.11ax HE20 TX 5580MHz
Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7205.00	37.10	6.70	43.36	43.03	43.47	68.20	24.73	Peak
2	8038.00	38.00	6.94	43.19	41.21	42.96	74.00	31.04	Peak
3	9500.00	39.20	7.59	42.85	41.47	45.41	68.20	22.79	Peak
4	11200.00	39.54	8.80	41.80	39.61	46.15	74.00	27.85	Peak
5	12475.00	40.19	9.16	40.29	38.87	47.93	74.00	26.07	Peak
6	14192.00	41.62	10.37	40.33	38.29	49.95	68.20	18.25	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 52

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 52
Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aron Zhang
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : IEEE 802.11ax HE20 TX 5580MHz
Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7137.00	36.83	6.68	43.37	42.89	43.03	68.20	25.17	Peak
2	8004.00	38.20	6.94	43.20	41.04	42.98	68.20	25.22	Peak
3	9483.00	39.17	7.57	42.86	41.12	45.00	74.00	29.00	Peak
4	10622.00	39.47	8.52	42.26	40.41	46.14	74.00	27.86	Peak
5	12560.00	40.21	9.21	40.16	37.70	46.96	74.00	27.04	Peak
6	13954.00	42.01	10.18	39.88	36.62	48.93	68.20	19.27	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 53

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 53
Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aron Zhang
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : IEEE 802.11ax HE20 TX 5700MHz
Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7222.00	36.95	6.71	43.36	43.78	44.08	68.20	24.12	Peak
2	8735.00	38.67	7.03	43.05	41.97	44.62	68.20	23.58	Peak
3	10027.00	39.59	8.13	42.68	40.77	45.81	68.20	22.39	Peak
4	11404.00	39.68	8.83	41.59	40.63	47.55	74.00	26.45	Peak
5	13257.00	40.76	9.63	39.60	37.86	48.65	74.00	25.35	Peak
6	14141.00	41.75	10.33	40.21	37.53	49.40	68.20	18.80	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 54

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 54
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
 Limit : FCCPART 15E PEAK NII
 Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : 11.1.4 Channel Dolby Atmos Sound Bar
 with Wireless Subwoofer and
 Satellite Speakers
 Power : AC 120V/60Hz
 M/N : Q95K
 Test Mode : IEEE 802.11ax HE20 TX 5700MHz
 Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7205.00	37.10	6.70	43.36	42.18	42.62	68.20	25.58	Peak
2	8055.00	37.90	6.95	43.19	42.32	43.98	74.00	30.02	Peak
3	9823.00	39.72	7.93	42.75	40.11	45.01	68.20	23.19	Peak
4	11251.00	39.58	8.81	41.75	39.58	46.22	74.00	27.78	Peak
5	12526.00	40.21	9.19	40.21	37.45	46.64	74.00	27.36	Peak
6	14141.00	41.75	10.33	40.21	37.31	49.18	68.20	19.02	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official
 limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel:+86-769-83081888
Fax:+86-769-83081878

Data: 55

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 55
Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aron Zhang
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : IEEE 802.11ax HE20 TX 5745MHz
Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7205.00	37.10	6.70	43.36	43.03	43.47	68.20	24.73	Peak
2	9636.00	39.80	7.73	42.81	41.25	45.97	68.20	22.23	Peak
3	11200.00	39.54	8.80	41.80	40.80	47.34	74.00	26.66	Peak
4	12441.00	40.19	9.14	40.34	38.20	47.19	74.00	26.81	Peak
5	13495.00	41.18	9.82	39.70	37.86	49.16	68.20	19.04	Peak
6	14022.00	42.06	10.23	39.94	37.88	50.23	68.20	17.97	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 56

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 56
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
 Limit : FCCPART 15E PEAK NII
 Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : 11.1.4 Channel Dolby Atmos Sound Bar
 with Wireless Subwoofer and
 Satellite Speakers
 Power : AC 120V/60Hz
 M/N : Q95K
 Test Mode : IEEE 802.11ax HE20 TX 5745MHz
 Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7069.00	36.43	6.66	43.39	42.86	42.56	68.20	25.64	Peak
2	9568.00	39.40	7.66	42.83	41.19	45.42	68.20	22.78	Peak
3	10503.00	39.50	8.45	42.34	40.33	45.94	68.20	22.26	Peak
4	11761.00	39.93	8.88	41.24	38.67	46.24	74.00	27.76	Peak
5	13546.00	41.28	9.86	39.72	37.09	48.51	68.20	19.69	Peak
6	14107.00	41.84	10.30	40.13	37.35	49.36	68.20	18.84	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official
 limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 57

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 57
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
 Limit : FCCPART 15E PEAK NII
 Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : 11.1.4 Channel Dolby Atmos Sound Bar
 with Wireless Subwoofer and
 Satellite Speakers
 Power : AC 120V/60Hz
 M/N : Q95K
 Test Mode : IEEE 802.11ax HE20 TX 5785MHz
 Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7222.00	36.95	6.71	43.36	42.40	42.70	68.20	25.50	Peak
2	8004.00	38.20	6.94	43.20	40.85	42.79	68.20	25.41	Peak
3	9551.00	39.35	7.64	42.83	41.06	45.22	68.20	22.98	Peak
4	11081.00	39.46	8.78	41.92	40.04	46.36	74.00	27.64	Peak
5	12271.00	40.15	9.06	40.59	38.45	47.07	74.00	26.93	Peak
6	13529.00	41.25	9.85	39.71	37.13	48.52	68.20	19.68	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official
 limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 58

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 58
Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aron Zhang
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : IEEE 802.11ax HE20 TX 5785MHz
Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7222.00	36.95	6.71	43.36	42.51	42.81	68.20	25.39	Peak
2	9534.00	39.30	7.62	42.84	41.95	46.03	68.20	22.17	Peak
3	11047.00	39.44	8.78	41.95	39.57	45.84	74.00	28.16	Peak
4	12509.00	40.20	9.18	40.24	38.51	47.65	74.00	26.35	Peak
5	13580.00	41.34	9.89	39.73	36.75	48.25	68.20	19.95	Peak
6	14192.00	41.62	10.37	40.33	37.99	49.65	68.20	18.55	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 59

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 59
Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aron Zhang
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : IEEE 802.11ax HE20 TX 5825MHz
Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7188.00	37.03	6.70	43.36	43.14	43.51	68.20	24.69	Peak
2	7936.00	37.73	6.92	43.21	41.06	42.50	68.20	25.70	Peak
3	9568.00	39.40	7.66	42.83	40.60	44.83	68.20	23.37	Peak
4	10894.00	39.42	8.70	42.07	39.91	45.96	74.00	28.04	Peak
5	12526.00	40.21	9.19	40.21	38.47	47.66	74.00	26.34	Peak
6	13954.00	42.01	10.18	39.88	36.94	49.25	68.20	18.95	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 60

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 60
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
 Limit : FCCPART 15E PEAK NII
 Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : 11.1.4 Channel Dolby Atmos Sound Bar
 with Wireless Subwoofer and
 Satellite Speakers
 Power : AC 120V/60Hz
 M/N : Q95K
 Test Mode : IEEE 802.11ax HE20 TX 5825MHz
 Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7205.00	37.10	6.70	43.36	42.52	42.96	68.20	25.24	Peak
2	9024.00	38.34	7.08	42.99	40.96	43.39	74.00	30.61	Peak
3	10979.00	39.40	8.76	42.01	40.72	46.87	74.00	27.13	Peak
4	11710.00	39.90	8.88	41.29	40.07	47.56	74.00	26.44	Peak
5	13563.00	41.31	9.87	39.72	37.13	48.59	68.20	19.61	Peak
6	14515.00	40.78	10.64	41.07	39.52	49.87	68.20	18.33	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official
 limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 61

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-05-14



Site no. : 5# 966 Chamber Data no. : 61
Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aron Zhang
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : IEEE 802.11ax HE20 TX 5720MHz
Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7222.00	36.95	6.71	43.36	42.46	42.76	68.20	25.44	Peak
2	9415.00	39.03	7.49	42.88	40.08	43.72	74.00	30.28	Peak
3	10809.00	39.44	8.65	42.13	38.37	44.33	74.00	29.67	Peak
4	11778.00	39.95	8.89	41.22	38.46	46.08	74.00	27.92	Peak
5	12543.00	40.21	9.20	40.19	36.54	45.76	74.00	28.24	Peak
6	13971.00	42.04	10.19	39.89	35.21	47.55	68.20	20.65	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 62

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-05-14



Site no. : 5# 966 Chamber Data no. : 62
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
 Limit : FCCPART 15E PEAK NII
 Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : 11.1.4 Channel Dolby Atmos Sound Bar
 with Wireless Subwoofer and
 Satellite Speakers
 Power : AC 120V/60Hz
 M/N : Q95K
 Test Mode : IEEE 802.11ax HE20 TX 5720MHz
 Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	7256.00	36.65	6.72	43.35	42.51	42.53	74.00	31.47	Peak
2	8956.00	38.65	7.05	43.01	39.97	42.66	68.20	25.54	Peak
3	10486.00	39.50	8.43	42.36	38.85	44.42	68.20	23.78	Peak
4	11778.00	39.95	8.89	41.22	36.97	44.59	74.00	29.41	Peak
5	13002.00	40.30	9.43	39.50	36.56	46.79	68.20	21.41	Peak
6	14090.00	41.88	10.29	40.09	35.22	47.30	68.20	20.90	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

Note:


- The amplitude of 18GHz to 40GHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.
- All test mode had been pre-test, only Low/Middle/High Channel of the worst case modulation mode was reported.

Band Edge

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 1 File: \\EMC-966-1\test data\2026\REPORT\RF\Tong Li (TCL Duo Mei Ti)\Q95K-Wireless.EM6 (6)



Site no. : 1# 966 Chamber Data no. : 1
Dis. / Ant. : 3m 9120D-2667 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aron Zhang
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : IEEE 802.11ax HE20 TX 5180MHz
Sample No. : EST-260410010-006


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5150.00	32.75	7.72	43.23	46.80	44.04	68.20	24.16	Peak
2	5185.30	32.85	7.75	43.24	98.65	96.01	68.20	-27.81	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 2 File: \\EMC-966-1\test data\2026\REPORT\RFIT\Tong Li (TCL Duo Mei Ti)\Q95K-Wireless.EM6 (6)



Site no. : 1# 966 Chamber Data no. : 2
Dis. / Ant. : 3m 9120D-2667 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aron Zhang
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : IEEE 802.11ax HE20 TX 5180MHz
Sample No. : EST-260410010-006


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5150.00	32.75	7.72	43.23	49.31	46.55	68.20	21.65	Peak
2	5176.20	32.85	7.75	43.24	97.35	94.71	68.20	-26.51	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 3 File: \\EMC-966-1\test data\2026\REPORT\RFIT\Tong Li (TCL Duo Mei Ti)\Q95K-Wireless.EM6 (6)



Site no. : 1# 966 Chamber Data no. : 3
Dis. / Ant. : 3m 9120D-2667 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aron Zhang
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : IEEE 802.11ax HE20 TX 5320MHz
Sample No. : EST-260410010-006


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5329.30	32.63	7.87	43.27	104.94	102.17	68.20	-33.97	Peak
2	5350.00	32.65	7.88	43.27	48.52	45.78	54.00	8.22	Average
3	5350.00	32.65	7.88	43.27	66.64	63.90	68.20	4.30	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 4 File: \\EMC-966-1\test data\2026\REPORT\RFIT\Tong Li (TCL Duo Mei Ti)\Q95K-Wireless.EM6 (6)



Site no. : 1# 966 Chamber Data no. : 4
Dis. / Ant. : 3m 9120D-2667 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aron Zhang
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : IEEE 802.11ax HE20 TX 5320MHz
Sample No. : EST-260410010-006


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5318.90	32.62	7.85	43.26	101.24	98.45	68.20	-30.25	Peak
2	5350.00	32.65	7.88	43.27	44.10	41.36	54.00	12.64	Average
3	5350.00	32.65	7.88	43.27	60.99	58.25	68.20	9.95	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 5 File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM



Site no. : 5# 966 Chamber Data no. : 5
Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aron Zhang
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : IEEE 802.11ax HE20 TX 5500MHz
Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5460.00	33.20	5.61	43.29	44.57	40.09	54.00	13.91	Average
2	5460.00	33.20	5.61	43.29	59.39	54.91	68.20	13.29	Peak
3	5492.64	33.53	5.63	43.30	107.68	103.54	68.20	-35.34	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 6

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 6
Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aron Zhang
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : IEEE 802.11ax HE20 TX 5500MHz
Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5460.00	33.20	5.61	43.29	54.86	50.38	68.20	17.82	Peak
2	5494.08	33.53	5.63	43.30	104.30	100.16	68.20	-31.96	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 7

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 7
Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aron Zhang
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : IEEE 802.11ax HE20 TX 5700MHz
Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5694.09	33.00	5.73	43.34	106.26	101.65	68.20	-33.45	Peak
2	5725.00	33.13	5.75	43.35	68.33	63.86	68.20	4.34	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 8

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-04-28



Site no. : 5# 966 Chamber Data no. : 8
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
 Limit : FCCPART 15E PEAK NII
 Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : 11.1.4 Channel Dolby Atmos Sound Bar
 with Wireless Subwoofer and
 Satellite Speakers
 Power : AC 120V/60Hz
 M/N : Q95K
 Test Mode : IEEE 802.11ax HE20 TX 5700MHz
 Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5691.90	33.00	5.73	43.34	105.30	100.69	68.20	-32.49	Peak
2	5725.00	33.13	5.75	43.35	68.57	64.10	68.20	4.10	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official
 limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 35

File: \\EMC-966-5\Test Data2\2026\Report\RF\TCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-05-14



Site no. : 5# 966 Chamber Data no. : 35
 Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : VERTICAL
 Limit : FCCPART 15E PEAK NII
 Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
 Engineer : Aron Zhang
 EUT : 11.1.4 Channel Dolby Atmos Sound Bar
 with Wireless Subwoofer and
 Satellite Speakers
 Power : AC 120V/60Hz
 M/N : Q95K
 Test Mode : IEEE 802.11ax HE20 TX 5720MHz
 Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5717.50	33.13	5.75	43.35	102.41	97.94	68.20	-29.74	Peak
2	5750.00	33.20	5.76	43.35	47.97	43.58	68.20	24.62	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official
 limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 36

File: \\EMC-966-5\Test Data2\2026\Report\RF\TTCL Duo Mei Ti\Q95K-Soundbar-Wireless-FCC.EM

Date: 2026-05-14



Site no. : 5# 966 Chamber Data no. : 36
Dis. / Ant. : 3m 9120D-1002 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:20.3°C;Humi:49%;Press:101.55kPa
Engineer : Aron Zhang
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : IEEE 802.11ax HE20 TX 5720MHz
Sample No. : EST-260410010-006

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5721.00	33.13	5.75	43.35	102.72	98.25	68.20	-30.05	Peak
2	5750.00	33.20	5.76	43.35	50.20	45.81	68.20	22.39	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official
limit are not reported.

U-NII-3:

Refer to Appendix E of Appendix FCC ID 5G Wi-Fi (the test data).

18000MHz-40000MHz

Pass

Note: The amplitude of spurious emission that is attenuated by more than 20dB below the permissible


limit has no need to be reported.

7.FREQUENCY STABILITY

7.1.Limit

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the operational description.

7.2.Test Setup



7.3.Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	10KHz
VBW	10KHz
Span	200KHz
Sweep Time	Auto
Detector	PEAK
Trace Mode	Max Hold

7.4.Test Procedure

For measurement frequency stability under temperature variation :

- a. Supply the EUT with a nominal ac voltage or install a new or fully charged battery in the EUT.
- b. Turn the EUT OFF and place it inside the environmental temperature chamber.
- c. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- d. Spectrum analyzer setting parameters in accordance with section 7.3.
- e. Set the temperature control on the chamber to the Specified temperature and allow the oscillator heater and the chamber temperature to stabilize.
- f. Turn the EUT ON with the rated voltage, and the EUT transmit continuously with maximum output power.
- g. Record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized.
- h. Repeat step d through step f to measured the temperature form -20°C to +50°C in 10°C steps.

For frequency stability under voltage variation:

- a. Supply the EUT with a nominal ac voltage or install a new or fully charged battery in the EUT.
- b. Turn the EUT OFF and place it inside the environmental temperature chamber.
- c. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- d. Spectrum analyzer setting parameters in accordance with section 7.3.
- e. Unless otherwise specified, set the temperature control on the chamber to the ambient room temperature (+15°C to +25°C) and allow the oscillator heater and the chamber temperature to stabilize.
- f. Turn the EUT ON with the rated voltage, and the EUT transmit continuously with maximum output power.
- g. Record the operating frequency.
- h. Repeat step d through step f to measured the varied from 85% to 115% of the rated voltage.

Note: Normal voltage=AC 120V, Low voltage=AC 102V, High voltage=138V.

Normal temperature=26.9°C

7.5.Test Result

Refer to Appendix F of Appendix FCC ID 5G Wi-Fi (the test data).

8.AC POWER LINE CONDUCTED EMISSIONS


8.1.Limit

Frequency			Maximum RF Line Voltage	
			Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz	~	500kHz	66 ~ 56*	56 ~ 46*
500kHz	~	5MHz	56	46
5MHz	~	30MHz	60	50

Notes:

1. * Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

8.2.Test Setup



8.3.Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	9KHz
VBW	9KHz
Start frequency	150KHz
Stop frequency	30MHz
Sweep Time	Auto
Detector	QP/AVG
Trace Mode	Max Hold

8.4.Test Procedure

- a. The EUT was placed on a non-metallic table, 80cm above the ground plane.
- b. The EUT Power connected to the power mains through a line impedance stabilization network.
- c. Provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs).
- d. Set the EUT transmit continuously with maximum output power.
- e. Spectrum analyzer setting parameters in accordance with section 8.3.
- f. The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2020 on Conducted Emission Test.
- g. Record the results in the test report.

8.5. Test Result


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 30

File: \\CE-Z\Test Data\2026\Report\RF\TCL Duo Mei Ti\Q95K -.EM6 (32)

Date: 2026-06-02



Site no : 2#CE Shield Room Data no. : 30
Env. / Ins. : Temp:27.5°C Humi:68% Press:101.20kPa LINE Phase : LINE
Limit : FCC PART 15E QP
Engineer : Micheal Huang
EUT : 11.1.4 Channel Dolby Atmos Sound Bar
with Wireless Subwoofer and
Satellite Speakers
Power : AC 120V/60Hz
M/N : Q95K
Test Mode : TX Mode
Sample No. : EST-260410010-006
Wireless

	Freq. (MHz)	LISN Factor (db)	Cable Loss (db)	Reading dBuV	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.160	9.94	9.83	0.30	20.07	55.47	35.40	Average
2	0.160	9.94	9.83	19.18	38.95	65.47	26.52	QP
3	0.205	9.90	9.85	0.77	20.52	53.40	32.88	Average
4	0.205	9.90	9.85	17.67	37.42	63.40	25.98	QP
5	0.220	9.90	9.85	0.92	20.67	52.83	32.16	Average
6	0.220	9.90	9.85	7.88	27.63	62.83	35.20	QP
7	0.435	9.83	9.84	0.69	20.36	47.15	26.79	Average
8	0.435	9.83	9.84	9.53	29.20	57.15	27.95	QP
9	0.510	9.84	9.84	0.11	19.79	46.00	26.21	Average
10	0.510	9.84	9.84	12.16	31.84	56.00	24.16	QP
11	0.579	9.82	9.84	0.52	20.18	46.00	25.82	Average
12	0.579	9.82	9.84	11.48	31.14	56.00	24.86	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. If the average limit is met when using a quasi-peak detector,
the EUT shall be deemed to meet both limits and measurement
with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 32

File: \\CE-2\Test Data\2026\Report\RF\TTC\ Duo Mei Ti\Q95K -.EM6 (32)

Date: 2026-06-02



Trace: 31

Site no : 2#CE Shield Room Data no. : 32
 Env. / Ins. : Temp:27.5°C Humi:68% Press:101.20kPa LINE Phase : NEUTRAL
 Limit : FCC PART 15E QP
 Engineer : Micheal Huang
 EUT : 11.1.4 Channel Dolby Atmos Sound Bar
 with Wireless Subwoofer and
 Satellite Speakers
 Power : AC 120V/60Hz
 M/N : Q95K
 Test Mode : TX Mode
 Sample No. : EST-260410010-006
 Wireless

	Freq. (MHz)	LISN Factor (db)	Cable Loss (db)	Reading dBuV	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.160	9.92	9.83	8.89	28.64	55.47	26.83	Average
2	0.160	9.92	9.83	27.74	47.49	65.47	17.98	QP
3	0.180	9.86	9.85	7.86	27.57	54.50	26.93	Average
4	0.180	9.86	9.85	25.76	45.47	64.50	19.03	QP
5	0.200	9.86	9.85	5.72	25.43	53.62	28.19	Average
6	0.200	9.86	9.85	22.63	42.34	63.62	21.28	QP
7	0.274	9.86	9.85	6.80	26.51	50.98	24.47	Average
8	0.274	9.86	9.85	14.74	34.45	60.98	26.53	QP
9	0.505	9.86	9.84	5.83	25.53	46.00	20.47	Average
10	0.505	9.86	9.84	11.75	31.45	56.00	24.55	QP
11	0.573	9.85	9.84	5.52	25.21	46.00	20.79	Average
12	0.573	9.85	9.84	14.41	34.10	56.00	21.90	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.

9.ANTENNA REQUIREMENTS

9.1.Limit

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

9.2.Test Result

The antennas used for this product is FPC antenna, so compliance with antenna requirements. (Please refer to the EUT photo for details)

10.TEST SETUP PHOTO


Conducted Test



Radiated Test (Below 1GHz)



Radiated Test (Above 1GHz)



Radio Spectrum Testing



11.EUT PHOTO

Refer to report no. ESTE-R2606120

End of Test Report