

RF Exposure Report

Product name: 3.1 Channel Dolby Atmos Sound Bar with Wireless Subwoofer

Trademark: TCL, FFALCON

Model no.: S60K

Series Model(s).: S60K Pro, S60KS, S61K, S62K, S63K, S64K, S601K, S602K, S603K, S604K, S605K, S606K, S607K, S608K, S609K, S60K-UK, S601K-UK, S602K-UK, S603K-UK, S604K-UK, S605K-UK, S606K-UK, S607K-UK, S608K-UK, S609K-UK

FCC ID: 2BEHES60K

Report No: C260227073-RF03

Test Standards: CFR47 FCC Part 2: Section 2.1091
CFR47 FCC Part 1: Section 1.1310

Applicant: TCL OVERSEAS MARKETING LTD.

Address of applicant: Unit 1905, 19/F, Nan Fung Centre, 264-298 Castle Peak Road, Tsuen Wan, New Territories, Hong Kong

Manufacturer: TCL OVERSEAS MARKETING LTD.

Manufacturer Address: Unit 1905, 19/F, Nan Fung Centre, 264-298 Castle Peak Road, Tsuen Wan, New Territories, Hong Kong

Date of Test Date: N/A


Date of issue.: May 18, 2026

Test result: Compliance

Prepared By :


Adil Yang/Engineer

Reviewed By :


Greg Zhang/Engineer

Approved By :


Tom Gan/Manager

The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of preparer, reviewer and approver. Any objections must be raised to CSIC within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.

Table of Contents**Page**

1	TEST SUMMARY.....	3
1.1	TEST FACILITY	3
2	GENERAL INFORMATION.....	4
2.1	GENERAL DESCRIPTION OF EUT	4
3	MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	5
3.1	RF EXPOSURE	5

1 TEST SUMMARY

1.1 Test Facility

Shenzhen Central Standard International Center Co., Ltd. (CSIC)

Room 201, Building 1, Mogen Fashion Industrial Park, No. 10, Shilongzai Road, Xinshi Community, Dalang Street, Longhua District, Shenzhen.

The test facility is recognized, certified or accredited by the following organizations:

CNAS Registration No.: L11671

FCC Registration No.: 0031378433 Designation Number: CN1317

IC CAB identifier: CN0051

A2LA Lab Cert. No.: 6426.01

2 GENERAL INFORMATION

2.1 General Description of EUT

EUT(Product Specifications)	
Product Name:	3.1 Channel Dolby Atmos Sound Bar with Wireless Subwoofer
Model:	S60K
Series Model(s):	S60K Pro, S60KS, S61K, S62K, S63K, S64K, S601K, S602K, S603K, S604K, S605K, S606K, S607K, S608K, S609K, S60K-UK, S601K-UK, S602K-UK, S603K-UK, S604K-UK, S605K-UK, S606K-UK, S607K-UK, S608K-UK, S609K-UK
Power supply:	AC 100-240V 50/60Hz
Hardware version:	S60K
Software version:	V15
Technical Specification of Bluetooth	
Operating Frequency	2402MHz to 2480MHz
Type of Modulation	GFSK, $\pi/4$ DQPSK, 8-DPSK
Channel Number	79
Channel Separation	1MHz
Antenna Type	PCB
Max. Antenna Gain	2.38 dBi
Technical Specification of Bluetooth LE	
Frequency Range:	2402 MHz to 2480 MHz, 2404 MHz to 2478 MHz
Type of Modulation:	GFSK
Channel Number:	LE 1M: 40 channels LE 2M: 38 channels
Data Rate:	1Mbps, 2 Mbps
Channel Separation:	2 MHz
Antenna Type:	PCB
Antenna Gain:	2.38 dBi

Note: The above information and materials are provided by the Manufacturer.

3 Maximum Permissible Exposure (MPE)

3.1 RF Exposure

3.1.1 Limit

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio frequency (RF) radiation as specified in 1.1307 (b).

For FCC:

Frequency Range	Electric Field Strength	Magnetic Field Strength	Power Density
[MHz]	[V/m]	[A/m]	[mW/cm ²]
Limits for Occupational / controlled Exposures			
300 - 1500	--	--	f/300
1500 - 100000	--	--	5.0
Limits for General population / Uncontrolled Exposure			
300 - 1500	--	--	f/1500
1500 - 100000	--	--	1.0

NOTE: f = Frequency in MHz

3.1.2 Friss Formula

Per KDB 447498 D01 v06, simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on calculated or measured field strengths or power density, is ≤ 1.0 .

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.

3.1.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance from the antenna should be included in the User manual. So, this device is classified as Mobile device.

3.1.4 EUT Operating Conditions

EUT was enabled to transmit and receive at lowest, middle and highest channels.

3.1.5 Evaluation Result

1) tand-alone transmission MPE

For FCC

Test Results of RF Exposure Calculations for FCC, Stand-alone mode

Test Mode	Max. conducted power incl. tune-up (dBm)	Distance (cm)	MPE (mW/cm ²)	Threshold power (mW/cm ²)	Result
Bluetooth	7.11	20	0.0018	1.0	Pass

Test Results of RF Exposure Calculations for FCC, Simultaneous mode

Co-location Mode	Sum of the MPE ratios	Limit	Result
N/A	N/A	1.0	N/A

3.1.6 Conclusion

Therefore, the maximum calculations result of above are meet the requirement of Radio Frequency Exposure (MPE) limit.

*****THE END*****