

**RADIOCOMMUNICATIONS EQUIPMENT
RF EXPOSURE EXEMPTION ASSESSMENT AGAINST

FCC 47 CFR 1.1310 & 2.1093
RADIOFREQUENCY RADIATION EXPOSURE LIMITS**

Client:	PJM SYSTEMS PTY LTD
Address:	Unit 10, 3 Northward Street, Upper Coomera QLD 4209, Australia
Report Number:	0830WAL_MARS-24AT_EMR(FCC)
Date of Assessment	17 May 2024
File Number:	WAL230922

Equipment Name:	MARS-24AT
Equipment Model No:	MARS-24AT
Equipment FCC ID:	2BEI3-MARS24AT
Equipment Description:	Multiple Antenna Reader Systems

Result:	COMPLIES (General Population/Uncontrolled Exposure)
---------	---

Assessed by:	Colin Gan
--------------	-----------



Approved by:	Daniel Blunck
--------------	---------------



Date of Issue:	30 Aug 2024
----------------	-------------

Results appearing herein relate only to the sample(s) assessed through the submitted test report(s).
This report is issued errors and omissions exempt and is subject to withdrawal at Austest Laboratories discretion.

This document shall not be reproduced in any form except in full.

EQUIPMENT DETAILS	
MANUFACTURER:	PJM SYSTEMS PTY LTD
MODEL:	MARS-24AT
OPERATING FREQUENCY:	13.56 MHz
TRANSMITTER POWER INTO ANTENNA:	43.80 dBm (24 W) ^{Note 1}
TYPE OF ANTENNA:	1.6mm FR4 PCB 4 turn rectangular RfID antenna ^{Note 2}
ANTENNA GAIN:	-39 dBi ^{Note 2} (1.259×10^{-4} numeric gain)
TRANSMISSION CAPABILITY:	Single transmissions at a time only. ^{Note 3}

Notes:

1. Maximum conducted RF power data provided by client.
2. Data from ANTENNA 031-10-113 provided by client.
3. Although the equipment has 24 antenna ports client has stated that transmission is through one antenna at a time.

RF Exposure Exemption Assessment

References

- [1] CFR 47, Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices.
- [2] CFR 47, Part 2.1093 Radiofrequency radiation exposure evaluation: portable devices.
- [4] CFR 47, Part 1.1310 Radiofrequency radiation exposure limits.
- [5] 447498 D04 Interim General RF Exposure Guidance v01.

Maximum Permissible Exposure (MPE)

As specified in Table 1 (II) of 47 CFR 1.1310 – Limits for MPE, Limits for General Population / Uncontrolled Exposure:

<i>Frequency Range (MHz)</i>	<i>Power Density (mW/cm²)</i>
1.34 – 30	($180/f^2$)

f is frequency in MHz.

This document shall not be reproduced in any form except in full.

MPE Calculation

The Equipment Under Test (EUT) was supplied with transmitter antennas having maximum antenna gain as indicated in the Equipment Details above.

Results of MPE calculations for the EUT in standalone configuration is shown below.

Formulas

$$E (V/m) = \frac{\sqrt{30 \times P \times G}}{d}$$

$$P_d (W/m) = \frac{E^2}{377}$$

$$\text{hence, } P_d (W/m) = \frac{30 \times P \times G}{377 \times d^2}$$

where

E – Electric Field

P – RF Output Power (W)

G – Numeric Antenna Gain

d – Separation Distance (m)

Freq. (MHz)	P (W)	G (Numeric)	d (m)	P _d (mW/cm ²)	P _d Limit (mW/cm ²)
13.56	24	1.259 × 10 ⁻⁴	0.20	0.006	0.978

Based on the MPE calculations, the EUT complies with the FCC limit with a separation distance of 20 cm between the transmission point (generally referring to the transmit antenna or structure) and the human body, which is to be clearly and prominently stated in the product manuals for the indicated maximum antenna gain.

The above minimum safety distance is not valid for transmit antennas with higher antenna gains.

This document shall not be reproduced in any form except in full.

Austest Summary and Recommendations

The equipment complies with FCC 47 CFR 2.1091 requirements referencing 1.1310, Table 1 (II), Limits for Maximum Permissible Exposure (MPE), Limits for General Population / Uncontrolled Exposure, when the indicated minimum separation distance is adhered to.

If compliance is sought for model numbers other than those listed in the test report, then the compliance folder must hold additional documentation, demonstrating the equivalence of the products between the different model numbers.

This document shall not be reproduced in any form except in full.