

Case No. : <u>GTS20260831011-3-02</u>	
Ambient Condition: <u>24</u> °C, <u>50</u> %RH	
According Standard: ■Part15C	
Test Date: <u>2026.9.08-2026.10.19</u>	Test Engineer: <u>Evan ouyang</u>

Appendix A.1: DTS Bandwidth

Test Result


TestMode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE	Ant1	2402	0.688	2401.764	2402.452	0.5	PASS
		2440	0.708	2439.756	2440.464	0.5	PASS
		2480	0.696	2479.752	2480.448	0.5	PASS

Appendix A.2: Occupied Channel Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE	Ant1	2402	1.1430	2401.5065	2402.6495	---	---
		2440	1.1189	2439.5246	2440.6435	---	---
		2480	1.1004	2479.5478	2480.6482	---	---

Test Graphs





Appendix A.3: Maximum conducted output power

Test Result


TestMode	Antenna	Freq(MHz)	Conducted Peak Power[dBm]	Conducted Limit[dBm]	Verdict
BLE	Ant1	2402	-0.21	≤30	PASS
		2440	0.81	≤30	PASS
		2480	0.47	≤30	PASS


Appendix A.4: Maximum power spectral density

Test Result

TestMode	Antenna	Freq(MHz)	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE	Ant1	2402	-14.74	≤ 8.00	PASS
		2440	-13.56	≤ 8.00	PASS
		2480	-14.48	≤ 8.00	PASS

Test Graphs






Appendix A.5: Band edge measurements

Test Result

Test Mode	Antenna	ChName	Freq (MHz)	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
BLE	Ant1	Low	2402	-0.63	-30.93	≤-20.63	PASS
		High	2480	0.38	-39.16	≤-19.62	PASS

Test Graphs




Appendix A.6: Conducted Spurious Emission


Test Result


TestMode	Antenna	Freq(MHz)	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE	Ant1	2402	Reference	-0.56	-0.56	---	PASS
			30~1000	-0.56	-62.04	≤-20.56	PASS
			1000~26500	-0.56	-48.43	≤-20.56	PASS
		2440	Reference	0.57	0.57	---	PASS
			30~1000	0.57	-62.2	≤-19.43	PASS
			1000~26500	0.57	-47.97	≤-19.43	PASS
		2480	Reference	-0.51	-0.51	---	PASS
			30~1000	-0.51	-62.47	≤-20.51	PASS
			1000~26500	-0.51	-43.88	≤-20.51	PASS

Test Graphs










Appendix A.7: Duty Cycle

Test Result

TestMode	Antenna	Freq(MHz)	ON Time [ms]	Period [ms]	X	DC [%]	Duty Cycle Factor[dB]	1/T Factor[KHz]
BLE	Ant1	2402	0.40	0.62	0.6452	64.52	1.90	2.50
		2440	0.40	0.62	0.6452	64.52	1.90	2.50
		2480	0.41	0.63	0.6508	65.08	1.87	2.44

Test Graphs



BLE_Ant1_2440

Keysight Spectrum Analyzer - Swept SA

RF: 150.0 AC

SENSE:INT

ALIGN: AUTO/NO RF

12:25:29 AM Sep 18, 2026

Center Freq 2.440000000 GHz

Trig Delay: 200.0 μ s

#Avg Type: RMS

TRACED 1 2 3 4 5

PNO: Fast

IFGain: Low

Trig: Video

#Atten: 30 dB

TYPE: WWWW

DET: AAAAAA

Ref Offset 8.35 dB

Ref 20.00 dBm

Δ Mkr3 620.0 μ s

-41.63 dB

Center 2.440000000 GHz

Res BW 8 MHz

#VBW 8.0 MHz

Sweep 10.13 ms (8000 pts)

Span 0 Hz

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	t	3.550 ms	-0.02 dBm			
2	Δ 1	1	t	400.0 μ s (Δ)	-2.73 dB			
3	Δ 1	1	t	620.0 μ s (Δ)	-41.63 dB			
4								
5								
6								
7								
8								
9								
10								
11								

MSG

STATUS

Frequency

Auto Tune

Center Freq
2.440000000 GHz


Start Freq
2.440000000 GHz

Stop Freq
2.440000000 GHz

CF Step
8.000000 MHz
Auto Man

Freq Offset
0 Hz

BLE_Ant1_2480



Appendix A.8: Emissions in Restricted Bands

Test Result

TestMode	Antenna	ChName	Freq (MHz)	Detector	Freq [MHz]	Result [dBm]	Limit [dBm]	Result [dBuV/m]	Limit [dBuV/m]	Verdict
BLE	Ant1	Low	2402	AV	2310.000	-49.35	≤-41.20	45.85	≤54	PASS
				AV	2385.680	-45.77	≤-41.20	49.43	≤54	PASS
				AV	2390.000	-48.24	≤-41.20	46.96	≤54	PASS
				Peak	2310.000	-40.73	≤-21.20	54.47	≤74	PASS
				Peak	2386.520	-35.85	≤-21.20	59.35	≤74	PASS
				Peak	2390.000	-43.12	≤-21.20	52.08	≤74	PASS
		High	2480	AV	2483.500	-45.17	≤-41.20	50.03	≤54	PASS
				AV	2483.520	-45.17	≤-41.20	50.03	≤54	PASS
				AV	2500.000	-48.23	≤-41.20	46.97	≤54	PASS
				Peak	2483.500	-39.19	≤-21.20	56.01	≤74	PASS
				Peak	2483.680	-37.13	≤-21.20	58.07	≤74	PASS
				Peak	2500.000	-42.82	≤-21.20	52.38	≤74	PASS

Note:

1. The Antenna Gain is compensated in the graph.
2. The Duty Cycle Factor and RBW Factor is compensated in the graph.
3. The limit in dBm for average detector is conversion from 54dBuV/m, according to 15.209(a). The limit in dBm for peak detector is 20dB above the limit of average detector in dBm.

Test Graphs

