FCC ID: 2BEKB-R88

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[√f(GHZ)] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- f(GHZ) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BLE:1M

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-4.594	0.35	-4±1	-3.00	0.50	<5	0.15535	3.00	YES
	2.44	-4.431	0.36	-4±1	-3.00	0.50	<5	0.15658	3.00	YES
	2.480	-4.384	0.36	-4±1	-3.00	0.50	<5	0.15785	3.00	YES

BLE:2M

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-4.494	0.36	-4±1	-3.00	0.50	<5	0.15535	3.00	YES
	2.44	-4.218	0.38	-4±1	-3.00	0.50	<5	0.15658	3.00	YES
	2.480	-4.174	0.38	-4±1	-3.00	0.50	<5	0.15785	3.00	YES

Conclusion:

For the max result : 0.15785≤ FCC Limit 3.0 for 1g SAR.