



Shenzhen Huaxin Information Technology Service Co., Ltd

FCC TEST REPORT

On Behalf of

Shenzhen Aurora Photoelectricity & Technology Co., Ltd.

Symphony leather thread lamp

Model No.: AUR-HCPXD

FCC ID.: 2BELU-AUR-HCPXD

Prepared for : Shenzhen Aurora Photoelectricity & Technology Co., Ltd.
Address : 1404 3A HuaQiangChuangYiChanYeYuan FengEn Road
GuangMing ShenZhen China

Prepared By : Shenzhen Huaxin Information Technology Service Co., Ltd
Address : 101, R & D Building, No.3 guansheng 4th Road, Luhu Community,
Guanhu Street, Longhua District, Shenzhen, Guangdong, China

Report Number : HX240119R001
Date of Receipt : Jan.8th, 2024
Date of Test : Jan.9th, 2024-Jan.19th, 2024
Date of Report : Jan.19th, 2024
Version Number : V0



TABLE OF CONTENTS

Description	Page
1. Summary Of Standards And Results	6
1.1. Description of Standards and Results	6
2. General Information	7
2.1. Description of Device (EUT)	7
2.2. Accessories of Device (EUT)	8
2.3. Tested Supporting System Details	8
2.4. Block Diagram of connection between EUT and simulators	8
2.5. Test Mode Description	8
2.6. Test Conditions	9
2.7. Test Facility	9
2.8. Measurement Uncertainty (95% confidence levels, k=2)	9
2.9. Test Equipment List	10
3. Maximum Peak Output Power	12
3.1. Limit	12
3.2. Test Procedure	12
3.3. Test Setup	12
3.4. Test Result	12
4. Bandwidth	13
4.1. Limit	13
4.2. Test Procedure	13
4.3. Test Result	13
5. Carrier Frequency Separation	14
5.1. Limit	14
5.2. Test Procedure	14
5.3. Test Result	14
6. Number Of Hopping Channel	15
6.1. Limit	15
6.2. Test Procedure	15
6.3. Test Result	15
7. Dwell Time	16
7.1. Test limit	16
7.2. Test Procedure	16
7.3. Test Result	16
8. Emissions	17
8.1. Limit	17
8.2. Block Diagram of Test setup	18
8.3. Test Procedure	19
8.4. Test Result	19
9. Band Edge Compliance	23
9.1. Block Diagram of Test Setup	23



9.2. Limit	23
9.3. Test Procedure	23
9.4. Test Result	23
10. Power Line Conducted Emissions	24
10.1. Block Diagram of Test Setup	24
10.2. Limit	24
10.3. Test Procedure	24
10.4. Test Result	25
11. Antenna Requirements	27
11.1. Limit	27
11.2. Result	27
12. Test Setup Photo	28
13. EUT Photo	29



TEST REPORT DECLARATION

Applicant : Shenzhen Aurora Photoelectricity & Technology Co., Ltd.
Address : 1404 3A HuaQiangChuangYiChanYeYuan FengEn Road GuangMing ShenZhen China
Manufacturer : Shenzhen Aurora Photoelectricity & Technology Co., Ltd.
Address : 1404 3A HuaQiangChuangYiChanYeYuan FengEn Road GuangMing ShenZhen China
EUT :
Description : Symphony leather thread lamp

(A) Model No. : AUR-HCPXD/AUR-CLD/AUR-HCCLD/AUR-PBD/AUR-HCPBD/AUR-HCXYQ/AUR-TYNDC/AUR-TZD/AUR-HCYSDD/AUR-XBQDC/AUR-HCG40/AUR-HCS14/AUR-DSPXD/AUR-ZXPXD
(B) Trademark : N/A

Measurement Standard Used:

**FCC Rules and Regulations Part 15 Subpart C Section 15.247,
ANSI C63.10-2013**

The device described above is tested by Shenzhen Huaxin Information Technology Service Co., Ltd. to determine the maximum emission levels emanating from the device. The test results are contained in this test report and Shenzhen Huaxin Information Technology Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After the test, our opinion is that EUT compliance with the requirement of the above standards.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Huaxin Information Technology Service Co., Ltd.

Tested by (name + signature).....: Eason Tan
Project Engineer

Approved by (name + signature).....: Michael Wu
Project Manager

Date of issue..... : Jan.19th, 2024





Revision History

Revision	Issue Date	Revisions	Revised By
V0	Jan.19th, 2024	Initial released Issue	Eason Tan



1. Summary Of Standards And Results

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Standards Paragraph	Result
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1)	P
Bandwidth	FCC Part 15: 15.215	P
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1)	P
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)	P
Dwell Time	FCC Part 15: 15.247(a)(1)	P
Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d)	P
Band Edge Compliance	FCC Part 15: 15.247(d)	P
Power Line Conducted Emissions	FCC Part 15: 15.207	P
Antenna requirement	FCC Part 15: 15.203	P
Note:	1. P is an abbreviation for Pass. 2. F is an abbreviation for Fail. 3. N/A is an abbreviation for Not Applicable.	



2. General Information

2.1. Description of Device (EUT)

Description/PMN	: Symphony leather thread lamp
Model	AUR-HCPXD/AUR-CLD/AUR-HCCLD/AUR-PBD/AUR-HCPBD/AUR-HCXYQ/AU
Number/HVIN(s)	: R-TYNDG/AUR-TZD/AUR-HCYSD/AUR-XBQDC/AUR-HCG40/AUR-HCS14/AUR-DSPXD/AUR-ZXPXD
Diff.	: PCB board, structure and internal of these model(s) are the same, these different models are based on market demands and regional differences, just model names and color are different, so no additional models were tested.
Trademark	: N/A
Test Voltage	: DC 5V
Radio Technology	: Bluetooth BR
Operation frequency	: 2402MHz-2480MHz
Modulation	: GFSK
Channel No.	: 79 Channels
Channel Separation	: 1MHz
Antenna Type	: Internal Antenna, max gain 3.81dBi. Antenna information is provided by applicant.
Software version	: V1.0
Hardware version	: V1.0

Remark:

1. The worst-case simultaneous transmission configuration was evaluated with no non-compliance found. Results in this report are only for Bluetooth BR function, and there is no other transmitter involved.
2. This report only shows the worst data.




2.2. Accessories of Device (EUT)

Accessories : /
Manufacturer : /
Model : /
Input : /
Output : /

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number	Certification or SDOC
1.	/	/	/	/	/

2.4. Block Diagram of connection between EUT and simulators



2.5. Test Mode Description

The test software “RFTestTool.app” was used to control EUT work in Continuous TX mode, and select test channel, wireless mode

Tested mode, channel, and data rate information		
Mode	Channel	Frequency (MHz)
Carrier Tx Mode	CH0	2402
	CH39	2441
	CH78	2480
GFSK	CH0 to CH78	2402 to 2480
GFSK	CH0	2402
	CH39	2441
	CH78	2480



2.6. Test Conditions

Items	Required	Actual
Temperature range:	15-35°C	25°C
Humidity range:	25-75%	56%
Pressure range:	86-106kPa	98kPa

2.7. Test Facility

Shenzhen Huaxin Information Technology Service Co., Ltd

101, R & D Building, No.3 guansheng 4th Road, Luhua Community, Guanhu Street, Longhua District, Shenzhen, Guangdong, China

FCC Test Firm Registration Number: 932271

Designation Number: CN1344

CAB ID : CN0147

ISED#: 31786

2.8. Measurement Uncertainty (95% confidence levels, k=2)

Item	MU	Remark
Conducted Emission (9K~0.15MHz)	2.18dB	
Conducted Emission (0.15M~30MHz)	2.17dB	
Radiation Emission ,3m (30MHz~1GHz)	4.45 dB	Polarize: V
	2.76 dB	Polarize: H
Radiation Emission, 3m (1GHz~6GHz)	4.02 dB	
Radiation Emission ,3m (6GHz~18GHz)	4.30 dB	
RF output power (conducted)	0.41 dB	
Power Spectral Density (conducted)	0.39 dB	
Spurious emissions (conducted)	0.59 dB	
Occupied Channel Bandwidth (conducted)	4.22%	



2.9. Test Equipment List

Equipment	Manufacture	Model No.	Firmware version	Serial No.	Last cal.	Cal Interval
9*6*6 anechoic chamber	Mao Rui	9*6*6	N/A	N/A	2022.06.15	3Year
Spectrum analyzer	R&S	FSV40-N	V7.0-4-62-2	101795	2023.09.19	1Year
Spectrum analyzer	Agilent	N9020A	A.14.16	MY51280803	2023.04.15	1Year
Receiver	R&S	ESR7	5.812	102543	2023.10.20	1Year
Receiver	R&S	ESCI	N/A		2023.10.20	1Year
Bilog Antenna	Schwarzbeck	VULB 9168	N/A	01318	2022.06.19	2Year
Horn Antenna	A.H. Systems	SAS-571	N/A	915	2022.06.17	2Year
Active Loop Antenna	Schwarzbeck	FMZB 1519B	N/A	N/A		2Year
RF Cable	/	N/J-NJ-RG58(1G) 9m	N/A	RE1	2023.09.17	1Year
RF Cable	/	N/J-NJ-RG58(1G) 10m	N/A	RE2	2023.09.17	1Year
RF Cable	/	N/J-SMAAJ-406(18G) 9m	N/A	CE1	2023.09.17	1Year
Pre-amplifier	HP	8447D	N/A	1616A02061	2023.04.15	1Year
Pre-amplifier	Agilent	8449B	N/A	3008A00551	2023.04.15	1Year
L.I.S.N.#1	R&S	ESH3-Z5	N/A	894981/024	2023.03.28	1Year
L.I.S.N.#2	R&S	ENV216	N/A	101291	2023.03.28	1 Year
Horn Antenna	A.H. Systems	SAS-571	N/A	915	2022.06.17	2 Year
power amplifier	Micotop	MPA-80-1000-250	N/A	MPA2206215	2023.04.15	1 Year
Power Meter	Keysight	E9300A	N/A	MY45105087	2023.04.15	1 Year
Power Sensor	Keysight	E9300A	N/A	MY55060025	2023.04.15	1 Year
power amplifier	Wei Huang	WHTH-1000-40-880	N/A	MPA2206216	2023.04.15	1 Year
Switching Mode Power Supply	PinHong	PH-1110	N/A	20220423007	2023.04.15	1 Year
Adjustable attenuator	MWRFtest	N/A	N/A	/	/	/
10dB Attenuator	/	10dB	N/A	N/A	2023.09.17	1 Year
Temperature and humidity test chamber	Asprey	LX-150L	N/A	N/A	2023.04.2	1 Year

Shenzhen Huaxin Information Technology Service Co.,Ltd

101,R&D Building,No.3 guansheng 4th Road,Luhu Community,Guanhu Street,Longhua District,Shenzhen,Guangdong,China

Tel:+86-755-21018313

Http://www.tecovo.net



Software Information			
Test Item	Software Name	Manufacturer	Version
RE	EMC-I	SKET	V1.4.0.1
CE	EMC-I	SKET	V1.4.0.1
RF-CE	RF Test Software	TACHOY	V2.0



3. Maximum Peak Output Power

3.1. Limit


Please refer FCC part 15.247 & RSS-247..

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W

3.2. Test Procedure

The transmitter output is connected to the RF Power meter. The Power meter is set to the peak power detection.

3.3. Test Setup



3.4. Test Result

For the measurement records, refer to the appendix I.



4. Bandwidth

4.1. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in RSS-GEN, FCC Section 15.247(a)(1), must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.3. Test Result

For the measurement records, refer to the appendix I.



5. Carrier Frequency Separation

5.1. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW

5.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The carrier frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW.

5.3. Test Result

For the measurement records, refer to the appendix I.



6. Number Of Hopping Channel

6.1. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels

6.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The number of hopping channel was measured by spectrum analyzer with 100kHz RBW and 300KHz VBW.

6.3. Test Result

For the measurement records, refer to the appendix I.



7. Dwell Time

7.1. Test limit

Please refer FCC part 15.247 & RSS-247.

Frequency hopping systems operating in the 2400MHz-2483.5 MHz. The average time of occupancy on any frequency shall not greater than 0.4 s within period of 0.4 seconds multiplied by the number of hopping channel employed.

7.2. Test Procedure

7.2.1. Place the EUT on the table and set it in transmitting mode.

7.2.2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

7.2.3. Set center frequency of spectrum analyzer = operating frequency.

7.2.4. Set the spectrum analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.

7.2.5. Repeat above procedures until all frequency measured were complete.

7.3. Test Result

For the measurement records, refer to the appendix I.



8. Emissions

8.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

15.209 Limit


FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009-0.490	300	2400/F(KHz)	/
0.490-1.705	30	24000/F(KHz)	/
1.705-30	30	30	29.5
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Note: The peak limit is 20 dB higher than the average limit




8.2. Block Diagram of Test setup


8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 30MHz



8.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



8.2.2 In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz





Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

8.3. Test Procedure

- (1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.
- (2) Setup EUT and simulator
- (3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.
 - (a) Change work frequency or channel of device if practicable.
 - (b) Change modulation type of device if practicable.
 - (c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions
- (4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated
- (5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 :2013on Radiated Emission test.
- (6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

8.4. Test Result

We have scanned from 9kHz to the 10th harmonic of the EUT's highest frequency.
Detailed information please see the following page.


From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



From 30MHz to 1000MHz: Conclusion: PASS


Vertical:



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Delta dB	Detector	Polar	Height cm	Angle deg
1*	44.308MHz	24.6	14.2	38.8	40.0	-1.2	QP	Ver	100.0	0.0
2*	53.765MHz	26.0	13.6	39.6	40.0	-0.4	QP	Ver	100.0	0.0
3*	73.286MHz	28.8	10.8	39.6	40.0	-0.4	QP	Ver	100.0	0.0
4*	118.513MHz	24.4	12.3	36.7	43.5	-6.8	QP	Ver	100.0	0.0
5*	181.441MHz	18.1	12.5	30.6	43.5	-12.9	QP	Ver	100.0	0.0
6*	221.939MHz	17.8	12.0	29.8	46.0	-16.2	QP	Ver	100.0	0.0



Horizontal:



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Delta dB	Detector	Polar	Height cm	Angle deg
1*	44.429MHz	12.5	14.2	26.7	40.0	-13.3	QP	Hor	100.0	0.0
2*	58.615MHz	16.2	13.1	29.3	40.0	-10.7	QP	Hor	100.0	0.0
3*	123.484MHz	19.0	12.7	31.7	43.5	-11.8	QP	Hor	100.0	0.0
4*	190.535MHz	15.8	11.8	27.6	43.5	-15.9	QP	Hor	100.0	0.0
5*	263.285MHz	19.0	13.7	32.7	46.0	-13.3	QP	Hor	100.0	0.0
6*	368.530MHz	14.5	16.7	31.2	46.0	-14.8	QP	Hor	100.0	0.0

Remark: All modes have been tested, and only worst data of GFSK mode, Channel 2441MHz was listed in this report.



From 1G-18GHz

Test Mode: GFSK TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	44.26	V	33.95	10.18	34.26	54.13	74	-19.87	PK
4804	36.31	V	33.95	10.18	34.26	46.18	54	-7.82	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	46.55	H	33.95	10.18	34.26	56.42	74	-17.58	PK
4804	36.91	H	33.95	10.18	34.26	46.78	54	-7.22	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: GFSK TX Mid									
4882	44.03	V	33.93	10.2	34.29	53.87	74	-20.13	PK
4882	35.51	V	33.93	10.2	34.29	45.35	54	-8.65	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
4882	43.83	H	33.93	10.2	34.29	53.67	74	-20.33	PK
4882	34.49	H	33.93	10.2	34.29	44.33	54	-9.67	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
Test Mode: GFSK TX High									
4960	44.88	V	33.98	10.22	34.25	54.83	74	-19.17	PK
4960	36.15	V	33.98	10.22	34.25	46.10	54	-7.90	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	42.75	H	33.98	10.22	34.25	52.70	74	-21.30	PK
4960	32.91	H	33.98	10.22	34.25	42.86	54	-11.14	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
Note: 1, Result = Read level + Antenna factor + cable loss-Amp factor 2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.									




Conducted RF Spurious Emission

For the measurement records, refer to the appendix I.

9. Band Edge Compliance

9.1. Block Diagram of Test Setup



9.2. Limit

All the lower and upper band-edges emissions appearing within restricted frequency bands shall not exceed the limits shown in FCC part 15.209 and RSS-GEN, all the other emissions outside operation shall be at least 20dB below the fundamental emissions, or comply with FCC part 15.209 and RSS-GEN limits.

9.3. Test Procedure

Refer to ANSI C 63.10, Clause 6.10.

All restriction band and non- restriction band have been tested, only worse case is reported.

9.4. Test Result


For the measurement records, refer to the appendix I.

Note: 1. *:Maximum data; x:Over limit; !:over margin.

2.Measurement=Reading Level+Correct Factor; Correct Factor=Antenna Factor+Cable Loss.

10. Power Line Conducted Emissions

10.1. Block Diagram of Test Setup



10.2. Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

10.3. Test Procedure

- (1) The EUT was placed on a non-metallic table, 80cm above the ground plane.
- (2) Setup the EUT and simulator as shown in 10.1
- (3) The EUT Power connected to the power mains through a power adapter and a line impedance stabilization network (L.I.S.N1). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N2), this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013on conducted Emission test.
- (4) The bandwidth of test receiver is set at 10KHz.

Shenzhen Huaxin Information Technology Service Co.,Ltd

101,R&D Building,No.3 guansheng 4th Road,Luhu Community,Guanhu Street,LonghuaDistrict,Shenzhen,Guangdong,China
Tel:+86-755-21018313 Http://www.tecovo.net




(5) The frequency range from 150 KHz to 30MHz is checked.

10.4.Test Result

PASS. (See below detailed test data)


Line:



No.	Frequency	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Delta dB	Detector	Polar
1*	20.414MHz	48.8	10.0	58.8	60.0	-1.2	PK	L1
2*	10.242MHz	46.0	9.9	55.9	60.0	-4.1	PK	L1
3*	27.582MHz	43.0	10.3	53.3	60.0	-6.7	PK	L1
4*	542.000kHz	29.1	9.7	38.8	56.0	-17.2	PK	L1
5*	3.578MHz	25.6	9.9	35.5	56.0	-20.5	PK	L1
6*	174.000kHz	32.8	9.7	42.5	64.8	-22.3	PK	L1
7*	20.414MHz	35.3	10.0	45.3	50.0	-4.7	AV	L1
8*	27.582MHz	27.6	10.3	37.9	50.0	-12.1	AV	L1
9*	10.430MHz	27.8	9.9	37.7	50.0	-12.3	AV	L1
10*	854.000kHz	18.4	9.8	28.2	46.0	-17.8	AV	L1
11*	202.000kHz	17.2	9.8	27.0	53.5	-26.5	AV	L1
12*	3.578MHz	5.4	9.9	15.3	46.0	-30.7	AV	L1



Neutral:



No.	Frequency	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Delta dB	Detector	Polar
1*	20.398MHz	48.6	10.1	58.7	60.0	-1.3	PK	N
2*	10.226MHz	46.9	9.9	56.8	60.0	-3.2	PK	N
3*	670.000kHz	34.3	9.6	43.9	56.0	-12.1	PK	N
4*	3.578MHz	29.3	9.8	39.1	56.0	-16.9	PK	N
5*	1.486MHz	26.6	9.6	36.2	56.0	-19.8	PK	N
6*	170.000kHz	32.0	9.9	41.9	65.0	-23.1	PK	N
7*	10.598MHz	36.5	9.9	46.4	50.0	-3.6	AV	N
8*	20.398MHz	35.2	10.1	45.3	50.0	-4.7	AV	N
9*	26.886MHz	30.9	10.3	41.2	50.0	-8.8	AV	N
10*	670.000kHz	19.6	9.6	29.2	46.0	-16.8	AV	N
11*	3.578MHz	12.8	9.8	22.6	46.0	-23.4	AV	N
12*	182.000kHz	16.9	9.9	26.8	54.4	-27.6	AV	N

Remark: All modes have been tested, and only worst data of GFSK mode, Channel 2441MHz was listed in this report.



11. Antenna Requirements

11.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203 and RSS-GEN, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2. Result

The EUT antenna is internal antenna. It complies with the standard requirement.



12. Test Setup Photo

Please refer to separated files for APPENDIX IV Test Setup Photos.



13. EUT Photo

Please refer to separated files for APPENDIX II External Photos and APPENDIX III Internal Photos.

-----THE END OF REPORT-----