

FCC 47 CFR MPE
Report

FCC ID: 2BEMA-HCL-001-8

RF Exposure Report

FCC 47 CFR MPE

Maximum Permissible Exposure

1. Maximum Permissible Exposure Applicable Standards

According to KDB 447498 D01 General RF Exposure Guidance v06, Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

	FCC 47 CFR MPE Report	FCC ID: 2BEMA-HCL-001-8
--	------------------------------	-------------------------

1.2. Maximum Permissible Exposure Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

BLE 1M							
Mode/Type	Frequency	Peak Output Power	Peak Output Power	Max Tune-up Power		Antenna gain	
	(MHz)	(dBm)	(mW)	(dBm)		(dBi)	(Linear)
GFSK	2402	1.47	1.403	1	± 1	0.17	1.040
	2440	3.24	2.109	3	± 1	0.17	1.040
	2480	3.21	2.094	3	± 1	0.17	1.040

Remark: The Peak Output Power data is derived from the RF test report number mentioned in the title of this document.

	FCC 47 CFR MPE Report	FCC ID: 2BEMA-HCL-001-8
--	------------------------------	-------------------------

3. Calculated Result and Limit

BLE 1M						
Mode/Type	Max Tune-up Power	Antenna Gain		Power Density	Limited of Power Density	Result
	(dBm)	(dBi)	(Linear)	(S) (mW/cm ²)	(S) (mW/cm ²)	
2.4G Band						
GFSK	4	0.17	1.040	0.00052	1.0	Complies

Conclusion: So, SAR test is not required

-----End of RF Exposure Evaluation -----

