



FCC PART 15.247 TEST REPORT

On Behalf of

RayNeo Co., Ltd.

5F TCL Electronics Building, TCL International E City, No.1001 Zhongshan
Park Road, Nanshan District, Shenzhen

FCC ID: 2BEMZ-ARGF20

Model: ARGF20

April 19, 2025

This Report Concerns: ☒ Original Report	Equipment Type: RayNeo X3 Pro
Test Engineer: LBi Li / <i>Li Li</i>	
Report Number: QCT25AR-1161E-01	
Test Date: March 14~April 16, 2025	
Test Result: Pass	
Reviewed By: Vincent Yang / <i>Vincent Yang</i>	
Approved By: Kendy Wang / <i>Kendy Wang</i>	
Prepared By: Shenzhen QC Testing Laboratory Co., Ltd. East of 1/F., Building E, Xinghong Science Park, No.111, Shuiku Road, Fenghuanggang, Xixiang Street, Bao'an District, Shenzhen, Guangdong, China Tel: 0755-23008269 Fax: 0755-23726780	





Table of Contents

1. GENERAL INFORMATION.....	5
1.1 Product Description for Equipment under Test (EUT)	5
1.2 System Test Configuration	6
1.3 Test Facility.....	7
1.4 Measurement Uncertainty.....	7
2. SUMMARY OF TEST RESULTS	8
3. LIST OF TEST AND MEASUREMENT INSTRUMENTS	9
3.1 Radiated Emission Test.....	9
3.2 RF Conducted test.....	9
4. ANTENNA REQUIREMENT	10
5. CONDUCTED PEAK OUTPUT POWER.....	11
5.1. Applicable Standard.....	11
5.2. Limit	11
5.3. Test setup.....	11
5.4. Test Procedure	11
5.5. Test Data	11
6. 20DB EMISSION BANDWIDTH.....	17
6.1 Applicable Standard.....	17
6.2 Limit	17
6.3 Test setup.....	17
6.4 Test Procedure	17
6.5 Test Data	17
7. CARRIER FREQUENCIES SEPARATION	28
7.1 Applicable Standard.....	28
7.2 Limit	28
7.3 Test setup.....	28
7.4 Test Procedure	28
7.5 Test Data	28
8. HOPPING CHANNEL NUMBER.....	31
8.1 Applicable Standard.....	31
8.2 Limit	31
8.3 Test setup.....	31
8.4 Test Procedure	31
8.5 Test Data	31
9. DWELL TIME	34
9.1 Applicable Standard.....	34



9.2	Limit	34
9.3	Test setup	34
9.4	Test Data	34
10.	SPURIOUS EMISSION IN NON-RESTRICTED & RESTRICTED BANDS	45
10.1	Conducted Emission Method	45
10.2	Radiated Emission Method	70



Report Number

Description

Issued Date

QCT25AR-1161E-01

Initial Issue

2025-4-19



1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Description:	RayNeo X3 Pro
Model No.:	ARGF20
Tested Model:	ARGF20
Sample(s) Status:	Engineer sample
Operation Frequency:	2402MHz~2480MHz
Channel numbers:	79
Channel separation:	1MHz
Modulation type:	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Antenna Type:	FPC Antenna
Antenna gain*1:	-1.4dBi
Power supply:	DC 3.87V (Powered by battery)
Trade Mark:	RayNeo
Applicant:	RayNeo Co., Ltd.
Address:	5F TCL Electronics Building,TCL International E City, No.1001 Zhongshan Park Road,Nanshan District, Shenzhen
Manufacturer:	RayNeo Co., Ltd.
Address:	5F TCL Electronics Building,TCL International E City, No.1001 Zhongshan Park Road,Nanshan District, Shenzhen
Sample No.:	Y25A1161E01LY

Note: *1This information provided by Manufacturer, SZ QC Lab is not responsible for the accuracy of this information.



1.2 System Test Configuration

1.2.1 Channel List

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note: In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency	Channel	Frequency
The lowest channel	2402MHz	The middle channel	2441MHz
The Highest channel	2480MHz		

1.2.2 EUT Exercise Software

" QRCT " software was used to test, The power level is 10. The software and power level was provided by the applicant.

1.2.3 Support Equipment

Manufacturer	Description	Model	Serial Number
/	/	/	/

1.2.4 Test mode and test voltage

Transmitting mode: Keep the EUT in continuously transmitting.

Test voltage: DC 3.87V (Powered by battery)



1.3 Test Facility

Test Firm : Shenzhen QC Testing Laboratory Co., Ltd.

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19. The testing quality system of our laboratory meets with ISO/IEC-17025 requirements. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS – Registration No.: L8464

The EMC Laboratory has been accredited by CNAS, and in compliance with ISO/IEC 17025:2017 General Requirements for testing Laboratories.

A2LA Certificate Number: 6759.01

The EMC Laboratory has been accredited by A2LA, and in compliance with ISO/IEC 17025:2017 General Requirements for testing Laboratories.

FCC Registration Number: 561109

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission.

IC Registration Number: 29628

CAB identifier: CN0141

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada.

1.4 Measurement Uncertainty

Parameter	Uncertainty
Occupied Channel Bandwidth	$\pm 1.42 \times 10^{-4}\%$
RF output power, conducted	$\pm 1.06\text{dB}$
Power Spectral Density, conducted	$\pm 1.06\text{dB}$
Unwanted Emissions, conducted	$\pm 2.51\text{dB}$
AC Power Line Conducted Emission	$\pm 1.80\text{dB}$
Radiated Spurious Emission test (9kHz-30MHz)	$\pm 2.66\text{dB}$
Radiated Spurious Emission test (30MHz-1000MHz)	$\pm 4.04\text{dB}$
Radiated Spurious Emission test (1000MHz-18000MHz)	$\pm 4.70\text{ dB}$
Radiated Spurious Emission test (18GHz-40GHz)	$\pm 4.80\text{dB}$
Temperature	$\pm 0.8^{\circ}\text{C}$
Humidity	$\pm 3.2\%$
DC and low frequency voltages	$\pm 0.1\%$
Time	$\pm 5\%$
Duty cycle	$\pm 5\%$

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2



2. Summary of Test Results

Test Item	Section	Result
Antenna Requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Not Applicable
Conducted Peak Output Power	15.247 (b)(1)	Pass
20dB Occupied Bandwidth	15.247 (a)(1)	Pass
Carrier Frequencies Separation	15.247 (a)(1)	Pass
Hopping Channel Number	15.247 (b)(1)	Pass
Dwell Time	15.247 (a)(1)(iii)	Pass
Radiated Emission	15.205/15.209	Pass
Band Edge	15.247(d)	Pass

Note: 1. In the configuration tested, the EUT complied with the standards specified above.
2. Test according to ANSI C63.10:2020
3.. All indications of Pass/Fail in this report are opinions expressed by Shenzhen QC Testing Laboratory Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.



3. List of Test and Measurement Instruments

3.1 Radiated Emission Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.Due
1.	EMI Test Receiver	Rohde&Schwarz	ESIB 7	2277573376	2025.03.17	2026.03.16
2.	EMI Test Receiver	Rohde&Schwarz	ESPI3	101131	2025.03.17	2026.03.16
3.	Spectrum Analyzer	Rohde&Schwarz	FSV 40	101458	2025.03.18	2026.03.17
4.	TRILOG Broadband Test-Antenna	SCHWARZBECK	VULB9168	VULB9168-588	2025.03.22	2026.03.21
5.	Loop Antenna	EMCO	6502	2133	2025.03.19	2026.03.18
6.	horn antenna	SCHWARZBECK	BBHA9120D	2069	2024.08.10	2025.08.09
7.	Horn Antenna	COM-MW	ZLB7-18-40G-950	12221225	2024.08.10	2026.08.09
8.	Pre-amplifier	MITEQ	TTA0001-18	2063645	2025.03.17	2026.03.16
9.	Pre-amplifier	MITEQ	TTA1800-30-HG	2063644	2025.03.17	2026.03.16
10.	Pre-amplifier	COM-MW	DLAN-18000-40000-02	10229104	2025.03.22	2026.03.21
11.	966 Camber	ZhongYU	9*6*6	/	2023.05.08	2026.05.07

Radiated Emission Measurement Software: EZ EMC Ver QCT03A2 RE+

3.2 RF Conducted test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.Due
1.	Wideband Radio Communication Tester	Rohde & Schwarz	CW500	151583	2025.03.18	2026.03.17
2.	Spectrum Analyzer	ROHDE&SCHWARZ	FSV 40	101458	2025.03.18	2026.03.17
3.	Signal Generator	Agilent	N5182A	MY50141563	2025.03.18	2026.03.17
4.	RF Automatic Test System	MW	MW100-RFCB/MW100-PSB	MW2007004	2025.03.18	2026.03.17

RF Conducted Measurement Software: MTS 8310 Ver 2.0.0.0



4. Antenna requirement

Standard requirement: FCC Part15 C Section 15.203 /247(c)

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

EUT Antenna: The Ant is FPC Antenna, the best case gain of the antenna is -1.4dBi, reference to the Internal photo for details.

5. Conducted Peak Output Power


5.1. Applicable Standard

FCC Part15 C Section 15.247 (a)(1)

5.2. Limit

For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

5.3. Test setup



5.4. Test Procedure

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

- Set the $RBW \geq DTS$ bandwidth.
- Set $VBW \geq [3 \times RBW]$.
- Set $span \geq [3 \times RBW]$.
- Sweep time = auto couple.
- Detector = peak.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use peak marker function to determine the peak amplitude level.

5.5. Test Data

Temperature	26.2 °C	Humidity	47 %
ATM Pressure	101.1kPa	Antenna Gain	-1.4dBi
Test by	LBi Li	Test result	PASS


Please refer to following table and plots.



Output Power:

Mode	Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
GFSK	Lowest	15.31	20.97	Pass
	Middle	15.87		
	Highest	15.72		
$\pi/4$ -DQPSK	Lowest	15.77	20.97	Pass
	Middle	15.24		
	Highest	14.95		
8-DPSK	Lowest	16.34	20.97	Pass
	Middle	15.71		
	Highest	15.16		


Power NVNT 1-DH5 2402MHz Ant1



Date: 16. APR 2025 11:07:33




Power NVNT 1-DH5 2441MHz Ant1



Date: 16.APR 2025 11:13:45


Power NVNT 1-DH5 2480MHz Ant1



Date: 16.APR 2025 11:18:34




Power NVNT 2-DH5 2402MHz Ant1



Date: 16.APR.2025 11:27:11


Power NVNT 2-DH5 2441MHz Ant1



Date: 16.APR.2025 11:33:27




Power NVNT 2-DH5 2480MHz Ant1



Date: 16.APR.2025 11:39:57


Power NVNT 3-DH5 2402MHz Ant1



Date: 16.APR.2025 11:50:34




Power NVNT 3-DH5 2441MHz Ant1



Date: 16.APR.2025 12:21:20

Power NVNT 3-DH5 2480MHz Ant1



Date: 16.APR.2025 13:46:12

6. 20dB Emission Bandwidth


6.1 Applicable Standard

FCC Part15 C Section 15.247 (a)(1)

6.2 Limit

N/A

6.3 Test setup



6.4 Test Procedure

The following conditions shall be observed for measuring the occupied bandwidth and x dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to "Sample". However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or "Max Hold") may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

6.5 Test Data

Temperature	26.2 °C	Humidity	47 %
ATM Pressure	101.1kPa	Antenna Gain	-1.4dBi
Test by	LBi Li	Test result	PASS

Please refer to following table and plots.




Measurement Data

Mode	Test channel	-20dB Emission Bandwidth (MHz)	99% Occupy Bandwidth (MHz)
GFSK	Lowest	0.949	0.862
	Middle	0.951	0.871
	Highest	0.996	0.892
$\pi/4$ -DQPSK	Lowest	1.322	1.187
	Middle	1.323	1.187
	Highest	1.323	1.186
8-DPSK	Lowest	1.307	1.186
	Middle	1.303	1.188
	Highest	1.3	1.188




-20dB Bandwidth:

-20dB Bandwidth NVNT 1-DH5 2402MHz Ant1




-20dB Bandwidth NVNT 1-DH5 2441MHz Ant1






-20dB Bandwidth NVNT 1-DH5 2480MHz Ant1




-20dB Bandwidth NVNT 2-DH5 2402MHz Ant1






-20dB Bandwidth NVNT 2-DH5 2441MHz Ant1




-20dB Bandwidth NVNT 2-DH5 2480MHz Ant1






-20dB Bandwidth NVNT 3-DH5 2402MHz Ant1




-20dB Bandwidth NVNT 3-DH5 2441MHz Ant1






-20dB Bandwidth NVNT 3-DH5 2480MHz Ant1




99% Occupied Bandwidth:

OBW NVNT 1-DH5 2402MHz Ant1






OBW NVNT 1-DH5 2441MHz Ant1




OBW NVNT 1-DH5 2480MHz Ant1






OBW NVNT 2-DH5 2402MHz Ant1



Date: 16.APR.2025 11:29:01

OBW NVNT 2-DH5 2441MHz Ant1



Date: 16.APR.2025 11:35:18




OBW NVNT 2-DH5 2480MHz Ant1



Date: 16.APR.2025 11:41:48


OBW NVNT 3-DH5 2402MHz Ant1



Date: 16.APR.2025 11:52:25




OBW NVNT 3-DH5 2441MHz Ant1



Date: 16.APR.2025 12:23:13

OBW NVNT 3-DH5 2480MHz Ant1



Date: 16.APR.2025 13:48:03

7. Carrier Frequencies Separation


7.1 Applicable Standard

FCC Part15 C Section 15.247 (a)(1)

7.2 Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

7.3 Test setup



7.4 Test Procedure

1. Set the EUT in transmitting mode, max hold the channel.
2. Set the adjacent channel of the EUT and max hold another trace.
3. Measure the channel separation.

7.5 Test Data

Temperature	26.2 °C	Humidity	47 %
ATM Pressure	101.1kPa	Antenna Gain	-1.4dBi
Test by	LBi Li	Test result	PASS

Please refer to following table and plots.



Measurement Data


Mode	Test channel	Carrier Frequencies Separation (MHz)	≥Limit (MHz)	Result
GFSK	Middle	1.044	0.664	Pass
π/4-DQPSK	Middle	0.999	0.882	Pass
8-DPSK	Middle	0.993	0.871	Pass

Mode	-20dB bandwidth (MHz) (worse case)	Limit (MHz) (Carrier Frequencies Separation)
GFSK	0.996	0.664
π/4-DQPSK	1.323	0.882
8-DPSK	1.307	0.871

Note: According to section 7.5

$$\text{Limit} = (2/3) * 20\text{dB bandwidth}$$


CFS NVNT 1-DH5 2441MHz Ant1




Date: 16.APR.2025 13:53:53



CFS NVNT 2-DH5 2441MHz Ant1



CFS NVNT 3-DH5 2441MHz Ant1



8. Hopping Channel Number


8.1 Applicable Standard

FCC Part15 C Section 15.247 (a) (1) (iii)

8.2 Limit

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

8.3 Test setup



8.4 Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.

8.5 Test Data

Temperature	26.2 °C	Humidity	47 %
ATM Pressure	101.1kPa	Antenna Gain	-1.4dBi
Test by	LBi Li	Test result	PASS


Please refer to following table and plots.

Measurement Data:


Mode	Hopping channel numbers	Limit	Result
GFSK	79	15	Pass
$\pi/4$ -DQPSK	79	15	Pass
8-DPSK	79	15	Pass



Hopping No. NVNT 1-DH5 2441MHz Ant1




Hopping No. NVNT 2-DH5 2441MHz Ant1





Hopping No. NVNT 3-DH5 2441MHz Ant1



9. Dwell Time


9.1 Applicable Standard

FCC Part15 C Section 15.247 (a)(1)(iii)

9.2 Limit

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

9.3 Test setup



9.4 Test Data

Temperature	26.2 °C	Humidity	47 %
ATM Pressure	101.1kPa	Antenna Gain	-1.4dBi
Test by	LBi Li	Test result	PASS

Please refer to following table and plots.




Mode	Channel	Burst Width [ms]	Total Hops [Num]	Result[s]	Limit[s]	Result
DH1	Hop	0.383	317	0.121	≤ 0.4	PASS
DH3	Hop	1.639	170	0.279	≤ 0.4	PASS
DH5	Hop	2.887	118	0.341	≤ 0.4	PASS
2DH1	Hop	0.387	315	0.122	≤ 0.4	PASS
2DH3	Hop	1.639	168	0.275	≤ 0.4	PASS
2DH5	Hop	2.884	99	0.286	≤ 0.4	PASS
3DH1	Hop	0.387	315	0.122	≤ 0.4	PASS
3DH3	Hop	1.638	163	0.267	≤ 0.4	PASS
3DH5	Hop	2.886	118	0.341	≤ 0.4	PASS


Note: The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$.



Dwell NVNT 1-DH1 2441MHz Ant1 One Burst




Dwell NVNT 1-DH1 2441MHz Ant1 Accumulated






Dwell NVNT 1-DH3 2441MHz Ant1 One Burst




Dwell NVNT 1-DH3 2441MHz Ant1 Accumulated






Dwell NVNT 1-DH5 2441MHz Ant1 One Burst




Dwell NVNT 1-DH5 2441MHz Ant1 Accumulated






Dwell NVNT 2-DH1 2441MHz Ant1 One Burst




Dwell NVNT 2-DH1 2441MHz Ant1 Accumulated






Dwell NVNT 2-DH3 2441MHz Ant1 One Burst




Dwell NVNT 2-DH3 2441MHz Ant1 Accumulated






Dwell NVNT 2-DH5 2441MHz Ant1 One Burst




Dwell NVNT 2-DH5 2441MHz Ant1 Accumulated






Dwell NVNT 3-DH1 2441MHz Ant1 One Burst




Dwell NVNT 3-DH1 2441MHz Ant1 Accumulated






Dwell NVNT 3-DH3 2441MHz Ant1 One Burst




Dwell NVNT 3-DH3 2441MHz Ant1 Accumulated






Dwell NVNT 3-DH5 2441MHz Ant1 One Burst



Dwell NVNT 3-DH5 2441MHz Ant1 Accumulated



10. Spurious Emission in Non-restricted & restricted Bands

10.1 Conducted Emission Method


10.1.1 Applicable Standard

FCC Part15 C Section 15.247 (d)

10.1.2 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

10.1.3 Test setup



10.1.4 Test Procedure

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- Repeat above procedures until all measured frequencies were complete.

10.1.5 Test Data

Temperature	26.2 °C	Humidity	47 %
ATM Pressure	101.1kPa	Antenna Gain	-1.4dBi
Test by	LBi Li	Test result	PASS

Please refer to following plots.




Band Edge:


Modulation	Frequency (MHz)	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
1-DH5	2402	No-Hopping	-65.4	-20	Pass
1-DH5	2480	No-Hopping	-64.66	-20	Pass
2-DH5	2402	No-Hopping	-60.64	-20	Pass
2-DH5	2480	No-Hopping	-58.21	-20	Pass
3-DH5	2402	No-Hopping	-62.8	-20	Pass
3-DH5	2480	No-Hopping	-61.8	-20	Pass



Band Edge NVNT 1-DH5 2402MHz Ant1 No-Hopping Ref




Band Edge NVNT 1-DH5 2402MHz Ant1 No-Hopping Emission






Band Edge NVNT 1-DH5 2480MHz Ant1 No-Hopping Ref



Date: 16.APR.2025 11:23:08


Band Edge NVNT 1-DH5 2480MHz Ant1 No-Hopping Emission



Date: 16.APR.2025 11:24:54




Band Edge NVNT 2-DH5 2402MHz Ant1 No-Hopping Ref



Date: 16.APR.2025 11:30:56


Band Edge NVNT 2-DH5 2402MHz Ant1 No-Hopping Emission



Date: 16.APR.2025 11:30:58




Band Edge NVNT 2-DH5 2480MHz Ant1 No-Hopping Ref



Date: 16.APR.2025 11:45:27

Band Edge NVNT 2-DH5 2480MHz Ant1 No-Hopping Emission



Date: 16.APR.2025 11:47:12