Appendix B

RF Test Data for BT (BLE) (Conducted Measurement)

Product Name: Remote control

Trade Mark: N/A

Test Model: L5B83G

Environmental Conditions

Temperature:	24.6° C
Relative Humidity:	52.4%
ATM Pressure:	100.0 kPa
Test Engineer:	Simba Huang
Supervised by:	Seal Chen

Contents

Page

COVER PAGE

1 Duty Cycle 3
1.1 Test Result 3
1.2 Test Graphs 4
2 Maximum Conducted Output Power 6
2.1 Test Result 6
2.2 Test Graphs 7
3 -6dB Bandwidth 9
3.1 Test Result 9
3.2 Test Graphs 10
4 Maximum Power Spectral Density Level 12
4.1 Test Result 12
4.2 Test Graphs 13
5 Band Edge 15
5.1 Test Result 15
5.2 Test Graphs 16
6 Conducted RF Spurious Emission 18
6.1 Test Result 18
6.2 Test Graphs 19
7 Restrict Band 22
7.1 Test Result 22
7.2 Test Graphs 23

1 Duty Cycle

1.1 Test Result

Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor	1/T (kHz)
BLE 1M	2402	64.79	1.88	2.56
BLE 1M	2440	64.49	1.9	2.56
BLE 1M	2480	64	1.94	2.56

1.2 Test Graphs

Test Graphs

BLE 1M 2402MHz



BLE 1M 2440MHz



BLE 1M 2480MHz



2 Maximum Conducted Output Power

2.1 Test Result

Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
BLE 1M	2402	1.13	30	Pass
BLE 1M	2440	1.84	30	Pass
BLE 1M	2480	1.26	30	Pass

2.2 Test Graphs

Test Graphs
BLE 1M 2402MHz



BLE 1M 2440MHz



BLE 1M 2480MHz



3 -6dB Bandwidth

3.1 Test Result

Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
BLE 1M	2402	0.707	0.5	Pass
BLE 1M	2440	0.671	0.5	Pass
BLE 1M	2480	0.738	0.5	Pass

3.2 Test Graphs

Test Graphs

BLE 1M 2402MHz



BLE 1M 2440MHz



BLE 1M 2480MHz



4 Maximum Power Spectral Density Level

4.1 Test Result

Mode	Frequency (MHz)	Conducted PSD (dBm/3-100kHz)	Limit (dBm/3kHz)	Verdict
BLE 1M	2402	-14.1	≤8	Pass
BLE 1M	2440	-13.47	≤8	Pass
BLE 1M	2480	-14.63	≤8	Pass

4.2 Test Graphs

Test Graphs
BLE 1M 2402MHz



BLE 1M 2440MHz



BLE 1M 2480MHz



5 Band Edge

5.1 Test Result

Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
BLE 1M	2402	-56.78	-20	Pass
BLE 1M	2480	-49.23	-20	Pass

5.2 Test Graphs

Test Graphs

BLE 1M 2402MHz Ref



BLE 1M 2402MHz Emission



Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40195 GHz	0.93 dBm		
M2		1	2.4 GHz	-45.93 dBm		
M3		1	2.39 GHz	-58.83 dBm		
M4		1	2.3137 GHz	-55.80 dBm		

BLE 1M 2480MHz Ref



BLE 1M 2480MHz Emission



6 Conducted RF Spurious Emission

6.1 Test Result

Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
BLE 1M	2402	-43.29	-20	Pass
BLE 1M	2440	-44.81	-20	Pass
BLE 1M	2480	-43.9	-20	Pass

6.2 Test Graphs

Test Graphs

BLE 1M 2402MHz Ref



BLE 1M 2402MHz Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.397 GHz	-0.52 dBm		
M2		1	16.362 GHz	-42.70 dBm		
M3		1	4.9269 GHz	-52.42 dBm		
M4		1	7.0446 GHz	-49.51 dBm		
M5		1	9.5857 GHz	-49.02 dBm		

BLE 1M 2440MHz Ref



BLE 1M 2440MHz Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.45 GHz	1.13 dBm		
M2		1	19.3531 GHz	-43.11 dBm		
M3		1	5.0064 GHz	-52.52 dBm		
M4		1	7.3357 GHz	-50.47 dBm		
M5		1	9.9298 GHz	-48.70 dBm		

BLE 1M 2480MHz Ref



BLE 1M 2480MHz Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.476 GHz	-0.86 dBm		
M2		1	19.8296 GHz	-43.15 dBm		
M3		1	4.9269 GHz	-52.52 dBm		
M4		1	7.3093 GHz	-49.74 dBm		
M5		1	9.8768 GHz	-48.95 dBm		

7 Restrict Band

7.1 Test Result

Mode	Frequency (MHz)	Spur Freq (MHz)	Power (dBm)	Gain (dBi)	Duty Factor	E (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
BLE 1M	2402	2310	-49.18	2	-	48.08	Peak	74	Pass
BLE 1M	2402	2310	-56.57	2	1.88	42.57	Average	54	Pass
BLE 1M	2402	2344.848	-46.08	2	-	51.18	Peak	74	Pass
BLE 1M	2402	2338.608	-54.53	2	1.88	44.61	Average	54	Pass
BLE 1M	2402	2390	-49.95	2	-	47.31	Peak	74	Pass
BLE 1M	2402	2390	-57.05	2	1.88	42.09	Average	54	Pass
BLE 1M	2480	2483.5	-47.26	2	-	50	Peak	74	Pass
BLE 1M	2480	2483.5	-55.44	2	1.94	43.76	Average	54	Pass
BLE 1M	2480	2487.376	-44.73	2	-	52.53	Peak	74	Pass
BLE 1M	2480	2487.688	-55	2	1.94	44.2	Average	54	Pass
BLE 1M	2480	2500	-50.08	2	-	47.18	Peak	74	Pass
BLE 1M	2480	2500	-56.45	2	1.94	42.75	Average	54	Pass

7.2 Test Graphs

Test Graphs

BLE 1M 2402MHz Peak



BLE 1M 2402MHz Average



BLE 1M 2480MHz Peak



BLE 1M 2480MHz Average



---The End---