



FCC REPORT

Applicant	:	Shenzhen Kuge Times Technology Co., Ltd.
Address of Applicant	:	1002, Complex Building C6, Hengfeng Industrial City, No. 739, Zhoushi Road, Hezhou Community, Hangcheng Street, Baoan District, Shenzhen, China
Manufacturer	:	Shenzhen Kuge Times Technology Co., Ltd.
Address of Manufacturer	:	1002, Complex Building C6, Hengfeng Industrial City, No. 739, Zhoushi Road, Hezhou Community, Hangcheng Street, Baoan District, Shenzhen, China
Equipment under Test	:	All-In-One CD phonograph
Model No.	:	X6
FCC ID	:	2BEOA-X6
Test Standard(s)	:	FCC Rules and Regulations Part 15 Subpart C Section 15.247, ANSI C63.10-2020 + Cor. 1-2023 + C63.10a- 2024 + Errata to C63.10a-2024
Report No.	:	A2601362-C01-R01
Issue Date	:	2026/02/28
Issued By	:	Shenzhen Alpha Product Testing Co., Ltd. Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103, Shenzhen City, Guangdong Province, P.R. China.

Table of Contents

1.	Summary of Test Results	7
2.	General Test Information.....	8
2.1.	Description of EUT.....	8
2.2.	Accessories of EUT	9
2.3.	Block diagram of EUT configuration for test.....	9
2.4.	Test mode description	9
2.5.	Deviations of test standard	10
2.6.	Test environment conditions.....	10
2.7.	Test laboratory	10
2.8.	Measurement uncertainty	11
3.	Maximum Peak Output Power	12
3.1.	Test equipment	12
3.2.	Block diagram of test setup	12
3.3.	Limits.....	12
3.4.	Assistant equipment used for test	12
3.5.	Test procedure	12
3.6.	Test result	12
4.	99% Bandwidth&20 dB Bandwidth	14
4.1.	Test equipment	14
4.2.	Block diagram of test setup	14
4.3.	Limits.....	14
4.4.	Assistant equipment used for test	14
4.5.	Test procedure	14
4.6.	Test result	14
5.	Carrier Frequency Separation	16
5.1.	Test equipment	16
5.2.	Block diagram of test setup	16
5.3.	Limits.....	16
5.4.	Assistant equipment used for test	16
5.5.	Test procedure	16
5.6.	Test result	16
6.	Number of Hopping Channel	18
6.1.	Test equipment	18
6.2.	Block diagram of test setup	18
6.3.	Limits.....	18
6.4.	Assistant equipment used for test	18

6.5.	Test procedure.....	18
6.6.	Test result	18
7.	Dwell Time	19
7.1.	Test equipment.....	19
7.2.	Block diagram of test setup	19
7.3.	Limits.....	19
7.4.	Assistant equipment used for test	19
7.5.	Test procedure.....	19
7.6.	Test result	20
8.	RF Conducted Spurious Emissions.....	21
8.1.	Test equipment.....	21
8.2.	Block diagram of test setup	21
8.3.	Limits.....	21
8.4.	Assistant equipment used for test	21
8.5.	Test procedure.....	21
8.6.	Test result	22
9.	Radiated Emission.....	23
9.1.	Test equipment.....	23
9.2.	Block diagram of test setup	23
9.3.	Limits.....	24
9.4.	Assistant equipment used for test	25
9.5.	Test procedure.....	25
9.6.	Test result	26
9.7.	Test data	27
10.	Band Edge(Conducted)	32
10.1.	Test equipment.....	32
10.2.	Block diagram of test setup	32
10.3.	Limits.....	32
10.4.	Assistant equipment used for test	32
10.5.	Test procedure.....	33
10.6.	Test result	33
11.	Power Line Conducted Emissions.....	34
11.1.	Test equipment.....	34
11.2.	Block diagram of test setup	34
11.3.	Limits.....	34
11.4.	Assistant equipment used for test	34
11.5.	Test procedure.....	34
11.6.	Test result	35

11.7.	Test data	36
12.	Band Edge(Radiated)	38
12.1.	Test equipment	38
12.2.	Block diagram of test setup	38
12.3.	Limits.....	38
12.4.	Assistant equipment used for test	39
12.5.	Test procedure.....	39
12.6.	Test result	39
12.7.	Test data	40
13.	Antenna Requirement.....	43
13.1.	Test equipment	43
13.2.	Block diagram of test setup	43
13.3.	Limits.....	43
13.4.	Assistant equipment used for test	43
13.5.	Test procedure.....	44
13.6.	Test result	44
14.	Test Setup Photograph.....	45
15.	Photos of the EUT	47
16.	Annex.....	55

Test Report Declare

Applicant	:	Shenzhen Kuge Times Technology Co., Ltd.
Address of Applicant	:	1002, Complex Building C6, Hengfeng Industrial City, No. 739, Zhoushi Road, Hezhou Community, Hangcheng Street, Baoan District, Shenzhen, China
Manufacturer	:	Shenzhen Kuge Times Technology Co., Ltd.
Address of Manufacturer	:	1002, Complex Building C6, Hengfeng Industrial City, No. 739, Zhoushi Road, Hezhou Community, Hangcheng Street, Baoan District, Shenzhen, China
Equipment under Test	:	All-In-One CD phonograph
Model No.	:	X6
Trademark	:	/

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247, ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024

We Declare:

The equipment described above is tested by Shenzhen Alpha Product Testing Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Shenzhen Alpha Product Testing Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	A2601362-C01-R01		
Date of Receipt:	2026/02/06	Date of Test:	2026/02/06 - 2026/02/10

Prepared By:

Yannis Wen

Yannis Wen/Engineer

Approved By:

Jack Xu

Jack Xu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen Alpha Product Testing Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
V0	Initial issue	2026/02/28	Yannis Wen

1. Summary of Test Results

No.	Test Parameter	Clause No.	Result
1	Maximum Peak Output Power	FCC Part 15: 15.247(b)(1), ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024	Pass
2	99% Bandwidth&20 dB Bandwidth	FCC Part 15: 15.215, ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024	Pass
3	Carrier Frequency Separation	FCC Part 15: 15.247(a)(1), ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024	Pass
4	Number of Hopping Channel	FCC Part 15: 15.247(a)(1), ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024	Pass
5	Dwell Time	FCC Part 15: 15.247(a)(1), ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024	Pass
6	RF Conducted Spurious Emissions	FCC Part 15: 15.247(d), ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024	Pass
7	Radiated Emission	FCC Part 15: 15.209, FCC Part 15: 15.247(d), ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024	Pass
8	Band Edge(Conducted)	FCC Part 15: 15.247(d), ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024	Pass
9	Power Line Conducted Emissions	FCC Part 15: 15.207, ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024	Pass
10	Band Edge(Radiated)	FCC Part 15: 15.247(d), ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024	Pass
11	Antenna Requirement	FCC Part 15: 15.203	Pass

Note: 1.N/A is an abbreviation for Not Applicable, and means this item is not applicable for this device or no need to test according to standard.

2. Decision rules for the conclusion of this test report: decision by actual test data without considering measurement uncertainty.

Software Information			
Test Item	Software Name	Manufacturer	Version
RE	EZ-EMC	Farad	Alpha-3A1
RF-CE	MTS 8310	MWRfTest	V2.0.0.0

2. General Test Information

2.1. Description of EUT

EUT Name	: All-In-One CD phonograph
Model Number	: X6
Difference of model number	: /
Power Supply	: DC 3.7V from battery, DC 5V from Type-C
Hardware Version	: V1.0
Software Version	: V1.0

Radio Specification	: Bluetooth BR/EDR
Operation Frequency	: 2402 MHz to 2480 MHz
Modulation	: GFSK, $\pi/4$ -DQPSK, 8-DPSK
Antenna Type	: PCB Antenna
Max Antenna Gain(dBi)	: 1.7dBi (Antenna information is provided by applicant.)

Channel information					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	27	2429	54	2456
1	2403	28	2430	55	2457
2	2404	29	2431	56	2458
3	2405	30	2432	57	2459
4	2406	31	2433	58	2460
5	2407	32	2434	59	2461
6	2408	33	2435	60	2462
7	2409	34	2436	61	2463
8	2410	35	2437	62	2464
9	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477

22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

“☑” means to be chosen or applicable; “☐” means don't to be chosen or not applicable; This note applies to entire report.

2.2. Accessories of EUT


Accessories	Manufacturer	Model number	Description
/	/	/	/

2.3. Block diagram of EUT configuration for test

Conducted Test Setup



Radiated Test Setup



2.4. Test mode description

The test software “BT_Tool” was used to control EUT work in Continuous Bluetooth TX mode, and select test channel, default power level, wireless mode.

Mode	Data rate(Mbps)	Channel	Frequency (MHz)
GFSK hopping off mode	1	Low :CH0	2402
	1	Middle: CH39	2441
	1	High: CH78	2480
$\pi/4$ DQPSK hopping off mode	2	Low :CH0	2402
	2	Middle: CH39	2441
	2	High: CH78	2480
8-DPSK hopping off mode	3	Low :CH0	2402

	3	Middle: CH39	2441
	3	High: CH78	2480
GFSK hopping on mode	1	CH0 to CH78	2402-2480
$\pi/4$ -DQPSK hopping on mode	2	CH0 to CH78	2402-2480
8-DPSK hopping on mode	3	CH0 to CH78	2402-2480

2.5. Deviations of test standard

No deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Items	Required
Temperature range:	15-35°C
Humidity range:	25-75%
Pressure range:	86-106kPa

Note: The specific temperature and humidity information of each test item refers to the temperature and humidity record in the corresponding test data.

2.7. Test laboratory

Shenzhen Alpha Product Testing Co., Ltd.

Add.: Building i, No.2, Lixin Road, Fuyong Street, Bao'an District, 518103, Shenzhen City, Guangdong Province, P.R. China.

Tel.: 4008-3008-95, Website: <http://www.a-lab.cn>, Email: service@a-lab.cn

CNAS Accreditation No. L7472; A2LA Accreditation Number: 4762.01

FCC Designation Number: CN1182, Test Firm Registration Number: 203110

Innovation, Science and Economic Development Canada Site Registration Number: 12135A

CAB identifier: CN0085

2.8. Measurement uncertainty


Item	Uncertainty
Uncertainty for Power point Conducted Emissions Test	1.63dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	3.5dB
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.74dB(Polarize: V)
	3.76dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	3.77dB(Polarize: V)
	3.80dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (18GHz to 40GHz)	4.31 dB(Polarize: V)
	4.30 dB(Polarize: H)
Uncertainty for radio frequency	5.06×10^{-8} GHz
Uncertainty for conducted RF Power	0.40dB
Uncertainty for temperature	0.2°C
Uncertainty for humidity	1%
Uncertainty for DC and low frequency voltages	0.06%

3. Maximum Peak Output Power

3.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal Due To
CMW500	ROHDE&SCH WARZ	CMW500	Aa-EE073	2025/08/04	2026/08/03
Spectrum analyzer	ROHDE&SCH WARZ	FSV40-N	Aa-EE081	2025/08/04	2026/08/03
Vector Signal Generator	Agilent	N5182A	Aa-EE040	2025/08/04	2026/08/03
Power Sensor	DARE	RPR3006W	Aa-EE071	2025/08/04	2026/08/03
Power Sensor	DARE	RPR3006W	Aa-EE070	2025/08/04	2026/08/03
Power meter	Agilent	E4419B	Aa-EE045	2025/08/04	2026/08/03

3.2. Block diagram of test setup



3.3. Limits

Please refer section 15.247

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W

3.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

3.5. Test procedure

Details see the KDB 558074 D01 15.247 Meas Guidance v05r02

Place the EUT on the table and set it in transmitting mode.

Measure out each mode and each bands peak output power of EUT.

Note: The cable loss and attenuator loss were offset into measure device as amplitude offset.

3.6. Test result

Test Site: RF Laboratory	Test Date: 2026/02/06--2026/02/06
Condition: 24.2°C,56%RH,101kPa	Test Engineer: Yannis Wen

Memo: Only show the test data of the worst case.
--

EUT Name: All-In-One CD phonograph	EUT Model: X6
Sample No.: A2601362-S0001	Test Mode: hopping off mode
Power supply: DC 3.7V from battery	Memo: Please refer to Maximum Conducted Output Power of the Annex.


/

4. 99% Bandwidth&20 dB Bandwidth

4.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal Due To
CMW500	ROHDE&SCH WARZ	CMW500	Aa-EE073	2025/08/04	2026/08/03
Spectrum analyzer	ROHDE&SCH WARZ	FSV40-N	Aa-EE081	2025/08/04	2026/08/03
Vector Signal Generator	Agilent	N5182A	Aa-EE040	2025/08/04	2026/08/03
Power Sensor	DARE	RPR3006W	Aa-EE071	2025/08/04	2026/08/03
Power Sensor	DARE	RPR3006W	Aa-EE070	2025/08/04	2026/08/03
Power meter	Agilent	E4419B	Aa-EE045	2025/08/04	2026/08/03

4.2. Block diagram of test setup



4.3. Limits

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in FCC Section 15.247(a)(1), must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

4.5. Test procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.6. Test result

Test Site: RF Laboratory	Test Date: 2026/02/06--2026/02/06
Condition: 24.2°C,56%RH,101kPa	Test Engineer: Yannis Wen
Memo: Only show the test data of the worst case.	

EUT Name: All-In-One CD phonograph	EUT Model: X6
Sample No.: A2601362-S0001	Test Mode: hopping off mode
Power supply: DC 3.7V from battery	Memo: Please refer to -20dB Bandwidth & Occupied Channel Bandwidth of the Annex.


/

5. Carrier Frequency Separation

5.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal Due To
CMW500	ROHDE&SCH WARZ	CMW500	Aa-EE073	2025/08/04	2026/08/03
Spectrum analyzer	ROHDE&SCH WARZ	FSV40-N	Aa-EE081	2025/08/04	2026/08/03
Vector Signal Generator	Agilent	N5182A	Aa-EE040	2025/08/04	2026/08/03
Power Sensor	DARE	RPR3006W	Aa-EE071	2025/08/04	2026/08/03
Power Sensor	DARE	RPR3006W	Aa-EE070	2025/08/04	2026/08/03
Power meter	Agilent	E4419B	Aa-EE045	2025/08/04	2026/08/03

5.2. Block diagram of test setup



5.3. Limits

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW

5.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

5.5. Test procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The carrier frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW.

5.6. Test result

Test Site: RF Laboratory	Test Date: 2026/02/06--2026/02/06
Condition: 24.2°C,56%RH,101kPa	Test Engineer: Yannis Wen
Memo: Only show the test data of the worst case.	

EUT Name: All-In-One CD phonograph	EUT Model: X6
------------------------------------	---------------

Sample No.: A2601362-S0001	Test Mode: hopping onmode
Power supply: DC 3.7V from battery	Memo: Please refer to Carrier Frequencies Separation of the Annex.


/

6. Number of Hopping Channel

6.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal Due To
CMW500	ROHDE&SCH WARZ	CMW500	Aa-EE073	2025/08/04	2026/08/03
Spectrum analyzer	ROHDE&SCH WARZ	FSV40-N	Aa-EE081	2025/08/04	2026/08/03
Vector Signal Generator	Agilent	N5182A	Aa-EE040	2025/08/04	2026/08/03
Power Sensor	DARE	RPR3006W	Aa-EE071	2025/08/04	2026/08/03
Power Sensor	DARE	RPR3006W	Aa-EE070	2025/08/04	2026/08/03
Power meter	Agilent	E4419B	Aa-EE045	2025/08/04	2026/08/03

6.2. Block diagram of test setup



6.3. Limits

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels

6.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

6.5. Test procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The number of hopping channel was measured by spectrum analyzer with 100kHz RBW and 300KHz VBW.

6.6. Test result

Test Site: RF Laboratory	Test Date: 2026/02/06--2026/02/06
Condition: 24.2°C,56%RH,101kPa	Test Engineer: Yannis Wen
Memo: Only show the test data of the worst case.	


EUT Name: All-In-One CD phonograph	EUT Model: X6
Sample No.: A2601362-S0001	Test Mode: hopping on mode
Power supply: DC 3.7V from battery	Memo: Please refer to Number of Hopping Channel of the Annex.

7. Dwell Time

7.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal Due To
CMW500	ROHDE&SCH WARZ	CMW500	Aa-EE073	2025/08/04	2026/08/03
Spectrum analyzer	ROHDE&SCH WARZ	FSV40-N	Aa-EE081	2025/08/04	2026/08/03
Vector Signal Generator	Agilent	N5182A	Aa-EE040	2025/08/04	2026/08/03
Power Sensor	DARE	RPR3006W	Aa-EE071	2025/08/04	2026/08/03
Power Sensor	DARE	RPR3006W	Aa-EE070	2025/08/04	2026/08/03
Power meter	Agilent	E4419B	Aa-EE045	2025/08/04	2026/08/03

7.2. Block diagram of test setup



7.3. Limits

Please refer section 15.247

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz. The average time of occupancy on any frequency shall not greater than 0.4 s within period of 0.4 seconds multiplied by the number of hopping channel employed.

7.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

7.5. Test procedure

Place the EUT on the table and set it in transmitting mode.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Set center frequency of spectrum analyzer = operating frequency.

Set the spectrum analyzer as RBW=1MHz, VBW=1MHz, Span = 0Hz, Sweep = auto.

Repeat above procedures until all frequency measured were complete.

7.6. Test result

Test Site: RF Laboratory	Test Date: 2026/02/06--2026/02/06
Condition: 24.2°C,56%RH,101kPa	Test Engineer: Yannis Wen
Memo: Only show the test data of the worst case.	

EUT Name: All-In-One CD phonograph	EUT Model: X6
Sample No.: A2601362-S0001	Test Mode: hopping on mode
Power supply: DC 3.7V from battery	Memo: Please refer to Dwell Time of the Annex.


/

8. RF Conducted Spurious Emissions

8.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal Due To
CMW500	ROHDE&SCH WARZ	CMW500	Aa-EE073	2025/08/04	2026/08/03
Spectrum analyzer	ROHDE&SCH WARZ	FSV40-N	Aa-EE081	2025/08/04	2026/08/03
Vector Signal Generator	Agilent	N5182A	Aa-EE040	2025/08/04	2026/08/03
Power Sensor	DARE	RPR3006W	Aa-EE071	2025/08/04	2026/08/03
Power Sensor	DARE	RPR3006W	Aa-EE070	2025/08/04	2026/08/03
Power meter	Agilent	E4419B	Aa-EE045	2025/08/04	2026/08/03

8.2. Block diagram of test setup



8.3. Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20dB.

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

8.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

8.5. Test procedure

Place the EUT on the table and set it in transmitting mode.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Set frequency of spectrum analyzer = 30MHz-26.5GHz.

Set the spectrum analyzer as RBW=100kHz, VBW $\geq$ 3*RBW =300kHz, Sweep = auto.
The spectrum analyzer is set to the peak detection

8.6. Test result

Test Site: RF Laboratory	Test Date: 2026/02/06--2026/02/06
Condition: 24.2°C,56%RH,101kPa	Test Engineer: Yannis Wen
Memo: Only show the test data of the worst case.	

EUT Name: All-In-One CD phonograph	EUT Model: X6
Sample No.: A2601362-S0001	Test Mode: hopping off mode
Power supply: DC 3.7V from battery	Memo: Please refer to Conducted RF Spurious Emission of the Annex.


/


9. Radiated Emission

9.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal Due To
Spectrum analyzer	ROHDE&SCHWARZ	FSU	Aa-EE075	2025/08/04	2026/08/03
Horn Antenna	SCHWARZBECK	BBHA 9120 D	Aa-EE076	2025/08/11	2027/08/10
Test Receiver	ROHDE&SCHWARZ	ESR	Aa-EE048	2025/08/04	2026/08/03
Bilog Antenna	SCHWARZBECK	VULB 9168	Aa-EE001	2025/08/11	2027/08/10
Amplifier	SKET	LNPA_0118G-45	Aa-EE087	2025/08/04	2026/08/03
Horn Antenna	SCHWARZBECK	BBHA 9170	Aa-EE077	2025/08/11	2027/08/10
Loop Antenna	SCHWARZBECK	FMZB 1519B	Aa-EE074	2025/08/11	2027/08/10

9.2. Block diagram of test setup





9.3. Limits

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2

4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

1Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2Above 38.6

15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		uV/m	dBuV/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
960~1000	3	500	54.0
Above 1000	3	74.0 dBuV/m (Peak) 54.0 dBuV/m (Average)	

Note: Harmonic emissions limits comply with below 54 dBuV/m at 3m. Other emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or comply with the radiated emissions limits specified in section15.209(a) limit in the table below has to be followed.

9.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

9.5. Test procedure

The measuring distance of 3m shall be used for measurements at frequency up to 1GH and above 1GHz, The EUT was placed on a rotating 0.8 m high above ground for below 1GHz and 1.5m high for above1GHz testing, The table was rotated 360 degrees to determine the position of the highest radiation.

The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set of make measurement.

The initial step in collecting conducted emission data is a spectrum analyzer Peak detector mode pre-scanning the measurement frequency range. Significant Peaks are then marked. and then Qusia Peak Detector mode premeasured.

If Peak value comply with QP limit Below 1GHz.The EUT deemed to comply with QP limit. But the Peak value and average value both need to comply with applicable limit above 1GHz.

For the actual test configuration, please see the test setup photo.

9.6. Test result

Test Site: Chamber 1#(RSE)	Test Date: 2026/02/10--2026/02/10
Condition: 24°C,56%RH,101kPa	Test Engineer: Yannis Wen
Memo: /	

EUT Name: All-In-One CD phonograph	EUT Model: X6
Sample No.: A2601362-S0001	Test Mode: All modes
Power supply: DC 3.7V from battery	Memo: /

Test Condition

Continual Transmitting in maximum power.

9KHz~150KHz	RBW200Hz	VBW1KHz
150KHz~30MHz	RBW9KHz	VBW 30KHz
30MHz~1GHz	RBW120KHz	VBW 300KHz
Above1GHz	RBW1MHz	VBW 3MHz

We have scanned the 10th harmonic from 9 kHz to the EUT.

Detailed information please see the following page.

From 9KHz to 30MHz: Conclusion: PASS

Note: 1.The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

2. Only show the test data of the worst Channel in this report.


9.7. Test data



深圳阿尔法商品检验有限公司
SHENZHEN ALPHA PRODUCT TESTING CO.,LTD.

深圳阿尔法商品检验有限公司
Shenzhen Alpha Product Testing Co.,Ltd.
地址: ALPHA 广东省深圳市宝安区福永街道立新路 2 号 i 栋
TEL: 4008-3008-95

Test Lab: ALPHA test Lab chamber 1	Project: A2601362-C01
EUT: A2601362-S0001	Test Engineer: <i>yuanm3 wen</i>
M/N:	Temperature: 24℃
S/N:	Humidity: 56%RH
Test Mode: Mode 1	Test Voltage: DC 3.7V from battery
Note:	Test Data: 2026-02-10 09:50:48




No.	Frequency	Limit dBuV/m	Level dBuV/m	Margin dB	Factor dB/m	Detector	Height cm	Height cm	Angle deg
1*	69.649MHz	40.0	33.7	-6.3	19.6	PK	Hor	200.0	67.0
2*	139.489MHz	43.5	32.2	-11.3	20.8	PK	Hor	200.0	226.0
3*	174.409MHz	43.5	32.5	-11.0	20.6	PK	Hor	200.0	0.0
4*	260.739MHz	46.0	36.4	-9.6	19.9	PK	Hor	200.0	132.0
5*	391.689MHz	46.0	37.0	-9.0	22.5	PK	Hor	200.0	317.0
6*	488.689MHz	46.0	32.2	-13.8	24.4	PK	Hor	200.0	335.0



深圳阿尔法商品检验有限公司
SHENZHEN ALPHA PRODUCT TESTING CO.,LTD.

深圳阿尔法商品检验有限公司
Shenzhen Alpha Product Testing Co.,Ltd.
地址: ALPHA 广东省深圳市宝安区福永街道立新路 2 号 i 栋
TEL: 4008-3008-95

Test Lab: ALPHA test Lab chamber 1	Project: A2601362-C01
EUT: A2601362-S0001	Test Engineer: <i>Yanni3 wen</i>
M/N:	Temperature: 24℃
S/N:	Humidity: 56%RH
Test Mode: Mode 1	Test Voltage: DC 3.7V from battery
Note:	Test Data: 2026-02-10 09:53:37



No.	Frequency	Limit dBuV/m	Level dBuV/m	Margin dB	Factor dB/m	Detector	Height cm	Height cm	Angle deg
1	391.732MHz	46.0	39.2	-6.8	22.5	QP	Ver	100.0	56.0
2*	68.679MHz	40.0	33.3	-6.7	19.7	PK	Ver	100.0	202.0
3*	175.258MHz	43.5	28.2	-15.3	20.5	PK	Ver	100.0	176.0
4*	304.025MHz	46.0	37.2	-8.8	21.2	PK	Ver	100.0	165.0
5*	457.891MHz	46.0	38.6	-7.4	24.0	PK	Ver	100.0	144.0
6*	889.420MHz	46.0	34.1	-11.9	30.7	PK	Ver	100.0	176.0

From 1G-25GHz

Test Mode: GFSK TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	46.24	V	33.95	10.18	34.26	56.11	74	-17.89	PK
4804	36.12	V	33.95	10.18	34.26	45.99	54	-8.01	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	44.74	H	33.95	10.18	34.26	54.61	74	-19.39	PK
4804	34.22	H	33.95	10.18	34.26	44.09	54	-9.91	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: GFSK TX Mid									
4882	43.85	V	33.93	10.2	34.29	53.69	74	-20.31	PK
4882	37.02	V	33.93	10.2	34.29	46.86	54	-7.14	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
4882	41.78	H	33.93	10.2	34.29	51.62	74	-22.38	PK
4882	35.19	H	33.93	10.2	34.29	45.03	54	-8.97	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
Test Mode: GFSK TX High									
4960	43.54	V	33.93	10.2	34.29	53.38	74	-20.62	PK
4960	35.39	V	33.93	10.2	34.29	45.23	54	-8.77	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	46.10	H	33.93	10.2	34.29	55.94	74	-18.06	PK
4960	35.75	H	33.93	10.2	34.29	45.59	54	-8.41	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
Note:									
1, Result = Read level + Antenna factor + cable loss-Amp factor									
2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.									

Test Mode: $\pi/4$ DQPSK TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	46.24	V	33.95	10.18	34.26	56.11	74	-17.89	PK
4804	37.23	V	33.95	10.18	34.26	47.10	54	-6.90	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	46.03	H	33.95	10.18	34.26	55.90	74	-18.10	PK
4804	36.49	H	33.95	10.18	34.26	46.36	54	-7.64	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: $\pi/4$ DQPSK TX Mid									
4882	45.57	V	33.93	10.2	34.29	55.41	74	-18.59	PK
4882	34.67	V	33.93	10.2	34.29	44.51	54	-9.49	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
4882	44.36	H	33.93	10.2	34.29	54.20	74	-19.80	PK
4882	33.57	H	33.93	10.2	34.29	43.41	54	-10.59	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
Test Mode: $\pi/4$ DQPSK TX High									
4960	44.37	V	33.93	10.2	34.29	54.21	74	-19.79	PK
4960	36.04	V	33.93	10.2	34.29	45.88	54	-8.12	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	45.46	H	33.93	10.2	34.29	55.30	74	-18.70	PK
4960	35.25	H	33.93	10.2	34.29	45.09	54	-8.91	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
Note:									
1, Result = Read level + Antenna factor + cable loss-Amp factor									
2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.									


Test Mode: 8-DPSK TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	46.24	V	33.95	10.18	34.26	56.11	74	-17.89	PK
4804	35.18	V	33.95	10.18	34.26	45.05	54	-8.95	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	45.45	H	33.95	10.18	34.26	55.32	74	-18.68	PK
4804	34.32	H	33.95	10.18	34.26	44.19	54	-9.81	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: 8-DPSK TX Mid									
4882	47.00	V	33.93	10.2	34.29	56.84	74	-17.16	PK
4882	35.71	V	33.93	10.2	34.29	45.55	54	-8.45	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
4882	42.91	H	33.93	10.2	34.29	52.75	74	-21.25	PK
4882	33.91	H	33.93	10.2	34.29	43.75	54	-10.25	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
Test Mode: 8-DPSK TX High									
4960	44.87	V	33.93	10.2	34.29	54.71	74	-19.29	PK
4960	33.74	V	33.93	10.2	34.29	43.58	54	-10.42	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	42.99	H	33.93	10.2	34.29	52.83	74	-21.17	PK
4960	34.87	H	33.93	10.2	34.29	44.71	54	-9.29	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
Note:									
1, Result = Read level + Antenna factor + cable loss-Amp factor									
2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.									

10. Band Edge (Conducted)

10.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal Due To
CMW500	ROHDE&SCHWARZ	CMW500	Aa-EE073	2025/08/04	2026/08/03
Spectrum analyzer	ROHDE&SCHWARZ	FSV40-N	Aa-EE081	2025/08/04	2026/08/03
Vector Signal Generator	Agilent	N5182A	Aa-EE040	2025/08/04	2026/08/03
Power Sensor	DARE	RPR3006W	Aa-EE071	2025/08/04	2026/08/03
Power Sensor	DARE	RPR3006W	Aa-EE070	2025/08/04	2026/08/03
Power meter	Agilent	E4419B	Aa-EE045	2025/08/04	2026/08/03

10.2. Block diagram of test setup



10.3. Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under [paragraph \(b\)\(3\)](#) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in [§ 15.209\(a\)](#) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in [§ 15.205\(a\)](#), must also comply with the radiated emission limits specified in [§ 15.209\(a\)](#) (see [§ 15.205\(c\)](#)).

10.4. Assistant equipment used for test

Assistant	Manufacturer	Model number	Description	other
-----------	--------------	--------------	-------------	-------

equipment				
/	/	/	/	/

10.5. Test procedure

1) Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.

2) Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation.

3) Attenuation: Auto (at least 10 dB preferred).

4) Sweep time: Coupled.

5) Resolution bandwidth: 100 kHz.

6) Video bandwidth: 300 kHz.

7) Detector: Peak.

8) Trace: Max hold.

All restriction band and non- restriction band have been tested, only worse case is reported.

10.6. Test result

Test Site: RF Laboratory	Test Date: 2026/02/06--2026/02/06
Condition: 24.2°C,56%RH,101kPa	Test Engineer: Yannis Wen
Memo: Only show the test data of the worst case.	

EUT Name: All-In-One CD phonograph	EUT Model: X6
Sample No.: A2601362-S0001	Test Mode: hopping on/off mode-L/H
Power supply: DC 3.7V from battery	Memo: Please refer to Band Edge & Band Edge(Hopping) of the Annex.


/

11. Power Line Conducted Emissions

11.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal Due To
Test Receiver	ROHDE&SCHWARZ	ESCI	Aa-EE005	2025/08/04	2026/08/03
Pulse Limiter	SCHWARZBEC K	9516F	Aa-EE004	2025/08/04	2026/08/03
L.I.S.N.	SCHWARZBEC K	NSLK8126	Aa-EE003	2025/08/04	2026/08/03

11.2. Block diagram of test setup



11.3. Limits

Frequency	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150 kHz~500 kHz	66 ~ 56*	56 ~ 46*
500 kHz~5 MHz	56	46
5 MHz~30 MHz	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

3. The limit decreases in line with the logarithm of the frequency in rang of 0.15 to 0.50 MH

11.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

11.5. Test procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10-2020 + Cor. 1-2023 + C63.10a-2024 + Errata to C63.10a-2024 on Conducted Emission Measurement.

The bandwidth of test receiver is set at 9 kHz.

11.6. Test result

Test Site: Shield Room CE 1#	Test Date: 2026/02/10--2026/02/10
Condition: 24°C,45%RH,101kPa	Test Engineer: Yannis Wen
Memo: /	

EUT Name: All-In-One CD phonograph	EUT Model: X6
Sample No.: A2601362-S0001	Test Mode: All modes
Power supply: DC 5V from PC	Memo: /

PASS. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: "-----" means Peak detection; "-----" means Average detection.

Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded the worst case.


11.7. Test data



深圳阿尔法商品检验有限公司
SHENZHEN ALPHA PRODUCT TESTING CO.,LTD.

深圳阿尔法商品检验有限公司
Shenzhen Alpha Product Testing Co.,Ltd.
地址: ALPHA 广东省深圳市宝安区福永街道立新路 2 号 i 栋
TEL: 4008-3008-95

Test Lab: Alpha test Lab Conducted 1	Project: A2601362-C01
EUT: A2601362-S0001	Test Engineer: <i>Yanni3 wen</i>
M/N:	Temperature: 24℃
S/N:	Humidity: 45%RH
Test Mode: Mode 1	Test Voltage: DC 5V from Type-C
Note:	Test Data: 2026-02-10 14:26:50




No.	Frequency	Limit dBuV	Level dBuV	Delta dB	Factor dB	Detector	Polar
1*	178.000 kHz	64.6	39.2	-25.3	9.8	PK	L1
2*	250.000 kHz	61.8	37.6	-24.2	9.8	PK	L1
3*	438.000 kHz	57.1	36.1	-21.0	9.8	PK	L1
4*	570.000 kHz	56.0	37.3	-18.7	9.8	PK	L1
5*	3.160 MHz	56.0	39.2	-16.8	9.9	PK	L1
6*	13.180 MHz	60.0	35.6	-24.4	10.1	PK	L1
7*	182.000 kHz	54.4	29.8	-24.6	9.8	AV	L1
8*	394.000 kHz	48.0	25.1	-22.8	9.8	AV	L1
9*	462.000 kHz	46.7	25.8	-20.8	9.8	AV	L1
10*	630.000 kHz	46.0	25.4	-20.6	9.8	AV	L1
11*	3.320 MHz	46.0	26.3	-19.7	9.9	AV	L1
12*	13.060 MHz	50.0	26.8	-23.2	10.1	AV	L1



深圳阿尔法商品检验有限公司
Shenzhen Alpha Product Testing Co.,Ltd.
地址: ALPHA 广东省深圳市宝安区福永街道立新路2号i栋
TEL: 4008-3008-95

Test Lab: Alpha test Lab Conducted 1	Project: A2601362-C01
EUT: A2601362-S0001	Test Engineer: <i>Yanni's Wen</i>
M/N:	Temperature: 24℃
S/N:	Humidity: 45%RH
Test Mode: Mode 1	Test Voltage: DC 5V from Type-C
Note:	Test Data: 2026-02-10 14:27:37




No.	Frequency	Limit dBuV	Level dBuV	Delta dB	Factor dB	Detector	Polar
1*	186.000 kHz	64.2	39.4	-24.8	9.7	PK	N
2*	358.000 kHz	58.8	37.1	-21.7	9.7	PK	N
3*	630.000 kHz	56.0	37.5	-18.5	9.8	PK	N
4*	1.420 MHz	56.0	31.7	-24.3	9.8	PK	N
5*	3.240 MHz	56.0	36.8	-19.2	9.9	PK	N
6*	12.920 MHz	60.0	35.2	-24.8	10.0	PK	N
7*	178.000 kHz	54.6	33.0	-21.6	9.7	AV	N
8*	214.000 kHz	53.0	30.7	-22.4	9.7	AV	N
9*	462.000 kHz	46.7	25.4	-21.3	9.7	AV	N
10*	630.000 kHz	46.0	27.6	-18.4	9.8	AV	N
11*	3.220 MHz	46.0	26.0	-20.0	9.9	AV	N
12*	13.760 MHz	50.0	26.2	-23.8	10.0	AV	N

12. Band Edge (Radiated)

12.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal Due To
Spectrum analyzer	ROHDE&SCHWARZ	FSU	Aa-EE075	2025/08/04	2026/08/03
Horn Antenna	SCHWARZBECK	BBHA 9120 D	Aa-EE076	2025/08/11	2027/08/10
Test Receiver	ROHDE&SCHWARZ	ESR	Aa-EE048	2025/08/04	2026/08/03
Bilog Antenna	SCHWARZBECK	VULB 9168	Aa-EE001	2025/08/11	2027/08/10
Amplifier	SKET	LNPA_0118G-45	Aa-EE087	2025/08/04	2026/08/03
Horn Antenna	SCHWARZBECK	BBHA 9170	Aa-EE077	2025/08/11	2027/08/10
Loop Antenna	SCHWARZBECK	FMZB 1519B	Aa-EE074	2025/08/11	2027/08/10

12.2. Block diagram of test setup



12.3. Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under [paragraph \(b\)\(3\)](#) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in [§ 15.209\(a\)](#) is not required. In addition, radiated emissions which fall in the restricted

bands, as defined in [§ 15.205\(a\)](#), must also comply with the radiated emission limits specified in [§ 15.209\(a\)](#) (see [§ 15.205\(c\)](#)).

12.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

12.5. Test procedure

Details see the KDB 558074 D01 15.247 Meas Guidance v05r02

- § Put the EUT on a 0.8m high table, power on the EUT. Emissions were scanned and measured rotating the EUT to 360 degrees, Find the maximum Emission
- § Check the spurious emissions out of band.
- § RBW 1MHz, VBW 3MHz, peak detector for peak value, RBW 1MHz, VBW 3MHz, RMS detector for AV value.

All restriction band and non- restriction band have been tested, only worse case is reported.

12.6. Test result


Test Site: Chamber 1#(RSE)	Test Date: 2026/02/10--2026/02/10
Condition: 24°C,56%RH,101kPa	Test Engineer: Yannis Wen
Memo: Only show the test data of the worst case.	

EUT Name: All-In-One CD phonograph	EUT Model: X6
Sample No.: A2601362-S0001	Test Mode: hopping on/off mode-L/H
Power supply: DC 3.7V from battery	Memo: /


/

12.7. Test data


Test Mode: GFSK-Low Hopping-off




Test Mode: GFSK-High Hopping-off




Test Mode: GFSK-Low Hopping-on




Test Mode: GFSK-High Hopping-on




Test Mode: $\pi/4$ DQPSK-Low Hopping-off




Test Mode: $\pi/4$ DQPSK-High Hopping-off




Test Mode: $\pi/4$ DQPSK-Low Hopping-on




Test Mode: $\pi/4$ DQPSK-High Hopping-on




Test Mode: 8-DPSK-Low Hopping-off




Test Mode: 8-DPSK -High Hopping-off



Test Mode: 8-DPSK -Low Hopping-on



Test Mode: 8-DPSK -High Hopping-on




13. Antenna Requirement

13.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal Due To
CMW500	ROHDE&SCH WARZ	CMW500	Aa-EE073	2025/08/04	2026/08/03
Spectrum analyzer	ROHDE&SCH WARZ	FSV40-N	Aa-EE081	2025/08/04	2026/08/03
Vector Signal Generator	Agilent	N5182A	Aa-EE040	2025/08/04	2026/08/03
Power Sensor	DARE	RPR3006W	Aa-EE071	2025/08/04	2026/08/03
Power Sensor	DARE	RPR3006W	Aa-EE070	2025/08/04	2026/08/03
Power meter	Agilent	E4419B	Aa-EE045	2025/08/04	2026/08/03

13.2. Block diagram of test setup



13.3. Limits

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

13.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

13.5. Test procedure

The antenna is internal antenna and no consideration of replacement. Please see EUT photo for details.


13.6. Test result


Test Site: RF Laboratory	Test Date: 2026/02/06--2026/02/06
Condition: 24.2°C,56%RH,101kPa	Test Engineer: Yannis Wen
Memo: /	

EUT Name: All-In-One CD phonograph	EUT Model: X6
Sample No.: A2601362-S0001	Test Mode: /
Power supply: /	Memo: The EUT antenna is PCB Antenna. It complies with the standard requirement.

/

14. Test Setup Photograph





15. Photos of the EUT

