



FCC TEST REPORT

FCC ID:2BEPS-K03

Report Number..... : ZKT-2407017456E

Date of Test..... Jul. 01, 2024 to Aug. 06, 2024

Date of issue..... : Aug. 06, 2024

Total number of pages..... 39

Test Result : PASS

Testing Laboratory..... : Shenzhen ZKT Technology Co., Ltd.

Address 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name : Dongguan Zhenghao Electronics & Technology Co., Ltd.

Address Room 302, Building 6, No.8, Xiegang Xinlong Road,Xiegang Town, Dongguan City, Guangdong Province

Manufacturer's name : Dongguan Zhenghao Electronics & Technology Co., Ltd.

Address Room 302, Building 6, No.8, Xiegang Xinlong Road,Xiegang Town, Dongguan City, Guangdong Province

Test specification:

Standard..... FCC CFR Title 47 Part 15 Subpart C Section 15.247
ANSI C63.10:2013

Test procedure..... : /

Non-standard test method : N/A

Test Report Form No..... : /

Test Report Form(s) Originator..... : ZKT Testing

Master TRF : Dated: 2020-01-06

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name..... : K03 Keyboard

Trademark : N/A

K03

Model/Type reference..... : K08, K09, K04, K05, K06, EK8820, EK8890, F95, EK8988, EK8980, EK9980, EK9990

Ratings..... : Battery: DC 3V



Testing procedure and testing location:

Testing Laboratory.....: **Shenzhen ZKT Technology Co., Ltd.**

Address.....: 1/F, No. 101, Building B, No. 6, Tangwei Community
Industrial Avenue, Fuhai Street, Bao'an District,
Shenzhen, China

Tested by (name + signature).....: Jim Liu

Reviewer (name + signature).....: Jackson Fang

Approved (name + signature).....: Lake Xie





Table of Contents

Page

1.VERSION	5
2. SUMMARY OF TEST RESULTS	6
2.1 TEST FACILITY	7
2.2 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 DESCRIPTION OF TEST MODES	9
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	10
3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
4. EMC EMISSION TEST	13
4.1 CONDUCTED EMISSION MEASUREMENT	13
4.1.1 POWER LINE CONDUCTED EMISSION Limits	13
4.1.2 TEST PROCEDURE	13
4.1.3 DEVIATION FROM TEST STANDARD	13
4.1.4 TEST SETUP	14
4.1.5 EUT OPERATING CONDITIONS	14
4.2.1 RADIATED EMISSION LIMITS	15
4.2.2 TEST PROCEDURE	16
4.2.3 DEVIATION FROM TEST STANDARD	16
4.2.4 TEST SETUP	16
4.2.5 EUT OPERATING CONDITIONS	17
5.RADIATED BAND EMISSION MEASUREMENT	22
5.1 TEST REQUIREMENT:	22
5.2 TEST PROCEDURE	22
5.3 DEVIATION FROM TEST STANDARD	22
5.4 TEST SETUP	23
5.5 EUT OPERATING CONDITIONS	23
5.6 TEST RESULT	24
6.POWER SPECTRAL DENSITY TEST	25
6.1 APPLIED PROCEDURES / LIMIT	25
6.2 TEST PROCEDURE	25
6.3 DEVIATION FROM STANDARD	25
6.4 TEST SETUP	25
6.5 EUT OPERATION CONDITIONS	25
6.6 TEST RESULT	26



Table of Contents	Page
7. 6DB OCCUPIED BANDWIDTH	28
7.1 APPLIED PROCEDURES / LIMIT	28
7.2 TEST PROCEDURE	28
7.3 DEVIATION FROM STANDARD	28
7.4 TEST SETUP	28
7.5 EUT OPERATION CONDITIONS	28
7.6 TEST RESULT	29
8. PEAK OUTPUT POWER TEST	31
8.1 APPLIED PROCEDURES / LIMIT	31
8.2 TEST PROCEDURE	31
8.3 DEVIATION FROM STANDARD	31
8.4 TEST SETUP	31
8.5 EUT OPERATION CONDITIONS	31
8.6 TEST RESULT	32
9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION	33
9.1 APPLICABLE STANDARD	33
9.2 TEST PROCEDURE	33
9.3 DEVIATION FROM STANDARD	33
9.4 TEST SETUP	33
9.5 EUT OPERATION CONDITIONS	33
10. DUTY CYCLE	36
10.1 APPLIED PROCEDURES / LIMIT	36
10.2 DEVIATION FROM STANDARD	36
10.3 TEST SETUP	36
11. ANTENNA REQUIREMENT	38
12. TEST SETUP PHOTO	39
13. EUT CONSTRUCTIONAL DETAILS	39



1.VERSION

Report No.	Version	Description	Approved
ZKT-2407017456E	Rev.01	Initial issue of report	Aug. 06, 2024



2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
FCC part 15.203/15.247 (c)	Antenna requirement	PASS	
ANSI C63.10:2013	Duty Cycle	PASS	
FCC part 15.207	AC Power Line Conducted Emission	N/A	
FCC part 15.247 (b)(3)	Conducted Peak Output Power	PASS	
FCC part 15.247 (a)(2)	6dB Occupied Bandwidth	PASS	
FCC part 15.247 (e)	Power Spectral Density	PASS	
FCC part 15.247(d)	Band Edge	PASS	
FCC part 15.205/15.209	Spurious Emission	PASS	

NOTE:

(1)“N/A” denotes test is not applicable in this Test Report



2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.
Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225
Designation Number: CN1299
IC Registered No.: 27033
CAB identifier: CN0110

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	3m camber Radiated spurious emission(9KHz-30MHz)	U=4.5dB
2	3m camber Radiated spurious emission(30MHz-1GHz)	U=4.8dB
3	3m chamber Radiated spurious emission(1GHz-6GHz)	U=4.9dB
4	3m chamber Radiated spurious emission(6GHz-40GHz)	U=5.0dB
5	Conducted disturbance	U=3.2dB
6	RF Band Edge	U=1.68dB
7	RF power conducted	U=1.86dB
8	RF conducted Spurious Emission	U=2.2dB
9	RF Occupied Bandwidth	U=1.8MHz
10	RF Power Spectral Density	U=1.75dB
11	humidity uncertainty	U=5.3%
12	Temperature uncertainty	U=0.59°C



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	K03 Keyboard
Model No.:	K03
Model Different.:	All the model are the same circuit and RF module, except for different models
Serial No.:	K08, K09, K04, K05, K06, EK8820, EK8890, F95, EK8988, EK8980, EK9980, EK9990
Hardware Version:	H1.0
Software Version:	S1.0
Sample(s) Status:	Engineer sample
Operation Frequency:	2405MHz~2475MHz
Channel Numbers:	8
Channel Separation:	6MHz
Modulation Type:	FSK
Antenna Type:	PCB antenna
Antenna gain:	-0.58dBi
Battery :	DC 3V



Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2405 MHz						
2	2411 MHz						
3	2417 MHz						
4	2451 MHz						
5	2457 MHz						
6	2463 MHz						
7	2469 MHz						
8	2475 MHz						

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2405MHz
The middle channel	2451MHz
The Highest channel	2475MHz

3.2 DESCRIPTION OF TEST MODES


Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data. For battery operated equipment, the equipment tests shall be performed using a new battery.	

Test Software	FCC Test Tool v2.1
Power level setup	<5dBm



3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Emission



Conducted Spurious



3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	K03 Keyboard	N/A	K03	See page 8	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) EUT is tested with new batteries.



3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	N/A	Nov. 14, 2023	Nov. 13, 2024
2	LISN	CYBERTEK	EM5040A	E1850400149	N/A	Nov. 02, 2023	Nov. 01, 2024
3	Test Cable	N/A	C-01	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
4	Test Cable	N/A	C-02	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
5	Test Cable	N/A	C-03	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
6	EMI Test Receiver	R&S	ESCI3	101393	4.42 SP3	Nov. 02, 2023	Nov. 01, 2024
7	Triple-Loop Antenna	N/A	RF300	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
8	Absorbing Clamp	DZ	ZN23201	15034	N/A	Nov. 07, 2023	Nov. 06, 2024
9	EMC Software	Frad	EZ-EMC	Ver.EMC-CON 3A1.1	N/A	\	\

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	9020A	MY55370835	A.17.05	Nov. 02, 2023	Nov. 01, 2024
2	Spectrum Analyzer (10kHz-39.9GHz)	R&S	FSV40-N	100363	1.71 SP2	Nov. 02, 2023	Nov. 01, 2024
3	EMI Test Receiver (9kHz-7GHz)	R&S	ESCI7	101169	4.32	Nov. 02, 2023	Nov. 01, 2024
4	Bilog Antenna (30MHz-1500MHz)	Schwarzbeck	VULB9168	N/A	N/A	Nov. 13, 2023	Nov. 12, 2024
5	Horn Antenna (1GHz-18GHz)	Agilent	AH-118	071145	N/A	Nov. 13, 2023	Nov. 12, 2024
6	Horn Antenna (15GHz-40GHz)	A.H.System	SAS-574	588	N/A	Nov. 13, 2023	Nov. 12, 2024
7	Loop Antenna	TESEQ	HLA6121	58357	N/A	Nov. 16, 2023	Nov. 15, 2024
8	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	060747	N/A	Nov. 02, 2023	Nov. 01, 2024
9	Amplifier (1GHz-26.5GHz)	Agilent	8449B	3008A00315	N/A	Nov. 02, 2023	Nov. 01, 2024
10	Amplifier (500MHz-40GHz)	QuanJuDa	DLE-161	097	N/A	Nov. 02, 2023	Nov. 01, 2024
11	Test Cable	N/A	R-01	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
12	Test Cable	N/A	R-02	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
13	Test Cable	N/A	R-03	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
14	D.C. Power Supply	LongWei	TPR-6405D	N/A	N/A	\	\
15	EMC Software	Frad	EZ-EMC	Ver.EMC-CO N 3A1.1	N/A	\	\
16	Turntable	MF	MF-7802BS	N/A	N/A	\	\
17	Antenna tower	MF	MF-7802BS	N/A	N/A	\	\



RF Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	9020A	MY55370835	A.17.05	Nov. 02, 2023	Nov. 01, 2024
2	Spectrum Analyzer (10kHz-39.9GHz)	R&S	FSV40-N	100363	1.71 SP2	Nov. 02, 2023	Nov. 01, 2024
3	Test Cable	N/A	RF-01	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
4	Test Cable	N/A	RF-02	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
5	Test Cable	N/A	RF-03	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
6	ESG Signal Generator	Agilent	E4421B	N/A	B.03.84	Nov. 02, 2023	Nov. 01, 2024
7	Signal Generator	Agilent	N5182A	N/A	A.01.87	Nov. 02, 2023	Nov. 01, 2024
8	Magnetic Field Probe Tester	Narda	ELT-400	0-0344	N/A	Nov. 16, 2023	Nov. 15, 2024
9	Wideband Radio Communication Test	R&S	CMW500	106504	V 3.7.22	Nov. 02, 2023	Nov. 01, 2024
10	MWRF Power Meter Test system	MW	MW100-RF CB	N/A	N/A	Nov. 02, 2023	Nov. 01, 2024
11	Power Meter	KEYSIGHT	N1912A P	N/A	A.05.00	Nov. 02, 2023	Nov. 01, 2024
12	D.C. Power Supply	LongWei	TPR-6405D	N/A	N/A	\	\
13	RF Software	MW	MTS8310	V2.0.0.0	N/A	\	\



4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quas-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.

4.1.2 TEST PROCEDURE


- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation



4.1.4 TEST SETUP



- Note:**
- 1.Support units were connected to second LISN.
 - 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to Charging during test. This operating condition was tested and used to collect the included data.

4.1.6 Test Result

The EUT is powered by DC only the test items is not applicable.



4.2 RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average

4.2.1 RADIATED EMISSION LIMITS

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).



4.2.2 TEST PROCEDURE


- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 25GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-chamber test. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8m; above 1GHz, the height was 1.5m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.
- g. For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.
The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
Note:
Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD

No deviation


4.2.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz






(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


4.2.6 TEST RESULTS (Between 9KHz – 30 MHz)

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.



Between 30MHz – 1GHz


Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	DC 3V	Test Mode :	TX - 2405MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	55.6092	30.22	-14.15	16.07	40.00	-23.93	QP
2	131.7573	32.27	-17.61	14.66	43.50	-28.84	QP
3	150.0107	36.15	-16.56	19.59	43.50	-23.91	QP
4	252.0627	34.65	-15.85	18.80	46.00	-27.20	QP
5	515.4373	30.25	-11.18	19.07	46.00	-26.93	QP
6	750.1082	31.41	-6.82	24.59	46.00	-21.41	QP



Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	DC 3V	Test Mode :	TX - 2405MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	36.7661	33.30	-17.34	15.96	40.00	-24.04	QP
2	61.9949	31.84	-18.52	13.32	40.00	-26.68	QP
3	96.0985	35.46	-21.32	14.14	43.50	-29.36	QP
4	150.0107	33.63	-20.56	13.07	43.50	-30.43	QP
5	607.7866	29.98	-7.75	22.23	46.00	-23.77	QP
6	884.5027	29.85	-1.17	28.68	46.00	-17.32	QP

Remarks:

- 1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2.The emission levels of other frequencies are very lower than the limit and not show in test report.
- 3.The test data shows only the worst case TX - 2405MHz.



1GHz~25GHz

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel:2405MHz									
V	4810.00	51.74	30.55	5.77	24.66	51.62	74.00	-22.38	PK
V	4810.00	43.92	30.55	5.77	24.66	43.80	54.00	-10.20	AV
V	7215.00	53.51	30.33	6.32	24.55	54.05	74.00	-19.95	PK
V	7215.00	43.16	30.33	6.32	24.55	43.70	54.00	-10.30	AV
V	9620.00	51.44	30.85	7.45	24.69	52.73	74.00	-21.27	PK
V	9620.00	43.71	30.85	7.45	24.69	45.00	54.00	-9.00	AV
V	12025.00	53.09	31.02	8.99	25.57	56.63	74.00	-17.37	PK
V	12025.00	43.16	31.02	8.99	25.57	46.70	54.00	-7.30	AV
H	4810.00	53.30	30.55	5.77	24.66	53.18	74.00	-20.82	PK
H	4810.00	43.15	30.55	5.77	24.66	43.03	54.00	-10.97	AV
H	7215.00	51.00	30.33	6.32	24.55	51.54	74.00	-22.46	PK
H	7215.00	43.59	30.33	6.32	24.55	44.13	54.00	-9.87	AV
H	9620.00	52.06	30.85	7.45	24.69	53.35	74.00	-20.65	PK
H	9620.00	43.54	30.85	7.45	24.69	44.83	54.00	-9.17	AV
H	12025.00	53.39	31.02	8.99	25.57	56.93	74.00	-17.07	PK
H	12025.00	43.42	31.02	8.99	25.57	46.96	54.00	-7.04	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Middle Channel:2451MHz									
V	4902.00	50.60	30.55	5.77	24.66	50.48	74.00	-23.52	PK
V	4902.00	43.46	30.55	5.77	24.66	43.34	54.00	-10.66	AV
V	7353.00	54.30	30.33	6.32	24.55	54.84	74.00	-19.16	PK
V	7353.00	43.23	30.33	6.32	24.55	43.77	54.00	-10.23	AV
V	9804.00	52.50	30.85	7.45	24.69	53.79	74.00	-20.21	PK
V	9804.00	43.96	30.85	7.45	24.69	45.25	54.00	-8.75	AV
V	12255.00	50.24	31.02	8.99	25.57	53.78	74.00	-20.22	PK
V	12255.00	43.56	31.02	8.99	25.57	47.10	54.00	-6.90	AV
H	4902.00	54.71	30.55	5.77	24.66	54.59	74.00	-19.41	PK
H	4902.00	43.02	30.55	5.77	24.66	42.90	54.00	-11.10	AV
H	7353.00	50.24	30.33	6.32	24.55	50.78	74.00	-23.22	PK
H	7353.00	43.91	30.33	6.32	24.55	44.45	54.00	-9.55	AV
H	9804.00	53.08	30.85	7.45	24.69	54.37	74.00	-19.63	PK
H	9804.00	43.69	30.85	7.45	24.69	44.98	54.00	-9.02	AV
H	12255.00	51.82	31.02	8.99	25.57	55.36	74.00	-18.64	PK
H	12255.00	43.44	31.02	8.99	25.57	46.98	54.00	-7.02	AV



Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel:2475MHz									
V	4950.00	53.18	30.55	5.77	24.66	53.06	74.00	-20.94	PK
V	4950.00	43.06	30.55	5.77	24.66	42.94	54.00	-11.06	AV
V	7425.00	53.81	30.33	6.32	24.55	54.35	74.00	-19.65	PK
V	7425.00	43.68	30.33	6.32	24.55	44.22	54.00	-9.78	AV
V	9900.00	52.92	30.85	7.45	24.69	54.21	74.00	-19.79	PK
V	9900.00	43.33	30.85	7.45	24.69	44.62	54.00	-9.38	AV
V	12375.00	52.75	31.02	8.99	25.57	56.29	74.00	-17.71	PK
V	12375.00	43.43	31.02	8.99	25.57	46.97	54.00	-7.03	AV
H	4950.00	50.29	30.55	5.77	24.66	50.17	74.00	-23.83	PK
H	4950.00	43.73	30.55	5.77	24.66	43.61	54.00	-10.39	AV
H	7425.00	52.09	30.33	6.32	24.55	52.63	74.00	-21.37	PK
H	7425.00	43.70	30.33	6.32	24.55	44.24	54.00	-9.76	AV
H	9900.00	50.31	30.85	7.45	24.69	51.60	74.00	-22.40	PK
H	9900.00	43.95	30.85	7.45	24.69	45.24	54.00	-8.76	AV
H	12375.00	51.86	31.02	8.99	25.57	55.40	74.00	-18.60	PK
H	12375.00	43.82	31.02	8.99	25.57	47.36	54.00	-6.64	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



5. RADIATED BAND EMISSION MEASUREMENT

5.1 TEST REQUIREMENT:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2390MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above	Peak	1MHz	3MHz	Peak
	1GHz	Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
7. Test the EUT in the lowest channel, the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


5.3 DEVIATION FROM TEST STANDARD

No deviation



5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



5.6 TEST RESULT

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBu V/m)	Margin (dB)	Detect or Type	Result
FSK	Low Channel: 2405MHz										
	H	2390.00	54.10	30.22	4.85	23.98	52.71	74.00	-21.29	PK	PASS
	H	2390.00	44.58	30.22	4.85	23.98	43.19	54.00	-10.81	AV	PASS
	H	2400.00	54.81	30.22	4.85	23.98	53.42	74.00	-20.58	PK	PASS
	H	2400.00	44.87	30.22	4.85	23.98	43.48	54.00	-10.52	AV	PASS
	V	2390.00	53.52	30.22	4.85	23.98	52.13	74.00	-21.87	PK	PASS
	V	2390.00	44.09	30.22	4.85	23.98	42.70	54.00	-11.30	AV	PASS
	V	2400.00	54.85	30.22	4.85	23.98	53.46	74.00	-20.54	PK	PASS
	V	2400.00	44.15	30.22	4.85	23.98	42.76	54.00	-11.24	AV	PASS
	High Channel: 2475MHz										
	H	2483.50	54.10	30.22	4.85	23.98	52.71	74.00	-21.29	Pk	PASS
	H	2483.50	44.58	30.22	4.85	23.98	43.19	54.00	-10.81	AV	PASS
	H	2500.00	54.81	30.22	4.85	23.98	53.42	74.00	-20.58	Pk	PASS
	H	2500.00	44.87	30.22	4.85	23.98	43.48	54.00	-10.52	AV	PASS
	V	2483.50	53.52	30.22	4.85	23.98	52.13	74.00	-21.87	Pk	PASS
	V	2483.50	44.09	30.22	4.85	23.98	42.70	54.00	-11.30	AV	PASS
	V	2500.00	54.85	30.22	4.85	23.98	53.46	74.00	-20.54	Pk	PASS
	V	2500.00	44.15	30.22	4.85	23.98	42.76	54.00	-11.24	AV	PASS
Remark:											
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit.											



6. POWER SPECTRAL DENSITY TEST

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074 D0115.247 Meas Guidance v05r02

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8dBm/3kHz	2400-2483.5	PASS


6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.



6.6 TEST RESULT


Temperature :	26℃	Relative Humidity :	54%
Test Mode :	FSK	Test Voltage :	DC 3V

Frequency	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)	Result
2405MHz	-16.893	8	PASS
2451MHz	-16.783	8	PASS
2475MHz	-17.174	8	PASS






2451MHz



2475MHz





7. 6DB OCCUPIED BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB558074 D0115.247 Meas Guidance v05r02

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB Occupied Bandwidth)	2400-2483.5	PASS

7.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



7.6 TEST RESULT

Temperature :	26°C	Relative Humidity :	54%
Test Mode :	FSK	Test Voltage :	DC 3V

Test Mode	Test Channel (MHz)	6dB Occupied Bandwidth (MHz)	Limit (KHz)	Result
FSK	2405	0.6904	>500	Pass
	2451	0.697		
	2475	0.6765		






2451MHz



2475MHz





8. PEAK OUTPUT POWER TEST

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB558074 D0115.247 Meas Guidance v05r02

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



8.6 TEST RESULT

Temperature :	26℃	Relative Humidity :	54%
Test Mode :	FSK	Test Voltage :	DC 3V

Test channel (MHz)	Peak Output Power (dBm)	Limit (dBm)	Result
2405	-3.398	30.00	Pass
2451	-3.851		
2475	-4.553		



9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D0115.247 Meas Guidance v05r02

9.1 APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

9.2 TEST PROCEDURE


Using the following spectrum analyzer setting:

- A) Set the RBW = 100KHz.
- B) Set the VBW = 300KHz.
- C) Sweep time = auto couple.
- D) Detector function = peak.
- E) Trace mode = max hold.
- F) Allow trace to fully stabilize.

9.3 DEVIATION FROM STANDARD

No deviation.

9.4 TEST SETUP





9.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.





9.6 TEST RESULTS

Band Edge, Left Side



Band Edge, Right Side





Keylight Spectrum Analyzer - Sweep SA

Center Freq 2.405000000 GHz

Span 1.500 MHz

#Res BW 100 kHz

#VBW 300 kHz

Sweep 1.000 ms (1001 pts)

Ref Offset 2.01 dB

Ref 20.00 dBm

Mkr1 2.405 220 5 GHz

-2.403 dBm

02-06-15 AM 34 29, 2024

TRACED 3 3 4 5

TYPE MAAAAAA

DEF PNNNNNN

SENSE: PULSE

PNO: Wide

Trig: Free Run

#Atten: 30 dB

10 dB/div

0 dB

-10.0

-20.0

-30.0

-40.0

-50.0

-60.0

-70.0

0.00

-1.00

-2.00

-3.00

-4.00

-5.00

-6.00

-7.00

-8.00

-9.00

-10.00

-11.00

-12.00

-13.00

-14.00

-15.00

-16.00

-17.00

-18.00

-19.00

-20.00

-21.00

-22.00

-23.00

-24.00

-25.00

-26.00

-27.00

-28.00

-29.00

-30.00

-31.00

-32.00

-33.00

-34.00

-35.00

-36.00

-37.00

-38.00

-39.00

-40.00

-41.00

-42.00

-43.00

-44.00

-45.00

-46.00

-47.00

-48.00

-49.00

-50.00

-51.00

-52.00

-53.00

-54.00

-55.00

-56.00

-57.00

-58.00

-59.00

-60.00

-61.00

-62.00

-63.00

-64.00

-65.00

-66.00

-67.00

-68.00

-69.00

-70.00

-71.00

-72.00

-73.00

-74.00

-75.00

-76.00

-77.00

-78.00

-79.00

-80.00

-81.00

-82.00

-83.00

-84.00

-85.00

-86.00

-87.00

-88.00

-89.00

-90.00

-91.00

-92.00

-93.00

-94.00

-95.00

-96.00

-97.00

-98.00

-99.00

-100.00

-101.00

-102.00

-103.00

-104.00

-105.00

-106.00

-107.00

-108.00

-109.00

-110.00

-111.00

-112.00

-113.00

-114.00

-115.00

-116.00

-117.00

-118.00

-119.00

-120.00

-121.00

-122.00

-123.00

-124.00

-125.00

-126.00

-127.00

-128.00

-129.00

-130.00

-131.00

-132.00

-133.00

-134.00

-135.00

-136.00

-137.00

-138.00

-139.00

-140.00

-141.00

-142.00

-143.00

-144.00

-145.00

-146.00

-147.00

-148.00

-149.00

-150.00

-151.00

-152.00

-153.00

-154.00

-155.00

-156.00

-157.00

-158.00

-159.00

-160.00

-161.00

-162.00

-163.00

-164.00

-165.00

-166.00

-167.00

-168.00

-169.00

-170.00

-171.00

-172.00

-173.00

-174.00

-175.00

-176.00

-177.00

-178.00

-179.00

-180.00

-181.00

-182.00

-183.00

-184.00

-185.00

-186.00

-187.00

-188.00

-189.00

-190.00

-191.00

-192.00

-193.00

-194.00

-195.00

-196.00

-197.00

-198.00

-199.00

-200.00

-201.00

-202.00

-203.00

-204.00

-205.00

-206.00

-207.00

-208.00

-209.00

-210.00

-211.00

-212.00

-213.00

-214.00

-215.00

-216.00

-217.00

-218.00

-219.00

-220.00

-221.00

-222.00

-223.00

-224.00

-225.00

-226.00

-227.00

-228.00

-229.00

-230.00

-231.00

-232.00

-233.00

-234.00

-235.00

-236.00

-237.00

-238.00

-239.00

-240.00

-241.00

-242.00

-243.00

-244.00

-245.00

-246.00

-247.00

-248.00

-249.00

-250.00

-251.00

-252.00

-253.00

-254.00

-255.00

-256.00

-257.00

-258.00

-259.00

-260.00

-261.00

-262.00

-263.00

-264.00

-265.00

-266.00

-267.00

-268.00

-269.00

-270.00

-271.00

-272.00

-273.00

-274.00

-275.00

-276.00

-277.00

-278.00

-279.00

-280.00

-281.00

-282.00

-283.00

-284.00

-285.00

-286.00

-287.00

-288.00

-289.00

-290.00

-291.00

-292.00

-293.00

-294.00

-295.00

-296.00

-297.00

-298.00

-299.00

-300.00

-301.00

-302.00

-303.00

-304.00

-305.00

-306.00


-307.00

-308.00

-309.00

-310.00

-311.00



Keysight Spectrum Analyzer - Sweet 5A

Center Freq 2.45100000 GHz

PAC: Wide Trg: Free Run

IF: 50.0 kHz

IF Filter: Low

#Atten: 30 dB

#Avg Type: RMS

Avg Hold: 1001

02:08:39 AM Jul 29, 2024

TRAC 1 1 2 3 4 5 6

TYPE: MIN MAX

DEF: P MIN MAX

10 dB/Div

Ref Offset 202 dB

Ref 20.00 dBm

Mkr1 2.451 222 0 GHz

-3.064 dBm

Center 2.4510000 GHz

Span 1.500 MHz

#Res BW 100 kHz


#VBW 300 kHz

Sweep 1.000 ms (1001 pts)

dBm

Log

1



Keysight Spectrum Analyzer - Swept SA

Center Freq 2.475000000 GHz

SENSE: PULSE

#Avg Type: RMS
Avg/Hold: 100/100

02:59:54 AM Jul 29, 2024

PRC: Wide --> Trip: Free Run
IF Gain: Low #Atten: 30 dB

Ref Offset: 20.4 dB
Ref: 20.00 dBm


Mkr1 2.474 982 0 GHz
-3.536 dBm

10 dB/div
Log

Center 2.4750000 GHz
Span 1.500 MHz
#Res BW 100 kHz
#VBW 300 kHz
Sweep 1.000 ms (1001 pts)

WFS1

STATUS





10.DUTY CYCLE

Test Method:	ANSI C63.10:2013
--------------	------------------

10.1 APPLIED PROCEDURES / LIMIT


Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

- a) A diode detector and an oscilloscope that together have a sufficiently short response time to permit accurate measurements of the ON and OFF times of the transmitted signal.
- b) The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:
 - 1) Set the center frequency of the instrument to the center frequency of the transmission.
 - 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
 - 3) Set $VBW \geq RBW$. Set detector = peak or average.
 - 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

10.2 DEVIATION FROM STANDARD

No deviation.


10.3 TEST SETUP





10.4 TEST RESULTS

Mode	Frequency (MHz)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Result
FSK	2475	67.32	1.72	Pass



Note: All channel have been tested, and the report only reflects the worst case data.

Duty Cycle = Ton /Total*100%

Duty Cycle Correction Factor = 10log (1/Duty Cycle)



11.ANTENNA REQUIREMENT

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
EUT Antenna:	
The antenna is PCB Antenna, the best case gain of the antennas is -0.58dBi, reference to the appendix II for details	



12. TEST SETUP PHOTO

Reference to the appendix I for details.

13. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

***** END OF REPORT *****