# MPE REPORT

Wireless charger

MODEL No.: Z20, Z21, Z22, Z23, Z24, C01, C02 , C03, C04, C05, S01, S02, S03, S04, S05, T01, T02, T03, T04, T05

FCC ID: 2BEST-Z20

REPORT NO.:NCT24003223E-2

ISSUE DATE: Feb. 01, 2024

*Prepared for*

Shenzhen Jelemei Technology Co., LTD

3rd Floor, Building C, No. 8 Qixin Road, Longgang Street, Wulian Community, Longgang District, Shenzhen City, Guangdong Province, China

*Prepared by*

Shenzhen NCT Testing Technology Co., Ltd.

A101&2F B2, Fuqiao 6th Area, Xintian Community, Fuhai Street, Baoan District, Shenzhen, People's Republic of China

TEL: 400-8868-419

FAX: 86-755-27790922

# TABLE OF CONTENT

Test Report Description Page

**1. SUMMARY OF TEST RESULT ..... 4**

**2. GENERAL INFORMATION ..... 5**

2.1. DESCRIPTION OF DEVICE (EUT) ..... 5
2.2. TEST SETUP ..... 6
2.3. DESCRIPTION OF TEST FACILITY ..... 7
2.4. MEASUREMENT UNCERTAINTY ..... 7

**3. MEASURING DEVICE AND TEST EQUIPMENT ..... 8**

3.1. FOR MPE MEASUREMENT ..... 8

**4. RF EXPOSURE ..... 9**

4.1. MEASURING STANDARD ..... 9
4.2. REQUIMENTS ..... 9
4.3. TEST CONFIGURATION ..... 10
4.4. EQUIPMENT APPROVAL CONSIDERATIONS ..... 11
4.5. LIMITS ..... 12
4.6. MEASURING RESULTS ..... 13

**5. PHOTOGRAPHS OF TEST SETUP ..... 15**

# TEST REPORT DESCRIPTION

| | | |
|---|---|---|
| Applicant | : | Shenzhen Jelemei Technology Co., LTD |
| Address | : | 3F, Building C, No. 8, Qixin Road, Longgang Street, Wulian Community, Longgang District, Shenzhen |
| Manufacturer | : | Shenzhen Jelemei Technology Co., LTD |
| Address | : | 3F, Building C, No. 8, Qixin Road, Longgang Street, Wulian Community, Longgang District, Shenzhen |
| EUT | : | Wireless charger |
| Model Name | : | Z20, Z21, Z22, Z23, Z24, C01, C02 , C03, C04, C05, S01, S02, S03, S04, S05, T01, T02, T03, T04, T05 |
| Trademark | : | N/A |

**Measurement Procedure Used:**

FCC Part 1(1.1310) and Part 2(2.1091)
680106 D01 RF Exposure Wireless Charging App v03r01

The device described above is tested by Shenzhen NCT Testing Technology Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen NCT Testing Technology Co., Ltd. is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen NCT Testing Technology Co., Ltd.

Test Engineer:

Keven Wu / Engineer

Technical Manager:

Henry Wang / Manager

Shenzhen NCT Testing Technology Co., Ltd. 2008

# 1. SUMMARY OF TEST RESULT

| EMISSION | | |
|---|---|---|
| Description of Test Item | Standard & Limits | Results |
| MPE | FCC Part 1(1.1310) and Part 2(2.1091)<br>680106 D01 RF Exposure Wireless Charging App v03r01 | Pass |
| Note: N/A is an abbreviation for Not Applicable. | | |

# 2. GENERAL INFORMATION

## 2.1. Description of Device (EUT)

| | | |
|---|---|---|
| EUT | : | Wireless charger |
| Model Number | : | Z20, Z21, Z22, Z23, Z24, C01, C02 , C03, C04, C05, S01, S02, S03, S04, S05, T01, T02, T03, T04, T05 |
| Model different | : | All the same except the model number. |
| Power Rating | : | Type-c Input: 9Vdc,2.4A; 5Vdc,2A<br>Output(Magetic Wireless) :15W/10W/7.5W/5W<br>Output(Watch):2.5W<br>Output(Earphone):3W |
| Operation Frequency for WPT | : | 110-205 KHz for Phone and headset<br>319.6 KHz for Watch |
| Modulation | : | MSK |
| Antenna Type: | : | Coil Antenna |
| Date of Received | : | Jan.15, 2024 |
| Date of Test | : | Jan.15, 2024 to Feb.01, 2024 |

## 2.2. Test Setup

For Mobile exposure conditions



## 2.3. Description of Test Facility

Site Description

EMC Lab. : Accredited by CNAS, 2022-09-27
The certificate is valid until 2028.01.07
The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2017)
The Certificate Registration Number is L8251

Designation Number: CN1347
Test Firm Registration Number: 894804
Accredited by A2LA, June 14, 2023
The Certificate Registration Number is 6837.01

Accredited by Industry Canada, November 09, 2018
The Conformity Assessment Body Identifier is CN0150
Company Number: 30806

Name of Firm : Shenzhen NCT Testing Technology Co., Ltd.
Site Location : A101&2F B2, Fuqiao 6th Area, Xintian Community, Fuhai Street, Baoan District, Shenzhen, People's Republic of China

## 2.4. Measurement Uncertainty

| **Parameter** | **Uncertainty** |
|---|---|
| RF output power, conducted | ±1.0dB |
| Power Spectral Density, conducted | ±2.2dB |
| Radio Frequency | ± 1 x $10^{-6}$ |
| Bandwidth | ± 1.5 x $10^{-6}$ |
| Time | ±2% |
| Duty Cycle | ±2% |
| Temperature | ±1°C |
| Humidity | ±5% |
| DC and low frequency voltages | ±3% |
| Conducted Emissions (150kHz~30MHz) | ±3.64dB |
| Radiated Emission(30MHz~1GHz) | ±5.03dB |
| Radiated Emission(1GHz~25GHz) | ±4.74dB |

# 3. MEASURING DEVICE AND TEST EQUIPMENT

## 3.1. For MPE Measurement

| Used | Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal. Interval |
|---|---|---|---|---|---|---|
| □ | Exposure Level Tester(1Hz-400KHz) | Narda | EHP-200A | 180ZX00634 | 2023.06.21 | 2024.06.20 |

# 4. RF EXPOSURE

## 4.1. Measuring Standard

FCC Part 1(1.1310) and Part 2(2.1091)

## 4.2. Requiments

Three different categories of transmitters are defined by the FCC in OET Bulletin 65. These categories are fixed installation, mobile, and portable and are defined as follows: o Fixed Installations: fixed location means that the device, including its antenna, is physically secured at a permanent location and is not able to be easily moved to another location. Additionally, distance to humans from the antenna is maintained to at least 2 meters. o Mobile Devices: a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to be generally used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structures and the body of the user or nearby persons. Transmitters designed to be used by consumers or workers that can be easily re-located, such as a wireless modem operating in a laptop computer, are considered mobile devices if they meet the 20 centimeter separation requirement. The FCC rules for evaluating mobile devices for RF compliance are found in 47 CFR §2.1091. o Portable Devices: a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. Portable device requirements are found in Section 2.1093 of the FCC's Rules (47 CFR§2.1093). The FCC also categorizes the use of the device as based upon the user's awareness and ability to exercise control over his or her exposure. The two categories defined are Occupational/ Controlled Exposure and General Population/Uncontrolled Exposure. These two categories are defined as follows: Occupational/Controlled Exposure: In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means. Awareness of the potential for RF exposure in a workplace or similar environment can be provided through specific training as part of a RF safety program. If appropriate, warning signs and labels can also be used to establish such awareness by providing prominent information on the risk of potential exposure and instructions on methods to minimize such exposure risks. General Population/Uncontrolled Exposure: The general population / uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

## 4.3. Test configuration

For Mobile exposure conditions

1) The RF exposure test was performed on 360 degree turn table in anechoic chamber.
2) The measurement probe was placed at test distance (15cm for A,B,C,D four sides and 20cm for E Top ) which is between the edge of the charger and the geometric center of probe.
3) The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed.
4) The EUT were measured according to the dictates of 680106 D01 RF Exposure Wireless Charging App v03r01

## 4.4. Equipment Approval Considerations

Requirement for KDB Publication 680106 D01 RF Exposure Wireless Charging App v03r01

| Condition Requirement | Yes / No | Answers |
|---|---|---|
| Power transfer frequency is less than 1 MHz. | Yes | The power transfer frequency is less than 1 MHz . |
| Output power from each primary coil is less than or equal to 15 watts. | Yes | Output power is 15W Max. |
| The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils. | Yes | It has three coils and they are can Simultaneous emission at the same time. |
| Client device is placed directly in contact with the transmitter. | Yes | Client device is placed directly in contact with the transmitter. |
| Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion). | Yes | Mobile exposure conditions only |
| The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit. | Yes | Please refer to the result of Electric Field Emissions and Magnetic Field Emissions. |

## 4.5. Limits

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

| Frequency Range(MHz) | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density ($mW/cm^2$) | Averaging Time (minute) |
|---|---|---|---|---|
| Limits for Occupational/Controlled Exposure | | | | |
| 0.3-3.0 | 614 | 1.63 | *100 | 6 |
| 3.0-30 | 1842/f | 4.89/f | $*900/f^2$ | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1,500 | / | / | f/300 | 6 |
| 1,500-100,000 | / | / | 5 | 6 |

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

| Frequency Range(MHz) | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density ($mW/cm^2$) | Averaging Time (minute) |
|---|---|---|---|---|
| Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3-1.34 | 614 | 1.63 | *100 | 30 |
| 1.34-30 | 824/f | 2.19/f | $*180/f^2$ | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1,500 | / | / | f/1500 | 30 |
| 1,500-100,000 | / | / | 1.0 | 30 |

F=frequency in MHz
*=Plane-wave equivalent power density

According to FCC 680106 D01 RF Exposure Wireless Charging App v03r01 Section 3. RF Exposure Requirements clause 3 the Emission-Limits in the frequency range from 100 KHz to 300 KHz should be assessed versus the limits at 300 KHz in Table 1 of CFR 47 – Section1.310 as following (measured distance shall be 15cm from the center of the probe to the edge of the device):

| | E-Field | */* | B-Field |
|---|---|---|---|
| Frequency | V/m | A/m | uT |
| 0.3 MHz – 3.0 MHz | 614 | 1.613 | 2.0 |
| 3.0 MHz – 30 MHz | 824/f (=$27.5_{30MHz}$) | 2.19/f (=$0.073_{30MHz}$) | -- |

A KDB inquire was required to determine/confirm the applicable limits below 100 KHz.

Description of Support Unit

| Item | Equipment | Mfr/Brand | Model/Type No. | Series No. | Note |
|---|---|---|---|---|---|
| E-1 | Wireless charger | N/A | PW02-1A-5K-B | N/A | EUT |
| E-2 | Phone | Mi | Xiaomi 13 Ultra | N/A | Auxiliary |
| E-3 | Adapter | N/A | A18A-050100U-US2 | N/A | Auxiliary |
| E-4 | Wireless headset | N/A | TWU23 | N/A | Auxiliary |
| E-5 | Watches | N/A | QAM256 | N/A | Auxiliary |

Test Mode:

| Test Mode | Description | Remark() |
|---|---|---|
| Mode 1 | EUT + Phone | 5% |
| Mode 2 | | 50% |
| Mode 3 | | 95% |
| Mode 4 | EUT + watch | 5% |
| Mode 5 | | 50% |
| Mode 6 | | 95% |
| Mode 7 | EUT + Headset | 5% |
| Mode 8 | | 50% |
| Mode 9 | | 95% |
| Mode 10 | EUT + Phone + watch | 5% |
| Mode 11 | | 50% |
| Mode 12 | | 95% |
| Mode 13 | EUT + Phone + Headset | 5% |
| Mode 14 | | 50% |
| Mode 15 | | 95% |
| Mode 16 | EUT + watch + Headset | 5% |
| Mode 17 | | 50% |
| Mode 18 | | 95% |
| Mode 19 | EUT + Phone + watch + Headset | 5% |
| Mode 20 | | 50% |
| Mode 21 | | 95% |
| Remark: All the modes have tested and recorded the worst mode 19 & mode 20 & mode 21 in the report | | |

## 4.6. Measuring Results

For Mobile exposure conditions

*Test Mode: Mode 19*

| Electric Field Emissions | | | |
|---|---|---|---|
| Test Position | Measure Value (V/m) | Limit(V/m) | Distance(cm) |
| Top | 0.222 | 614 | 20 |
| Left | 0.336 | 614 | 15 |
| Right | 0.325 | 614 | 15 |
| Rear | 0.262 | 614 | 15 |
| Front | 0.123 | 614 | 15 |
| | | | |
| Magnetic Field Emissions | | | |
| Test Position | Measure Value (A/m) | Limit(A/m) | Distance(cm) |
| Top | 0.0178 | 1.63 | 20 |
| Left | 0.0316 | 1.63 | 15 |
| Right | 0.0278 | 1.63 | 15 |
| Rear | 0.0323 | 1.63 | 15 |
| Front | 0.0289 | 1.63 | 15 |

*Test Mode: Mode 20*

| Electric Field Emissions | | | |
|---|---|---|---|
| Test Position | Measure Value (V/m) | Limit(V/m) | Distance(cm) |
| Top | 0.233 | 614 | 20 |
| Left | 0.356 | 614 | 15 |
| Right | 0.325 | 614 | 15 |
| Rear | 0.223 | 614 | 15 |
| Front | 0.225 | 614 | 15 |
| | | | |
| Magnetic Field Emissions | | | |
| Test Position | Measure Value (A/m) | Limit(A/m) | Distance(cm) |
| Top | 0.0186 | 1.63 | 20 |
| Left | 0.0356 | 1.63 | 15 |
| Right | 0.0335 | 1.63 | 15 |
| Rear | 0.0313 | 1.63 | 15 |
| Front | 0.0278 | 1.63 | 15 |

*Test Mode: Mode 21*

| Electric Field Emissions | | | |
|---|---|---|---|
| Test Position | Measure Value (V/m) | Limit(V/m) | Distance(cm) |
| Top | 0.211 | 614 | 20 |
| Left | 0.327 | 614 | 15 |
| Right | 0.322 | 614 | 15 |
| Rear | 0.222 | 614 | 15 |
| Front | 0.236 | 614 | 15 |
| | | | |
| Magnetic Field Emissions | | | |
| Test Position | Measure Value (A/m) | Limit(A/m) | Distance(cm) |
| Top | 0.0121 | 1.63 | 20 |
| Left | 0.0225 | 1.63 | 15 |
| Right | 0.0158 | 1.63 | 15 |
| Rear | 0.0223 | 1.63 | 15 |
| Front | 0.0165 | 1.63 | 15 |

## 5. PHOTOGRAPHS OF TEST SETUP

For Mobile exposure conditions