# FCC TEST REPORT
# FCC ID:2BEV6-L156U

| | |
|---|---|
| **Report Number.....:** | **ZHT-240110020E-2** |
| Date of Test..... | Jan. 10, 2024 to Feb. 19, 2024 |
| Date of issue.....: | Feb. 19, 2024 |
| Test Result..... : | PASS |
| **Testing Laboratory.....:** | **Guangdong Zhonghan Testing Technology Co., Ltd.** |
| Address ..... : | Room 104, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China |
| **Applicant's name .....:** | **Thinkview International Limited** |
| Address ..... : | Office No.3 10/F Witty Commercial Building 1A-1L Tung Choi Street Mongkok Kowloon Hong Kong |
| **Manufacturer's name .....:** | **Shenzhen Thinkview Technology Co., Ltd** |
| Address ..... : | Room 1602, Bldg 4, Nan Tai Yun Chuang Gu, Fenghuang Street, Guangming District, Shenzhen, China |
| **Test specification:** | |
| Standard.....: | FCC Part 15 Subpart E 15.407<br>KDB789033 D02 General U-NII Test Procedures New Rules v02r01<br>KDB662911D01MultipleTransmitterOutputv02r01ANSI |
| Test procedure..... : | ANSI C63.10:2013 |
| Non-standard test method .....: | N/A |

This device described above has been tested by ZHT, and the test results show that the equipment under test (EUT) is in compliance with the IC requirements. And it is applicable only to the tested sample identified in the report.
This report shall not be reproduced except in full, without the written approval of ZHT, this document may be altered or revised by ZHT, personal only, and shall be noted in the revision of the document.

| | |
|---|---|
| **Product name.....:** | **Notebook** |
| Trademark .....: | / |
| Model/Type reference..... : | L156U<br>N***X, L***X, T***X, G***X (* representing 0-9, X representing letters A-Z, indicating different sales regions, without affecting product safety and electromagnetic compatibility performance) |
| Model difference.....: | Only the mode name is different. |
| Ratings..... : | Adapter:<br>Model: JHD-AP065U-19034BA-A<br>Input:100-240V, 50/60Hz 1.5A<br>Output: 19V, 3420mA<br>Battery:DC 11.4V |

**Testing procedure and testing location:**

| | |
|---|---|
| **Testing Laboratory.....:** | **Guangdong Zhonghan Testing Technology Co., Ltd.** |
| Address.....: | Room 104, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China |
| Tested by (name + signature).....: | Kimi Lu |
| Reviewer (name + signature).....: | Baret Wu |
| Approved (name + signature).....: | Levi Lee |

**Table of Contents** **Page**

1. VERSION ..... 5
2.SUMMARY OF TEST RESULTS ..... 6
2.1 TEST FACILITY ..... 7
2.2 MEASUREMENT UNCERTAINTY ..... 7
3. GENERAL INFORMATION ..... 8
3.1 GENERAL DESCRIPTION OF EUT ..... 8
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED ..... 11
3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE) ..... 11
3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS ..... 12
4.EMC EMISSION TEST ..... 14
4.1 CONDUCTED EMISSION MEASUREMENT ..... 14
4.1.1 POWER LINE CONDUCTED EMISSION Limits ..... 14
4.1.2 TEST PROCEDURE ..... 14
4.1.3 DEVIATION FROM TEST STANDARD ..... 14
4.1.4 TEST SETUP ..... 15
4.1.5 EUT OPERATING CONDITIONS ..... 15
4.1.6 TEST RESULTS ..... 16
4.2 RADIATED EMISSION MEASUREMENT ..... 18
4.2.1 APPLICABLE STANDARD ..... 18
4.2.2 CONFORMANCE LIMIT ..... 18
4.2.3 MEASURING INSTRUMENTS ..... 18
4.2.4 TEST CONFIGURATION ..... 19
4.2.5 TEST PROCEDURE ..... 20
5.POWER SPECTRAL DENSITY TEST ..... 25
5.1 APPLIED PROCEDURES / LIMIT ..... 25
5.2 TEST PROCEDURE ..... 26
5.3 DEVIATION FROM STANDARD ..... 26
5.4 TEST SETUP ..... 26
5.5 EUT OPERATION CONDITIONS ..... 26
5.6 TEST RESULTS ..... 27
6. 26DB & 6DB &99% EMISSION BANDWIDTH ..... 28
6.1 APPLIED PROCEDURES / LIMIT ..... 28
6.2 TEST PROCEDURE ..... 28
6.3 EUT OPERATION CONDITIONS ..... 29
6.4 TEST RESULTS ..... 29
7.MAXIMUM CONDUCTED OUTPUT POWER ..... 30
7.1 PPLIED PROCEDURES / LIMIT ..... 30

**Table of Contents** **Page**

7.2 TEST PROCEDURE ..... 31
7.3 DEVIATION FROM STANDARD ..... 31
7.4 TEST SETUP ..... 32
7.5 EUT OPERATION CONDITIONS ..... 32
7.6 TEST RESULTS ..... 32
8.OUT OF BAND EMISSIONS ..... 33
8.1 APPLICABLE STANDARD ..... 33
8.2 TEST PROCEDURE ..... 34
8.3 DEVIATION FROM STANDARD ..... 34
8.4 TEST SETUP ..... 34
8.5 EUT OPERATION CONDITIONS ..... 34
8.6 TEST RESULTS ..... 34
9.SPURIOUS RF CONDUCTED EMISSIONS ..... 35
9.1 CONFORMANCE LIMIT ..... 35
9.3 TEST SETUP ..... 35
9.4 TEST PROCEDURE ..... 35
9.5 TEST RESULTS ..... 36
10.ANTENNA REQUIREMENT ..... 38
11. TEST SETUP PHOTO ..... 39
12. EUT CONSTRUCTIONAL DETAILS ..... 39

## 1. VERSION

| ReportNo. | Version | Description | Approved |
|---|---|---|---|
| ZHT-240110020E-2 | Rev.01 | Initial issue of report | Feb. 19, 2024 |
| | | | |
| | | | |

## 2.SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

| FCC Part15 (15.407) , Subpart E | | | |
|---|---|---|---|
| Standard Section | Test Item | Judgment | Remark |
| 15.209(a),<br>15.407 (b)(1)<br>15.407 (b)(4) | Spurious Radiated Emissions | PASS | |
| 15.207 | Conducted Emission | PASS | |
| 15.407 (a)(12) | 26 dB and 99% Emission Bandwidth | PASS | |
| 15.407(e) | 6 dB bandwidth | PASS | |
| 15.407 (a)(1)<br>15.407 (a)(3) | Maximum Conducted Output Power | PASS | |
| 2.1051,<br>15.407(b)(1)<br>15.407(b)(4) | Band Edge | PASS | |
| 15.407 (a)(1)<br>15.407 (a)(3) | Power Spectral Density | PASS | |
| 2.1051,<br>15.407(b) | Spurious Emissions at Antenna Terminals | PASS | |
| 15.203 | Antenna Requirement | PASS | |
| 15.407(g) | Frequency Stability Measurement | PASS | |

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

(2) The product meets the requirements of 15.407 (C) standard

Operation in the absence of information to the transmit:

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ASK message transmitting from remote device and verify whether it shall resend or discontinue transmission. (manufacturer declare )

## 2.1 TEST FACILITY

Guangdong Zhonghan Testing Technology Co., Ltd.
Add. : Room 104, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

C Registered No.: 29832
CAB identifier: CN0143

## 2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

| No. | Item | Uncertainty |
|---|---|---|
| 1 | 3m camber Radiated spurious emission(30MHz-1GHz) | U=4.3dB |
| 2 | 3m chamber Radiated spurious emission(1GHz-18GHz) | U=4.5dB |
| 3 | 3m chamber Radiated spurious emission(18GHz-40GHz) | U=3.34dB |
| 4 | Conducted Adjacent channel power | U=1.38dB |
| 5 | All emissions radiated(9k-30MHz) | U=4.68dB |
| 6 | Conducted output power uncertainty Above 1G | U=1.576dB |
| 7 | Conducted output power uncertainty below 1G | U=1.28dB |
| 8 | humidity uncertainty | U=5.3% |
| 9 | Temperature uncertainty | U=0.59℃ |
| 10 | Radiated disturbance(30MHz-1000MHz) | U=4.8dB |
| 11 | Radiated disturbance(1GHz-6GHz) | U=4.9dB |
| 12 | Radiated disturbance(1GHz-18GHz) | U=5.0dB |
| 13 | Occupied Bandwidth | U=4.96dB |
| 14 | RF Power Density | U=0.77dB |

## 3. GENERAL INFORMATION

### 3.1 GENERAL DESCRIPTION OF EUT

| | | |
|---|---|---|
| Product Name: | Notebook | |
| Test Model No.: | L156U | |
| Product Description | IEEE 802.11 WLAN Mode Supported | ☒ 802.11a/n (20MHz channel bandwidth)<br>☒ 802.11n (40MHz channel bandwidth)<br>☒ 802.11ac(80MHz channel bandwidth) |
| | Data Rate | 802.11a: 6,9,12,18,24,36,48,54Mbps;<br>802.11n(HT20/HT40):MCS0-MCS7;<br>802.11ac(VHT80):NSS1, MCS0-MCS9 |
| | Modulation | OFDM with BPSK/QPSK/16QAM/64QAM/256QAM for 802.11a/n/ac; |
| | Operating Frequency Range | ☒ 5180-5240MHz for 802.11a/n(HT20)/ac20;<br>5190-5230MHz for 802.11n(HT40)/ac40;<br>5210MHz for 802.11 ac80;<br>☐ 5745-5825 MHz for802.11a/n(HT20)/ac20;<br>5755-5795 MHz for 802.11a/n(HT40)/ac40;<br>5775MHz for 802.11 ac80; |
| | Number of Channels | ☒ 4 channels for 802.11a/n20/ac20 in the 5180-5240MHz band ;<br>2 channels for 802.11 n40/ac40 in the 5190-5230 MHz band ;<br>1 channels for 802.11 ac80 in the 5210MHz band ;<br>☐ 5 channels for 802.11a/n20/ac20 in the 5745-5825MHz band ;<br>2 channels for 802.11 n40/ac40 in the 5755-5795 MHz band ;<br>1 channels for 802.11 ac80 in the 5775MHz band ; |
| Channel List | Please refer to the Note 2. | |
| Antenna Type and Antenna gain: | FPC Antenna, ANT1: 1.57dBi, ANT2: 1.57dBi | |
| Worst Case: | 5.2G WIFI 802.11a | |
| Power supply: | Adapter:<br>Model: JHD-AP065U-19034BA-A<br>Input:100-240V, 50/60Hz 1.5A<br>Output: 19V, 3420mA<br>Battery:DC 11.4V | |
| SWITCHING POWER ADAPTER: | / | |
| Sample Number: | 240110020E-1# | |

Note:

For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

The device supports SISO in all modes, and MIMO 2T2R in 802.11n/ac modes.

Directional gain(MIMO) $=G_{ant}+10\log(N_{ant})$ dBi=3.53 dBi

| 802.11a/n/ac( 20MHz) Frequency Channel | | | | | | | |
|---|---|---|---|---|---|---|---|
| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 36 | 5180 | 44 | 5220 | 40 | 5200 | 48 | 5240 |
| | | | | | | | |
| | | | | | | | |
| 802.11n /ac(40MHz)Frequency Channel | | | | | | | |
| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 38 | 5190 | 46 | 5230 | | | | |
| | | | | | | | |

| 802.11ac(80MHz) Frequency Channel | |
|---|---|
| Channel | Frequency (MHz) |
| 42 | 5210 |
| | |

## 3.2 DESCRIPTION OF TEST MODES

| | |
|---|---|
| Transmitting mode | Keep the EUT in continuously transmitting mode |
| Remark: During the test,the dutycycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data. | |

| Pretest Mode | Description |
|---|---|
| Mode 1 | 802.11a / n 20/CH36/ CH40/ CH48 |
| Mode 2 | 802.11n 40/CH38 |
| Mode 3 | 802.11 ac80/CH42 |
| Mode 4 | Link Mode |

| Conducted Emission | |
|---|---|
| Final Test Mode | Description |
| Mode 4 | Link Mode |

| For Radiated Emission | |
|---|---|
| Final Test Mode | Description |
| Mode 1 | 802.11a / n 20/CH36/ CH40/ CH48 |
| Mode 2 | 802.11n 40/CH38 |
| Mode 3 | 802.11 ac80/CH42 |

Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.

## 3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Emission




Conducted Spurious




## 3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment | Mfr/Brand | Model/Type No. | Series No. | Note |
|---|---|---|---|---|---|
| / | / | / | / | / | / |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |

| Item | Shielded Type | Ferrite Core | Length | Note |
|---|---|---|---|---|
| | | | | |
| | | | | |
| | | | | |

Note:

(1) The support equipment was authorized by Declaration of Confirmation.

(2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

(3) The test software is the SecureCRTPortable.exe which can set the EUT into the individual test modes.
802.11a/802.11n(HT20)/802.11ac(HT20) Power set point:63
802.11n /ac(40MHz)Power set point:44
802.11ac(80MHz)Power set point:44

## 3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

| Item | Equipment | Manufacturer | Model | Last Cal. | Next Cal. |
|---|---|---|---|---|---|
| 1 | Receiver | R&S | ESCI | May 12, 2023 | May 11, 2024 |
| 2 | Loop antenna | EMCI | LAP600 | May 12, 2023 | May 11, 2024 |
| 3 | Amplifier | Schwarzbeck | BBV 9743 B | May 12, 2023 | May 11, 2024 |
| 4 | Amplifier | Schwarzbeck | BBV 9718 B | May 12, 2023 | May 11, 2024 |
| 5 | Bilog Antenna | Schwarzbeck | VULB9162 | May 17, 2023 | May 16, 2024 |
| 6 | Horn Antenna | Schwarzbeck | BBHA9120D | May 17, 2023 | May 16, 2024 |
| 7 | Horn Antenna | A.H.SYSTEMS | SAS574 | May 12, 2023 | May 11, 2024 |
| 8 | Amplifier | AEROFLEX | 100KHz-40GHz | May 12, 2023 | May 11, 2024 |
| 9 | Spectrum Analyzer | R&S | FSV40 | May 12, 2023 | May 11, 2024 |
| 10 | 966 Anechoic Chamber | EMToni | 9m6m6m | Nov. 25, 2021 | Nov. 24, 2024 |
| 11 | Spectrum Analyzer | KEYSIGHT | N9020A | May 12, 2023 | May 11, 2024 |
| 12 | WIDBAND RADIO COMMUNICATION TESTER | R&S | CMW500 | May 12, 2023 | May 11, 2024 |
| 13 | Single Generator | Agilent | N5182A | May 12, 2023 | May 11, 2024 |
| 14 | Power Sensor | MWRFtest | MW100-RFCB | May 12, 2023 | May 11, 2024 |
| 15 | Audio analyzer | R&S | UPL | May 12, 2023 | May 11, 2024 |
| 16 | Single Generator | R&S | SMB100A | May 12, 2023 | May 11, 2024 |
| 17 | Power Amplifier Shielding Room | EMToni | 2m3m3m | Nov. 25, 2021 | Nov. 24, 2024 |

Conduction Test equipment

| Equipment | Manufacturer | Model | Last Cal. | Next Cal. |
|---|---|---|---|---|
| Receiver | R&S | ESCI | May 12, 2023 | May 11, 2024 |
| LISN | R&S | ENV216 | May 12, 2023 | May 11, 2024 |
| ISN CAT 6 | Schwarzbeck | NTFM 8158 | May 12, 2023 | May 11, 2024 |
| ISN CAT 5 | Schwarzbeck | CAT5 8158 | May 12, 2023 | May 11, 2024 |
| Capacitive Voltage Probe | Schwarzbeck | CVP 9222 C | May 12, 2023 | May 11, 2024 |
| Current Transformer Clamp | Schwarzbeck | SW 9605 | May 12, 2023 | May 11, 2024 |
| CE Shielding Room | EMToni | 9m4m3m | Nov. 25, 2021 | Nov. 24, 2024 |

## 4.EMC EMISSION TEST

### 4.1 CONDUCTED EMISSION MEASUREMENT

| | |
|---|---|
| Test Requirement: | FCC Part15 C Section 15.207 |
| Test Method: | ANSI C63.10:2013 |
| Test Frequency Range: | 150KHz to 30MHz |
| Receiver setup: | RBW=9KHz, VBW=30KHz, Sweep time=auto |

#### 4.1.1 POWER LINE CONDUCTED EMISSION Limits

| FREQUENCY (MHz) | Limit (dBuV) | | Standard |
|---|---|---|---|
| | Quasi-peak | Average | |
| 0.15 -0.5 | 66 - 56 * | 56 - 46 * | FCC |
| 0.50 -5.0 | 56.00 | 46.00 | FCC |
| 5.0 -30.0 | 60.00 | 50.00 | FCC |

Note:

(1) *Decreases with the logarithm of the frequency.

#### 4.1.2 TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

d. LISN at least 80 cm from nearest part of EUT chassis.

e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP




4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

### 4.1.6 TEST RESULTS

| | | | |
|---|---|---|---|
| Temperature: | 24.3℃ | Relative Humidity : | 50% |
| Pressure: | 101kPa | Phase : | L |
| Test Voltage: | AC 120V/60Hz | | |




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector | P/F | Remark |
|---|---|---|---|---|---|---|---|---|---|
| 1 | 0.9555 | 27.28 | 9.74 | 37.02 | 56.00 | -18.98 | QP | P | |
| 2 | 0.9555 | 13.16 | 9.74 | 22.90 | 46.00 | -23.10 | AVG | P | |
| 3 | 1.0095 | 26.78 | 9.74 | 36.52 | 56.00 | -19.48 | QP | P | |
| 4 | 1.0095 | 14.78 | 9.74 | 24.52 | 46.00 | -21.48 | AVG | P | |
| 5 | 1.0990 | 27.26 | 9.74 | 37.00 | 56.00 | -19.00 | QP | P | |
| 6 | 1.0990 | 16.75 | 9.74 | 26.49 | 46.00 | -19.51 | AVG | P | |
| 7 * | 1.1625 | 27.89 | 9.74 | 37.63 | 56.00 | -18.37 | QP | P | |
| 8 | 1.1625 | 16.22 | 9.74 | 25.96 | 46.00 | -20.04 | AVG | P | |
| 9 | 1.2520 | 27.63 | 9.74 | 37.37 | 56.00 | -18.63 | QP | P | |
| 10 | 1.2520 | 14.99 | 9.74 | 24.73 | 46.00 | -21.27 | AVG | P | |
| 11 | 1.3330 | 26.74 | 9.74 | 36.48 | 56.00 | -19.52 | QP | P | |
| 12 | 1.3330 | 15.61 | 9.74 | 25.35 | 46.00 | -20.65 | AVG | P | |

Notes:
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor
4.The test data shows only the worst case ANT 1-802.1a Low Channel:5180MHz.

| | | | |
|---|---|---|---|
| Temperature: | 24.3℃ | Relative Humidity : | 50% |
| Pressure: | 101kPa | Phase : | N |
| Test Voltage: | AC 120V/60Hz | | |




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector | P/F | Remark |
|---|---|---|---|---|---|---|---|---|---|
| 1 * | 1.9590 | 25.29 | 9.75 | 35.04 | 56.00 | -20.96 | QP | P | |
| 2 | 1.9590 | 5.94 | 9.75 | 15.69 | 46.00 | -30.31 | AVG | P | |
| 3 | 2.2559 | 24.60 | 9.77 | 34.37 | 56.00 | -21.63 | QP | P | |
| 4 | 2.2559 | 8.45 | 9.77 | 18.22 | 46.00 | -27.78 | AVG | P | |
| 5 | 2.4045 | 24.78 | 9.77 | 34.55 | 56.00 | -21.45 | QP | P | |
| 6 | 2.4045 | 8.25 | 9.77 | 18.02 | 46.00 | -27.98 | AVG | P | |
| 7 | 2.9355 | 23.80 | 9.79 | 33.59 | 56.00 | -22.41 | QP | P | |
| 8 | 2.9355 | 7.08 | 9.79 | 16.87 | 46.00 | -29.13 | AVG | P | |
| 9 | 15.2652 | 23.50 | 9.88 | 33.38 | 60.00 | -26.62 | QP | P | |
| 10 | 15.2652 | 16.12 | 9.88 | 26.00 | 50.00 | -24.00 | AVG | P | |
| 11 | 18.0419 | 23.74 | 9.88 | 33.62 | 60.00 | -26.38 | QP | P | |
| 12 | 18.0419 | 16.26 | 9.88 | 26.14 | 50.00 | -23.86 | AVG | P | |

Notes:
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor
4.The test data shows only the worst case ANT 1-802.1a Low Channel:5180MHz.

## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 APPLICABLE STANDARD

According to FCC Part 15.407(d) and 15.209, RSS-247 6.2.1.2, RSS-Gen

### 4.2.2 CONFORMANCE LIMIT

According to FCC Part 15.407(b)(7): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part15.205, Restricted bands

| MHz | MHz | MHz | GHz |
|---|---|---|---|
| 0.090-0.110 | 16.42-16.423 | 399.9-410 | 4.5-5.15 |
| 10.495-0.505 | 16.69475-16.69525 | 608-614 | 5.35-5.46 |
| 2.1735-2.1905 | 16.80425-16.80475 | 960-1240 | 7.25-7.75 |
| 4.125-4.128 | 25.5-25.67 | 1300-1427 | 8.025-8.5 |
| 4.17725-4.17775 | 37.5-38.25 | 1435-1626.5 | 9.0-9.2 |
| 4.20725-4.20775 | 73-74.6 | 1645.5-1646.5 | 9.3-9.5 |
| 6.215-6.218 | 74.8-75.2 | 1660-1710 | 10.6-12.7 |
| 6.26775-6.26825 | 123-138 | 2200-2300 | 14.47-14.5 |
| 8.291-8.294 | 149.9-150.05 | 2310-2390 | 15.35-16.2 |
| 8.362-8.366 | 156.52475-156.52525 | 2483.5-2500 | 17.7-21.4 |
| 8.37625-8.38675 | 156.7-156.9 | 2690-2900 | 22.01-23.12 |
| 8.41425-8.41475 | 162.0125-167.17 | 3260-3267 | 23.6-24.0 |
| 12.29-12.293 | 167.72-173.2 | 3332-3339 | 31.2-31.8 |
| 12.51975-12.52025 | 240-285 | 3345.8-3358 | 36.43-36.5 |
| 12.57675-12.57725 | 322-335.4 | 3600-4400 | (2) |
| 13.36-13.41 | | | |

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Restricted Frequency(MHz) | Field Strength (μV/m) | Field Strength (dBμV/m) | Measurement Distance |
|---|---|---|---|
| 0.009~0.490 | 2400/F(KHz) | 20 log (uV/m) | 300 |
| 0.490~1.705 | 2400/F(KHz) | 20 log (uV/m) | 30 |
| 1.705~30.0 | 30 | 29.5 | 30 |
| 30-88 | 100 | 40 | 3 |
| 88-216 | 150 | 43.5 | 3 |
| 216-960 | 200 | 46 | 3 |
| Above 960 | 500 | 54 | 3 |

Limits of Radiated Emission Measurement(Above 1000MHz)

| Frequency(MHz) | Class B (dBuV/m) (at 3M) | |
|---|---|---|
| | PEAK | AVERAGE |
| Above 1000 | 74 | 54 |

Remark :1. Emission level in dBuV/m=20 log (uV/m)
2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. Distance extrapolation factor =40log(Specific distance/ test distance)( dB);
Limit line=Specific limits(dBuV) + distance extrapolation factor.

### 4.2.3 MEASURING INSTRUMENTS

The Measuring equipment is listed in the section 6.3 of this test report.

4.2.4 TEST CONFIGURATION

1.For radiated emissions below 30MHz




2.For radiated emissions from 30MHz to 1000MHz




3. Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 TEST PROCEDURE

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m.The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.
This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.
Use the following spectrum analyzer settings:

| Spectrum Parameter | Setting |
|---|---|
| Attenuation | Auto |
| Start Frequency | 1000 MHz |
| Stop Frequency | 10th carrier harmonic |
| RB / VB (emission in restricted band) | 1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average |

| Receiver Parameter | Setting |
|---|---|
| Attenuation | Auto |
| Start ~ Stop Frequency | 9kHz~150kHz / RB 200Hz for QP |
| Start ~ Stop Frequency | 150kHz~30MHz / RB 9kHz for QP |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB 120kHz for QP |

a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
b. The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
f. For the actual test configuration, please refer to the related Item –EUT Test Photos.
Note:
Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

| Frequency Band (MHz) | Function | Resolution bandwidth | Video Bandwidth |
|---|---|---|---|
| 30 to 1000 | QP | 120 kHz | 300 kHz |
| Above 1000 | Peak | 1 MHz | 1 MHz |
| | Average | 1 MHz | 10 Hz |

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where RBWCF [dB] =10*lg(100 [kHz]/narrower RBW [kHz]). , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

**4.2.6 TEST RESULT**(Between 9KHz – 30MHz)

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Between 30MHz – 1GHz

| | | | |
|---|---|---|---|
| Temperature: | 25.2℃ | Relative Humidity: | 50% |
| Pressure: | 1010kPa | Polarization: | Horizontal |
| Test Voltage: | AC 120V | | |




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|---|---|---|---|---|---|---|---|
| 1 * | 94.0978 | 52.24 | -11.87 | 40.37 | 43.50 | -3.13 | QP |
| 2 | 289.0020 | 45.32 | -8.27 | 37.05 | 46.00 | -8.95 | QP |
| 3 | 454.3100 | 44.00 | -4.85 | 39.15 | 46.00 | -6.85 | QP |
| 4 | 465.5994 | 44.25 | -4.66 | 39.59 | 46.00 | -6.41 | QP |
| 5 | 478.8455 | 44.12 | -4.44 | 39.68 | 46.00 | -6.32 | QP |
| 6 | 526.3967 | 43.47 | -3.60 | 39.87 | 46.00 | -6.13 | QP |

| | | | |
|---|---|---|---|
| Temperature: | 25.2℃ | Relative Humidity: | 50% |
| Pressure: | 1010kPa | Polarization: | Vertical |
| Test Voltage: | AC 120V | | |




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|---|---|---|---|---|---|---|---|
| 1 * | 285.9778 | 48.18 | -8.32 | 39.86 | 46.00 | -6.14 | QP |
| 2 | 295.1469 | 47.11 | -8.14 | 38.97 | 46.00 | -7.03 | QP |
| 3 | 459.1144 | 44.32 | -4.76 | 39.56 | 46.00 | -6.44 | QP |
| 4 | 483.9094 | 43.88 | -4.36 | 39.52 | 46.00 | -6.48 | QP |
| 5 | 520.8882 | 43.00 | -3.71 | 39.29 | 46.00 | -6.71 | QP |
| 6 | 560.6928 | 42.37 | -2.98 | 39.39 | 46.00 | -6.61 | QP |

Remarks:
1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2.The emission levels of other frequencies are very lower than the limit and not show in test report.
3.The test data shows only the worst case ANT 1-802.1a Low Channel:5180MHz.

Between1GHz – 40GHz

| | | | |
|---|---|---|---|
| Temperature : | 24.2℃ | Relative Humidity: | 54% |
| Pressure : | 1010 hPa | Test Voltage : | AC 120V |
| Test Mode : | 5.2G TX- 802.11a | | |

802.11a

| Polar (H/V) | Frequency (MHz) | Meter Reading (dBuV) | Pre-amplifier (dB) | Cable Loss (dB) | Antenna Factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Detector Type |
|---|---|---|---|---|---|---|---|---|---|
| Low Channel:5180MHz | | | | | | | | | |
| V | 11490.00 | 58.56 | 30.55 | 5.77 | 24.66 | 58.44 | 68.2 | -9.76 | PK |
| V | 11490.00 | 41.33 | 30.55 | 5.77 | 24.66 | 41.21 | 54 | -12.79 | AV |
| V | 17235.00 | 57.4 | 30.33 | 6.32 | 24.55 | 57.94 | 68.2 | -10.26 | PK |
| V | 17235.00 | 42.26 | 30.33 | 6.32 | 24.55 | 42.8 | 54 | -11.2 | AV |
| H | 11490.00 | 58.48 | 30.55 | 5.77 | 24.66 | 58.36 | 68.2 | -9.84 | PK |
| H | 11490.00 | 41.93 | 30.55 | 5.77 | 24.66 | 41.81 | 54 | -12.19 | AV |
| H | 17235.00 | 59.7 | 30.33 | 6.32 | 24.55 | 60.24 | 68.2 | -7.96 | PK |
| H | 17235.00 | 43.96 | 30.33 | 6.32 | 24.55 | 44.5 | 54 | -9.5 | AV |
| Middle Channel:5200MHz | | | | | | | | | |
| V | 11570.00 | 56.06 | 30.55 | 5.77 | 24.66 | 55.94 | 68.2 | -12.26 | PK |
| V | 11570.00 | 41.51 | 30.55 | 5.77 | 24.66 | 41.39 | 54 | -12.61 | AV |
| V | 17355.00 | 58.85 | 30.33 | 6.32 | 24.55 | 59.39 | 68.2 | -8.81 | PK |
| V | 17355.00 | 44.28 | 30.33 | 6.32 | 24.55 | 44.82 | 54 | -9.18 | AV |
| H | 11570.00 | 55.9 | 30.55 | 5.77 | 24.66 | 55.78 | 68.2 | -12.42 | PK |
| H | 11570.00 | 42.26 | 30.55 | 5.77 | 24.66 | 42.14 | 54 | -11.86 | AV |
| H | 17355.00 | 56.75 | 30.33 | 6.32 | 24.55 | 57.29 | 68.2 | -10.91 | PK |
| H | 17355.00 | 43.35 | 30.33 | 6.32 | 24.55 | 43.89 | 54 | -10.11 | AV |
| High Channel:5240MHz | | | | | | | | | |
| V | 11650.00 | 57.64 | 30.55 | 5.77 | 24.66 | 57.52 | 68.2 | -10.68 | PK |
| V | 11650.00 | 41.28 | 30.55 | 5.77 | 24.66 | 41.16 | 54 | -12.84 | AV |
| V | 17475.00 | 56.26 | 30.33 | 6.32 | 24.55 | 56.8 | 68.2 | -11.4 | PK |
| V | 17475.00 | 42.32 | 30.33 | 6.32 | 24.55 | 42.86 | 54 | -11.14 | AV |
| H | 11650.00 | 58.41 | 30.55 | 5.77 | 24.66 | 58.29 | 68.2 | -9.91 | PK |
| H | 11650.00 | 41.17 | 30.55 | 5.77 | 24.66 | 41.05 | 54 | -12.95 | AV |
| H | 17475.00 | 55.92 | 30.33 | 6.32 | 24.55 | 56.46 | 68.2 | -11.74 | PK |
| H | 17475.00 | 42.54 | 30.33 | 6.32 | 24.55 | 43.08 | 54 | -10.92 | AV |

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
4. 802.11 a,802.11n20/40,802.11ac20/40/80 of ANT1, ANT2 and MIMO mode have been tested,The worst mode is ANT 1 802.11a is recorded.

RADIATED Band EMISSION MEASUREMENT

| | Polar (H/V) | Frequency (MHz) | Meter Reading (dBuV) | Pre-amplifier (dB) | Cable Loss (dB) | Antenna Factor (dB/m) | Emission level (dBuV/m) | Limit (dBuV/m) | Margin(dB) | Detector Type | Result |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 802.11a | LowChannel5180MHz | | | | | | | | | | |
| | H | 5141.5 | 59.12 | 30.22 | 4.85 | 23.98 | 57.73 | 74.00 | -16.27 | PK | PASS |
| | H | 5141.5 | 48.56 | 30.22 | 4.85 | 23.98 | 47.17 | 54.00 | -6.83 | AV | PASS |
| | H | 5150 | 61.61 | 30.22 | 4.85 | 23.98 | 60.22 | 74.00 | -13.78 | PK | PASS |
| | H | 5150 | 46.90 | 30.22 | 4.85 | 23.98 | 45.51 | 54.00 | -8.49 | AV | PASS |
| | V | 5141.5 | 61.02 | 30.22 | 4.85 | 23.98 | 59.63 | 74.00 | -14.37 | PK | PASS |
| | V | 5141.5 | 46.82 | 30.22 | 4.85 | 23.98 | 45.43 | 54.00 | -8.57 | AV | PASS |
| | V | 5150 | 62.67 | 30.22 | 4.85 | 23.98 | 61.28 | 74.00 | -12.72 | PK | PASS |
| | V | 5150 | 48.66 | 30.22 | 4.85 | 23.98 | 47.27 | 54.00 | -6.73 | AV | PASS |
| | High Channel 5240MHz | | | | | | | | | | |
| | H | 5350 | 59.24 | 30.22 | 4.85 | 23.98 | 57.85 | 74.00 | -16.15 | PK | PASS |
| | H | 5350 | 47.94 | 30.22 | 4.85 | 23.98 | 46.55 | 54.00 | -7.45 | AV | PASS |
| | H | 5410 | 60.26 | 30.22 | 4.85 | 23.98 | 58.87 | 74.00 | -15.13 | PK | PASS |
| | H | 5410 | 48.53 | 30.22 | 4.85 | 23.98 | 47.14 | 54.00 | -6.86 | AV | PASS |
| | V | 5350 | 61.62 | 30.22 | 4.85 | 23.98 | 60.23 | 74.00 | -13.77 | PK | PASS |
| | V | 5350 | 48.92 | 30.22 | 4.85 | 23.98 | 47.53 | 54.00 | -6.47 | AV | PASS |
| | V | 5410 | 61.86 | 30.22 | 4.85 | 23.98 | 60.47 | 74.00 | -13.53 | PK | PASS |
| | V | 5410 | 46.47 | 30.22 | 4.85 | 23.98 | 45.08 | 54.00 | -8.92 | AV | PASS |

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
4. 802.11 a,802.11n20/40,802.11ac20/40/80 of ANT1, ANT2 and MIMO mode have been tested,The worst mode is ANT 1 802.11a is recorded.

## 5.POWER SPECTRAL DENSITY TEST

### 5.1 APPLIED PROCEDURES / LIMIT

According to FCC §15.407(a), RSS-247 6.2.1.1

Power limits:

(1) For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or 1.76 + 10 log10B, dBm, whichever is less. Devices shall implement transmitter power control (TPC) in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.
For other devices, the maximum e.i.r.p. shall not exceed 200 mW or 10 + 10 log10B, dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.

## 5.2 TEST PROCEDURE

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, "provided that the measured power is integrated over the full reference bandwidth" to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or <500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:

a) Set RBW ≥ 1/T, where T is defined in section II.B.I.a).

b) Set VBW ≥ 3 RBW.

c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add 10log(500kHz/RBW) to the measured result, whereas RBW (< 500 KHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.

d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add 10log(1MHz/RBW) to the measured result, whereas RBW (< 1 MHz) is the reduced resolution bandwidth of spectrum analyzer set during measurement.

e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 KHz for the sections 5.c) and 5.d) above, since RBW=100 KHZ is available on nearly all spectrum analyzers.

## 5.3 DEVIATION FROM STANDARD

No deviation.

## 5.4 TEST SETUP

## 5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULTS

| | | | |
|---|---|---|---|
| Temperature： | 24.2℃ | Relative Humidity: | 53% |
| Pressure： | 1010 hPa | Test Voltage ： | DC 11.4V |
| Test Mode： | TX | | |
| 5.2G(5180-5240MHz): | Please refer to the Appendix B.5 for 5G WIFI RF Test Data. | | |

## 6. 26DB & 6DB &99% EMISSION BANDWIDTH

### 6.1 APPLIED PROCEDURES / LIMIT

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band, the minimum bandwidth 6 dB bandwidth of U-NII devices shall be at least 500KHz. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

### 6.2 TEST PROCEDURE

a) Set RBW = 100KHz.

b) Set the VBW > RBW.

c) Detector = Peak.

d) Trace mode = max hold.

e) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW ≥ 3 · RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.

## 6.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

## 6.4 TEST RESULTS

| | | | | |
|---|---|---|---|---|
| Temperature： | | 24.2℃ | Relative Humidity: | 53% |
| Pressure： | | 1010 hPa | Test Voltage ： | DC 11.4V |
| Test Mode ： | | TX | | |
| -26dB Bandwidth | 5.2G(5180-5240MHz): | Please refer to the Appendix B.3 for 5G WIFI RF Test Data. | | |
| 99% Bandwidth | 5.2G(5180-5240MHz): | Please refer to the Appendix B.4 for 5G WIFI RF Test Data. | | |

## 7.MAXIMUM CONDUCTED OUTPUT POWER

### 7.1 PPLIED PROCEDURES / LIMIT

According to FCC §15.407,
The maximum conduced output power should not exceed:

| Frequency Band(MHz) | Limit |
|---|---|
| 5150~5250 | 250mW |
| 5725~5850 | 1W |

RSS-247 6.2.1.1, RSS-247 6.2.4.1

| Frequency Band(MHz) | Limit |
|---|---|
| 5150~5250 | 200mW |
| 5725~5850 | 1W |

Frequency band 5150-5250 MHz
According to RSS-247 section 6.2.1.1: For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or 1.76 + 10 log10B, dBm, whichever is less. Devices shall implement transmitter power control (TPC) in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.
For other devices, the maximum e.i.r.p. shall not exceed 200 mW or 10 + 10 log10B, dBm, whichever power is less. B is the 99% emission bandwidth in megahertz. The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.
Frequency band 5250-5350 MHz
According to RSS-247 section 6.2.2.1: For OEM devices installed in vehicles, the maximum e.i.r.p. shall not exceed 30 mW or 1.76 + 10 log10B, dBm, whichever is less. Devices shall implement TPC in order to have the capability to operate at least 3 dB below the maximum permitted e.i.r.p. of 30 mW.
Devices, other than devices installed in vehicles, shall comply with the following:
The maximum conducted output power shall not exceed 250 mW or 11 + 10 log10B, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band;
The maximum e.i.r.p. shall not exceed 1.0 W or 17 + 10 log10B, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.
Frequency bands 5470-5600 MHz and 5650-5725 MHz
According to RSS-247 section 6.2.3.1: The maximum conducted output power shall not exceed 250 mW or 11 + 10 log10B, dBm, whichever is less. The power spectral density shall not exceed 11 dBm in any 1.0 MHz band.
The maximum e.i.r.p. shall not exceed 1.0 W or 17 + 10 log10B, dBm, whichever is less. B is the 99% emission bandwidth in megahertz. Note that devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.
Frequency bands 5725-5850 MHz
The maximum conducted output power shall not exceed 1 W. The output power spectral density shall not exceed 30 dBm in any 500 kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the output power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed point-to point operations exclude the use of point-to-multipointsystems, omnidirectional applications and multiple collocated transmitters transmitting the same information.

## 7.2 TEST PROCEDURE

The EUT was directly connected to the Power meter

1. Device Configuration

If possible, configure or modify the operation of the EUT so that it transmits continuously at its maximum power control level (see section II.B.).

a) The intent is to test at 100 percent duty cycle; however a small reduction in duty cycle (to no lower than 98 percent) is permitted if required by the EUT for amplitude control purposes. Manufacturers are expected to provide software to the test lab to permit such continuous operation.

b) If continuous transmission (or at least 98 percent duty cycle) cannot be achieved due to hardware limitations (e.g., overheating), the EUT shall be operated at its maximum power control level with the transmit duration as long as possible and the duty cycle as high as possible.

2. Measurement using a Spectrum Analyzer or EMI Receiver (SA)

Measurement of maximum conducted output power using a spectrum analyzer requires integrating the spectrum across a frequency span that encompasses, at a minimum, either the EBW or the 99-percent occupied bandwidth of the signal.1 However, the EBW must be used to determine bandwidth dependent limits on maximum conducted output power in accordance with § 15.407(a).

a) The test method shall be selected as follows: (i) Method SA-1 or SA-1 Alternative (averaging with the EUT transmitting at full power throughout each sweep) shall be applied if either of the following conditions can be satisfied:

• The EUT transmits continuously (or with a duty cycle ≥ 98 percent).

• Sweep triggering or gating can be implemented in a way that the device transmits at the maximum power control level throughout the duration of each of the instrument sweeps to be averaged. This condition can generally be achieved by triggering the instrument's sweep if the duration of the sweep (with the analyzer configured as in Method SA-1, below) is equal to or shorter than the duration T of each transmission from the EUT and if those transmissions exhibit full power throughout their durations.

(ii) Method SA-2 or SA-2 Alternative (averaging across on and off times of the EUT transmissions, followed by duty cycle correction) shall be applied if the conditions of (i) cannot be achieved and the transmissions exhibit a constant duty cycle during the measurement duration. Duty cycle will be considered to be constant if variations are less than ± 2 percent.

(iii) Method SA-3 (RMS detection with max hold) or SA-3 Alternative (reduced VBW with max hold) shall be applied if the conditions of (i) and (ii) cannot be achieved.

b) Method SA-1 (trace averaging with the EUT transmitting at full power throughout each sweep): (i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.

(ii) Set RBW = 1 MHz.

(iii) Set VBW ≥ 3 MHz.

(iv) Number of points in sweep ≥ 2 Span / RBW. (This ensures that bin-to-bin spacing is ≤ RBW/2, so that narrowband signals are not lost between frequency bins.)

(v) Sweep time = auto.

(vi) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.

(vii) If transmit duty cycle < 98 percent, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 percent, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run".

(viii) Trace average at least 100 traces in power averaging (i.e., RMS) mode.

(ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum

## 7.3 DEVIATION FROM STANDARD

No deviation.

## 7.4 TEST SETUP




## 7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

## 7.6 TEST RESULTS

| | | | |
|---|---|---|---|
| Temperature： | 24.2℃ | Relative Humidity: | 53% |
| Pressure： | 1010 hPa | Test Voltage ： | DC 11.4V |
| Test Mode ： | TX | | |
| 5.2G (5180-5240MHz)： | Please refer to the Appendix B.2 for 5G WIFI RF Test Data. | | |

## 8.OUT OF BAND EMISSIONS

### 8.1 APPLICABLE STANDARD

According to FCC §15.407(b), RSS-247 6.2.1.2, RSS-247 6.2.4.2

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.

(2)Devices operating in the band 5725-5850 MHz shall have e.i.r.p. of unwanted emissions comply with the following:
a) 27 dBm/MHz at frequencies from the band edges decreasing linearly to 15.6 dBm/MHz at 5 MHz above or below the band edges;
b) 15.6 dBm/MHz at 5 MHz above or below the band edges decreasing linearly to 10 dBm/MHz at 25 MHz above or below the band edges;
c) 10 dBm/MHz at 25 MHz above or below the band edges decreasing linearly to -27 dBm/MHz at 75 MHz above or below the band edges; and
d) -27 dBm/MHz at frequencies more than 75 MHz above or below the band edges.
According to RSS-247 section 6.2.1.2: For transmitters with operating frequencies in the band 5150-5250 MHz, all emissions outside the band 5150-5350 MHz shall not exceed -27 dBm/MHz e.i.r.p. Any unwanted emissions that fall into the band 5250-5350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth (i.e. 99% bandwidth), above 5250 MHz. The 26 dB bandwidth may fall into the 5250-5350 MHz band; however, if the occupied bandwidth also falls within the 5250-5350 MHz band, the transmission is considered as intentional and the devices shall comply with all requirements in the band 5250-5350 MHz including implementing dynamic frequency selection (DFS) and TPC, on the portion of the emission that resides in the 5250- 5350 MHz band.

8.2 TEST PROCEDURE

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal froman external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antennaterminal to measurement instrument via a low loss cable. Then set it to any one measured frequency withinits operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graphwith marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP




8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

8.6 TEST RESULTS

| | | | |
|---|---|---|---|
| Temperature： | 24.2℃ | Relative Humidity: | 53% |
| Pressure： | 1010 hPa | Test Voltage ： | DC 11.4V |
| Test Mode ： | TX | | |
| 5.2G (5180-5240MHz): | Please refer to the Appendix B.6 for 5G WIFI RF Test Data. | | |

## 9.SPURIOUS RF CONDUCTED EMISSIONS

### 9.1 CONFORMANCE LIMIT

Refer to 15.407(b):

Except as shown in paragraph 15.407(b)(7) of this section, the maximum emissionsoutside of the frequency bands of operation shall be attenuated in accordance with the following limits:

For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of −27 dBm/MHz.

Refer to RSS-247/6.2.1.2:

For transmitters with operating frequencies in the band 5150-5250 MHz, all emissions outside the band 5150-5350 MHz shall not exceed -27 dBm/MHz e.i.r.p. Any unwanted emissions that fall into the band 5250-5350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth (i.e. 99% bandwidth), above 5250 MHz. The 26 dB bandwidth may fall into the 5250-5350 MHz band; however, if the occupied bandwidth also falls within the 5250-5350 MHz band, the transmission is considered as intentional and the devices shall comply with all requirements in the band 5250-5350 MHz including implementing dynamic frequency selection (DFS) and TPC, on the portion of the emission that resides in the 5250-5350 MHz band.

Devices operating in the band 5725-5850 MHz shall have e.i.r.p. of unwanted emissions comply with the following:

a) 27 dBm/MHz at frequencies from the band edges decreasing linearly to 15.6 dBm/MHz at 5 MHz above or below the band edges;

b) 15.6 dBm/MHz at 5 MHz above or below the band edges decreasing linearly to 10 dBm/MHz at 25 MHz above or below the band edges;

c) 10 dBm/MHz at 25 MHz above or below the band edges decreasing linearly to -27 dBm/MHz at 75 MHz above or below the band edges; and

d) -27 dBm/MHz at frequencies more than 75 MHz above or below the band edges.

### 9.2 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

### 9.3 TEST SETUP

### 9.4 TEST PROCEDURE

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300KHz to measure the peak field strength, and measure frequency range from 30MHz to 1GHz.Set RBW=1MHz and VBW= 3MHz to measure the peak field strength, and measure frequency range from 1GHz to 40GHz.

9.5 TEST RESULTS

| | | | |
|---|---|---|---|
| Temperature： | 24.2℃ | Relative Humidity: | 53% |
| Pressure： | 1010 hPa | Test Voltage ： | DC 11.4V |
| Test Mode ： | TX | | |
| 5.2G (5180-5240MHz): | Please refer to the Appendix B.7 for 5G WIFI RF Test Data. | | |

Remark1: The measurement frequency range is from 30MHz to the 10th harmonic or 40G of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandedge measurement data.

Remark2: 27G to 40G is the background, so it does not show the data.

## 10.FREQUENCY STABILITY MEASUREMENT

### 10.1 LIMIT

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

The transmitter center frequency tolerance shall be ± 20 ppm maximum for the 5 GHz band (IEEE 802.11n specification).

### 10.2 TEST PROCEDURES

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 30 kHz with peak detector and maxhold settings.
5. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
6. Extreme temperature is 20°C~50°C.

### 10.3 TEST SETUP LAYOUT




### 10.4 EUT OPERATION DURING TEST

The EUT was programmed to be in continuously un-modulation transmitting mode.

### 10.5 TEST RESULTS

| | | | |
|---|---|---|---|
| Temperature : | 24.2℃ | Relative Humidity: | 53% |
| Pressure : | 1010 hPa | Test Voltage : | DC 12V |
| Test Mode : | TX | | |
| 5.2G (5180-5240MHz): | Please refer to the Appendix B.8 for 5G WIFI RF Test Data. | | |

## 10.ANTENNA REQUIREMENT

| Standard requirement: | FCC Part15 C Section 15.203, RSS-247 6.8 |
|---|---|
| 15.203 requirement:<br>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.<br>The applicant for equipment certification, as per RSP-100, must provide a list of all antenna types that may be used with the licence-exempt transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. Licence-exempt transmitters that have received equipment certification may operate with different types of antennas. However, it is not permissible to exceed the maximum equivalent isotropically radiated power (EIRP) limits specified in the applicable standard (RSS) for the licence-exempt apparatus. Testing shall be performed using the highest gain antenna of each combination of licence-exempt transmitter and antenna type, with the transmitter output power set at the maximum level.9 When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna manufacturer. | |
| EUT Antenna: | |
| The antenna is FPC Antenna, the best case gain of the antenna is 1.57dBi, reference to the appendix II for details | |

## 11. TEST SETUP PHOTO

Reference to the appendix I for details.

## 12. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

※※※※※ **END OF REPORT** ※※※※※