CFR 47 FCC PART 15 SUBPART C

TEST REPORT

For

Smart deadbolt lock

MODEL NUMBER: H2 C20, H1 C20

REPORT NUMBER: E04A24080413F00102

ISSUE DATE: September 25, 2024

FCC ID: 2BEW6-H1C20

Prepared for

Shenzhen Fenda Smart Home Co., Ltd.

Floors 7-9, Building 2, Phase II, Fenda Industrial Park, Baoyuan Community, Shiyan Street, Bao'an District, Shenzhen, China

Prepared by

Guangdong Global Testing Technology Co., Ltd.

Room 101-105, 203-210, Building 1, No.2, Keji 8 Road, Songshan Lake Park, Dongguan city, Guangdong, People's Republic of China, 523808

This report shall not be reproduced, except in full, without the written approval of Guangdong Global Testing Technology Co., Ltd.

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	September 25, 2024	Initial Issue	

Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
Antenna Requirement	N/A	FCC Part 15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	ANSI C63.10-2013, Clause 6.2	FCC Part 15.207	Pass
Conducted Output Power	ANSI C63.10-2013, Clause 11.9.1.3	FCC Part 15.247 (b)(3)	Pass
6dB Bandwidth	ANSI C63.10-2013, Clause 11.8.1	FCC Part 15.247 (a)(2)	Pass
Power Spectral Density	ANSI C63.10-2013, Clause 11.10.2	FCC Part 15.247 (e)	Pass
Conducted Band edge and spurious emission	ANSI C63.10-2013, Clause 11.11	FCC Part 15.247(d)	Pass
Radiated Band edge and Spurious Emission	ANSI C63.10-2013, Clause 11.11 & Clause 11.12	FCC Part 15.247 (d) FCC Part 15.205/15.209	Pass
Duty Cycle	ANSI C63.10-2013, Clause 11.6	None; for reporting purposes only.	Pass

*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.
*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART C> when <Accuracy Method> decision rule is applied.

CONTENTS

1. ATTESTATION OF TEST RESULTS 5

2. TEST METHODOLOGY 6

3. FACILITIES AND ACCREDITATION 6

4. CALIBRATION AND UNCERTAINTY 7

4.1. MEASURING INSTRUMENT CALIBRATION 7

4.2. MEASUREMENT UNCERTAINTY 7

5. EQUIPMENT UNDER TEST 8

5.1. DESCRIPTION OF EUT 8

5.2. CHANNEL LIST 8

5.3. Maximum Conducted Output Power 9

5.4. TEST CHANNEL CONFIGURATION 9

5.5. THE WORSE CASE POWER SETTING PARAMETER 9

5.6. DESCRIPTION OF AVAILABLE ANTENNAS 9

5.7. SUPPORT UNITS FOR SYSTEM TEST 10

5.8. SETUP DIAGRAM 10

6. MEASURING EQUIPMENT AND SOFTWARE USED 11

7. ANTENNA PORT TEST RESULTS 13

7.1. Conducted Output Power 13

7.2. 6dB Bandwidth 14

7.3. Power Spectral Density 16

7.4. Conducted Band edge and spurious emission 17

7.5. Duty Cycle 19

8. RADIATED TEST RESULTS 20

9. ANTENNA REQUIREMENT 37

10. AC POWER LINE CONDUCTED EMISSION 38

11. TEST DATA - Appendix B 41

APPENDIX: PHOTOGRAPHS OF TEST CONFIGURATION 73

APPENDIX: PHOTOGRAPHS OF THE EUT 74

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name:	Shenzhen Fenda Smart Home Co., Ltd.
Address:	Floors 7-9, Building 2, Phase II, Fenda Industrial Park, Baoyuan Community, Shiyan Street, Bao'an District, Shenzhen, China

Manufacturer Information

Company Name:	Shenzhen Fenda Smart Home Co., Ltd.
Address:	Floors 7-9, Building 2, Phase II, Fenda Industrial Park, Baoyuan Community, Shiyan Street, Bao'an District, Shenzhen, China

EUT Information

Product Description:	Smart deadbolt lock
Model:	H1 C20
Serial Model:	H2 C20
Brand:	N/A
Sample Received Date:	August 20, 2024
Sample Status:	Normal
Sample ID:	A24080413 001
Date of Tested:	August 28, 2024 to September 11, 2024

APPLICABLE STANDARDS	
STANDARD	**TEST RESULTS**
CFR 47 FCC PART 15 SUBPART C	**Pass**

Prepared By:

Win Huang

Project Engineer

Checked By:

Alan He

Laboratory Leader

Approved By:

Shawn Wen

Laboratory Manager

Guangdong Global Testing Technology Co., Ltd. GTG CERTIFICATE

2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART C

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	**A2LA (Certificate No.: 6947.01)** Guangdong Global Testing Technology Co., Ltd. has been assessed and proved to be in compliance with A2LA. **FCC (FCC Designation No.: CN1343)** Guangdong Global Testing Technology Co., Ltd. has been recognized to perform compliance testing on equipment subject to Supplier's Declaration of Conformity (SDoC) and Certification rules **ISED (Company No.: 30714)** Guangdong Global Testing Technology Co., Ltd. has been registered and fully described in a report filed with ISED. The Company Number is 30714 and the test lab Conformity Assessment Body Identifier (CABID) is CN0148.

Note: All tests measurement facilities use to collect the measurement data are located at Room 101-105, 203-210, Building 1, No.2, Keji 8 Road, Songshan Lake Park, Dongguan city, Guangdong, People’s Republic of China, 523808

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Items	k	Uncertainty
DTS Bandwidth	1.96	±9.2 PPM
20dB Emission Bandwidth	1.96	±9.2 PPM
Carrier Frequency Separation	1.96	±9.2 PPM
Time of Occupancy	1.96	±0.57%
Conducted Output Power	1.96	±1.5 dB
Power Spectral Density Level	1.96	±1.9 dB
Conducted Spurious Emission	1.96	9 kHz-30 MHz: ± 0.95 dB 30 MHz-1 GHz: ± 1.5 dB 1GHz-12.75GHz: ± 1.8 dB 12.75 GHz-26.5 GHz: ± 2.1dB
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.		

Test Item	Measurement Frequency Range	K	U(dB)
Conducted emissions from the AC mains power ports (AMN)	150 kHz ~ 30 MHz	2	3.37
Radiated emissions	9 kHz ~ 30 MHz	2	4.16
Radiated emissions	30 MHz ~ 1 GHz	2	3.79
Radiated emissions	1 GHz ~ 18 GHz	2	5.62
Radiated emissions	18 GHz ~ 40 GHz	2	5.54
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.			

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name		Smart deadbolt lock
Model		H1 C20
Series Model		H2 C20
Hardware Version		V1.1
Software Version		2.0.4
Ratings		Battery 7.4V
Power Supply	AC	120V/60Hz From Adapter
	DC	Battery 7.4V

Frequency Band:	2400 MHz to 2483.5 MHz
Frequency Range:	2402 MHz to 2480 MHz
Bluetooth Version:	Bluetooth 5.0
Bluetooth Mode:	Bluetooth LE
Type of Modulation:	GFSK
Number of Channels:	40
Channel Separation:	2 MHz
Maximum Peak Power:	0.72 dBm
Antenna Type:	Internal Antenna
Antenna Gain:	4.32 dBi
Normal Test Voltage:	5 Vdc
EUT Test software:	FCC_assist_v1.1.5

5.2. CHANNEL LIST

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	11	2424	22	2446	33	2468
1	2404	12	2426	23	2448	34	2470
2	2406	13	2428	24	2450	35	2472
3	2408	14	2430	25	2452	36	2474
4	2410	15	2432	26	2454	37	2476
5	2412	16	2434	27	2456	38	2478
6	2414	17	2436	28	2458	39	2480
7	2416	18	2438	29	2460	/	/
8	2418	19	2440	30	2462	/	/
9	2420	20	2442	31	2464	/	/
10	2422	21	2444	32	2468	/	/

5.3. MAXIMUM CONDUCTED OUTPUT POWER

Test Mode	Frequency (MHz)	Channel Number	Maximum Peak Output Power (dBm)
LE 1M	2402 ~ 2480	0-39[40]	0.36
LE 2M	2402 ~ 2480	0-39[40]	0.72

5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
LE 1M	CH 0(Low Channel), CH 19(MID Channel), CH 39(High Channel)	2402 MHz, 2440 MHz, 2480 MHz
LE 2M	CH 0(Low Channel), CH 19(MID Channel), CH 39(High Channel)	2402 MHz, 2440 MHz, 2480 MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band				
Test Software Version		FCC_assist_v1.1.5		
Modulation Type	Transmit Antenna Number	Test Software setting value		
		CH 0	CH 19	CH 39
GFSK(1Mbps)	1	default	default	default
GFSK(2Mbps)	1	default	default	default

5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2402-2480	Internal antenna	4.32 dBi

Test Mode	Transmit and Receive Mode	Description
LE 1M	☒1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.
LE 2M	☒1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.
Note:		

5.7. SUPPORT UNITS FOR SYSTEM TEST

The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	PC	Lenovo	B4650-D002	M90601U3	GTG Support
E-2	Adapter	Xiaomi	MDY-11-EX	N/A	GTG Support

The following cables were used to form a representative test configuration during the tests.

Item	Type of cable	Shielded Type	Ferrite Core	Length
C-1	USB cable	Shielded	without ferrite	0.33 m

5.8. SETUP DIAGRAM

AC conducted emission



Radiated Emission:

RF conducted:

6. MEASURING EQUIPMENT AND SOFTWARE USED

Test Equipment of Conducted RF					
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Last Cal.**	**Due Date**
Spectrum Analyzer	Rohde & Schwarz	FSV40	102257	2023/09/18	2024/09/17
Spectrum Analyzer	KEYSIGHT	N9020A	MY51285127	2023/09/18	2024/09/17
EXG Analog Signal Generator	KEYSIGHT	N5173B	MY61253075	2023/09/18	2024/09/17
Vector Signal Generator	Rohde & Schwarz	SMM100A	101899	2023/09/18	2024/09/17
RF Control box	MWRF-test	MW100-RFCB	MW220926GTG	2023/09/18	2024/09/17
Wideband Radio Communication Tester	Rohde & Schwarz	CMW270	102792	2023/09/18	2024/09/17
Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	103235	2023/09/18	2024/09/17
temperature humidity chamber	Espec	SH-241	SH-241-2014	2023/09/18	2024/09/17
RF Test Software	MWRF-test	MTS8310E (Ver. V2/0)	N/A	N/A	N/A

Test Equipment of Radiated emissions below 1GHz					
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Last Cal.**	**Due Date**
3m Semi-anechoic Chamber	ETS	9m*6m*6m	Q2146	2022/08/30	2025/08/29
EMI Test Receiver	Rohde & Schwarz	ESCI3	101409	2023/09/18	2024/09/17
Spectrum Analyzer	KEYSIGHT	N9020A	MY51283932	2023/09/18	2024/09/17
Pre-Amplifier	HzEMC	HPA-9K0130	HYPA21001	2023/09/18	2024/09/17
Biconilog Antenna	Schwarzbeck	VULB 9168	01315	2022/10/10	2025/10/09
Biconilog Antenna	ETS	3142E	00243646	2022/03/23	2025/03/22
Loop Antenna	ETS	6502	243668	2022/03/30	2025/03/29
Test Software	Farad	EZ-EMC (Ver.FA-03A2 RE)	N/A	N/A	N/A

Test Equipment of Radiated emissions above 1GHz					
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Last Cal.**	**Due Date**
3m Semi-anechoic Chamber	ETS	9m*6m*6m	Q2149	2022/08/30	2025/08/29
Spectrum Analyzer	Rohde & Schwarz	FSV40	101413	2023/09/18	2024/09/17
Spectrum Analyzer	KEYSIGHT	N9020A	MY51283932	2023/09/18	2024/09/17
Pre-Amplifier	A-INFO	HPA-1G1850	HYPA21003	2023/09/18	2024/09/17
Horn antenna	A-INFO	3117	246069	2022/03/11	2025/03/10
Pre-Amplifier	ZKJC	HPA-184057	HYPA21004	2023/09/18	2024/09/17

Horn antenna	ZKJC	3116C	246265	2022/03/29	2025/03/28
Test Software	Farad	EZ-EMC (Ver.FA-03A2 RE+)	N/A	N/A	N/A

Test Equipment of Conducted emissions					
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Last Cal.**	**Due Date**
Shielded Room	CHENG YU	8m*5m*4m	N/A	2022/10/29	2025/10/28
EMI Test Receiver	Rohde & Schwarz	ESR3	102647	2023/09/18	2024/09/17
LISN/AMN	Rohde & Schwarz	ENV216	102843	2023/09/18	2024/09/17
NNLK 8129 RC	Schwarzbeck	NNLK 8129 RC	5046	2023/09/18	2024/09/17
Test Software	Farad	EZ-EMC (Ver. EMC-con-3A1 1+)	N/A	N/A	N/A

7. ANTENNA PORT TEST RESULTS

7.1. CONDUCTED OUTPUT POWER

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3)	Peak Conduct Output Power	1 watt or 30 dBm	2400-2483.5

TEST PROCEDURE

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).
Measure peak emission level, the indicated level is the peak output power, after any corrections for external attenuators and cables.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.4℃	Relative Humidity	43%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix B

7.2. 6DB BANDWIDTH

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2)	6 dB Bandwidth	≥ 500 kHz	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.

Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission
Detector	Peak
RBW	For 6 dB Bandwidth: 100 kHz
VBW	For 6 dB Bandwidth: ≥3 × RBW
Trace	Max hold
Sweep	Auto couple

a) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.4℃	Relative Humidity	43%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix B

7.3. POWER SPECTRAL DENSITY

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.10.

Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	PEAK
RBW	3 kHz ≤ RBW ≤ 100 kHz
VBW	≥3 × RBW
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.
If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.4℃	Relative Humidity	43%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix B

7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

CFR 47 FCC Part15 (15.247) Subpart C		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d)	Conducted Bandedge and Spurious Emissions	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

LIMITS

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyser and use the following settings for reference level measurement:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	≥3 × RBW
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.
Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	≥3 × RBW
measurement points	≥span/RBW
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.4℃	Relative Humidity	43%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix B

7.5. DUTY CYCLE

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.4℃	Relative Humidity	43%
Atmosphere Pressure	101kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix B

8. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
[1]0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	([2])
13.36-13.41			

Note: [1]Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.
[2]Above 38.6c

TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyser

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.

2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.

3. The EUT was placed on a turntable with 80 cm above ground.

4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.

5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.

6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.

7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

8. measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω. For example, the measurement frequency X KHz resulted in a level of Y dBuV/m, which is equivalent to Y-51.5 = Z dBuA/m, W dB, to the limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyser

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.

2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

3. The EUT was placed on a turntable with 80 cm above ground.

4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.

5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1G

The setting of the spectrum analyser

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.

2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

3. The EUT was placed on a turntable with 1.5 m above ground.

4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.

5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.

6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1.ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

TEST SETUP







TEST ENVIRONMENT

Temperature	24.1℃	Relative Humidity	53%
Atmosphere Pressure	101kPa		

TEST RESULTS

- Undesirable radiated Spurious Emission below 1GHz (30MHz to 1GHz)

The worst result as bellow:

Mode:	BLE 1M 2402
Power:	DC 5V
TE:	Big
Date	2024/09/05
T/A/P	24.3℃/52% /101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	131.850	43.21	-24.1	19.11	43.50	24.39	PK+	V
2	227.880	37.72	-20.4	17.32	46.00	28.68	PK+	V
3	590.660	31.97	-	21.85	46.00	24.15	PK+	V
4	663.410	31.86	-8.25	23.61	46.00	22.39	PK+	V
5	762.350	32.21	-7.3	24.91	46.00	21.09	PK+	V
6	944.710	31.69	-3.33	28.36	46.00	17.64	PK+	V

Mode:	BLE 1M 2402
Power:	DC 5V
TE:	Big
Date	2024/09/05
T/A/P	24.3℃/52% /101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	229.820	38.33	-20.29	18.04	46.00	27.96	PK+	H
2	273.470	37.80	-18.77	19.03	46.00	26.97	PK+	H
3	378.230	34.33	-14.96	19.37	46.00	26.63	PK+	H
4	540.220	31.80	-10.25	21.55	46.00	24.45	PK+	H
5	720.640	31.51	-6.94	24.57	46.00	21.43	PK+	H
6	944.710	31.50	-3.33	28.17	46.00	17.83	PK+	H

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

- Undesirable radiated Spurious Emission Above 1GHz (1GHz to 40GHz)

The worst result as bellow:

Mode:	BLE 1M 2402
Power:	DC 5V
TE:	Big
Date	2024/09/05
T/A/P	24.3℃/52% /101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2570.000	53.41	-8.04	45.37	74.00	28.63	PK+	H
2	6045.000	51.62	-8.19	43.43	74.00	30.57	PK+	H
3	10816.500	48.75	-5.14	43.61	74.00	30.39	PK+	H
4	14382.000	47.76	-3.25	44.51	74.00	29.49	PK+	H
5	15990.000	47.91	-2.15	45.76	74.00	28.24	PK+	H
6	17697.000	45.65	0.2	45.85	74.00	28.15	PK+	H

Mode:	BLE 1M 2402
Power:	DC 5V
TE:	Big
Date	2024/09/05
T/A/P	24.3℃/52% /101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2190.000	57.41	-9.16	48.25	74.00	25.75	PK+	V
2	3726.000	56.14	-13.65	42.49	74.00	31.51	PK+	V
3	6000.000	52.24	-8.87	43.37	74.00	30.63	PK+	V
4	9876.000	50.29	-6.81	43.48	74.00	30.52	PK+	V
5	11212.500	48.02	-4.18	43.84	74.00	30.16	PK+	V
6	17673.000	46.09	0.3	46.39	74.00	27.61	PK+	V

Mode:	BLE 1M 2440
Power:	DC 5V
TE:	Big
Date	2024/09/05
T/A/P	24.3℃/52% /101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2528.000	53.76	-8.63	45.13	74.00	28.87	PK+	V
2	6316.500	50.49	-7.69	42.80	74.00	31.20	PK+	V
3	8670.000	51.63	-8.24	43.39	74.00	30.61	PK+	V
4	10740.000	49.10	-5.16	43.94	74.00	30.06	PK+	V
5	16734.000	46.70	-1.04	45.66	74.00	28.34	PK+	V
6	17694.000	45.88	0.21	46.09	74.00	27.91	PK+	V

Mode:	BLE 1M 2440
Power:	DC 5V
TE:	Big
Date	2024/09/05
T/A/P	24.3℃/52% /101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2844.000	53.50	-7.98	45.52	74.00	28.48	PK+	H
2	5449.500	52.76	-9.84	42.92	74.00	31.08	PK+	H
3	9327.000	49.39	-7.15	42.24	74.00	31.76	PK+	H
4	11443.500	48.25	-4.47	43.78	74.00	30.22	PK+	H
5	16249.500	46.05	-0.56	45.49	74.00	28.51	PK+	H
6	17700.000	45.81	0.18	45.99	74.00	28.01	PK+	H

Mode:	BLE 1M 2480
Power:	DC 5V
TE:	Big
Date	2024/09/05
T/A/P	24.3℃/52% /101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2524.000	55.79	-8.59	47.20	74.00	26.80	PK+	H
2	5935.500	51.79	-8.85	42.94	74.00	31.06	PK+	H
3	8514.000	50.67	-8.25	42.42	74.00	31.58	PK+	H
4	11278.500	47.90	-4.26	43.64	74.00	30.36	PK+	H
5	16686.000	45.45	-0.49	44.96	74.00	29.04	PK+	H
6	17677.500	45.24	0.3	45.54	74.00	28.46	PK+	H

Mode:	BLE 1M 2480
Power:	DC 5V
TE:	Big
Date	2024/09/05
T/A/P	24.3℃/52% /101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2200.000	54.51	-9.25	45.26	74.00	28.74	PK+	V
2	6327.000	51.36	-7.91	43.45	74.00	30.55	PK+	V
3	8992.500	51.83	-7.93	43.90	74.00	30.10	PK+	V
4	10819.500	49.08	-5.13	43.95	74.00	30.05	PK+	V
5	16254.000	46.57	-0.68	45.89	74.00	28.11	PK+	V
6	17724.000	47.09	-0.34	46.75	74.00	27.25	PK+	V

Other harmonics emissions are lower than 20dB below the allowable limit.

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

- Band Edge

Mode:	BLE 1M 2402
Power:	DC 5V
TE:	Big
Date	2024/09/05
T/A/P	24.3℃/52% /101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2341.200	23.45	22.66	46.11	74.00	27.89	PK+	V
2	2390.080	21.91	22.72	44.63	74.00	29.37	PK+	V

Mode:	BLE 1M 2402
Power:	DC 5V
TE:	Big
Date	2024/09/05
T/A/P	24.3℃/52% /101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2383.840	21.20	22.6	43.80	74.00	30.20	PK+	H
2	2390.080	19.90	22.72	42.62	74.00	31.38	PK+	H

Mode:	BLE 1M 2480
Power:	DC 5V
TE:	Big
Date	2024/09/05
T/A/P	24.3℃/52% /101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2483.360	20.23	23.15	43.38	74.00	30.62	PK+	V
2	2542.880	22.82	23.22	46.04	74.00	27.96	PK+	V

Mode:	BLE 1M 2480
Power:	DC 5V
TE:	Big
Date	2024/09/05
T/A/P	24.3℃/52% /101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	2483.360	20.33	23.15	43.48	74.00	30.52	PK+	H
2	2492.160	22.12	23.13	45.25	74.00	28.75	PK+	H

Note:

1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

9. ANTENNA REQUIREMENT

REQUIREMENT

Please refer to FCC §15.203
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)
The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DESCRIPTION

Pass

10. AC POWER LINE CONDUCTED EMISSION

LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

TEST PROCEDURE

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013.Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST SETUP



TEST ENVIRONMENT

Temperature	26℃	Relative Humidity	54%
Atmosphere Pressure	101kPa		

TEST RESULTS



Phase: N	Mode: BLE-1M-2402MHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1814	18.91	9.80	28.71	64.42	-35.71	QP
2	0.1814	0.56	9.80	10.36	54.42	-44.06	AVG
3	0.2310	17.07	9.83	26.90	62.41	-35.51	QP
4	0.2310	2.25	9.83	12.08	52.41	-40.33	AVG
5	4.7220	25.91	9.81	35.72	56.00	-20.28	QP
6	4.7220	-0.35	9.81	9.46	46.00	-36.54	AVG
7	5.6624	21.66	9.79	31.45	60.00	-28.55	QP
8	5.6624	-1.82	9.79	7.97	50.00	-42.03	AVG
9	7.3680	21.57	9.77	31.34	60.00	-28.66	QP
10	7.3680	-1.09	9.77	8.68	50.00	-41.32	AVG
11	20.7420	14.61	10.25	24.86	60.00	-35.14	QP
12	20.7420	-4.83	10.25	5.42	50.00	-44.58	AVG



Phase: L1	Mode: BLE-1M-2402MHz

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1641	21.45	9.90	31.35	65.25	-33.90	QP
2	0.1641	2.01	9.90	11.91	55.25	-43.34	AVG
3	0.3539	14.81	9.82	24.63	58.87	-34.24	QP
4	0.3539	-2.63	9.82	7.19	48.87	-41.68	AVG
5	6.8412	19.46	10.14	29.60	60.00	-30.40	QP
6	6.8412	-2.59	10.14	7.55	50.00	-42.45	AVG
7	8.3671	21.20	10.79	31.99	60.00	-28.01	QP
8	8.3671	0.01	10.79	10.80	50.00	-39.20	AVG
9	9.3518	28.25	11.25	39.50	60.00	-20.50	QP
10	9.3518	2.36	11.25	13.61	50.00	-36.39	AVG
11	24.5291	18.25	12.70	30.95	60.00	-29.05	QP
12	24.5291	-3.69	12.70	9.01	50.00	-40.99	AVG

Note: 1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

11. TEST DATA - Appendix B

Duty Cycle

Condition	Mode	Frequency (MHz)	Antenna	On Time (ms)	Period (ms)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)	Final settingFor VBW (kHz)
NVNT	BLE 1M	2402	Ant1	2.13	2.5	85.2	0.7	0.47	1
NVNT	BLE 1M	2440	Ant1	2.13	2.5	85.2	0.7	0.47	1
NVNT	BLE 1M	2480	Ant1	2.13	2.5	85.2	0.7	0.47	1
NVNT	BLE 2M	2402	Ant1	1.07	2.5	42.8	3.69	0.93	1
NVNT	BLE 2M	2440	Ant1	1.07	2.5	42.8	3.69	0.93	1
NVNT	BLE 2M	2480	Ant1	1.07	2.5	42.8	3.69	0.93	1

Test Graphs

Duty Cycle NVNT BLE 1M 2402MHz Ant1



Date: 31.AUG.2024 17:06:45

Duty Cycle NVNT BLE 1M 2440MHz Ant1



Date: 31.AUG.2024 17:08:10

Duty Cycle NVNT BLE 1M 2480MHz Ant1



Date: 31.AUG.2024 17:09:43

Duty Cycle NVNT BLE 2M 2402MHz Ant1



Date: 4.SEP.2024 08:57:34

Duty Cycle NVNT BLE 2M 2440MHz Ant1



Date: 4.SEP.2024 08:55:51

Duty Cycle NVNT BLE 2M 2480MHz Ant1



Date: 4.SEP.2024 08:53:18

Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	0.34	0	0.34	30	Pass
NVNT	BLE 1M	2440	Ant1	0.36	0	0.36	30	Pass
NVNT	BLE 1M	2480	Ant1	0.26	0	0.26	30	Pass
NVNT	BLE 2M	2402	Ant1	0.72	0	0.72	30	Pass
NVNT	BLE 2M	2440	Ant1	0.59	0	0.59	30	Pass
NVNT	BLE 2M	2480	Ant1	0.36	0	0.36	30	Pass

Test Graphs

Power NVNT BLE 1M 2402MHz Ant1



Power NVNT BLE 1M 2440MHz Ant1



Power NVNT BLE 1M 2480MHz Ant1



Date: 31.AUG.2024 17:09:51

Power NVNT BLE 2M 2402MHz Ant1



Date: 4.SEP.2024 08:56:28

Power NVNT BLE 2M 2440MHz Ant1



Date: 4.SEP.2024 08:54:08

Power NVNT BLE 2M 2480MHz Ant1



Date: 4.SEP.2024 08:52:24

-6dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	Ant1	0.65	0.5	Pass
NVNT	BLE 1M	2440	Ant1	0.66	0.5	Pass
NVNT	BLE 1M	2480	Ant1	0.65	0.5	Pass
NVNT	BLE 2M	2402	Ant1	1.22	0.5	Pass
NVNT	BLE 2M	2440	Ant1	1.21	0.5	Pass
NVNT	BLE 2M	2480	Ant1	1.22	0.5	Pass

Test Graphs

-6dB Bandwidth NVNT BLE 1M 2402MHz Ant1



-6dB Bandwidth NVNT BLE 1M 2440MHz Ant1



-6dB Bandwidth NVNT BLE 1M 2480MHz Ant1



Date: 31.AUG.2024 17:10:08

-6dB Bandwidth NVNT BLE 2M 2402MHz Ant1



Date: 4.SEP.2024 08:58:46

-6dB Bandwidth NVNT BLE 2M 2440MHz Ant1



-6dB Bandwidth NVNT BLE 2M 2480MHz Ant1



Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	BLE 1M	2402	Ant1	1.026
NVNT	BLE 1M	2440	Ant1	1.029
NVNT	BLE 1M	2480	Ant1	1.031
NVNT	BLE 2M	2402	Ant1	2.063
NVNT	BLE 2M	2440	Ant1	2.063
NVNT	BLE 2M	2480	Ant1	2.056

Test Graphs

OBW NVNT BLE 1M 2402MHz Ant1



OBW NVNT BLE 1M 2440MHz Ant1



OBW NVNT BLE 1M 2480MHz Ant1



Date: 31.AUG.2024 17:10:00

OBW NVNT BLE 2M 2402MHz Ant1



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.401954 GHz	-3.97 dBm		
T1		1	2.400966603 GHz	-20.03 dBm	Occ Bw	2.062793721 MHz
T2		1	2.403029397 GHz	-17.81 dBm		

Date: 4.SEP.2024 08:58:14

OBW NVNT BLE 2M 2440MHz Ant1



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.4399515 GHz	-4.07 dBm		
T1		1	2.438964604 GHz	-20.12 dBm	Occ Bw	2.062793721 MHz
T2		1	2.441027397 GHz	-20.17 dBm		

Date: 4.SEP.2024 08:59:14

OBW NVNT BLE 2M 2480MHz Ant1



Date: 4.SEP.2024 08:52:05

Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Duty Factor (dB)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	BLE 1M	2402	Ant1	-16.93	0	-16.93	8	Pass
NVNT	BLE 1M	2440	Ant1	-17.29	0	-17.29	8	Pass
NVNT	BLE 1M	2480	Ant1	-17.44	0	-17.44	8	Pass
NVNT	BLE 2M	2402	Ant1	-20.25	0	-20.25	8	Pass
NVNT	BLE 2M	2440	Ant1	-20.32	0	-20.32	8	Pass
NVNT	BLE 2M	2480	Ant1	-20.61	0	-20.61	8	Pass

Test Graphs

PSD NVNT BLE 1M 2402MHz Ant1



PSD NVNT BLE 1M 2440MHz Ant1



PSD NVNT BLE 1M 2480MHz Ant1



Date: 31.AUG.2024 17:10:13

PSD NVNT BLE 2M 2402MHz Ant1



Date: 4.SEP.2024 08:56:50

PSD NVNT BLE 2M 2440MHz Ant1



Date: 4.SEP.2024 08:54:30

PSD NVNT BLE 2M 2480MHz Ant1



Date: 4.SEP.2024 08:52:37

Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-47.54	-20	Pass
NVNT	BLE 1M	2480	Ant1	-54.72	-20	Pass
NVNT	BLE 2M	2402	Ant1	-35.89	-20	Pass
NVNT	BLE 2M	2480	Ant1	-54.75	-20	Pass

Test Graphs

Band Edge NVNT BLE 1M 2402MHz Ant1 Ref



Date: 31.AUG.2024 17:07:20

Band Edge NVNT BLE 1M 2402MHz Ant1 Emission



Date: 31.AUG.2024 17:07:23

Band Edge NVNT BLE 1M 2480MHz Ant1 Ref



Date: 31.AUG.2024 17:10:17

Band Edge NVNT BLE 1M 2480MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.48005 GHz	-0.75 dBm		
M2		1	2.4835 GHz	-57.21 dBm		
M3		1	2.4848 GHz	-55.75 dBm		

Date: 31.AUG.2024 17:10:20

Band Edge NVNT BLE 2M 2402MHz Ant1 Ref



Date: 4.SEP.2024 08:56:54

Band Edge NVNT BLE 2M 2402MHz Ant1 Emission



Date: 4.SEP.2024 08:56:58

Band Edge NVNT BLE 2M 2480MHz Ant1 Ref



Date: 4.SEP.2024 08:52:42

Band Edge NVNT BLE 2M 2480MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.48045 GHz	-0.78 dBm		
M2		1	2.4835 GHz	-56.67 dBm		
M3		1	2.4853 GHz	-56.03 dBm		

Date: 4.SEP.2024 08:52:45

Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-49.59	-20	Pass
NVNT	BLE 1M	2440	Ant1	-49.75	-20	Pass
NVNT	BLE 1M	2480	Ant1	-48.95	-20	Pass
NVNT	BLE 2M	2402	Ant1	-48.98	-20	Pass
NVNT	BLE 2M	2440	Ant1	-48.31	-20	Pass
NVNT	BLE 2M	2480	Ant1	-47.89	-20	Pass

Test Graphs

Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Ref



Date: 31.AUG.2024 17:07:29

Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Emission



Date: 31.AUG.2024 17:07:45

Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Ref



Date: 31.AUG.2024 17:08:49

Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.44001 GHz	-1.27 dBm		
M2		1	17.722548 GHz	-49.69 dBm		

Date: 31.AUG.2024 17:09:04

Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Ref



Date: 31.AUG.2024 17:10:25

Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.4806 GHz	-2.69 dBm		
M2		1	6.995139 GHz	-49.43 dBm		

Date: 31.AUG.2024 17:10:40

Tx. Spurious NVNT BLE 2M 2402MHz Ant1 Ref



Date: 4.SEP.2024 08:57:02

Tx. Spurious NVNT BLE 2M 2402MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40207 GHz	-3.08 dBm		
M2		1	4.804306 GHz	-49.78 dBm		

Date: 4.SEP.2024 08:57:18

Tx. Spurious NVNT BLE 2M 2440MHz Ant1 Ref



Date: 4.SEP.2024 08:54:35

Tx. Spurious NVNT BLE 2M 2440MHz Ant1 Emission



Date: 4.SEP.2024 08:54:51

Tx. Spurious NVNT BLE 2M 2480MHz Ant1 Ref



Date: 4.SEP.2024 08:52:49

Tx. Spurious NVNT BLE 2M 2480MHz Ant1 Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47972 GHz	-7.04 dBm		
M2		1	6.973963 GHz	-49.01 dBm		

Date: 4.SEP.2024 08:53:05

APPENDIX: PHOTOGRAPHS OF TEST CONFIGURATION

Please refer to the report : E04A24080413F00101.

APPENDIX: PHOTOGRAPHS OF THE EUT

Please refer to the report : E04A24080413F00101.

END OF REPORT