

TEST REPORT

Reference No...... : WTH26D05125401W006
FCC ID : 2BEWX-SS200C
Applicant..... : Zhejiang Lingzhu Technology Co., Ltd.
Address..... : Room 302, No 1 Building Huace Center, Xihu District, Hangzhou City, Zhejiang Province, China
Manufacturer : Zhejiang Lingzhu Technology Co., Ltd.
Address : Room 302, No 1 Building Huace Center, Xihu District, Hangzhou City, Zhejiang Province, China
Factory : SHENZHEN GIEC DIGITAL CO.,LTD
Address : 1st & 3rd Building, No. 26 Puzai Road, Pingdi, Longgang District, Shenzhen, China.
Product..... : AI Speaker
Model(s) : SS200, SS200-C, SS200-D
Standards..... : FCC 47CFR Part 2 Subpart J Section 2.1091
Date of Receipt Sample : 2026-05-11
Date of Test : 2026-05-12 to 2026-06-11
Date of Issue..... : 2026-06-24
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Testing Group Co., Ltd.

Address: No. 77, Houjie Section, Guantai Road, Houjie Town, Dongguan City, Guangdong, China

Tel: +86-769-2267 6998

Fax: +86-769-2267 6828

Compiled by:

Estel Qian

Estel Qian / Project Engineer

Approved by:

Deval Qin


Deval Qin / Designated Reviewer

2. Contents

	Page
1 COVER PAGE.....	1
2. CONTENTS.....	2
3. REVISION HISTORY.....	3
4. GENERAL INFORMATION.....	4
4.1. GENERAL DESCRIPTION OF E.U.T.....	4
4.2. DETAILS OF E.U.T.	4
4.3. TEST FACILITY	5
4.4. SUBCONTRACTED	5
4.5. ABNORMALITIES FROM STANDARD CONDITIONS	5
5. TEST SUMMARY	6
6. RF EXPOSURE.....	7
6.1. REQUIREMENTS	7
6.2. THE PROCEDURES / LIMIT	7
6.3. MPE CALCULATION METHOD.....	8
6.4. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION.....	8

3. Revision History

Test Report No.	Date of Receipt Sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTH26D05125401W006	2026-05-11	2026-05-12 to 2026-06-11	2026-06-24	Original	-	Valid

4. General Information

4.1. General Description of E.U.T.

Product:	AI Speaker
Model(s):	SS200, SS200-C, SS200-D
Model Description:	Only the model names are different. The model SS200-C was tested in this report.
Test Sample No.:	1-1/1
Bluetooth Version:	Tuya Module: V5.4 JL Module: V6.0
Wi-Fi Specification:	2.4G-802.11b/g/ n(HT20/40)/ax(HE20/40)
Hardware Version:	DMSS200-CV1.3
Software Version:	V2.6.0

4.2. Details of E.U.T.

Operation Frequency:	2.4G Wi-Fi: 802.11b/g/n HT20/ax HE20: 2412~2462MHz 802.11n HT40/ax HE40: 2422~2452MHz Bluetooth LE/ Bluetooth: 2402~2480MHz
Max. RF output power:	Tuya Module: 2.4G Wi-Fi: 18.81dBm LE 125k: 4.78dBm, LE 500k: 4.78dBm, LE 1M: 6.92dBm JL Module: LE 1M: 7.86dBm, LE 2M: 8.14dBm Bluetooth: 9.05dBm
Type of Modulation:	2.4G Wi-Fi: DSSS, OFDM, OFDMA Bluetooth LE: GFSK Bluetooth: GFSK, $\pi/4$ DQPSK, 8DPSK
Antenna installation:	Tuya Module 2.4G Wi-Fi/ Bluetooth LE: FPC Antenna JL Module Bluetooth LE/ Bluetooth: PCB Antenna
Antenna Gain:	Tuya Module 2.4G Wi-Fi/ Bluetooth LE: 3.89dBi JL Module Bluetooth LE/ Bluetooth: -0.48dBi

Note:

#: The antenna gain is provided by the applicant, and the applicant should be responsible for its authenticity, WALTERK lab has not verified the authenticity of its information.

Ratings:	Input: DC 5V=2A
Adapter:	Model: DCT10W050200US-C1 Input: 100-240V~, 50/60Hz, 0.3A Output: 5.0V=2.0A Manufacturer: Zhuzhou Dachuan Electronic Technology Co.,Ltd.

4.3. Test Facility

The test facility has a test site registered with the following organizations:

ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.

Waltek Testing Group Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files.

Registration number 7760A, October 15, 2016.

FCC Designation No.: CN1201. Test Firm Registration No.: 523476.

Waltek Testing Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration number 523476, September 10, 2019.

4.4. Subcontracted

Whether parts of tests for the product have been subcontracted to other labs:

☐ Yes ☒ No

If Yes, list the related test items and lab information:

Test Lab: N/A

Lab address: N/A

Test items: N/A

4.5. Abnormalities from Standard Conditions

None.

5. Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	FCC Part 2.1091	PASS

6. RF Exposure

Test Requirement: FCC 47CFR Part 2 Subpart J Section 2.1091

Evaluation Method: FCC 47CFR Part 1 Subpart I Section 1.1310,
KDB 447498 D01 General RF Exposure Guidance v06

6.1. Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

6.2. The procedures / limit

Table 1 to § 1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

6.3. MPE Calculation Method

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = output power to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

From the peak EUT RF output power, the minimum mobile separation distance, R=20cm, as well as the gain of the used antenna, the RF power density can be obtained

6.4. Radio Frequency Radiation Exposure Evaluation

Band	Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (mW/cm ²)	Limit mW/cm ²)
2.4G Wi-Fi (Tuya Module)	3.89	2.45	18.81	76.03	0.037040	1.0
Bluetooth LE (JL Module)	-0.48	1.00	8.14	6.52	0.001161	1.0
Bluetooth LE (Tuya Module)	3.89	2.45	6.92	4.92	0.002397	1.0
Bluetooth (JL Module)	-0.48	1.00	9.05	8.04	0.001431	1.0

Simultaneous Transmission

Mode	Power Density (mW/cm ²)	Limit (mW/cm ²)
2.4G Wi-Fi+Bluetooth LE+ Bluetooth	0.042029	1.0

Note: Chose the maximum power to do MPE analysis.

Conclusion:

RF Exposure is FCC compliant.

=====End of Report=====