



MPE Report

Report No.:STS2512451H01

Issued for

Zhejiang Lingzhu Technology Co., Ltd.

Room 302, No 1 Building Huace Center, Xihu District,
Hangzhou, China

Product Name: Smart Camera

Brand Name: N/A

Model Name: SC315-WBP4

Series Model(s): SC315-WBPA, SC315-WBPB, SC315-WBP
C, SC315-WBPD, SC315-WBPE, SC315-W
BPF, SC315-WBPG

FCC ID: 2BEWXSC315P

Test Standard: FCC 47CFR §2.1091

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the ShenZhen STS Test Services Co., Ltd.

**TEST REPORT****Applicant's Name**: Zhejiang Lingzhu Technology Co., Ltd.

Address: Room 302, No 1 Building Huace Center, Xihu District, Hangzhou, China

Manufacturer's Name: Zhejiang Lingzhu Technology Co., Ltd.

Address: Room 302, No 1 Building Huace Center, Xihu District, Hangzhou, China

Product Description

Product Name: Smart Camera

Brand Name: N/A

Model Name: SC315-WBP4

Series Model(s): SC315-WBPA, SC315-WBPB, SC315-WBPC, SC315-WBPD, SC315-WBPE, SC315-WBPF, SC315-WBPG

Test Standards: FCC 47CFR §2.1091
447498 D01 Interim General RF Exposure Guidance v06

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the ShenZhen STS Test Services Co., Ltd.

Date of Test

Date of receipt of test item 2025-12-02

Date (s) of performance of tests 2025-12-02 to 2025-12-17

Date of Issue 2025-12-17

Test Result **Pass**

Testing Engineer :

Aaron Bu

(Aaron Bu)

Technical Manager :

Skylar Li

(Skylar Li)

Authorized Signatory :

Bovey Yang

(Bovey Yang)





TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF THE EUT	5
1.2 TEST FACTORY	6
2. FCC 47CFR §2.1091 REQUIREMENT	6
2.1 TEST STANDARDS	6
2.2 LIMIT	6
2.3 TEST RESULT	8

**Revision History**

Rev.	Issue Date	Report No.	Effect Page	Contents
00	2025-12-17	STS2512451H01	ALL	Initial Issue



1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF THE EUT

Product Name	Smart Camera	
Brand Name	N/A	
Model Name	SC315-WBP4	
Series Model(s)	SC315-WBPA,SC315-WBPB,SC315-WBPC,SC315-WBPD,SC315-WBPE,SC315-WBPF,SC315-WBPG	
Model Difference	The main model and subsequent models tested in this test differ only in naming and color. All other aspects, including materials, other manufacturing processes, circuit design, and manufacturers, are exactly the same. We finally decided on the SC315-WBP4 as the test model.	
Product Description	The EUT is Smart Camera	
	Operation Frequency:	2402~2480 MHz
	Modulation Type:	GFSK
	Radio Technology:	BLE
	Bluetooth Configuration:	BLE(Support 1M, 2M)
	Number Of Channel:	40
	Antenna Type:	Internal antenna
	Antenna Gain (dBi)	0.26
	Operation Frequency:	802.11b/g/n 20: 2412~2462 MHz 802.11n40:2422~2452MHz
	Modulation Type:	802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM
	Bit Rate of Transmitter:	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6Mbps 802.11n(20MHz): 65/58.5/52/39/26/19.5/13/6.5Mbps 802.11n(40MHz): 135/121.5/108/81/54/40.5/37/13.5Mbps
	Number of Channel:	802.11b/g/n20: 11CH 802.11n 40: 7CH
	Antenna Type:	Internal antenna
	Antenna Gain (dBi):	0.26
	Operation Frequency:	IEEE 802.11a/ n(HT20): 5.180GHz-5.240GHz
		IEEE 802.11n(HT40): 5.190GHz-5.230GHz
		IEEE 802.11a/ n(HT20):5.260GHz-5.320GHz
		IEEE 802.11 n(HT40): 5.270GHz-5.310GHz
		IEEE 802.11a/ n(HT20):5.500GHz-5.700GHz
		IEEE 802.11 n(HT40):5.510GHz-5.670GHz
	Operation Frequency:	IEEE 802.11a/ n(HT20):5.745GHz-5.825GHz
		IEEE 802.11 n(HT40):5.755GHz-5.795GHz



	Modulation Type:	802.11a(OFDM): BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM): BPSK,QPSK,16-QAM,64-QAM
		802.11a Support SISO 802.11n Support SISO
	Antenna Type:	Internal antenna
	Antenna Gain:	2.67 dBi
Power Rating	DC 5V/1A	
Adapter	Input: AC 100-240V,50/60Hz,0.25A Output: DC 5V/1000mA,	
Battery	N/A	
Hardware Version	N/A	
Software Version	N/A	

1.2 TEST FACTORY

SHENZHEN STS TEST SERVICES CO., LTD

Add. : 101, Building B, Zhuoke Science Park, No.190 Chongqing Road, ZhanChengShequ, Fuhai Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration Number: 625569

IC test Firm Registration Number: 12108A

A2LA Certificate No.: 4338.01

2. FCC 47CFR §2.1091 REQUIREMENT

2.1 TEST STANDARDS

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

2.2 LIMIT

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)
Limits for Occupational / controlled Exposures			
300 - 1500	--	--	F/300
3.0-30	1842/f	4.89/f	*(900/f ²)
1500 – 100000	--	--	5.0
Limits for General population / Uncontrolled Exposure			
300 - 1500	--	--	F/1500
1.34-30	824/f	2.19/f	*(180f ²)



1500 – 100000

--

--

1.0

F= Frequency in MHz

Friss Formula

Friss Transmission Formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.



2.3 TEST RESULT

Tune up

Mode	Detector	Tune up Power
BLE	PK	0±1dBm
2.4GWIFI	PK	16±1dBm
5GWIFI	PK	11±1dBm

Protocol	Fre. (GHz)	Separation distance (cm)	Max Tune up power (dBm)	ANT Gain (dBi)	Max EIRP (dBm)	Max EIRP (mW)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Ratio	Result
5GWIFI	5.550	20	12	2.67	14.67	29.31	0.0109	1	0.0109	Pass
2.4GWIFI	2.437	20	17	0.26	17.26	53.21	0.0112	1	0.0112	Pass
BLE	2.440	20	1	0.26	1.26	1.34	0.0003	1	0.0003	Pass

Multiple transmission:

$$5GWIFI+2.4GWIFI+BLE = 0.0109+0.0112+0.0003=0.0224 < 1$$

Note: 1. The Maximum power is less than the limit, complies with the exemption requirements.

2. The Bluetooth and WLAN can't simultaneous transmission at the same time.

3. ERP = EIRP - 2.15

※※※※※END OF THE REPORT※※※※※