

TEST REPORT

Applicant: NETPRISMA INC.
EUT Description: Multi-mode Smart LTE Module with Wi-Fi & Bluetooth
Model Tested: SUE200-LD
Model Covered: SUE209-LD
Brand: Vrileg
FCC ID: 2BEY3SUE200LDA
Standards: FCC 47 CFR Part 2.1091
Date of Receipt: 2025/03/03
Date of Issue: 2025/04/14

TOWE. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

the results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of the model are manufactured with identical electrical and mechanical components. All sample tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise. without written approval of TOWE, the test report shall not be reproduced except in full.



A handwritten signature in black ink, appearing to be "Huang Kun".

Huang Kun
Approved By:

A handwritten signature in black ink, appearing to be "Chen Chengfu".

Chen Chengfu
Reviewed By:

Revision History

Rev.	Issue Date	Description	Revised by
01	2025/04/14	Original	Chen Chengfu

Product Differentiation Statement

SUE209-LD shares the same hardware design and supports same bands with SUE200-LD. The only difference between the two models is the operating system. The different OS is as below:

Module	SUE200-LD	SUE209-LD
System	Android	Linux

Above changes won't impact the protocol and RF performance for all frequency bands.

So, only the test data for Model No.(SUE200-LD) was presented in the report.

Table of Contents

1	General Description	5
1.1	Lab Information.....	5
1.1.1	Testing Location	5
1.1.2	Test Facility / Accreditations	5
1.2	Client Information	5
1.2.1	Applicant.....	5
1.2.2	Manufacturer.....	5
1.3	Product Information.....	6
2	Maximum Permissible RF Exposure	7
2.1	RF Exposure Limit Introduction	7
2.2	Equations	8
3	RF Exposure Results	9
3.1	Standalone Exposure Calculations	9
3.2	Multiple Sources Exposure Calculations.....	10

1 General Description

1.1 Lab Information

1.1.1 Testing Location

These measurements tests were conducted at the Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. facility located at F401 and F101, Building E, Hongwei Industrial Zone, Liuxian 3rd Road, Bao'an District, Shenzhen, China. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014
Tel.: +86-755-27212361
Contact Email: info@towewireless.com

1.1.2 Test Facility / Accreditations

A2LA (Certificate Number: 7088.01)

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).

FCC Designation No.: CN1353

Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. has been recognized as an accredited testing laboratory. Designation Number: CN1353.

ISED CAB identifier: CN0152

Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0152

Company Number: 31000

1.2 Client Information

1.2.1 Applicant

Applicant:	NETPRISMA INC.
Address:	1301 6TH AVE, SEATTLE, WA, 98101-2304, UNITED STATES

1.2.2 Manufacturer

Manufacturer:	NETPRISMA INC.
Address:	1301 6TH AVE, SEATTLE, WA, 98101-2304, UNITED STATES

1.3 Product Information

EUT Description:	Multi-mode Smart LTE Module with Wi-Fi & Bluetooth		
Model Tested:	SUE200-LD		
Model Covered:	SUE209-LD		
Brand:	Vrileg		
Hardware Version:	R1.0		
Software Version:	SUE200LDDA1301 SUE209LDDA6001		
SN:	D1C25AM1T000076		
Antenna Type:	☒ External, ☐ Integrated		
Antenna gain:	Band	Ant0 (dBi)	Ant1 (dBi)
	LTE Band 2	/	1.8
	LTE Band 4	/	1.2
	LTE Band 5	/	0.3
	LTE Band 7	/	1.4
	LTE Band 12	/	-0.5
	LTE Band 13	/	-0.7
	LTE Band 14	/	-0.5
	LTE Band 17	/	-0.5
	LTE Band 25	/	1.8
	LTE Band 26	/	0.3
	LTE Band 41	/	1.4
	LTE Band 66	/	1.5
	LTE Band 71	/	-0.9
	Bluetooth	0.47	/
	2.4G Wi-Fi	0.47	/
	U-NII-1	-0.67	/
	U-NII-2A	-0.19	/
	U-NII-2C	1.28	/
	U-NII-3	1.1	/
Remark: The above EUT's information was declared by applicant, please refer to the specifications or user manual for more detailed description.			

2 Maximum Permissible RF Exposure

2.1 RF Exposure Limit Introduction

§1.1310 the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to RF radiation as specified in §1.1307(b).

- (1) Table 1 to § 1.1310(e)(1) sets forth limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields.

Table 1 to § 1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3~3.0	614	1.63	*(100)	≤6
3.0~30	1842/f	4.89/f	*(900/f ²)	<6
30~300	61.4	0.163	1.0	<6
300~1500			f/300	<6
1500~100000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3~1.34	614	1.63	*(100)	<30
1.34~30	824/f	2.19/f	*(180/f ²)	<30
30~300	27.5	0.073	0.2	<30
300~1500			f/1500	<30
1500~100000			1.0	<30

Note: f = frequency in MHz. * = Plane-wave equivalent power density.

- (2) Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. The phrase *fully aware* in the context of applying these exposure limits means that an exposed person has received written and/or verbal information fully explaining the potential for RF exposure resulting from his or her employment. With the exception of transient persons, this phrase also means that an exposed person has received appropriate training regarding work practices relating to controlling or mitigating his or her exposure. In situations when an untrained person is transient through a location where occupational/controlled limits apply, he or she must be made aware of the potential for exposure and be supervised by trained personnel pursuant to § 1.1307(b)(2) of this part where use of time averaging is required to ensure compliance with the general population exposure limit. The phrase exercise control means that an exposed person is allowed and also knows how to reduce or avoid exposure by administrative or engineering work practices, such as use of personal protective equipment or time averaging of exposure.
- (3) General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure. For example, RF sources intended for consumer use shall be subject to the limits for general population/uncontrolled exposure in this section.

The MPE was calculated at **20cm** to show compliance with the power density limit.

2.2 Equations

Power Density is given by:

$$S = \frac{\text{EIRP}}{4\pi R^2}$$

Where:

S = Power density in mW/cm²

EIRP= Equivalent isotropic Radiated power in mW

R = Distance from transmitting antenna in cm

Power density in units of mW/cm² is converted to units of W/m² by multiplying by 10.

Distance:

$$R = \sqrt{\frac{\text{EIRP}}{4\pi S}}$$

Where:

S = Power density in mW/cm²

EIRP= Equivalent isotropic Radiated power in mW

R = Distance from transmitting antenna in cm

EIRP:

$$\text{EIRP} = P + G$$

Where:

EIRP = Equivalent isotropic Radiated power in Mw

P = Output power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

Source-Based Duty Cycle:

Where applicable (for example, multi-slot cell phone applications) a duty cycle factor may be applied.

Source-based time-averaged EIRP = (DC / 100)* EIRP

Where:

DC = Duty Cycle in %, as applicable

EIRP= Equivalent isotropic Radiated power in mW

MIMO and collocated transmitters (identical limit for all transmitters):

For multiple chain devices, and collocated transmitters operating simultaneously in frequency bands where the limit is identical, the total power density is calculated using the total EIRP obtained by summing the PG (in linear units) of each transmitter.

Total EIRP = (EIRP 1) + (EIRP 2) + ... + (EIRP n)

MIMO and collocated transmitters:

For multiple collocated transmitters operating simultaneously in frequency bands where different limit apply:

The power density at the specified separation distance is calculated for each transmitter chain or transmitter.

The fraction of the exposure limit is calculated for each chain or transmitter as

Power density of chain or transmitter / limit applicable to the chain or transmitter.

The fractions are summed.

Compliance is established if the sum of the fractions is less than or equal to one.

3 RF Exposure Results

3.1 Standalone Exposure Calculations

For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band. The manufacturing configures output power so that the maximum power, after accounting for manufacturing tolerances, will never exceed the maximum power level measured.

The antenna gain in the tables below is the maximum antenna gain among various channels within the specified band.

Operating Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	EIRP/ERP (dBm)	EIRP/ERP Limit (dBm)	EIRP/ERP (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Gain According to EIRP/ERP (dBi)	Gain According to Pd (dBi)	Maximum Gain Allowed (dBi)	Results
LTE Band 2	1850.7	1.8	25.00	26.80	33.00	478.6301	0.1441	1.0000	8.00	10.21	8.00	Pass
LTE Band 4	1710.7	1.2	25.00	26.20	30.00	416.8694	0.1093	1.0000	5.00	10.81	5.00	Pass
LTE Band 5	824.7	0.3	25.00	23.15	38.45	206.5380	0.0268	0.5498	15.60	13.41	13.41	Pass
LTE Band 7	2502.5	1.4	25.00	26.40	33.00	436.5158	0.1199	1.0000	8.00	10.61	8.00	Pass
LTE Band 12	699.7	-0.5	25.00	22.35	34.77	171.7908	0.0186	0.4665	11.92	13.50	11.92	Pass
LTE Band 13	779.5	-0.7	25.00	22.15	34.77	164.0590	0.0169	0.5197	11.92	14.16	11.92	Pass
LTE Band 14	790.5	-0.5	25.00	22.35	34.77	171.7908	0.0186	0.5270	11.92	14.03	11.92	Pass
LTE Band 17	706.5	-0.5	25.00	22.35	34.77	171.7908	0.0186	0.4710	11.92	13.54	11.92	Pass
LTE Band 25	1850.7	1.8	25.00	26.80	33.00	478.6301	0.1441	1.0000	8.00	10.21	8.00	Pass
LTE Band 26 (814~824)	814.7	0.3	25.00	23.15	50.00	206.5380	0.0268	0.5431	27.15	13.36	13.36	Pass
LTE Band 26 (824~849)	824.7	0.3	25.00	23.15	38.45	206.5380	0.0268	0.5498	15.60	13.41	13.41	Pass
LTE Band 41	2498.5	1.4	25.00	26.40	33.00	436.5158	0.1199	1.0000	8.00	10.61	8.00	Pass
LTE Band 66	1710.7	1.5	25.00	26.50	30.00	446.6836	0.1255	1.0000	5.00	10.51	5.00	Pass
LTE Band 71	665.5	-0.9	25.00	21.95	34.77	156.6751	0.0154	0.4437	11.92	13.68	11.92	Pass
Bluetooth	2402	0.47	10.50	10.97	30.00	12.5026	0.0028	1.0000	NA			Pass
2.4GWIFI	2412	0.47	19.50	19.97	30.00	99.3116	0.0220	1.0000				Pass
U-NII-1	5180	-0.67	18.50	17.83	30.00	60.6736	0.0103	1.0000				Pass
U-NII-2A	5260	-0.19	18.50	18.31	30.00	67.7642	0.0129	1.0000				Pass
U-NII-2C	5500	1.28	18.50	19.78	30.00	95.0605	0.0254	1.0000				Pass
U-NII-3	5745	1.1	18.50	19.60	30.00	91.2011	0.0234	1.0000				Pass

Remark: "Maximum Power" comes from the largest "Tune-up" provided by the customer.

3.2 Multiple Sources Exposure Calculations

When a number of sources at different frequencies, and/or broadband sources, contribute to the total exposure, it becomes necessary to weigh each contribution relative to the MPE in accordance with the provisions of Table(A) and Table(B). To comply with the MPE, the fraction of the MPE in terms of E2, H2 (or power density) incurred within each frequency interval should be determined and the sum of all such fractions should not exceed unity.

In order to ensure compliance with the MPE for a controlled environment, the sum of the ratios of the power density to the corresponding MPE should not exceed unity.

$$\sum_{i=1}^n \frac{S_i}{MPE_i} \leq 1$$

The product also has multiple transmitters The Simultaneous Transmission Possibilities are as below:

Simultaneous Tx Combination	Configuration
1	WLAN 5GHz + Bluetooth
2	WWAN + WLAN 2.4GHz + Bluetooth
3	WWAN + WLAN 5GHz + Bluetooth

Operating Band	Frequency (MHz)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	MEs
LTE Band 2	1850.7	0.1441	1.0000	0.1441
LTE Band 4	1710.7	0.1093	1.0000	0.1093
LTE Band 5	824.7	0.0268	0.5498	0.0488
LTE Band 7	2502.5	0.1199	1.0000	0.1199
LTE Band 12	699.7	0.0186	0.4665	0.0398
LTE Band 13	779.5	0.0169	0.5197	0.0326
LTE Band 14	790.5	0.0186	0.5270	0.0352
LTE Band 17	706.5	0.0186	0.4710	0.0394
LTE Band 25	1850.7	0.1441	1.0000	0.1441
LTE Band 26 (814~824)	814.7	0.0268	0.5431	0.0494
LTE Band 26 (824~849)	824.7	0.0268	0.5498	0.0488
LTE Band 41	2498.5	0.1199	1.0000	0.1199
LTE Band 66	1710.7	0.1255	1.0000	0.1255
LTE Band 71	665.5	0.0154	0.4437	0.0348
Bluetooth	2402	0.0028	1.0000	0.0028
2.4GWIFI	2412	0.0220	1.0000	0.0220
U-NII-1	5180	0.0103	1.0000	0.0103
U-NII-2A	5260	0.0129	1.0000	0.0129
U-NII-2C	5500	0.0254	1.0000	0.0254
U-NII-3	5745	0.0234	1.0000	0.0234

The worst-case combination:

Combination	MEs	Total MEs	Limit	Conclusion
LTE Band 2	0.1441	0.1723	<1	PASS
WLAN 5GHz	0.0254			
Bluetooth	0.0028			

~The End~