



Test report issued under the responsibility of:
EMITECH MONTPELLIER laboratory
MRA US-EU Designation Number: FR0006
Canadian CAB Identifier: FR0003

RADIO TEST REPORT

FCC 47 CFR PART 15
RSS-247_Issue 3
RSS-Gen Issue 5
ANSI C 63.10: 2013

Company: **ENLESS WIRELESS**
Address.....: 45 TER AVENUE DE VERDUN
33520 BRUGES
FRANCE

Test item description.: **LoRa CO2, VOC, temperature & humidity wireless transmitter**
Trade Mark.: ENLESS WIRELESS
Manufacturer.: ENLESS WIRELESS
Model/Type reference.....: 600123402 / TX CO2 VOC T&H AMB 600-123
FCC ID......: 2BEZP600123
IC.: 32107-600123
Ratings.....: 3.6 Vdc to 3.8 Vdc

Testing Laboratory: **EMITECH MONTPELLIER laboratory**
Address.....: 145 rue de Massacan
34740 VENDARGUES
FRANCE

Report Reference No.: **RR-EVE-23B292-3A**
Test procedure.: FCC IC Certification
Diffusion......: Mr PETIT
Applicant's name.: ENLESS WIRELESS
Date of issue......: July 10, 2024
Total number of pages......: 49
Revision......: 0
Compiled by......: Morgan PATEY
Approved by (+ signature).: David MONTAULON (Technical Manager)

*Duplication of this test report is only permitted for an integral photographic facsimile. It includes the number of pages referenced here above.
This document is the result of testing a specimen or a sample of the product submitted. It does not imply an assessment of the conformity of
the whole manufactured products of the tested sample.*

REPORT INDEX:

1. GENERAL INFORMATIONS	3
2. REFERENCE DOCUMENT(S)	4
3. EQUIPMENT TECHNICAL DESCRIPTION	5
3.1. TEST CONDITIONS	5
3.2. E.U.T. MARKING PLATE	5
3.3. E.U.T. GENERAL VIEW	6
3.4. E.U.T. FRONT VIEW	6
3.5. E.U.T. BACK VIEW	7
3.6. E.U.T. INTERNAL VIEW & ELECTRONIC BOARD.....	7
3.7. E.U.T. MECHANICAL AND ELECTRICAL DESIGN.....	8
3.8. E.U.T. INPUT/OUTPUT PORTS.....	8
3.9. EUT RADIO SPECIFICATIONS.....	9
4. RESULT SUMMARY	10
5. MEASUREMENT UNCERTAINTY	12
6. TEST CONDITIONS AND RESULTS	13
6.1. RADIATED EMISSION LIMITS.....	13
6.2. NUMBER OF CHANNELS, 20 dB BANDWIDTH, AND AVERAGE TIME OF OCCUPANCY	27
6.3. EQUIVALENT ISOTROPIC RADIATED POWER	35
6.4. BAND-EDGE COMPLIANCE	40
6.5. MEASUREMENT OF FREQUENCY STABILITY.....	43
6.6. OCCUPIED BANDWIDTH	46

REVISION HISTORY:

Revision	Date	Modified pages	Modifications
0	July 10, 2024	/	Creation

1. GENERAL INFORMATION

This document submits the results of Radio tests performed on the equipment **LoRa CO2, VOC, temperature & humidity wireless transmitter 600123402 / TX CO2 VOC T&H AMB 600-123** (denominated hereafter E.U.T.: equipment under test) according to document(s) listed in §2 of this test report.

TESTING PROCEDURE AND TESTING LOCATION:					
Testing Location : EMITECH MONTPELLIER laboratory Address : 145 rue de Massacan 34740 VENDARGUES FRANCE Test procedure. : FCC IC Certification Tested by : Morgan PATEY Test supervisor : None Date of receipt of test item : N/A Date (s) of performance of tests : From November 22 nd of 2023 to January 15 th of 2024					
APPLICANT'S GENERAL INFORMATIONS:					
Company name : ENLESS WIRELESS Company address. : 45 TER AVENUE DE VERDUN 33520 BRUGES FRANCE Person(s) present during the tests. : No representative for company attended the tests. Responsible. : Mr PETIT					
GENERAL REMARKS:					
The information in italics is declared by the manufacturer and is under his responsibility The test results presented in this report relate only to the object tested. The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report. "(see Enclosure #)" refers to additional information appended to the report. "(see appended table)" refers to a table appended to the report. Throughout this report the decimal separator is point.					
POSSIBLE TEST CASE VERDICTS:					
Test case does not apply to the test object. . : N/A Test case not performed..... : N/P Test object does meet the requirement..... : P (Pass) Test object does not meet the requirement.. : F (Fail)					
DEFINITIONS AND ABBREVIATIONS:					
E.U.T.	Equipment Under Test	AE	Ancillary Equipment	Pk	Peak detector
RBW	Resolution BandWidth	VBW	Video BandWidth	QP	Quasi-peak detector
FSOATS	Free Space Open Area Test Site	FAR	Full Anechoic Room	Av	Average detector
VP	Vertical Polarization	HP	Horizontal Polarization	RMS	Root Mean Square
RF	Radio Frequency	N.T.R	Nothing To Report	N/C	Not Communicated
SAC	Semi Anechoic Chamber				

2. REFERENCE DOCUMENT(S)

NORMATIVE REFERENCES:

The following referenced documents are necessary for the application of the present test report.

FCC 47 CFR Part 15: October 2023

Code of federal regulations – Title 47 telecommunication - Part 15 - Radio frequency devices

FCC 47 CFR Part 15.247

Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

RSS-247_Issue 3: August 2023

Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and Licence Exempt Local Area Network (LE-LAN) Devices

RSS-Gen Issue 5: April 2018 / AMD1: 2019 / AMD2: 2021

General Requirements for Compliance of Radio Apparatus

ANSI C 63.10: 2013

American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

Although the product standard uses obsolete technical standards, the latest versions of standards achievable by the laboratory will be used for testing.

INFORMATIVE REFERENCES:

The following referenced documents are not necessary for the application of the present test report but they assist the user with regard to a particular subject area.

3. EQUIPMENT TECHNICAL DESCRIPTION

3.1. Test Conditions

Test item description. : LoRa CO2, VOC, temperature & humidity wireless transmitter
Model/Type reference..... : 600123402 / TX CO2 VOC T&H AMB 600-123
Trade Mark. : ENLESS WIRELESS
Serial number (S/N)..... : Not communicated
Part number (P/N). : Not communicated
Software version..... : *Not communicated*
Firmware version. : *Not communicated*
Type of sample. : Standard equipment
Function(s)..... : Not communicated
Manufacturer name. : ENLESS WIRELESS
Address..... : 45 TER AVENUE DE VERDUN
33520 BRUGES
FRANCE

General product information:

N/A

3.2. E.U.T. Marking plate



3.3.E.U.T. General view



3.4.E.U.T. Front view



3.5. E.U.T. Back view



3.6. E.U.T. Internal view & Electronic board



3.7.E.U.T. Mechanical and Electrical Design

Power supply. : 3.6 VDC
Power supply range..... : 3.6 Vdc to 3.8 Vdc
Power type..... : Battery powered
Power (W)..... : Not communicated
Nominal current (A). : Not communicated
Dimensions (L x W x H) (m). : Not communicated
Weight (kg). : Not communicated
Temperature range (°C). : -25 to +55
Ground bounding strap..... : No

Comments:

N/A

3.8.E.U.T. Input/Output ports

TX CO2/VOC/T&H
AMB 600-123



Internal
Battery



RF antenna



PORT	NAME	TYPE	LENGTH	CABLE TYPE	COMMENTS
0	Main frame	N/E	N/A	Plastic	N/A
1	Internal Battery	DC	N/A	N/A	3.6 Vdc
2	RF antenna	RF	N/A	N/A	900 MHz

AC/DC : AC/DC Converter port

AC : Alternative current port

DC : Direct current port

I/O : Input or Output port

TP : Telecommunication port

RF : Radio frequency port

N/E : Non Electrical port

3.9. EUT Radio Specifications

a) GENERAL INFORMATIONS	
According to manufacturer's declarations :	
EUT type.....	<i>Transceiver</i>
Technology	<i>LoRa</i>
Environmental profile.....	<i>Data transmissions</i>
Temperature range.....	<i>-25°C to +55°C</i>
Antenna type	<i>Integrated</i>
Antenna Gain.....	<i>Not communicated</i>
Comments:	
<i>N/A</i>	
b) TRANSMITTER PARAMETERS (Tx)	
Frequency bands.....	<i>902 MHz to 928 MHz</i>
RF Power.....	<i>25 mw</i>
Number of channels / Separation.....	<i>64 for FHSS/200kHz</i> <i>8 for DSSS/1.6MHz (Refer to test report RR-EVE-23B292-4A)</i>
Modulation type	<i>LoRa</i>
Duty cycle	<i>Not communicated</i>
Tested frequency.....	<i>902.3 MHz</i> <i>908.5 MHz</i> <i>914.9 MHz</i>
c) RECEIVER PARAMETERS (Rx)	
Frequency bands.....	<i>902 MHz to 928 MHz</i>
Category/Class	<i>Not communicated</i>
Bandwidth	<i>Not communicated</i>

4. RESULT SUMMARY

TEST DESIGNATION	SEVERITY	VERDICT	COMMENTS
GENERAL			
Labeling requirements		N/P	15.19 / See certification documents
Information to user		N/P	15.21 / See certification documents
Home-built devices		N/A	15.23
Kits		N/A	15.25
Special Accessories		N/P	15.27 / See certification documents
Inspection by the Commission		N/A	15.29
Measurement standards		PASS	15.31
Test procedure for CPU boards and computer power supplies		N/A	15.32
Frequency range of radiated measurements		PASS	15.33
Measurement detector functions and bandwidths		PASS	15.35
Transition provisions for compliance with the rules		N/P	15.37 / See certification documents
UNINTENTIONAL RADIATORS			
Equipment authorization			15.101
- Verification		N/A	
- Declaration of Conformity		N/A	
CPU boards and power supplies used in personal computers		N/A	15.102
Exempted device		N/A	15.103
Information to the user		N/P	15.105 / See certification documents
Conducted limits		N/A	15.107 / Battery powered equipment
Radiated emission limits	Class B	PASS	15.109
Antenna power conduction limits for receivers		N/A	15.111
Power line carrier systems		N/A	15.113
TV interface devices, including cable system terminal devices		N/A	15.115
TV broadcast receivers		N/A	15.117
Cable ready consumer electronics equipment		N/A	15.118
Program blocking technology requirements for TV receivers		N/A	15.120
Scanning receivers and frequency converters used with scanning receivers		N/A	15.121
Labeling of digital cable ready products		N/A	15.123
INTENTIONAL RADIATORS			

TEST DESIGNATION	SEVERITY	VERDICT	COMMENTS
Equipment authorization requirement	Class B	PASS	15.201 / Transmitter part is subject to Certification procedure
Certified operating frequency range		N/A	15.202
Antenna requirement		PASS	15.203 / Dedicated integral antenna
External radio frequency power amplifiers and antenna modifications		N/A	15.204
Restricted bands of operation		PASS	15.205
Conducted limits		N/A	15.207 / Battery powered equipment
Radiated emission limits; general requirements		PASS	15.209
Tunnel radio systems		N/A	15.211
Modular transmitters		N/A	15.212
Cable locating equipment		N/A	15.213
Cordless telephones		N/A	15.214
Additional provisions to the general radiated emission limits		PASS	15.215
Operation within the band 902-928MHz, 2400-2483.5MHz and 5725-5850MHz			15.247
- Frequency hopping and digitally modulated		-	a)
- Frequency hopping system		PASS	a) (1)
- Digital modulation system		N/A	a) (2) Refer to test report RR-EVE-23B292-4A
- Maximum peak conducted output power		-	b)
- For hopping system in the 2400-2483.5 MHz and 5725-5850 MHz bands		N/A	b) (1)
- For hopping system in the 902-928MHz band		PASS	b) (2)
- For system using digital modulation in the 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz bands		N/A	b) (3) Refer to test report RR-EVE-23B292-4A
- Operation with directional antenna gains > 6 dBi		N/A	c)
- Out-of-band emissions		PASS	d)
- Power spectral density conducted		N/A	e) Refer to test report RR-EVE-23B292-4A
- Hybrid system		N/A	f)
- Frequency hopping additional requirements		N/A	g)
- Frequency hopping intelligence		N/A	h)
- RF exposure compliance		PASS	i)

Sample subject to the test complies with the requirements of the reference document(s) listed in §2 of this test report and, where applicable, with deviation(s) specified in this document.

To declare, or not, the compliance with the specifications, it was not explicitly taken account of uncertainty associated with the results.

Opinion(s) and interpretation(s): N/A

5. MEASUREMENT UNCERTAINTY

PARAMETER	MAXIMAL EMITECH UNCERTAINTY	MINIMAL STANDARD UNCERTAINTY
Radio frequency	$\pm 1 \times 10^{-7}$	$\pm 1 \times 10^{-7}$
RF power, conducted		
RF power	$\pm 0.8\text{dB}$	$\pm 1 \text{ dB}$
Power spectral density	$\pm 2.3\text{dB}$	$\pm 3 \text{ dB}$
Occupied bandwidth		
RF power	$\pm 3.8 \%$	$\pm 5 \%$
Conducted emission (spurious)		
$f \leq 1 \text{ GHz}$	$\pm 0.8 \text{ dB}$	$\pm 3 \text{ dB}$
$1 \text{ GHz} - 12.75 \text{ GHz}$	$\pm 1.6 \text{ dB}$	
Radiated emission (ERP / EIRP)		
$f \leq 62.5 \text{ MHz}$	$\pm 5.7 \text{ dB}$	$\pm 6 \text{ dB}$
$62.5 \text{ MHz} - 1 \text{ GHz}$	$\pm 5.8 \text{ dB}$	$\pm 6 \text{ dB}$
$1 \text{ GHz} - 18 \text{ GHz}$	$\pm 5.6 \text{ dB}$	$\pm 6 \text{ dB}$
$18 \text{ GHz} - 40 \text{ GHz}$	$\pm 5.6 \text{ dB}$	$\pm 6 \text{ dB}$
Radiated emission (magnetic field)		
$9\text{kHz} - 30\text{MHz}$	$\pm 3.4 \text{ dB}$	$\pm 6 \text{ dB}$
Supply voltages	$\pm 3 \%$	$\pm 3 \%$
Temperature	$\pm 1 \text{ }^{\circ}\text{C}$	$\pm 1^{\circ}\text{C}$
Humidity	$\pm 5 \%$	$\pm 5 \%$
Time / Duty cycle	$\pm 4.4 \%$	$\pm 5 \%$
Conducted emission (FCC)		
(Artificial Mains Network) $150\text{kHz} - 30\text{MHz}$	$\pm 3.4 \text{ dB}$	$\pm 3.4 \text{ dB}$
Radiated emission (electric field for FCC standard)		
$9\text{kHz} - 30\text{MHz}$	$\pm 2.7 \text{ dB}$	/
$30\text{MHz} - 1\text{GHz}$	$\pm 5.0 \text{ dB}$	/
$1\text{GHz} - 18\text{GHz}$	$\pm 5.3 \text{ dB}$	/
$18\text{GHz} - 40\text{GHz}$	$\pm 6.1 \text{ dB}$	/
$40\text{GHz} - 140\text{GHz}$	$\pm 5.7 \text{ dB}$	/

For the calculation of expanded uncertainty, the confidence interval is 95 % (k=2).

6. TEST CONDITIONS AND RESULTS

6.1. Radiated emission limits

Reference standard:	FCC 47 CFR Part 15.247; 15.209; 15.205 RSS-247; RSS-Gen
Test method:	ANSI C63.10: 2013
Test description: : For f <30MHz, EUT is set on an insulating support at 80cm above the ground reference plane. Preliminary (peak) measurements were performed at an antenna to EUT separation distance of 3-meter in a semi-anechoic chamber. The EUT was rotated 360° in order to maximize radiated levels. Test antenna was oriented in 3 axes (0°, 45° and 90°). Final measurements (quasi-peak) were then performed in a 10-meter Open Area Test Site that complies to CISPR 16 in the same measurement conditions. For f > 30MHz, EUT is set on an insulating support at 80cm above the ground reference plane (150cm for f >1GHz). Preliminary (peak) measurements were performed at an antenna to EUT separation distance of 3-meter. The EUT was rotated 360° about its azimuth with the receive antenna located at various heights in horizontal and vertical polarities. Final measurements (quasi-peak or average) were then performed in a semi-anechoic chamber or Open Area Test Site that complies to CISPR 16. The EUT was rotated 360° about its azimuth and adjusting the receive antenna height from 1 to 4 m. All frequencies were investigated, where applicable. For portable equipments a research of maximum level is done on the 3 axes. Only the highest levels are recorded.	

TESTED CONFIGURATION	PARAMETER	SEVERITY	RESULT TAB.	VERDICT
Radiated measurement / 9 kHz to 30 MHz / 0°	9kHz-30MHz	15.209	EMI4992	PASS
Radiated measurement / 9 kHz to 30 MHz / 45°	9kHz-30MHz	15.209	EMI4993	PASS
Radiated measurement / 9 kHz to 30 MHz / 90°	9kHz-30MHz	15.209	EMI4994	PASS
Radiated measurement / 30 MHz to 1 GHz / FHSS	30MHz-1GHz	15.209	EMI4858	PASS
Radiated measurement / 1 GHz to 12.75 GHz / Low channel	1GHz-12.75GHz	15.209	EMI4898	PASS
Radiated measurement / 1 GHz to 12.75 GHz / Mid channel	1GHz-12.75GHz	15.209	EMI4899	PASS
Radiated measurement / 1 GHz to 12.75 GHz / High channel	1GHz-12.75GHz	15.209	EMI4901	PASS


LABORATORY PARAMETERS:	REQUIRED PRIOR TO THE TEST	DURING THE TEST
Ambient Temperature	15 to 35 °C	See Graph(s)
Relative Humidity	20 to 75 %	See Graph(s)
Atmospheric pressure	N/A	See Graph(s)
Test method deviation: N/A		
Supplementary information: From 9 kHz to 30MHz: limit indicated on the curves is calculated with 40 dB/decade extrapolation factor and 51.5 dB conversion factor.		
From 30MHz to 1GHz Quasi peak limit provided is the limit given in §15.209.		
Above 1GHz average limit in restricted bands §15.205 is 54dBµV/m. Otherwise, the limit is 20dB under carrier emission level at 3m without averaging.		

TEST EQUIPMENT USED					
CATEGORY	BRAND	TYPE	IDENTIFIER	CAL. DATE	CAL. DUE
Antenna	Rohde & Schwarz	HFH2-Z2	5825	16/08/2022	16/10/2024
Antenna	ETS lindgren	3142E	14523	27/01/2022	27/03/2025
Antenna	AARONIA	Powerlog 70180	15306	04/01/2023	04/03/2026
Cable	/	N-1m	3625	02/05/2023	02/07/2025
Cable	Techniwave	N-3.5m	18353	17/08/2023	17/10/2025
Cable	Techniwave	N-4m	18355	17/08/2023	17/10/2025
Cable	Techniwave	N-1.5m	18341	17/08/2023	17/10/2025
Cable	Techniwave	N-1.5m	18342	25/01/2022	25/03/2024
Cable	SUCOFLEX	N-3m	14378	17/08/2023	17/10/2025
Cable	SUCOFLEX	N-6,5m	14380	17/08/2023	17/10/2025
Cable	Techniwave	N-8m	18349	17/08/2023	17/10/2025
Filter	Micro-Tronics	HPM18865	12843	24/08/2021	24/10/2024
Preamplifier	IMPULSE	CA118-546ACN	9169	15/06/2023	15/08/2024
Receiver	Rohde & Schwarz	ESW26	17791	08/02/2023	08/04/2024
Receiver	Rohde & Schwarz	FSW43	14830	10/08/2022	10/10/2024
Shielded enclosure	COMTEST	FAR-3m	18014	17/08/2021	17/10/2024
Shielded enclosure	COMTEST	SAC 3m	14494	08/08/2023	08/10/2026
Software	Nexio	BAT EMC	0000		
Thermohygrometer	Testo	608-H2	12269	07/06/2022	07/08/2024
Thermohygrometer	Bioblock Scientific	Météostar	0963	25/09/2023	25/11/2025

BAT-EMC software version: V3.18.0.26

Blank cells = Permanent validity

TEST SETUP PHOTO(S) - RADIATED MEASUREMENT / POSITION



TEST SETUP PHOTO(S) - RADIATED MEASUREMENT / 30 MHz TO 1 GHz



TEST SETUP PHOTO(S) - RADIATED MEASUREMENT / 1 GHz TO 12.75 GHz



RADIATED EMISSION LIMITS – TABULATED RESULTS

RADIATED MEASUREMENT / 9 kHz TO 30 MHz / 0°							EMI4992	
FREQUENCY (MHz)	POLARIZATION	PEAK LEVEL (dBμA/m)	AVERAGE LEVEL (dBμA/m)	AVERAGE LIMIT (dBμA/m)	AVERAGE MARGIN (dB)	QPEAK LEVEL (dBμA/m)	QPEAK LIMIT (dBμA/m)	QPEAK MARGIN (dB)
0.944	0°	-18.90	N/A	N/A	N/A	N/P	16.60	-35.50
0.995	0°	-18.97	N/A	N/A	N/A	N/P	16.15	-35.12
1.293	0°	-18.80	N/A	N/A	N/A	N/P	13.87	-32.67
1.455	0°	-18.10	N/A	N/A	N/A	N/P	12.85	-30.95
1.493	0°	-18.92	N/A	N/A	N/A	N/P	12.62	-31.54
1.522	0°	-18.85	N/A	N/A	N/A	N/P	12.46	-31.31
COMMENT:		When margin between peak measurements and Average/Qpeak limit(s) is > 6dB, no Average/Qpeak measurements were performed. No spurious were detected.						

RADIATED EMISSION LIMITS – TABULATED RESULTS

RADIATED MEASUREMENT / 9 kHz TO 30 MHz / 45°							EMI4993	
FREQUENCY (MHz)	POLARIZATION	PEAK LEVEL (dBμA/m)	AVERAGE LEVEL (dBμA/m)	AVERAGE LIMIT (dBμA/m)	AVERAGE MARGIN (dB)	QPEAK LEVEL (dBμA/m)	QPEAK LIMIT (dBμA/m)	QPEAK MARGIN (dB)
1.102	45°	-18.99	N/A	N/A	N/A	N/P	15.26	-34.25
1.339	45°	-19.12	N/A	N/A	N/A	N/P	13.57	-32.69
1.432	45°	-19.20	N/A	N/A	N/A	N/P	12.98	-32.18
1.455	45°	-18.66	N/A	N/A	N/A	N/P	12.85	-31.51
1.525	45°	-19.07	N/A	N/A	N/A	N/P	12.44	-31.51
1.655	45°	-19.11	N/A	N/A	N/A	N/P	11.73	-30.84
COMMENT:		When margin between peak measurements and Average/Qpeak limit(s) is > 6dB, no Average/Qpeak measurements were performed. No spurious were detected.						


RADIATED EMISSION LIMITS – TABULATED RESULTS								
RADIATED MEASUREMENT / 9 KHz TO 30 MHz / 90°							EMI4994	
FREQUENCY (MHz)	POLARIZATION	PEAK LEVEL (dBμA/m)	AVERAGE LEVEL (dBμA/m)	AVERAGE LIMIT (dBμA/m)	AVERAGE MARGIN (dB)	QPEAK LEVEL (dBμA/m)	QPEAK LIMIT (dBμA/m)	QPEAK MARGIN (dB)
0.978	90°	-18.86	N/A	N/A	N/A	N/P	16.30	-35.16
0.986	90°	-18.98	N/A	N/A	N/A	N/P	16.23	-35.21
1.264	90°	-19.08	N/A	N/A	N/A	N/P	14.07	-33.15
1.484	90°	-19.16	N/A	N/A	N/A	N/P	12.67	-31.83
1.653	90°	-19.09	N/A	N/A	N/A	N/P	11.74	-30.83
1.705	90°	-19.42	N/A	N/A	N/A	N/P	11.47	-30.89
COMMENT:		When margin between peak measurements and Average/Qpeak limit(s) is > 6dB, no Average/Qpeak measurements were performed. No spurious were detected.						


RADIATED EMISSION LIMITS – TABULATED RESULTS					
RADIATED MEASUREMENT / 30 MHz TO 1 GHz / FHSS					EMI4858
FREQUENCY (MHz)	POLARIZATION	PEAK LEVEL (dBμV/m)	QPEAK LEVEL (dBμV/m)	QPEAK LIMIT (dBμV/m)	QPEAK MARGIN (dB)
805.09	Vertical	40.25	N/P	88	-47.75
805.73	Vertical	39.36	N/P	88	-48.64
806.32	Vertical	39.86	N/P	88	-48.14
806.80	Vertical	40.87	N/P	88	-47.13
808.71	Vertical	39.36	N/P	88	-48.64
809.49	Vertical	39.77	N/P	88	-48.23
806.22	Horizontal	42.56	N/P	88	-45.44
808.06	Horizontal	42.73	N/P	88	-45.27
810.04	Horizontal	42.09	N/P	88	-45.91
899.67	Horizontal	41.63	N/P	88	-46.37
900.70	Horizontal	45.02	N/P	88	-42.98
901.06	Horizontal	44.54	N/P	88	-43.46
COMMENT:		When margin between peak measurements and Qpeak limit(s) is > 6dB, no Qpeak measurements were performed.			


RADIATED EMISSION LIMITS – TABULATED RESULTS							
RADIATED MEASUREMENT / 1 GHz TO 12.75 GHz / LOW CHANNEL						EMI4898	
FREQUENCY (MHz)	POLARIZATION	PEAK LEVEL (dBμV/m)	PEAK LIMIT (dBμV/m)	PEAK MARGIN (dB)	AVERAGE LEVEL (dBμV/m)	AVERAGE LIMIT (dBμV/m)	AVERAGE MARGIN (dB)
1804.12	Vertical	53.32	88	-34.68	N/P	68	-14.68
8598.19	Vertical	48.12	88	-39.88	N/P	68	-19.88
8733.72	Vertical	48.98	88	-39.02	N/P	68	-19.02
9022.78	Vertical	52.71	74	-21.29	42.34	54	-11.66
9323.19	Vertical	48.05	74	-25.95	N/P	54	-5.95
9475.95	Vertical	48.44	74	-25.56	N/P	54	-5.56
1015.28	Horizontal	48.92	74	-25.08	42.18	54	-11.82
1804.51	Horizontal	49.87	88	-38.13	N/P	68	-18.13
8432.91	Horizontal	48.38	74	-25.62	N/P	54	-5.62
8798.34	Horizontal	48.45	88	-39.55	N/P	68	-19.55
9023.17	Horizontal	49.52	74	-24.48	42.18	54	-11.82
9458.32	Horizontal	48.62	74	-25.38	N/P	54	-5.38
COMMENT:		When margin between peak measurements and average limit is > 6dB, no average measurements were performed. According to the paragraph (d) §15.247, outside restricted bands the limit is 20 dBc under carrier emission level at 3m without averaging: In this case 108 dBμV/m – 20 dB = 88 dBμV/m					


RADIATED EMISSION LIMITS – TABULATED RESULTS							
RADIATED MEASUREMENT / 1 GHz TO 12.75 GHz / MID CHANNEL						EMI4899	
FREQUENCY (MHz)	POLARIZATION	PEAK LEVEL (dBμV/m)	PEAK LIMIT (dBμV/m)	PEAK MARGIN (dB)	AVERAGE LEVEL (dBμV/m)	AVERAGE LIMIT (dBμV/m)	AVERAGE MARGIN (dB)
1816.65	Vertical	53.67	88	-34.33	N/P	68	-14.33
8584.49	Vertical	49.15	88	-38.85	N/P	68	-18.85
8863.36	Vertical	48.82	88	-39.18	N/P	68	-19.18
8920.16	Vertical	48.23	88	-39.77	N/P	68	-19.77
9085.05	Vertical	52.32	74	-21.68	46.02	54	-7.98
9677.27	Vertical	48.24	88	-39.76	N/P	68	-19.76
1005.09	Horizontal	52.27	74	-21.73	41.46	54	-12.54
1027.03	Horizontal	48.57	74	-25.43	39.04	54	-14.96
1816.65	Horizontal	51.66	88	-36.34	N/P	68	-16.34
8885.69	Horizontal	49.25	88	-38.75	N/P	68	-18.75
9152.81	Horizontal	48.46	74	-25.54	N/P	54	-5.54
9289.90	Horizontal	48.23	88	-39.77	N/P	68	-19.77
COMMENT:		When margin between peak measurements and average limit is > 6dB, no average measurements were performed. According to the paragraph (d) §15.247, outside restricted bands the limit is 20 dBc under carrier emission level at 3m without averaging: In this case 108 dBμV/m – 20 dB = 88 dBμV/m					


RADIATED EMISSION LIMITS – TABULATED RESULTS							
RADIATED MEASUREMENT / 1 GHz TO 12.75 GHz / HIGH CHANNEL						EMI4901	
FREQUENCY (MHz)	POLARIZATION	PEAK LEVEL (dB μ V/m)	PEAK LIMIT (dB μ V/m)	PEAK MARGIN (dB)	AVERAGE LEVEL (dB μ V/m)	AVERAGE LIMIT (dB μ V/m)	AVERAGE MARGIN (dB)
1829.58	Vertical	54.08	88	-33.92	N/P	68	-13.92
8511.24	Vertical	47.87	88	-40.13	N/P	68	-20.13
8680.45	Vertical	47.91	88	-40.09	N/P	68	-20.09
9080.74	Vertical	47.63	74	-26.37	N/P	54	-6.37
9148.90	Vertical	49.43	74	-24.57	47.18	54	-6.82
9492.79	Vertical	47.70	74	-26.30	N/P	54	-6.30
1014.88	Horizontal	52.23	74	-21.77	40.36	54	-13.64
1829.58	Horizontal	52.52	88	-35.48	N/P	68	-15.48
8430.16	Horizontal	48.02	74	-25.98	N/P	54	-5.98
8650.29	Horizontal	47.97	88	-40.03	N/P	68	-20.03
9148.90	Horizontal	48.68	74	-25.32	42.48	54	-11.52
9172.01	Horizontal	48.18	74	-25.82	N/P	54	-5.82
COMMENT:		When margin between peak measurements and average limit is > 6dB, no average measurements were performed. According to the paragraph (d) §15.247, outside restricted bands the limit is 20 dBc under carrier emission level at 3m without averaging: In this case 108 dBμV/m – 20 dB = 88 dBμV/m					

















6.2. Number of channels, 20 dB bandwidth, and average time of occupancy

Reference standard:	FCC 47 CFR Part 15.247 RSS 247
Test method:	ANSI C63.10: 2013
Test description: (a) (1) (i) For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.	

TESTED PARAMETER	RESULT	SEVERITY	RESULT TAB.	VERDICT
Number of channels / FHSS	64 channels	≥ 50 channels	EMI5242	PASS
Channels separation / FHSS	200.36 kHz	≥ 200 kHz	EMI5243	PASS
20 dB bandwidth / Low channel	147.757 kHz	< 200.36 kHz	EMI5990	PASS
20 dB bandwidth / Mid channel	152.071 kHz	< 200.36 kHz	EMI5991	PASS
20 dB bandwidth / High channel	148.296 kHz	< 200.36 kHz	EMI5992	PASS
Average time of occupancy	0.034 ms / 20 s	≤ 400 ms / 20 s	EMI5993	PASS

LABORATORY PARAMETERS:	REQUIRED PRIOR TO THE TEST	DURING THE TEST
Ambient Temperature	15 to 35 °C	See Graph(es)
Relative Humidity	20 to 75 %	See Graph(es)
Atmospheric pressure	N/A	See Graph(es)
TEST METHOD DEVIATION: N/A		
Supplementary information: N/A		

TEST EQUIPMENT USED					
CATEGORY	BRAND	TYPE	IDENTIFIER	CAL. DATE	CAL. DUE
Antenna	ETS lindgren	3143B	17930	12/08/2021	12/10/2024
Cable	/	N-1m	3625	02/05/2023	02/07/2025
Cable	Techniwave	N-3.5m	18353	17/08/2023	17/10/2025
Cable	Techniwave	N-4m	18355	17/08/2023	17/10/2025
Receiver	Rohde & Schwarz	FSW43	14830	10/08/2022	10/10/2024
Shielded enclosure	COMTEST	FAR-3m	18014	17/08/2021	17/10/2024
Software	Nexio	BAT EMC	0000		
Thermohygrometer	Testo	608-H2	12269	07/06/2022	07/08/2024
Thermohygrometer	Bioblock Scientific	Météostar	0963	25/09/2023	25/11/2025

BAT-EMC software version: V3.18.0.26

Blank cells = Permanent validity


TEST SETUP PHOTO(S) – POSITION



TEST SETUP PHOTO(S)



Page 29 on 49



6.3. Equivalent isotropic radiated power

Reference standard:	FCC Part 15.247 and RSS 247
Test method:	ANSI C63.10: 2013
Test description: b) (2) For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section. Only the highest levels are recorded. The measurement is performed in radiated mode because the product antenna is a simple wire type antenna. The results are directly compared to the radiated limits (conducted limits + 6dB)	

TESTED CONFIGURATION	RESULTS	SEVERITY	RESULT TAB.	VERDICT
RF output power (EIRP) / Low channel	9.83 dBm	4W (36dBm)	EMI4894	PASS
RF output power (EIRP) / Mid channel	10.00 dBm	4W (36dBm)	EMI4895	PASS
RF output power (EIRP) / High channel	9.62 dBm	4W (36dBm)	EMI4896	PASS

LABORATORY PARAMETERS:	REQUIRED PRIOR TO THE TEST	DURING THE TEST
Ambient Temperature	15 to 35 °C	See Graph(es)
Relative Humidity	20 to 75 %	See Graph(es)
Atmospheric pressure	N/A	See Graph(es)
TEST METHOD DEVIATION: N/A		
Supplementary information: Measurements are performed in radiated.		

TEST EQUIPMENT USED					
CATEGORY	BRAND	TYPE	IDENTIFIER	CAL. DATE	CAL. DUE
Antenna	ETS lindgren	3143B	17930	12/08/2021	12/10/2024
Attenuator	EMITECH	SUB.V4-H	18112	10/03/2023	10/05/2024
Attenuator	EMITECH	SUB.V4-V	18111	10/03/2023	10/05/2024
Cable	/	N-1m	3625	02/05/2023	02/07/2025
Cable	Techniwave	N-3.5m	18353	17/08/2023	17/10/2025
Cable	Techniwave	N-4m	18355	17/08/2023	17/10/2025
Receiver	Rohde & Schwarz	FSW43	14830	10/08/2022	10/10/2024
Shielded enclosure	COMTEST	FAR-3m	18014	17/08/2021	17/10/2024
Software	Nexio	BAT EMC	0000		
Thermohygrometer	Testo	608-H2	12269	07/06/2022	07/08/2024
Thermohygrometer	Bioblock Scientific	Météostar	0963	25/09/2023	25/11/2025

BAT-EMC software version: V3.18.0.26


Blank cells = Permanent validity


TEST SETUP PHOTO(S) – POSITION




TEST SETUP PHOTO(S)









6.4. Band-edge compliance

Reference standard:	FCC 47 CFR Part 15.247 RSS 247
Test method:	ANSI C63.10: 2013
Test description: d) In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Only the highest levels are recorded.	

TESTED CONFIGURATION	PARAMETER	SEVERITY	RESULT TAB.	VERDICT
Band edge / All channels	876MHz-954MHz	20 dBc and §15.209	EMI4858	PASS

LABORATORY PARAMETERS:	REQUIRED PRIOR TO THE TEST	DURING THE TEST
Ambient Temperature	15 to 35 °C	See Graph(es)
Relative Humidity	20 to 75 %	See Graph(es)
Atmospheric pressure	N/A	See Graph(es)
Test method deviation: N/A		
Supplementary information: N/A		

TEST EQUIPMENT USED					
CATEGORY	BRAND	TYPE	IDENTIFIER	CAL. DATE	CAL. DUE
Antenna	ETS lindgren	3142E	14523	27/01/2022	27/03/2025
Cable	Techniwave	N-8m	18349	17/08/2023	17/10/2025
Cable	SUCOFLEX	N-6,5m	14380	17/08/2023	17/10/2025
Cable	SUCOFLEX	N-3m	14378	17/08/2023	17/10/2025
Receiver	Rohde & Schwarz	ESW26	17791	08/02/2023	08/04/2024
Shielded enclosure	COMTEST	SAC 3m	14494	08/08/2023	08/10/2026
Software	Nexio	BAT EMC	0000		
Thermohygrometer	Testo	608-H2	12269	07/06/2022	07/08/2024
Thermohygrometer	Bioblock Scientific	Météostar	0963	25/09/2023	25/11/2025

BAT-EMC software version: V3.18.0.26


Blank cells = Permanent validity

TEST SETUP PHOTO(S) – POSITION



TEST SETUP PHOTO(S)





6.5. Measurement of frequency stability

Reference standard:	FCC 47 CFR Part 15.215 RSS-Gen
Test method:	ANSI C63.10: 2013
General test setup: The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation. EUT is set inside the climatic enclosure.	

TEST CASE	EUT MODE	SEVERITY	RESULT TAB.	VERDICT
Low channel	Tx mode	Within 902MHz to 928MHz	EMI6410	PASS
Mid channel	Tx mode		EMI6411	PASS
High channel	Tx mode		EMI6412	PASS


LABORATORY PARAMETERS:	REQUIRED PRIOR TO THE TEST	DURING THE TEST
Ambient Temperature	15 to 35 °C	21.8 °C
Relative Humidity	20 to 75 %	38.2 %
Atmospheric pressure	N/A	1009 hPa
Test method deviation: N/A		
Supplementary information: N/A		

TEST EQUIPMENT USED					
CATEGORY	BRAND	TYPE	IDENTIFIER	CAL. DATE	CAL. DUE
Antenna	EMITECH	3.5 cm	4653		
Cable	C&C	N-3m	14332	28/04/2023	28/06/2025
Climatic enclosure	CLIMATS	EXCAL 7714-HA	14261	21/10/2022	21/06/2024
Multimeter	Agilent Technologies	U1252A	6138	29/06/2023	29/08/2024
Power supply	TTI	PL303QMD	8496		
Receiver	Rohde & Schwarz	FPL1007	17908	03/11/2022	03/07/2024
Thermohygrometer	Bioblock Scientific	Météostar	0963	09/06/2021	09/02/2024
Thermohygrometer	Testo	608-H1	7562	11/06/2021	11/02/2024
Thermometer contactless	GHM Greisinger	GMH 3710	12968	28/02/2023	28/04/2025

BAT-EMC software version: V3.18.0.26

Blank cells = Permanent validity

TEST SETUP PHOTO(S)



MEASUREMENT OF FREQUENCY STABILITY - TABULATED RESULTS

LOW CHANNEL					EMI6410
Test case	Temperature (°C)	Power supply (Vdc)	Frequency (MHz)	Frequency error (kHz)	Limit
Normal conditions	+25	3.7	902.300168	-	Within 902MHz to 928MHz
Extrem voltage conditions	+25	3.6	902.300227	-0.059	
		3.8	902.300171	+0.003	
Extrem temperature conditions	-25	3.7	902.300339	+0.171	
	+55		902.300463	+0.295	

MEASUREMENT OF FREQUENCY STABILITY - TABULATED RESULTS

MID CHANNEL					EMI6411
Test case	Temperature (°C)	Power supply (Vdc)	Frequency (MHz)	Frequency error (kHz)	Limit
Normal conditions	+25	3.7	908.500413	-	Within 902MHz to 928MHz
Extrem voltage conditions	+25	3.6	908.500398	-0.015	
		3.8	908.500315	-0.098	
Extrem temperature conditions	-25	3.7	908.500676	+0.263	
	+55		908.500580	+0.167	

MEASUREMENT OF FREQUENCY STABILITY - TABULATED RESULTS					
HIGH CHANNEL					EMI6412
Test case	Temperature (°C)	Power supply (Vdc)	Frequency (MHz)	Frequency error (kHz)	Limit
Normal conditions	+25	3.7	914.900250	-	Within 902MHz to 928MHz
Extrem voltage conditions	+25	3.6	914.900332	+0.082	
		3.8	914.900307	+0.057	
Extrem temperature conditions	-25	3.7	914.900504	+0.254	
	+55		914.900728	+0.478	

6.6. Occupied Bandwidth

Reference standard:	RSS-Gen
Test method:	ANSI C63.10: 2013
Test description: The occupied bandwidth (OBW) is the Frequency Range in which 99 % of the total mean power of a given emission falls. The residual part of the total power being denoted as β, which, in cases of symmetrical spectra, splits up into $\beta/2$ on each side of the spectrum. Unless otherwise specified, $\beta/2$ is taken as 0,5 %. The maximum occupied bandwidth includes all associated side bands above the appropriate emissions level and the frequency error or drift under extreme test conditions. EUT is connected to the measuring receiver via 50Ω attenuator(s).	

TESTED CABLE	FREQUENCY	SEVERITY	RESULT TAB.	VERDICT
99% Bandwidth / Low channel	902.3 MHz	Within the 902MHz-928MHz band	EMI4470	PASS
99% Bandwidth / Mid channel	908.5 MHz	Within the 902MHz-928MHz band	EMI4471	PASS
99% Bandwidth / High channel	914.9 MHz	Within the 902MHz-928MHz band	EMI4472	PASS

LABORATORY PARAMETERS:	REQUIRED PRIOR TO THE TEST	DURING THE TEST
Ambient Temperature	15 to 35 °C	20.3 °C
Relative Humidity	20 to 75 %	33.0 %
Atmospheric pressure	N/A	1013 hPa
Test method deviation: N/A		
Supplementary information: N/A		

TEST EQUIPMENT USED					
CATEGORY	BRAND	TYPE	IDENTIFIER	CAL. DATE	CAL. DUE
Antenna	ETS lindgren	3143B	17930	12/08/2021	12/10/2024
Cable	/	N-1m	3625	02/05/2023	02/07/2025
Cable	Techniwave	N-3.5m	18353	17/08/2023	17/10/2025
Cable	Techniwave	N-4m	18355	17/08/2023	17/10/2025
Receiver	Rohde & Schwarz	FSW43	14830	10/08/2022	10/10/2024
Shielded enclosure	COMTEST	FAR-3m	18014	17/08/2021	17/10/2024
Thermohygrometer	Testo	608-H2	12269	07/06/2022	07/08/2024
Thermohygrometer	Bioblock Scientific	Météostar	0963	25/09/2023	25/11/2025

Blank cells = Permanent validity

Page 47 on 49

Page 48 on 49

