Shenzhen GUOREN Certification Technology Service Co., Ltd.

101#, Building K & Building T, The Second Industrial Zone, Jiazitang Community, Fenghuang Street, Guangming District, Shenzhen, China

FCC PART 15 SUBPART C TEST REPORT

FCC PART 15.247

Report Reference No.....:	**GRCTR240402024-03**	
FCC ID..... :	**2BF3U-H1SE**	
Compiled by (position+printed name+signature)..:	Testing Engineer Jimmy Wang	
Supervised by (position+printed name+signature)..:	Project Engineer Kelley Zhang	
Approved by (position+printed name+signature)..:	Manager Sam Wang	
Date of issue.....:	May. 13, 2024	
Testing Laboratory Name.....:	**Shenzhen GUOREN Certification Technology Service Co., Ltd.**	
Address..... :	101#, Building K & Building T, The Second Industrial Zone, Jiazitang Community, Fenghuang Street, Guangming District, Shenzhen, China	
Applicant's name.....:	**Shenzhen Jingsha Technology Industry Co.,Ltd**	
Address..... :	1st Floor,A2 Block,Xinshidaigongrong Industrial Park,No.2 Shihuan Road,Shiyan Street,Baoan District,Shenzhen,Guangdong,China	
Test specification.....:		
Standard.....:	**FCC Part 15.247**	

Shenzhen GUOREN Certification Technology Service Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen GUOREN Certification Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen GUOREN Certification Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description.....:	**Mini PC**
Trade Mark.....:	JINGSHA
Manufacturer.....:	Shenzhen Jingsha Technology Industry Co.,Ltd
Model/Type reference..... :	Mini H1 SE
Listed Models ..... :	Mini H1, Mini H1 S, Mini H1 PRO, Mini H1 Ultra, Mini H1 SER, Mini P1 SE, Mini P1, Mini X1, Mini GT1, Mini H2 SE, Mini H2, Mini H2 S, Mini H2 PRO, Mini H2 Ultra, Mini H2 SER, Mini P2 SE, Mini P2, Mini X2 Mini GT2
Firmware Version.....:	RTL8852BE_EFUSE_V1.0
Hardware Version..... :	RTL8852BE_HW_V1.0
Modulation Type..... :	DSSS/ OFDM
Operation Frequency..... :	From 2412 - 2462MHz
Rating.....:	DC 19V from external circuit
Result.....:	**PASS**

TEST REPORT

Equipment under Test	:	Mini PC
Model /Type	:	Mini H1 SE
Listed Models	:	Mini H1, Mini H1 S, Mini H1 PRO, Mini H1 Ultra, Mini H1 SER, Mini P1 SE, Mini P1, Mini X1, Mini GT1, Mini H2 SE, Mini H2, Mini H2 S, Mini H2 PRO, Mini H2 Ultra, Mini H2 SER, Mini P2 SE, Mini P2, Mini X2 Mini GT2
Applicant	:	**Shenzhen Jingsha Technology Industry Co.,Ltd**
Address	:	1st Floor,A2 Block,Xinshidaigongrong Industrial Park,No.2 Shihuan Road,Shiyan Street,Baoan District,Shenzhen,Guangdong,China
Manufacturer	:	**Shenzhen Jingsha Technology Industry Co.,Ltd**
Address	:	1st Floor,A2 Block,Xinshidaigongrong Industrial Park,No.2 Shihuan Road,Shiyan Street,Baoan District,Shenzhen,Guangdong,China

Test Result:	**PASS**

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1 TEST STANDARDS 4

2 SUMMARY 5

2.1 General Remarks 5
2.2 Product Description 5
2.3 Short description of the Equipment under Test (EUT) 5
2.4 EUT configuration 5
2.5 EUT operation mode 6
2.6 Block Diagram of Test Setup 6
2.7 Related Submittal(s) / Grant (s) 6
2.8 Modifications 6

3 TEST ENVIRONMENT 7

3.1 Address of the test laboratory 7
3.2 Test Facility 7
3.3 Environmental conditions 7
3.4 Test Description 8
3.5 Statement of the measurement uncertainty 8
3.6 Equipments Used during the Test 9

4 TEST CONDITIONS AND RESULTS 11

4.1 AC Power Conducted Emission 11
4.2 Radiated Emission 14
4.3 Maximum Conducted Output Power 20
4.4 Power Spectral Density 23
4.5 6dB Bandwidth 31
4.6 Out-of-band Emissions 39
4.7 Antenna Requirement 64

5 TEST SETUP PHOTOS OF THE EUT 65

6 PHOTOS OF THE EUT 66

1 TEST STANDARDS

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.
ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices
KDB558074 D01 v05r02: Guidance for Compliance Measurements on Digital Transmission Systems (DTS) ,Frequency Hopping Spread Spectrum System(HFSS), and Hybrid System Devices Operating Under §15.247 of The FCC rules.

2 SUMMARY

2.1 General Remarks

Date of receipt of test sample	:	Apr. 17, 2024
Testing commenced on	:	Apr. 17, 2024
Testing concluded on	:	May. 13, 2024

2.2 Product Description

Product Name:	Mini PC
Model/Type reference:	Mini H1 SE
Listed Models:	Mini H1, Mini H1 S, Mini H1 PRO, Mini H1 Ultra, Mini H1 SER, Mini P1 SE, Mini P1, Mini X1, Mini GT1, Mini H2 SE, Mini H2, Mini H2 S, Mini H2 PRO, Mini H2 Ultra, Mini H2 SER, Mini P2 SE, Mini P2, Mini X2 Mini GT2(The products are identical in interior structure, electrical circuits and components, just model names and color are different.)
Power supply:	DC 19V from external circuit
Adapter Information:	M/N:SAW48C-190-2500U Input:AC 100-240V 50/60Hz 1.3A Output:19V/2.5A
Testing sample ID:	GRCTR240402024-1# (Engineer sample), GRCTR240402024-2# (Normal sample)
WIFI:	
Supported type:	802.11b/802.11g/802.11n(H20) /802.11n(H40)/802.11ax(H20) /802.11ax(H40)
Modulation:	802.11b: DSSS 802.11g/802.11n(H20) /802.11n(H40)/802.11ax(H20) /802.11ax(H40): OFDM
Operation frequency:	802.11b/802.11g/802.11n(H20)/802.11ax(H20): 2412MHz~2462MHz 802.11n(H40)/802.11ax(H40): 2422MHz~2452MHz
Channel number:	802.11b/802.11g/802.11n(H20)/802.11ax(H20): 11 802.11n(H40)/802.11ax(H40): 7
Channel separation:	5MHz
Antenna type:	FPC antenna
Antenna gain*(Supplied by the customer):	Ant 1: 1.34 dBi Ant 2: 4.61 dBi
Remark:*When the information provided by the customer was used to calculate test results, if the information provided by the customer is not accurate, shenzhen GUOREN Certification Technology Service Co., Ltd. does not assume any responsibility.	

2.3 Short description of the Equipment under Test (EUT)

This is a Mini PC.
For more details, refer to the user's manual of the EUT.

2.4 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - supplied by the lab

○	/	M/N:	/
		Manufacturer:	/

2.5 EUT operation mode

The Applicant provides communication tools software(SecureCRT) to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) for testing meet KDB558074 test requirement.

IEEE 802.11b/g/n H20/n H40/ax H20 /ax H40:

Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432		
6	2437		
7	2442		

2.6 Block Diagram of Test Setup



2.7 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

2.8 Modifications

No modifications were implemented to meet testing criteria.

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

Shenzhen GUOREN Certification Technology Service Co., Ltd.
101#, Building K & Building T, The Second Industrial Zone, Jiazitang Community, Fenghuang Street, Guangming District, Shenzhen, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 920798 Designation Number: CN1304

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA-Lab Cert. No.: 6202.01

Shenzhen GUOREN Certification Technology Service Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

ISED#: 27264 CAB identifier: CN0115
Shenzhen GUOREN Certification Technology Service Co., Ltd. has been listed by Innovation, Science and Economic Development Canada to perform electromagnetic emission measurement.

CNAS-Lab Code: L15631
Shenzhen GUOREN Certification Technology Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories for the Competence of Testing and Calibration Laboratories.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.10 and CISPR 16-1-4:2010.

3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	15-35 ℃
Relative Humidity	30-60 %
Air Pressure	950-1050mbar

3.4 Test Description

FCC PART 15.247		
FCC Part 15.207	AC Power Conducted Emission	PASS
FCC Part 15.247(a)(2)	6dB Bandwidth	PASS
FCC Part 15.247(d)	Spurious RF Conducted Emission	PASS
FCC Part 15.247(b)	Maximum Conducted Output Power	PASS
FCC Part 15.247(e)	Power Spectral Density	PASS
FCC Part 15.109/ 15.205/ 15.209	Radiated Emissions	PASS
FCC Part 15.247(d)	Band Edge	PASS
FCC Part 15.203/15.247 (b)	Antenna Requirement	PASS

Data Rate Used:
Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel
Maximum Peak Conducted Output Power Power Spectral Density 6dB Bandwidth Spurious RF conducted emission Radiated Emission 9KHz~1GHz& Radiated Emission 1GHz~10th Harmonic	11b/DSSS	1 Mbps	1/6/11
	11g/OFDM	6 Mbps	1/6/11
	11n(20MHz)/OFDM	6.5Mbps	1/6/11
	11n(40MHz)/OFDM	13.5Mbps	3/6/9
	11ax(20MHz)/OFDM	8.6 Mbps	1/6/11
	11ax(40MHz)/OFDM	17.2 Mbps	3/6/9
Band Edge	11b/DSSS	1 Mbps	1/11
	11g/OFDM	6 Mbps	1/11
	11n(20MHz)/OFDM	6.5Mbps	1/11
	11n(40MHz)/OFDM	13.5Mbps	3/6/9
	11ax(20MHz)/OFDM	8.6 Mbps	1/6/11
	11ax(40MHz)/OFDM	17.2 Mbps	3/6/9

3.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01” Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1” and TR-100028-02 “Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 “ and is documented in the Shenzhen GUOREN Certification Technology Service Co., Ltd.quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GUOREN Certification Technology Service Co., Ltd.:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.06 dB	(1)
Radiated Emission	1~18GHz	5.14 dB	(1)
Radiated Emission	18-40GHz	5.38 dB	(1)
Conducted Disturbance	0.15~30MHz	2.14 dB	(1)
Max output power	30MHz~18GHz	0.54 dB	(1)
Power spectral density	/	0.56 dB	(1)
Spectrum bandwidth	/	1.2%	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.6 Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Equipment No.	Calibration Date	Calibration Due Date
LISN	R&S	ENV216	GRCTEE009	2023/09/27	2024/09/26
LISN	R&S	ENV216	GRCTEE010	2023/09/27	2024/09/26
EMI Test Receiver	R&S	ESPI	GRCTEE017	2023/09/28	2024/09/27
EMI Test Receiver	R&S	ESCI	GRCTEE008	2023/09/27	2024/09/26
Spectrum Analyzer	Agilent	N9020A	GRCTEE002	2023/09/27	2024/09/26
Spectrum Analyzer	R&S	FSP	GRCTEE003	2023/09/28	2024/09/27
Vector Signal generator	Agilent	N5181A	GRCTEE007	2023/09/27	2024/09/26
Analog Signal Generator	R&S	SML03	GRCTEE006	2023/09/27	2024/09/26
Climate Chamber	QIYA	LCD-9530	GRCTES016	2023/09/27	2024/09/26
Ultra-Broadband Antenna	Schwarzbeck	VULB9163	GRCTEE018	2023/09/28	2026/09/27
Horn Antenna	Schwarzbeck	BBHA 9120D	GRCTEE019	2023/09/28	2026/09/27
Loop Antenna	Zhinan	ZN30900C	GRCTEE020	2023/10/15	2026/10/14
Horn Antenna	Beijing Hangwei Dayang	OBH100400	GRCTEE049	2023/09/28	2026/09/27
Amplifier	Schwarzbeck	BBV 9745	GRCTEE021	2023/09/27	2024/09/26
Amplifier	Taiwan chengyi	EMC051845B	GRCTEE022	2023/09/28	2024/09/27
Temperature/Humidity Meter	Huaguan	HG-308	GRCTES037	2023/09/27	2024/09/26
Directional coupler	NARDA	4226-10	GRCTEE004	2023/09/27	2024/09/26
High-Pass Filter	XingBo	XBLBQ-GTA18	GRCTEE053	2023/09/27	2024/09/26
High-Pass Filter	XingBo	XBLBQ-GTA27	GRCTEE054	2023/09/27	2024/09/26

Automated filter bank	Tonscend	JS0806-F	GRCTEE055	2023/09/27	2024/09/26
Power Sensor	Agilent	U2021XA	GRCTEE070	2023/09/27	2024/09/26
EMI Test Software	ROHDE & SCHWARZ	ESK1-V1.71	GRCTEE060	N/A	N/A
EMI Test Software	Fera	EZ-EMC	GRCTEE061	N/A	N/A

4 TEST CONDITIONS AND RESULTS

4.1 AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
2 Support equipment, if needed, was placed as per ANSI C63.10-2013
3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
4 The EUT received power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5 All support equipments received AC power from a second LISN, if any.
6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT.The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) and RSS-Gen Issue 5 AC Power Conducted Emission Limits is as following：

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
* Decreases with the logarithm of the frequency.		

TEST RESULTS

Remark:

1. All modes of 802.11b/g/n/ax were tested at Low, Middle, and High channel; only the worst result of 802.11b CH11 was reported as below:
2. Both 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz power supply have been tested, only the worst result of 120 VAC, 60 Hz was reported as below:

Power supply:	DC 19V From Adapter AC 120V/60Hz	Polarization	L



MEASUREMENT RESULT: "GRCT24417015_fin"

4/17/2024 6:09PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.278000	52.00	9.6	61	8.9	QP	L1	GND
0.766000	44.00	9.7	56	12.0	QP	L1	GND
1.934000	45.60	10.0	56	10.4	QP	L1	GND
2.906000	44.70	10.0	56	11.3	QP	L1	GND
6.358000	38.40	10.0	60	21.6	QP	L1	GND
13.614000	35.30	10.0	60	24.7	QP	L1	GND

MEASUREMENT RESULT: "GRCT24417015_fin2"

4/17/2024 6:09PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.330000	39.90	9.5	50	9.6	AV	L1	GND
0.782000	37.60	9.7	46	8.4	AV	L1	GND
1.822000	36.00	10.0	46	10.0	AV	L1	GND
3.782000	35.30	9.9	46	10.7	AV	L1	GND
6.122000	32.20	10.0	50	17.8	AV	L1	GND
23.098000	34.80	10.2	50	15.2	AV	L1	GND

Note:1).Level (dBµV)= Reading (dBµV)+ Transducer (dB)
2). Transducer (dB)=insertion loss of LISN (dB) + Cable loss (dB)
3). Margin(dB) = Limit (dBµV) - Level (dBµV)

Power supply:	DC 19V From Adapter AC 120V/60Hz	Polarization	N



MEASUREMENT RESULT: "GRCT24417014_fin"

4/17/2024 6:06PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.174000	53.20	9.5	65	11.6	QP	N	GND
0.770000	43.50	9.7	56	12.5	QP	N	GND
1.338000	44.40	10.0	56	11.6	QP	N	GND
4.018000	40.30	9.8	56	15.7	QP	N	GND
5.294000	35.10	10.0	60	24.9	QP	N	GND
13.394000	35.40	10.0	60	24.6	QP	N	GND

MEASUREMENT RESULT: "GRCT24417014_fin2"

4/17/2024 6:06PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.338000	38.30	9.5	49	11.0	AV	N	GND
0.370000	38.70	9.6	49	9.8	AV	N	GND
1.062000	32.80	10.0	46	13.2	AV	N	GND
2.110000	31.50	10.0	46	14.5	AV	N	GND
7.546000	31.00	10.0	50	19.0	AV	N	GND
22.594000	35.20	10.2	50	14.8	AV	N	GND

Note:1).Level (dBµV)= Reading (dBµV)+ Transducer (dB)

2). Transducer (dB)=insertion loss of LISN (dB) + Cable loss (dB)

3). Margin(dB) = Limit (dBµV) - Level (dBµV)

4.2 Radiated Emission

TEST CONFIGURATION

Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz, the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Anternna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz,Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz,Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz,Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

Transd=AF +CL-AG

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the100kHz bandwidth within the band that contains the highest level of desired power.

The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.

Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	20log(2400/F(KHz))+40log(300/3)	2400/F(KHz)
0.49-1.705	3	20log(24000/F(KHz))+ 40log(30/3)	24000/F(KHz)
1.705-30	3	20log(30)+ 40log(30/3)	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS

Remark:

1. This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
2. All three channels (lowest/middle/highest) of each mode were measured below 1GHz and recorded worst case at 802.11b low channel.
3. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.

For 30MHz-1GHz

Horizontal



Site LAB
Limit: FCC Part15 RE-Class B_30-1000MHz
EUT:
M/N:
Mode:
Note:

Polarization: ***Horizontal***
Power: AC120V/60Hz
Distance: 3m

Temperature: 24.5(C)
Humidity: 52 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	48.6719	41.19	-17.49	23.70	40.00	-16.30	peak	200	105	P	
2	88.9639	48.57	-20.91	27.66	43.50	-15.84	peak	200	123	P	
3	124.1330	55.03	-21.68	33.35	43.50	-10.15	peak	200	78	P	
4 *	249.4250	57.64	-18.31	39.33	46.00	-6.67	peak	200	257	P	
5	360.4476	51.97	-16.36	35.61	46.00	-10.39	peak	200	141	P	
6	517.4104	52.77	-14.25	38.52	46.00	-7.48	QP	200	203	P	

Note:1).Level (dBμV/m)= Reading (dBμV)+ Factor (dB/m)

2). Factor(dB/m)=Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)

3). Margin(dB) = Level (dBμV/m) - Limit (dBμV/m)

Vertical



Site LAB
Limit: FCC Part15 RE-Class B_30-1000MHz
EUT:
M/N:
Mode:
Note:

Polarization: *Vertical*
Power: AC120V/60Hz
Distance: 3m

Temperature: 24.5(C)
Humidity: 52 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	31.4884	51.82	-19.80	32.02	40.00	-7.98	QP	100	358	P	
2 *	48.3316	53.99	-17.49	36.50	40.00	-3.50	peak	100	271	P	
3	106.3850	52.92	-19.23	33.69	43.50	-9.81	peak	100	47	P	
4	251.1804	52.60	-18.26	34.34	46.00	-11.66	peak	100	153	P	
5 !	357.9287	57.98	-16.41	41.57	46.00	-4.43	peak	100	135	P	
6	517.6367	52.39	-14.25	38.14	46.00	-7.86	QP	100	19	P	

Note:1).Level (dBμV/m)= Reading (dBμV)+ Factor (dB/m)
2). Factor(dB/m)=Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB)
3). Margin(dB) = Level (dBμV/m) - Limit (dBμV/m)

For 1GHz to 25GHz

Note: 802.11b/802.11g/802.11n (H20)/802.11n (H40)/802.11ax (H20)/802.11ax (H40) Mode all have been tested, only worse case 802.11b mode is reported.

(above 1GHz)

Frequency(MHz):			2412		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4824.00	54.93	PK	74	19.07	76.16	28.37	5.10	54.70	-21.23
4824.00	42.52	AV	54	11.48	63.75	28.37	5.10	54.70	-21.23
7236.00	51.32	PK	74	22.68	65.81	34.10	6.42	55.01	-14.49
7236.00	40.32	AV	54	13.68	54.81	34.10	6.42	55.01	-14.49

Frequency(MHz):			2412		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4824.00	54.29	PK	74	19.71	75.52	28.37	5.10	54.70	-21.23
4824.00	42.15	AV	54	11.85	63.38	28.37	5.10	54.70	-21.23
7236.00	51.92	PK	74	22.08	66.41	34.10	6.42	55.01	-14.49
7236.00	39.17	AV	54	14.83	53.66	34.10	6.42	55.01	-14.49

Frequency(MHz):			2437		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4874.00	56.45	PK	74	17.55	76.72	28.76	5.35	54.38	-20.27
4874.00	43.28	AV	54	10.72	63.55	28.76	5.35	54.38	-20.27
7311.00	51.65	PK	74	22.35	65.28	34.40	6.83	54.86	-13.63
7311.00	41.00	AV	54	13.00	54.63	34.40	6.83	54.86	-13.63

Frequency(MHz):			2437		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4874.00	55.60	PK	74	18.40	75.87	28.76	5.35	54.38	-20.27
4874.00	42.21	AV	54	11.79	62.48	28.76	5.35	54.38	-20.27
7311.00	52.69	PK	74	21.31	66.32	34.40	6.83	54.86	-13.63
7311.00	41.99	AV	54	12.01	55.62	34.40	6.83	54.86	-13.63

Frequency(MHz):			2462		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4924.00	54.85	PK	74	19.15	74.30	29.54	5.66	54.65	-19.45
4924.00	41.57	AV	54	12.43	61.02	29.54	5.66	54.65	-19.45
7386.00	53.58	PK	74	20.42	66.72	34.51	7.25	54.9	-13.14
7386.00	41.63	PK	54	12.37	54.77	34.51	7.25	54.9	-13.14

Frequency(MHz):			2462		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4924.00	56.18	PK	74	17.82	75.63	29.54	5.66	54.65	-19.45
4924.00	42.11	AV	54	11.89	61.56	29.54	5.66	54.65	-19.45
7386.00	52.03	PK	74	21.97	65.17	34.51	7.25	54.9	-13.14
7386.00	43.13	PK	54	10.87	56.27	34.51	7.25	54.9	-13.14

1) Emission level (dBuV/m) = Meter Reading+ antenna Factor+ cable loss- preamp factor.
2) Margin value = Limits-Emission level.
3) -- Mean the PK detector measured value is below average limit.
4) The other emission levels were very low against the limit.
5) RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.

Results of Band Edges Test (Radiated)

Note: 802.11b/802.11g/802.11n (H20)/802.11n (H40)/802.11ax (H20)/802.11ax (H40) Mode all have been tested, only worse case 802.11b mode is reported.

Frequency(MHz):			**2412**		**Polarity:**		**HORIZONTAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390.00	54.26	PK	74	19.74	78.98	25.72	4.32	54.76	-24.72
2390.00	39.07	AV	54	14.93	63.79	25.72	4.32	54.76	-24.72
2400.00	55.35	PK	74	18.65	79.61	25.73	4.33	54.75	-24.26
2400.00	40.74	AV	54	13.26	65.00	25.73	4.33	54.75	-24.26
Frequency(MHz):			**2412**		**Polarity:**		**VERTICAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2390.00	55.31	PK	74	18.69	80.03	25.72	4.32	54.76	-24.72
2390.00	38.71	AV	54	15.29	63.43	25.72	4.32	54.76	-24.72
2400.00	56.50	PK	74	17.50	80.76	25.73	4.33	54.75	-24.26
2400.00	41.53	AV	54	12.47	65.79	25.73	4.33	54.75	-24.26
Frequency(MHz):			**2462**		**Polarity:**		**HORIZONTAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	53.96	PK	74	20.04	78.53	25.78	4.48	54.83	-24.57
2483.50	39.29	AV	54	14.71	63.86	25.78	4.48	54.83	-24.57
Frequency(MHz):			**2462**		**Polarity:**		**VERTICAL**		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2483.50	54.58	PK	74	19.42	79.15	25.78	4.48	54.83	-24.57
2483.50	39.67	AV	54	14.33	64.24	25.78	4.48	54.83	-24.57

Note：

1) Emission level (dBuV/m) = Meter Reading+ antenna Factor+ cable loss- preamp factor.
2) Margin value = Limits-Emission level.
3) -- Mean the PK detector measured value is below average limit.
4) The other emission levels were very low against the limit.
5) RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.

4.3 Maximum Conducted Output Power

Limit

The Maximum Peak Output Power Measurement is 30dBm.

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power sensor.

Test Configuration



Test Results

Ant 1

Type	Channel	Output power PK (dBm)	Limit (dBm)	Result
802.11b	01	14.69	30	Pass
	06	15.35		
	11	15.70		
802.11g	01	13.90	30	Pass
	06	13.96		
	11	14.40		
802.11n(HT20)	01	13.27	30	Pass
	06	13.78		
	11	14.22		
802.11n(HT40)	03	11.36	30	Pass
	06	11.46		
	09	12.15		
802.11ax(HT20)	01	12.51	30	Pass
	06	12.88		
	11	13.29		
802.11ax(HT40)	03	11.58	30	Pass
	06	11.59		
	09	12.10		

Ant 2

Type	Channel	Output power PK (dBm)	Limit (dBm)	Result
802.11b	01	12.68	30	Pass
	06	13.34		
	11	13.40		
802.11g	01	13.92	30	Pass
	06	13.08		
	11	12.73		
802.11n(HT20)	01	11.59	30	Pass
	06	12.99		
	11	12.74		
802.11n(HT40)	03	11.24	30	Pass
	06	11.55		
	09	11.87		
802.11ax(HT20)	01	12.75	30	Pass
	06	13.19		
	11	13.13		
802.11ax(HT40)	03	11.28	30	Pass
	06	11.48		
	09	11.97		

MIMO

Type	Channel	Output power PK(dBm) ANT1	Output power PK(dBm) ANT2	Output power PK(dBm) MIMO	Limit (dBm)	Result
802.11n(HT20)	01	13.27	11.59	15.52	30	Pass
	06	13.78	12.99	16.41		
	11	14.22	12.74	16.55		
802.11n(HT40)	03	11.36	11.24	14.31	30	Pass
	06	11.46	11.55	14.52		
	09	12.15	11.87	15.02		
802.11ax(HT20)	01	12.51	12.75	15.64	30	Pass
	06	12.88	13.19	16.05		
	11	13.29	13.13	16.22		
802.11ax(HT40)	03	11.58	11.28	14.44	30	Pass
	06	11.59	11.48	14.55		
	09	12.10	11.97	15.05		

Note:
1) Measured output power at difference data rate for each mode and recorded worst case for each mode.
2) Test results including cable loss.
3) Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40; 8.6Mbps at IEEE 802.11ax HT20; 17.2Mbps at IEEE 802.11ax HT40.

4.4 Power Spectral Density

Limit

The resulting peak PSD level shall not be greater than 8 dBm/3KHz.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW ≥ 3 kHz.
3. Set the VBW ≥ 3× RBW.
4. Set the span to 1.5 times the DTS channel bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
11. The resulting peak PSD level shall not be greater than 8 dBm/3KHz.

Test Configuration

Test Results

Ant 1

Type	Channel	Power Spectral Density (dBm/3KHz)	Limit (dBm/3KHz)	Result
802.11b	01	-18.90	8	Pass
	06	-17.50		
	11	-17.72		
802.11g	01	-15.29	8	Pass
	06	-16.85		
	11	-16.55		
802.11n(HT20)	01	-18.13	8	Pass
	06	-16.98		
	11	-17.43		
802.11n(HT40)	03	-18.39	8	Pass
	06	-19.57		
	09	-19.54		
802.11ax(HT20)	01	-17.92	8	Pass
	06	-18.44		
	11	-18.38		
802.11ax(HT40)	03	-19.10	8	Pass
	06	-19.88		
	09	-19.42		

Ant 2

Type	Channel	Power Spectral Density (dBm/3KHz)	Limit (dBm/3KHz)	Result
802.11b	01	-19.77	8	Pass
	06	-18.35		
	11	-18.52		
802.11g	01	-15.37	8	Pass
	06	-17.12		
	11	-17.77		
802.11n(HT20)	01	-19.55	8	Pass
	06	-18.52		
	11	-18.41		
802.11n(HT40)	03	-18.48	8	Pass
	06	-19.46		
	09	-19.17		
802.11ax(HT20)	01	-18.26	8	Pass
	06	-18.12		
	11	-18.12		
802.11ax(HT40)	03	-18.46	8	Pass
	06	-19.47		
	09	-18.52		

MIMO

Type	Channel	Power Spectral Density (dBm/3KHz) ANT1	Power Spectral Density (dBm/3KHz) ANT2	Power Spectral Density (dBm/3KHz) MIMO	Limit(dBm/3KHz)	Result
802.11n(HT20)	01	-18.13	-19.55	-15.77	8	Pass
	06	-16.98	-18.52	-14.67		
	11	-17.43	-18.41	-14.88		
802.11n(HT40)	03	-18.39	-18.48	-15.42	8	Pass
	06	-19.57	-19.46	-16.50		
	09	-19.54	-19.17	-16.34		
802.11ax(HT20)	01	-17.92	-18.26	-15.08	8	Pass
	06	-18.44	-18.12	-15.27		
	11	-18.38	-18.12	-15.24		
802.11ax(HT40)	03	-19.10	-18.46	-15.76	8	Pass
	06	-19.88	-19.47	-16.66		
	09	-19.42	-18.52	-15.94		

Note:
1) Measured peak power spectrum density at difference data rate for each mode and recorded worst case for each mode.
2) Test results including cable loss;
3) Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 13.5Mbps at IEEE 802.11n HT40; 8.6Mbps at IEEE 802.11ax HT20; 17.2Mbps at IEEE 802.11ax HT40.

Please refer to following plots;

Ant 1

802.11b	802.11g
	
CH01	CH01
	
CH06	CH06
	
CH11	CH11

802.11n(HT20)



CH01

802.11n(HT40)



CH03



CH06



CH06



CH11



CH09

802.11ax(HT20)	802.11ax(HT40)
	
CH01	*CH03*
	
CH06	*CH06*
	
CH11	*CH09*

Ant 2

802.11b	802.11g
	
CH01	CH01
	
CH06	CH06
	
CH11	CH11

802.11n(HT20)



CH01

802.11n(HT40)



CH03



CH06



CH06



CH11



CH09

802.11ax(HT20)



CH01

802.11ax(HT40)



CH03



CH06



CH06



CH11



CH09