RF MEASUREMENT REPORT

FCC ID:	2BF3W-7161
Applicant:	Wireless (US) Inc
Product:	SkyNet IAB Node
Model No.:	SkyNet SR7161, SkyNet SC7161
Brand Name:	SkyNet
FCC Classification:	Digital Transmission System (DTS)
FCC Rule Part(s):	Part 15 Subpart C (Section 15.247)
Result:	Complies
Received Date:	2024-06-28
Test Date:	2024-07-12 ~ 2024-08-10

Reviewed By: Vincent Yu

Approved By: Robin Wu

ACCREDITED
TESTING LABORATORY
CERTIFICATE #3628.01

The test results relate only to the samples tested.
This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.
The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2407RSU001-U1	V01	Initial Report	2024-08-27	Invalid
2407RSU001-U1	V02	Update Product Model	2024-08-28	Valid

CONTENTS

Description Page

1. General Information 5

1.1. Applicant 5
1.2. Manufacturer 5
1.3. Testing Facility 5
1.4. Product Information 6
1.5. Radio Specification under Test 7
1.6. Working Frequencies 7
1.7. Antenna Details 8

2. Test Configuration 9

2.1. Test Mode 9
2.2. Test System Connection Diagram 10
2.3. Test Software 10
2.4. Applied Standards 11
2.5. Test Environment Condition 11

3. Antenna Requirements 12

4. Measuring Instrument 13

5. Decision Rules and Measurement Uncertainty 14

5.1. Decision Rules 14
5.2. Measurement Uncertainty 14

6. Test Result 15

6.1. Summary 15
6.2. 6dB Bandwidth Measurement 16
6.2.1. Test Limit 16
6.2.2. Test Procedure 16
6.2.3. Test Setting 16
6.2.4. Test Setup 16
6.2.5. Test Result 16
6.3. Output Power Measurement 17
6.3.1. Test Limit 17
6.3.2. Test Procedure 17
6.3.3. Test Setting 17
6.3.4. Test Setup 17
6.3.5. Test Result 17
6.4. Power Spectral Density Measurement 18
6.4.1. Test Limit 18

6.4.2. Test Procedure 18
6.4.3. Test Setting 18
6.4.4. Test Setup 18
6.4.5. Test Result 19
6.5. Conducted Band Edge and Out-of-Band Emissions Measurement 20
6.5.1. Test Limit 20
6.5.2. Test Procedure 20
6.5.3. Test Settitng 20
6.5.4. Test Setup 21
6.5.5. Test Result 21
6.6. Radiated Spurious Emission Measurement 22
6.6.1. Test Limit 22
6.6.2. Test Procedure 22
6.6.3. Test Setting 22
6.6.4. Test Setup 24
6.6.5. Test Result 25
6.7. Radiated Restricted Band Edge Measurement 26
6.7.1. Test Limit 26
6.7.2. Test Procedure 27
6.7.3. Test Setting 27
6.7.4. Test Setup 28
6.7.5. Test Result 28
6.8. AC Conducted Emissions Measurement 29
6.8.1. Test Limit 29
6.8.2. Test Setup 29
6.8.3. Test Result 29

Appendix A – Test Result 30

A.1 Duty Cycle Test Result 30
A.2 6dB Bandwidth Test Result 32
A.3 Output Power Test Result 41
A.4 Power Spectral Density Test Result 43
A.5 Conducted Band Edge and Out-of-Band Emissions Test Result 76
A.6 Radiated Spurious Emission Test Result 141
A.7 Radiated Restricted Band Edge Test Result 151
A.8 AC Conducted Emissions Test Result 295

Appendix B – Test Setup Photograph 297

Appendix C – EUT Photograph 298

1. General Information

1.1. Applicant

Wireless (US) Inc

10 CORPORATE PARK STE 330 IRVINE, CA 92606, USA

1.2. Manufacturer

Wireless (US) Inc

10 CORPORATE PARK STE 330 IRVINE, CA 92606, USA

1.3. Testing Facility

☐	**Test Site – MRT Suzhou Laboratory**				
	Laboratory Location (Suzhou - Wuzhong) D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China **Laboratory Location (Suzhou - SIP)** 4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China **Laboratory Location (Suzhou - Wujiang)** Building 1, No.1 Xingdong Road, Wujiang, Suzhou, Jiangsu, People's Republic of China				
	Laboratory Accreditations				
	A2LA: 3628.01		CNAS: L10551		
	FCC: CN1166		ISED: CN0001		
	VCCI:	☐ R-20025	☐ G-20034	☐ C-20020	☐ T-20020
		☐ R-20141	☐ G-20134	☐ C-20103	☐ T-20104
☒	**Test Site – MRT Shenzhen Laboratory**				
	Laboratory Location (Shenzhen) 1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China				
	Laboratory Accreditations				
	A2LA: 3628.02		CNAS: L10551		
	FCC: CN1284		ISED: CN0105		
☐	**Test Site – MRT Taiwan Laboratory**				
	Laboratory Location (Taiwan) No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)				
	Laboratory Accreditations				
	TAF: 3261				
	FCC: 291082, TW3261		ISED: TW3261		

1.4. Product Information

Product Name	SkyNet IAB Node
Model No.	SkyNet SR7161, SkyNet SC7161
EUT Identification No.	20240628Sample#01 (For Conducted) 20240705Sample#01 (For Bandedge) 20240705Sample#03 (For Radiated)
Wi-Fi Specification	802.11a/b/g/n/ac/ax/be
Antenna Information	Refer to selection 1.7
Working Voltage	By PoE
Operating Temp.	-40 ~ 55°C
Operating Environment	Outdoor Use
Accessory	
PoE Injector	Model: UPI3301-PSC Input: AC 100-240V, 50/60Hz Output: 54V, DC

Remark:

1. The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.
2. SkyNet SR7161 with built-in omnidirectional antenna, SkyNet SC7161 with built-in directional antenna and 2.4G Wi-Fi is disabled by SW based on SkyNet SR7161 hardware. The circuit parts of SkyNet SR7161 and SkyNet SC7161 are the same.
3. This report was assessed the SkyNet SR7161 model.

1.5. Radio Specification under Test

Frequency Range	802.11b/g/n-HT20/ax-HE20/be-EHT20: 2412 ~ 2462MHz 802.11n-HT40/ax-HE40/be-EHT40: 2422 ~ 2452MHz	
Channel Number	802.11b/g/n-HT20/ax-HE20/be-EHT20: 11 802.11n-HT40/ax-HE40/be-EHT40: 7	
Type of Modulation	802.11b: DSSS 802.11g/n: OFDM 802.11ax/be: OFDMA	
Data Rate	802.11b: 1/2/5.5/11Mbps 802.11g: 6/9/12/18/24/36/48/54Mbps 802.11n: up to 600Mbps 802.11ax: up to 1147.2Mbps 802.11be: up to 1376Mbps	
Channel Puncturing Function	☐ Supported	☒ Unsupported
Support RU	☒ Full RU	☐ Partial RU

1.6. Working Frequencies

802.11b/g/n-HT20/ax-HE20/be-EHT20

Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10	2457 MHz	11	2462 MHz	--	--

802.11n-HT40/ax-HE40/be-EHT40

Channel	Frequency	Channel	Frequency	Channel	Frequency
03	2422 MHz	04	2427 MHz	05	2432 MHz
06	2437 MHz	07	2442 MHz	08	2447 MHz
09	2452 MHz	--	--	--	--

1.7. Antenna Details

Antenna Type	Frequency Range (MHz)	Antenna Gain (dBi)				Directional Gain (dBi)		30°elevation Gain (dBi)
		Ant 0	Ant 1	Ant 2	Ant 3	For Power	For PSD	
Model No.: SkyNet SR7161								
Built-in omni antenna	2412 ~ 2462	7.53	6.85	7.26	6.50	7.53	13.55	--
	5150 ~ 5850	6.97	7.65	7.80	8.12	8.12	14.14	7.65
	5925 ~ 6425	8.01	9.30	7.79	9.86	9.86	15.88	9.62
	6525 ~ 6875	6.51	8.81	6.78	8.71	8.81	14.83	8.70
Model No.: SkyNet SC7161								
Built-in directional antenna	5150 ~ 5850	8.58	10.19	10.12	10.32	10.32	16.34	3.92
	5925 ~ 6425	12.53	11.50	11.91	11.55	12.53	18.55	1.23
	6525 ~ 6875	12.24	11.25	12.72	11.29	12.72	18.74	-0.63

Note 1: The antenna gain and directional gain refer to manufacturer's antenna specification.

Note 2: The EUT supports Cyclic Delay Diversity (CDD) mode for 802.11a/b/g/n/ac/ax/be.

Note 3: Software automatically backs power down based on CDD power for beamforming operation.

Note 4: The transmit power of SkyNet SC7161 will be adjusted according to the difference in antenna gain between the two models.

2. Test Configuration

2.1. Test Mode

CDD Mode
Mode 1: Transmit by 802.11b _Nss=1 (1Mbps)
Mode 2: Transmit by 802.11g _Nss=1 (6Mbps)
Mode 3: Transmit by 802.11n-HT20 _Nss=1 (MCS0)
Mode 4: Transmit by 802.11n-HT40 _Nss=1 (MCS0)
Mode 5: Transmit by 802.11ax-HE20 _Nss=1 (MCS0)
Mode 6: Transmit by 802.11ax-HE40 _Nss=1 (MCS0)
Mode 7: Transmit by 802.11be-EHT20_Nss=1 (MCS0)
Mode 8: Transmit by 802.11be-EHT40_Nss=1 (MCS0)
Note: 1. The modulation and the data rate picked for testing are determined by the Max. RF conducted power. 2. For CDD mode, this device supports 4 Nss and power level is the same of spatial multiplexing. The worst case is Nss=1. 3. As Designated by manufacturer, the lowest data rate was the worst condition, so all the tests were done with lowest data rate.

2.2. Test System Connection Diagram

The device was tested per the guidance ANSI C63.10: 2013 was used to reference the appropriate EUT setup for radiated emissions testing and AC line conducted testing.

Connection Diagram



Cable Type		Cable Description	Length
A	LAN Cable	Non shielded	1.5m
B	LAN Cable	Non shielded	> 10m
C	LAN Cable	Non shielded	> 10m
D	USB Cable	Shielded	> 10m
Product		Manufacturer	Model No.
1	Notebook	HP	ZHAN99 G1
2	Notebook	HP	735G5

2.3. Test Software

The test utility software used during testing was “QSPR”, and the version was 6.00.00130.1.

Final power setting please refer to operational description.

2.4. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15.247
- KDB 558074 D01v05r02
- KDB 662911 D01v02r01
- ANSI C63.10-2013

2.5. Test Environment Condition

Ambient Temperature	15 ~ 35°C
Relative Humidity	20 ~ 75%RH

3. Antenna Requirements

Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The antenna of the device is **permanently attached.**
- There are no provisions for connection to an external antenna.

Conclusion:

The unit complies with the requirement of §15.203.

4. Measuring Instrument

Instrument	Manufacturer	Model No.	Asset No.	Cali. Interval	Cali. Due Date	Test Site
Loop Antenna	Schwarzbeck	FMZB 1519	MRTSUE06025	1 year	2024-09-17	NS-AC1
TRILOG Antenna	Schwarzbeck	VULB 9162	MRTSUE06573	1 year	2025-05-12	NS-AC1
Horn Antenna	Schwarzbeck	BBHA 9120D	MRTSUE06572	1 year	2025-03-15	NS-AC1
Horn Antenna	Schwarzbeck	BBHA 9170	MRTSUE06292	1 year	2024-10-21	NS-AC1
Anechoic Chamber	BOOMWAVE	NS-AC1	MRTSUE06496	1 year	2025-07-05	NS-AC1
Preamplifier	Schwarzbeck	BBV 9718	MRTSUE06574	1 year	2025-07-06	NS-AC1
Preamplifier	EMCI	EMC184045SE	MRTSUE06641	1 year	2025-01-07	NS-AC1
EMI Test Receiver	R&S	ESR3	MRTSUE06575	1 year	2025-06-10	NS-AC1
Signal Analyzer	Agilent	N9010A	MRTSUE06195	1 year	2024-12-10	NS-AC1
Thermohygrometer	testo	608-H1	MRTSUE11294	1 year	2025-05-14	NS-AC1
Two-Line V-Network	R&S	ENV216	MRTSUE06578	1 year	2025-04-06	NS-SR2
Thermohygrometer	testo	608-H1	MRTSUE11106	1 year	2025-04-08	NS-SR2
Shielding Room	BOOMWAVE	NS-SR2	MRTSUE06551	5 years	2029-06-10	NS-SR2
Thermohygrometer	DELI	NO.8813	MRTSUE06783	1 year	2024-12-05	NS-TR2
Temperature Chamber	OUKE	OK-TH-100C	MRTSUE06899	1 year	2025-04-06	NS-TR2
Signal Analyzer	Keysight	N9020A	MRTSUE10075	1 year	2025-07-16	NS-AC1
USB Power Sensor	Keysight	U2021XA	MRTSUE06581	1 year	2025-06-29	NS-TR2
Attenuator	MVE	MVE2213	MRTSUE11062	1 year	2025-06-06	NS
Attenuator	MVE	MVE2213	MRTSUE11063	1 year	2025-06-06	NS
Attenuator	MVE	MVE2213	MRTSUE11064	1 year	2025-06-06	NS

Software	Version	Function
EMI Software	V3.0.0	EMI Test Software
Controller_T-E-TAC-2	1.02	RE Antenna & Turntable
BenchVue Power Meter	2021	Power
Agilent Power Panel	V 3.9	Power

5. Decision Rules and Measurement Uncertainty

5.1. Decision Rules

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

5.2. Measurement Uncertainty

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

AC Conducted Emission Measurement
The maximum measurement uncertainty is evaluated as: 9kHz~150kHz: 3.58dB 150kHz~30MHz: 3.20dB
Radiated Emission Measurement
The maximum measurement uncertainty is evaluated as: Coaxial: 9kHz~30MHz: 2.61dB Coplanar: 9kHz~30MHz: 2.62dB Horizontal: 30MHz~200MHz: 3.49dB 200MHz~1GHz: 4.03dB 1GHz~40GHz: 4.70dB Vertical: 30MHz~200MHz: 4.07dB 200MHz~1GHz: 5.42dB 1GHz~40GHz: 4.63dB
Spurious Emissions, Conducted
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 2.3dB
Output Power
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 1.5dB
Power Spectrum Density
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 2.3dB
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)): 1.7%

6. Test Result

6.1. Summary

FCC Section(s)	Test Description	Test Condition	Verdict
15.247(a)(2)	6dB Bandwidth	Conducted	Pass
15.247(b)(3)	Output Power		Pass
15.247(e)	Power Spectral Density		Pass
15.247(d)	Band Edge / Out-of-Band Emissions		Pass
15.205 15.209	General Field Strength (Restricted Bands and Radiated Emission)	Radiated	Pass
15.207	AC Conducted Emissions 150kHz - 30MHz	Line Conducted	Pass

Notes:

1. The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
2. For radiated emission tests, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst-case emissions.

6.2. 6dB Bandwidth Measurement

6.2.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.

6.2.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.8

6.2.3. Test Setting

1. The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 6. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Set RBW = 100 kHz
3. VBW ≥ 3 × RBW
4. Detector = Peak
5. Trace mode = Max hold
6. Sweep = Auto couple
7. Allow the trace to stabilize.

6.2.4. Test Setup



6.2.5. Test Result

Refer to Appendix A.2.

6.3. Output Power Measurement

6.3.1. Test Limit

The maximum output power shall be less 1 Watt (30dBm).

The conducted output power limit specified in paragraph FCC Part 15.247(b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs FCC Part 15.247(b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.3.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.9.2.3.2

6.3.3. Test Setting

Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.

6.3.4. Test Setup



6.3.5. Test Result

Refer to Appendix A.3.

6.4. Power Spectral Density Measurement

6.4.1. Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.

The same method of determining the conducted output power shall be used to determine the power spectral density.

6.4.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.10.5

6.4.3. Test Setting

1. Measure the duty cycle (x) of the transmitter output signal.
2. Set instrument center frequency to DTS channel center frequency.
3. Set span to at least 1.5 times the OBW.
4. RBW = 10 kHz.
5. VBW = 30 kHz.
6. Detector = RMS.
7. Ensure that the number of measurement points in the sweep ≥ 2 x span/RBW.
8. Sweep time = auto couple.
9. Don't use sweep triggering. Allow sweep to "free run".
10. Employ trace averaging (RMS) mode over a minimum of 100 traces.
11. Use the peak marker function to determine the maximum amplitude level.
12. Add 10 log (1/x), where x is the duty cycle measured in step (a, to the measured PSD to compute the average PSD during the actual transmission time. If measured value exceeds requirement specified by regulatory agency, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).

6.4.4. Test Setup



6.4.5. Test Result

Refer to Appendix A.4.

6.5. Conducted Band Edge and Out-of-Band Emissions Measurement

6.5.1. Test Limit

The limit for out-of-band spurious emissions at the band edge is 30dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth per the PSD procedure.

6.5.2. Test Procedure

ANSI C63.10-2013 - Section 11.11

6.5.3. Test Settitng

Reference level measurement

1. Set instrument center frequency to DTS channel center frequency
2. Set the span to ≥ 1.5 times the DTS bandwidth
3. Set the RBW = 100 kHz
4. Set the VBW ≥ 3 x RBW
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Allow trace to fully stabilize

Emission level measurement

1. Set the center frequency and span to encompass frequency range to be measured
2. RBW = 100kHz
3. VBW = 300kHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

6.5.4. Test Setup



6.5.5. Test Result

Refer to Appendix A.5.

6.6. Radiated Spurious Emission Measurement

6.6.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [μV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

6.6.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.11 & 11.12

ANSI C63.10 - 2013 - Section 6.3 (General Requirements)

ANSI C63.10 - 2013 - Section 6.4 (Standard test method below 30MHz)

ANSI C63.10 - 2013 - Section 6.5 (Standard test method above 30MHz to 1GHz)

ANSI C63.10 - 2013 - Section 6.6 (Standard test method above 1GHz)

6.6.3. Test Setting

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000MHz	1MHz

Quasi-Peak Measurements below 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1MHz
3. RBW = as specified in Table 1
4. Detector = CISPR quasi-peak
5. Sweep time = auto couple
6. Trace was allowed to stabilize

Peak Measurements above 1GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Sweep time = Auto couple
6. Trace mode = Max hold
7. Trace was allowed to stabilize

Average Measurements above 1GHz (Method VB)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; if the EUT is configured to transmit with duty cycle ≥ 98%, set VBW = 10Hz

   If the EUT duty cycle is < 98%, set VBW ≥ 1/T. T is the minimum transmission duration.
4. As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = Auto
7. Trace mode = Max hold
8. Trace was allowed to stabilize

6.6.4. Test Setup

Below 30MHz Test Setup:



Below 1GHz Test Setup:



Above 1GHz Test Setup:



6.6.5. Test Result

Refer to Appendix A.6.

6.7. Radiated Restricted Band Edge Measurement

6.7.1. Test Limit

For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
[1] 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	([2])
13.36 - 13.41	--	--	--

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [μV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

6.7.2. Test Procedure

ANSI C63.10-2013 Section 6.3 & 6.6 & 11.13

6.7.3. Test Setting

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW; If the EUT is configured to transmit with duty cycle ≥ 98%, set VBW = 10 Hz.

   If the EUT duty cycle is < 98%, set VBW ≥ 1/T. T is the minimum transmission duration.
4. As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Allow max hold to run for at least 50 times (1/duty cycle) traces

6.7.4. Test Setup



6.7.5. Test Result

Refer to Appendix A.7.

6.8. AC Conducted Emissions Measurement

6.8.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dBμV)	AV (dBμV)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50
Note 1: The lower limit shall apply at the transition frequencies.		
Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.		

6.8.2. Test Setup



6.8.3. Test Result

Refer to Appendix A.8.

Appendix A – Test Result

A.1 Duty Cycle Test Result

Test Site	NS-SR1	Test Engineer	Summer Tang
Test Date	2024-07-12		

Test Mode	Duty Cycle
802.11b	91.60%
802.11g	98.65%
802.11n-HT20	98.00%
802.11n-HT40	97.83%
802.11ax-HE20	98.19%
802.11ax-HE40	98.55%
802.11be-EHT20	97.30%
802.11be-EHT40	97.84%

Duty Cycle (T = Transmission Duration)	
802.11b (T = 687.4μs)	802.11g (T = 1.968ms)
	

Duty Cycle (T = Transmission Duration)	
802.11n-HT20 (T = 5.400ms)	802.11n-HT40 (T = 5.410ms)
	
802.11ax-HE20 (T = 5.420ms)	802.11ax-HE40 (T = 5.420ms)
	
802.11be-EHT20 (T = 5.400ms)	802.11be-EHT40 (T = 5.440ms)
	

A.2 6dB Bandwidth Test Result

Test Site	NS-SR1	Test Engineer	Summer Tang
Test Date	2024-07-22		

Test Mode	Data Rate / MCS	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
11b	1Mbps	01	2412	7.606	≥ 0.5
11b	1Mbps	06	2437	7.607	≥ 0.5
11b	1Mbps	11	2462	8.073	≥ 0.5
11g	6Mbps	01	2412	16.39	≥ 0.5
11g	6Mbps	06	2437	16.38	≥ 0.5
11g	6Mbps	11	2462	16.37	≥ 0.5
11n-HT20	MCS0	01	2412	17.65	≥ 0.5
11n-HT20	MCS0	06	2437	17.62	≥ 0.5
11n-HT20	MCS0	11	2462	17.62	≥ 0.5
11n-HT40	MCS0	03	2422	36.38	≥ 0.5
11n-HT40	MCS0	06	2437	36.38	≥ 0.5
11n-HT40	MCS0	09	2452	36.35	≥ 0.5
11ax-HE20	MCS0	01	2412	19.08	≥ 0.5
11ax-HE20	MCS0	06	2437	19.03	≥ 0.5
11ax-HE20	MCS0	11	2462	19.07	≥ 0.5
11ax-HE40	MCS0	03	2422	38.22	≥ 0.5
11ax-HE40	MCS0	06	2437	38.21	≥ 0.5
11ax-HE40	MCS0	09	2452	38.18	≥ 0.5
11be-EHT20	MCS0	01	2412	19.10	≥ 0.5
11be-EHT20	MCS0	06	2437	19.05	≥ 0.5
11be-EHT20	MCS0	11	2462	19.07	≥ 0.5
11be-EHT40	MCS0	03	2422	38.19	≥ 0.5
11be-EHT40	MCS0	06	2437	38.21	≥ 0.5
11be-EHT40	MCS0	09	2452	38.16	≥ 0.5

802.11b 6dB Bandwidth	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11g 6dB Bandwidth	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11n-HT20 6dB Bandwidth	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11n-HT40 6dB Bandwidth	
Channel 03 (2422MHz)	Channel 06 (2437MHz)
	
Channel 09 (2452MHz)	
	

802.11ax-HE20 6dB Bandwidth	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11ax-HE40 6dB Bandwidth	
Channel 03 (2422MHz)	Channel 06 (2437MHz)
	
Channel 09 (2452MHz)	
	

802.1be-EHT20 6dB Bandwidth	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11be-EHT40 6dB Bandwidth	
Channel 03 (2422MHz)	Channel 06 (2437MHz)
	
Channel 09 (2452MHz)	

A.3 Output Power Test Result

Test Site	NS-SR1	Test Engineer	Summer Tang
Test Date	2024-07-12 ~ 2024-07-24		

Test Mode	Data Rate / MCS	Channel No.	Freq. (MHz)	Average Power (dBm)				Total Average Power (dBm)	Limit (dBm)
				Ant 0	Ant 1	Ant 2	Ant 3		
11b	1Mbps	01	2412	14.74	14.67	14.69	14.77	20.74	≤ 28.47
11b	1Mbps	06	2437	15.65	15.83	15.86	15.65	21.77	≤ 28.47
11b	1Mbps	11	2462	14.48	14.76	14.77	14.56	20.66	≤ 28.47
11g	6Mbps	01	2412	17.95	18.03	18.02	17.83	23.98	≤ 28.47
11g	6Mbps	02	2417	22.11	22.17	22.13	21.96	28.11	≤ 28.47
11g	6Mbps	06	2437	21.86	21.99	22.06	21.84	27.96	≤ 28.47
11g	6Mbps	09	2452	20.63	21.01	21.02	20.81	26.89	≤ 28.47
11g	6Mbps	10	2457	18.49	18.98	18.99	18.81	24.84	≤ 28.47
11g	6Mbps	11	2462	16.65	16.89	16.97	16.72	22.83	≤ 28.47
11n-HT20	MCS0	01	2412	17.92	18.08	18.04	17.89	24.00	≤ 28.47
11n-HT20	MCS0	02	2417	22.11	22.20	22.18	22.02	28.15	≤ 28.47
11n-HT20	MCS0	06	2437	21.70	22.10	22.14	22.13	28.04	≤ 28.47
11n-HT20	MCS0	09	2452	20.70	21.09	21.02	20.83	26.93	≤ 28.47
11n-HT20	MCS0	10	2457	18.54	18.90	19.05	18.93	24.88	≤ 28.47
11n-HT20	MCS0	11	2462	15.74	15.94	16.20	15.85	21.96	≤ 28.47
11n-HT40	MCS0	03	2422	16.01	16.24	16.37	16.17	22.22	≤ 28.47
11n-HT40	MCS0	06	2437	17.96	18.01	18.34	18.10	24.13	≤ 28.47
11n-HT40	MCS0	09	2452	14.92	15.40	15.33	15.03	21.20	≤ 28.47
11ax-HE20	MCS0	01	2412	17.01	17.34	17.19	16.96	23.15	≤ 28.47
11ax-HE20	MCS0	02	2417	20.11	20.22	20.07	20.08	26.14	≤ 28.47
11ax-HE20	MCS0	06	2437	21.25	21.48	21.57	21.28	27.42	≤ 28.47
11ax-HE20	MCS0	09	2452	19.78	20.24	20.14	19.78	26.01	≤ 28.47
11ax-HE20	MCS0	10	2457	17.57	17.98	18.11	17.87	23.91	≤ 28.47
11ax-HE20	MCS0	11	2462	14.89	15.12	15.22	14.92	21.06	≤ 28.47
11ax-HE40	MCS0	03	2422	16.12	16.33	16.47	16.18	22.30	≤ 28.47
11ax-HE40	MCS0	06	2437	17.13	17.14	17.42	17.26	23.26	≤ 28.47
11ax-HE40	MCS0	09	2452	14.94	15.41	15.34	15.00	21.20	≤ 28.47

Test Mode	Data Rate / MCS	Channel No.	Freq. (MHz)	Average Power (dBm)				Total Average Power (dBm)	Limit (dBm)
				Ant 0	Ant 1	Ant 2	Ant 3		
11be-EHT20	MCS0	01	2412	17.09	17.32	17.27	16.94	23.18	≤ 28.47
11be-EHT20	MCS0	02	2417	20.19	20.33	20.18	20.15	26.23	≤ 28.47
11be-EHT20	MCS0	06	2437	21.14	21.52	21.54	21.48	27.44	≤ 28.47
11be-EHT20	MCS0	09	2452	19.73	20.26	20.09	19.82	26.00	≤ 28.47
11be-EHT20	MCS0	10	2457	15.79	16.24	16.14	16.08	22.09	≤ 28.47
11be-EHT20	MCS0	11	2462	14.96	15.25	15.26	15.01	21.14	≤ 28.47
11be-EHT40	MCS0	03	2422	15.83	16.15	16.19	16.01	22.07	≤ 28.47
11be-EHT40	MCS0	06	2437	17.80	17.83	18.17	17.95	23.96	≤ 28.47
11be-EHT40	MCS0	08	2447	16.81	16.93	17.25	17.06	23.04	≤ 28.47
11be-EHT40	MCS0	09	2452	14.85	15.18	15.16	14.80	21.02	≤ 28.47

Note: Total Average Power (dBm) = $10*\log\{10^{(\text{Ant 0 Average Power }/10)} + 10^{(\text{Ant 1 Average Power }/10)} + 10^{(\text{Ant 2 Average Power }/10)} + 10^{(\text{Ant 3 Average Power }/10)}\}$ (dBm).

A.4 Power Spectral Density Test Result

Test Site	NS-SR1	Test Engineer	Summer Tang
Test Date	2024-07-22 ~ 2024-08-05		

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	PSD (dBm/ 10kHz)				Duty Cycle (%)	10*log (1/x)	Total PSD (dBm/10kHz)	Limit (dBm/3kHz)
				Ant 0	Ant 1	Ant 2	Ant 3				
11b	1Mbps	01	2412	-10.604	-10.836	-11.110	-10.874	91.60	0.38	-4.45	≤ 0.45
11b	1Mbps	06	2437	-10.139	-9.830	-9.890	-9.859	91.60	0.38	-3.53	≤ 0.45
11b	1Mbps	11	2462	-10.901	-10.923	-10.733	-11.007	91.60	0.38	-4.49	≤ 0.45
11g	6Mbps	01	2412	-11.337	-11.381	-11.341	-11.461	98.65	0.06	-5.36	≤ 0.45
11g	6Mbps	06	2437	-6.840	-6.839	-6.992	-7.334	98.65	0.06	-0.98	≤ 0.45
11g	6Mbps	11	2462	-12.705	-12.252	-12.040	-12.268	98.65	0.06	-6.29	≤ 0.45
11n-HT20	MCS0	01	2412	-11.744	-11.434	-11.179	-11.561	98.00	0.09	-5.45	≤ 0.45
11n-HT20	MCS0	06	2437	-7.297	-7.315	-7.354	-7.285	98.00	0.09	-1.29	≤ 0.45
11n-HT20	MCS0	11	2462	-13.723	-13.367	-13.179	-13.213	98.00	0.09	-7.34	≤ 0.45
11n-HT40	MCS0	03	2422	-16.586	-16.143	-16.101	-16.115	97.83	0.10	-10.12	≤ 0.45
11n-HT40	MCS0	06	2437	-14.333	-14.210	-13.354	-14.351	97.83	0.10	-7.93	≤ 0.45
11n-HT40	MCS0	09	2452	-17.511	-16.753	-17.230	-17.404	97.83	0.10	-11.10	≤ 0.45
11ax-HE20	MCS0	01	2412	-13.396	-13.003	-12.925	-12.918	98.19	0.08	-7.04	≤ 0.45
11ax-HE20	MCS0	06	2437	-9.082	-8.685	-8.443	-9.089	98.19	0.08	-2.80	≤ 0.45
11ax-HE20	MCS0	11	2462	-14.954	-15.064	-14.761	-15.153	98.19	0.08	-8.96	≤ 0.45
11ax-HE40	MCS0	03	2422	-17.093	-16.834	-16.516	-17.029	98.55	0.06	-10.84	≤ 0.45
11ax-HE40	MCS0	06	2437	-15.425	-15.449	-15.414	-15.780	98.55	0.06	-9.49	≤ 0.45
11ax-HE40	MCS0	09	2452	-17.820	-17.144	-17.629	-17.948	98.55	0.06	-11.60	≤ 0.45
11be-EHT20	MCS0	01	2412	-13.250	-13.213	-12.913	-12.469	97.30	0.12	-6.81	≤ 0.45
11be-EHT20	MCS0	06	2437	-8.978	-8.286	-8.434	-8.810	97.30	0.12	-2.48	≤ 0.45
11be-EHT20	MCS0	11	2462	-15.531	-14.852	-14.900	-14.979	97.30	0.12	-8.92	≤ 0.45
11be-EHT40	MCS0	03	2422	-17.139	-17.146	-16.693	-17.350	97.84	0.09	-10.96	≤ 0.45
11be-EHT40	MCS0	06	2437	-14.761	-15.234	-14.803	-14.954	97.84	0.09	-8.82	≤ 0.45
11be-EHT40	MCS0	09	2452	-18.030	-17.464	-17.898	-18.154	97.84	0.09	-11.76	≤ 0.45

Note 1:

When EUT duty cycle ≥ 98%, Total PSD (dBm / 10kHz) = 10*log {$10^{(\text{Ant 0 PSD}/10)}$ + $10^{(\text{Ant 1 PSD}/10)}$ + $10^{(\text{Ant 2 PSD}/10)}$ + $10^{(\text{Ant 3 PSD}/10)}$} (dBm / 10kHz).

When EUT duty cycle < 98%, Total PSD (dBm / 10kHz) = 10*log {$10^{(\text{Ant 0 PSD}/10)}$ + $10^{(\text{Ant 1 PSD}/10)}$ + $10^{(\text{Ant 2 PSD}/10)}$ + $10^{(\text{Ant 3 PSD}/10)}$} (dBm / 10kHz) + 10*log (1/Duty Cycle).

Note 2: Limit (dBm/3kHz) = 8 – (13.55-6) = 0.45 dBm/3kHz.

802.11b - AVGPSD - Ant 0	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
Channel 11 (2462MHz)	
	

802.11g - AVGPSD - Ant 0	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11n-HT20 - AVGPSD - Ant 0	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11n-HT40 - AVGPSD - Ant 0	
Channel 03 (2422MHz)	Channel 06 (2437MHz)
	
Channel 09 (2452MHz)	
	

802.11ax-HE20 - AVGPSD - Ant 0	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11ax-HE40 - AVGPSD - Ant 0	
Channel 03 (2422MHz)	Channel 06 (2437MHz)
	
Channel 09 (2452MHz)	
	

802.11be-EHT20 - AVGPSD - Ant 0	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11be-EHT40 - AVGPSD - Ant 0	
Channel 03 (2422MHz)	Channel 06 (2437MHz)
	
Channel 09 (2452MHz)	
	

802.11b - AVGPSD - Ant 1	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
Channel 11 (2462MHz)	
	

802.11g - AVGPSD - Ant 1	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)	
	

802.11n-HT20 - AVGPSD - Ant 1	
Channel 01 (2412MHz)	Channel 06 (2437MHz)
	
Channel 11 (2462MHz)