

客 户
CUSTOMER

KFT-067

ROHS

SPECIFICATION FOR APPROVAL

型 号
MODEL NO. : 43.5X5.3X0.7

柯菲特料号
KEFEITE NO. : 067-43.5-0.08X24PX2SX10TS-6.7uH-9mm

客户料号
CUSTOMER P/N: 1130200060

日期
DATE : 2024/11/13

版 本
REV : A1

※产品符合: ☒RoHS ☐PAHS ☐6P ☐REACH

确认后签名, 并返回一份。

PLEASE RETURN TO US COPY OF "SPECIFICATION FOR APPROVAL" WITH YOUR APPROVED SIGNATURES.

	"√"	CUSTOMER'S SIGNATURE	NOTE
FULL APPROVED			
CONDITIONAL APPROVED			
REJECTED			

深圳市柯菲特电子有限公司
SHENZHEN KEFEITE ELELECTRONICS CO., LTD

深圳、宝安、石岩官田新时代工业区C幢2楼

FactoryAddress:2/F,New era industrial area C Building
Guantiancommunity, Shenzhen.

TEL:86-755-27352660

FAX:86-755-27352742

HTTP:WWW.Kefeite.net(了解更多资讯, 请浏览本公司网站)



深圳市柯菲特电子有限公司

SHENZHEN KEFEITE ELECTRONICS CO., LTD

CUSTOMER:	KFT-067	VERSION:	A1	
CUSTOMER NO:	1130200060	PAGE:	2/4	
KFT P/N:	67-43.5-0.08X24PX2SX10TS-6.7uH-9mm	Date:	2024/11/13	
VERSION	MODIFY THE CONTENT	Date	Drawn By	Checked By
A1	新 版 本	2024/11/13	胡国强	周 渺 



NOTES:

深圳市柯菲特电子有限公司

SHENZHEN KEFEITE ELECTRONICS CO., LTD

CUSTOMER:	KFT-067	VERSION:	A1
CUSTOMER NO:	1130200060	PAGE:	3/4
KFT P/N:	67-43.5-0.08X24PX2SX10TS-6.7uH-9mm	Date:	2024/11/13

1. CONFIGURATION&DIMENSIONS:



A	20.5±1.0mm
B	38.5±1.5mm
C	12±1.5mm
D	43.5±1.0mm
E	2.5±1.0mm
F	0.72±0.5mm
G	2.1mm MAX


NOTE:

- H尺寸测量位，包含固定胶带及双面胶
- 产品背贴带手撕位双面胶

2. ELEETRICAL CHARACTER:

项 目	规 格	测试条件	测试仪器
电感量 (Ls)	6.7±10%uH	100KHZ/1.0V	CH1062
直流电阻 (RDC)	≤97mΩ	at:25℃	HG2512
品质因数 (Q)	≥30	100KHZ/1.0V	CH1062

3. SCHEMATIC



4. PART NUMBERING:PRODUCT IDENTIFICATION

67	43.5	0.08X24PX2SX10TS	6.7uH	9mm	
					Line Length
					Inductance
					Wire Diameter
					Magnetic Sheet Specification
					Customer number

DRAWN BY:	CHECKED BY:	Q. C DEPT:	APPROVED BY:
胡国强	周渺		万建军

深圳市柯菲特电子有限公司

SHENZHEN KEFEITE ELECTRONICS CO.,LTD

CUSTOMER:	KFT-067	VERSION:	A1
CUSTOMER NO:	1130200060	PAGE:	4/4
KFT P/N:	67-43.5-0.08X24PX2SX10TS-6.7uH-9mm	Date:	2024/11/13

5. MATERIAL LIST:

NO	ITEM	DESCRIPTION	RATING	SUPPLIERS	UL NO.	REMARK
1	WIRE	Hot air line	155℃	SHANTOU SHENGANG ELECTRICAL INU\DUSTRIAL CO.,LTD	E239508	
2	SOLDER	99.3/0.7		SHENZHEN Hong Xing Wei solder Limited		
3	CORE	43.5/5.3/0.7		Changxing B0 Cheng Electronics CO.,LTD		
4	EPOXY	1603HFR-HS		DONGBU FINE CHEMICAL CO LTD		
5	TAPE	KAPTON 260℃		SU ZHOU MAILADUONA ELECTRIC MATERIAL CO.,LTD	E188295	

6. GENERAL SPECIFICATION:

- 1 Tested at 1.0KHZ/0.25Vrms, 0 Adc.
Average current for 40℃ temperature rise from25℃.
- 2 Saturaion current(Isat):
Inductance drop:10% typ at Isat.
- 3 Heat rating current(Irms):
 $L@I_{rms}=\Delta T\leq 40^{\circ}C$.
- 4 Electrical specifications at25℃
- 5 Storage Temp:-40℃.....+85℃
- 6 Operating Temp:-40℃.....+85℃

项目	测试条件	判断标准
Isat (饱和电流)	1. 正常室内环境25℃. 2. 分十步外加直流电流. 3. 待电感值变化稳定后再加下一步电流.	$I_{sat}@.L_a\geq \%L_0$ L:加载直流电流后测试感值 L0:未加载直流电流的标准值.
Irms (温升电流)	1. 正常室内环境25℃, 禁止通风. 2. 分十步外加直流电流. 3. 每步时间间隔为5分钟.	$I_{rms}@\Delta T\leq 40^{\circ}C$ 1. ΔT 是电感表面温度, 相对于初始测试温度的上升温度. 2. 不得有电感部件颜色外形变化.
L(85℃) (电感量)	1. 在85℃烘烤15Min, 即时取出测试电感量. 2产品必需在10sec之内测试完成, 温度约在85℃ TYP.	$L(85^{\circ}C)\approx L_s$ 1. L_s :电感标准值 (25℃) $L(85^{\circ}C)$:电感量 (85℃) 2. 电感量的变化率在标准值的范围之内.
DRAWN BY:	CHECKED BY:	Q. C DEPT:
胡 国 强	周 渺	万建军