



Tengxiang Technology.Inc

东莞市腾祥电子有限公司

Product Number:AN5000-FPC01BLO

Product Name: Antenna

Specification For Approval

Date: 2023.11.1

Version: 1.0

客户名称

Customer:

四海伽蓝

客户料号

Customer P/N:

腾祥料号

T X P/N:

AN5000-FPC01BLO

规格描述

Description :

5G FPC 天线 1.13mm 蓝色线 L=140mm

Tengxiang Checked By: 腾祥审核		Customer Approved By: 客户审核	
DRAWN 制 作	路婷	TESTED BY 检 测	
CHECKED BY 审 核	胡超	CHECKED BY 审 核	
Q.C.DEPT. 品 管	梁凤珍	Q.C.DEPT. 品 管	
APPROVED BY 核 准	韦佳	APPROVEDBY 核 准	



NO.53 Shatou ShaChong Road, ChangAn Town, Guangdong province, China

中国广东省东莞市长安镇沙头区沙涌路 53 号

TEL:86-769-81873082 FAX:86-769-82663788

<http://www.tenxiang.cn>



Tengxiang Technology.Inc

东莞市腾祥电子有限公司

Product Number:AN5000-FPC01BLO

Product Name: Antenna

Index:

1. Specification (规格)
2. Characteristics and Reliability Test (产品特性和可靠性测试标准)
3. Antenna - S Parameter Test Data (样品测试数据)
4. Antenna - Radiation Pattern Test Data (辐射模式测试数据)
5. Mechanical and Packing Drawing (图纸包装规范)


Revision History (变更履历)

Revision	Date	Change Notification	Description
1.0	2023.11.1	初版	

Product Number:AN5000-FPC01BLO

Product Name: Antenna

1. Specification

Sample Photo	
	
A. Electrical Characteristics	
Frequency 频率	5150-5850MHz
S.W.R. 驻波比	<= 2.0
Antenna Gain 增益	5.10dBi
Polarization 极化方式	Linear
Impedance 阻抗	50 Ohm
B. Material & Mechanical Characteristics	
Cable Type 线材规格	OD1.13mm ,BIUE
Connector Type 连接器规格	/
C. Environmental	
Storage Temperature 存储温度	-40°C ~ +80°C
Operation Temperature 工作温度	-40°C ~ +80°C

Product Number:AN5000-FPC01BLO

Product Name: Antenna


2. Characteristics and Reliability Test

Test Items 测试项目		Test Condition and Procedure 测试方法	Requirements 要求	Result 结果
1	V.S.W.R. 电压驻波比	Set DUT on Network Analyzer; make individual calibration to test 设置网络分析仪参数进行测试	Directive DUT specification 符合待测物规范	PASS
2	Insertion Loss 插入损失	Set DUT on Network Analyzer; make individual calibration to test 设置网络分析仪参数进行测试	Directive DUT specification 符合待测物规范	PASS
3	Antenna Gain 天线增益	Set DUT on Antenna Chamber; make individual calibration to test 设置天线暗室参数进行测试	Directive DUT specification 符合待测物规范	PASS
4	Solderability 可焊性	GB / T2423.28-2005 Temp: 260±5° C;Duration: 5 seconds 温度 260±5° C;持续 5 秒	Tin evenly on full 上锡均匀饱满	PASS
5	Pull Test 拉力	Holding with individual specification; force applied to axis of terminal .单独定义产品端子拉力	1. Directive DUT specification 2. Frequency Tol.≤5% 符合待测物规范;频率偏移≤5%	PASS
6	Dimension 尺寸	Inspection of dimension, color, material, package, surface process.检查尺寸,颜色,材料,包装,表面处理	Directive DUT specification 符合待测物规范	PASS
7	Salt Spray 盐雾	GB / T 2423.17-2008 Temp: 35°C; RH: ≥ 95%; NaCl solution: ≥ 5%;Time: 24H 温度 35°C; 湿度≥95%;盐水浓度≥5%; 测试 24H	1. No Visual Damage 2. Frequency Tol.≤5% 无明显外观不良;频率偏移≤5%	PASS
8	RoHS	With Reference to IEC 62321:2008 with flow chart 参考 IEC 62321 测试流程	Directive RoHS 2015/863/EU 符合 RoHS 2015/863/EU 标准	PASS

Product Number:AN5000-FPC01BLO

Product Name: Antenna

3. Antenna - S Parameter Test Data




4. Antenna - Radiation Pattern Test Data

Frequency ID	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
Frequency (MHz)	5150.0	5200.0	5250.0	5300.0	5350.0	5400.0	5450.0	5500.0	5550.0	5600.0	5650.0	5700.0	5750.0	5800.0	5850.0
Gain (dBi)	3.43	3.36	3.96	3.52	3.62	3.97	3.91	3.33	4.10	4.49	4.53	4.36	5.10	5.07	4.17
Efficiency (%)	56.41	59.48	61.84	58.80	58.73	60.76	57.79	49.51	56.79	58.82	61.45	58.01	64.15	64.60	55.49


Product Number:AN5000-FPC01BLO

Product Name: Antenna


5150MHz



5500MHz




5850MHz



5. Mechanical Drawing See attached files

HF	☐
RoHS 2.0	☒
REACH	☐
CONFIDENTIAL	

SIGN	DATE	DESCRIPTION	APPROVER
			
			
			



Note:

- 1.Mark* is important dimension;"Cpk "Identify for process control($CpK \geq 1.33$).
- 2.Tolerance:Unmarked tolerance refer to the standard tolerance please.
- 3.Pay attention to the direction of the connector.



Tengxiang Electronics Co., Ltd.

2	CB-113BL	Coaxial Cable	OD1.13	Blue	1
1	AN5000-FPC1024-1	FPC		Black	1
No.	Part Number	Name	Material	Finish	Q'ty

TITLE: Antenna						
PART NO.: AN5000-FPC01BLO				CUSTOMER P/N: /		
APP BY	CHK BY	RF BY	DES BY		Tolerance	
YCX	WJ	HC	SYX		UNITS: mm	X.X ±0.5
2023.11.01	2023.11.01	2023.11.01	2023.11.01		SCALE: 1/1	X.XX ±0.2
					REVISION: A	X° ±1

1	2	3	4	5	6	7	8
---	---	---	---	---	---	---	---

产品包装规范

PACKING CRITERION

Date: 2023.11.01

Page: 1 of 1


Part Number : AN5000-FPC01BLO

Revision : A

Name: Antenna


Customer : ALL

1 . Enter PE bag。




100pcs/ PE bag

2.PACKING。




8000pcs/Carton



3. SEALING。



SIDE



FRONT



APPROVED BY : YCX

CHECKED BY : HC

DESIGNED BY : SY Y