

Dates of Tests: May 03 ,2024 ~ May 24 ,2024

Test Report S/N: LR500112405J

Test Site : LTA CO., LTD.

CERTIFICATION OF COMPLIANCE

FCC ID.

2BF8ORL-CDE-SC-200

APPLICANT

ROBOLINK INC.

Equipment Class	:	Digital Transmission System (DTS)
Manufacturing Description	:	Drone Controller
Manufacturer	:	Apex Drone(Shenzhen)Co., Ltd
Model name	:	RL-CDE-SC-200
Variant Model name	:	-
Test Device Serial No.:	:	Identical prototype
Rule Part(s)	:	FCC Part 15.247 Subpart C ; ANSI C63.10 - 2013
Frequency Range	:	2403 ~ 2480 MHz
Max. Output Power	:	Max 3.32 dBm - Conducted
Data of issue	:	May 27 ,2024

This test report is issued under the authority of:



Ja-Beom Koo, Manager

The test was supervised by:



Eun-Hwan Jung, Test Engineer

TABLE OF CONTENTS

1. GENERAL INFORMATION ----- 3

2. INFORMATION ABOUT TEST ITEM ----- 4

3. TEST REPORT ----- 5

 3.1 SUMMARY OF TESTS ----- 5

 3.2 RF EXPOSURE EVULATION----- 6

1. General information

1-1 Test Performed

Company name : LTA Co., Ltd.
Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822
Web site : <http://www.ltalab.com>
E-mail : chahn@ltalab.com
Telephone : +82-31-323-6008
Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
RRA	KOREA	KR0049	-	EMC accredited Lab.
FCC	U.S.A	649054	2025-03-29	FCC CAB
VCCI	JAPAN	C-4948,	2026-09-10	VCCI registration
VCCI	JAPAN	T-2416,	2026-09-10	VCCI registration
VCCI	JAPAN	R-4483(10 m),	2026-10-15	VCCI registration
VCCI	JAPAN	G-847	2024-12-13	VCCI registration
IC	CANADA	5799A-1	2024-08-15	IC filing

2. Information about test item

2-1 Client & Manufacturer

Client Company name : ROBOLINK INC.
Address : 5075 Shoreham Pl. Ste 110, San Diego, CA 92122 USA
Tel / Fax : +1-858-876-5123 / -
Manufacturer : Apex Drone(Shenzhen)Co., Ltd
Address : F401/A001 Building, Zhiji Group Industrial Park, No.92 Jinye, Road,
Kuichong Dapeng New District, Shenzhen, China
Tel / Fax : +1-858-876-5123 / -

2-2 Equipment Under Test (EUT)

Model name : ROBOLINK INC.
Serial number : Identical prototype
Date of receipt : April 02 ,2024
EUT condition : Pre-production, not damaged
Antenna type : Wire Antenna (Max Gain : 0 dBi)
Frequency Range : 2403 ~ 2480 MHz
RF output power : Max 3.32 dBm – Conducted
Type of Modulation : GFSK
Power Source : DC 3 V

2-3 Tested frequency

Bluetooth	LOW	MID	HIGH
Frequency (MHz)	2403	2440	2480

2-4 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
-	-	-	-

3. Test Report

3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
§ 1.1310 and §2.1091	RF EXPOSURE EVULATION	-	-	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

-

3.2 RF EXPOSURE EVULATION

1.1 Limit

According to §1.1310 and §2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength	Magnetic field Strength	Power density (mW/cm ²)	Averaging time
1.34 - 30.....	824/f	2.19/f	*(180/ f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....			f/1500	30
1500 - 100.000.....			1.0	30

F = frequency in MHz

* = Plane-wave equivalent power density

1.2 MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

Power density at the specific separation:

$S = PG/(4R^2\pi)$ $S = (2.15 * 1.00) / (4 * 20^2 * \pi)$ $S = 0.0004 \text{ mW/cm}^2$	Where, S = Maximum power density (mW/cm ²) P = Power input to the antenna (mW) G = Numeric power gain of the antenna R = Distance to the center of the radiation of the antenna (20 cm = limit for MPE)
--	--

1.3 MAXIMUM PERMISSIBLE EXPOSURE Prediction

- Calculated under the worst-case conditions of each mode.

(Measured power 2.0 dBm $\pm$ 0.5dB)

2.4GHz Mode

Max Peak output Power at antenna input terminal	3.32	dBm
Max Peak output Power at antenna input terminal	2.15	mW
Prediction distance	20	cm
Prediction frequency	2480	MHz
Antenna Gain(typical)	0	dBi
Antenna Gain(numeric)	1.00	-

SAR Test exclusion thresholds for 100MHz to 6GHz at test separation distance $\leq$ 50 mm = **Used**

$[(\text{max.power of channel, including tune-up torelance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f}(\text{GHz})]$

$= [2.15 / 5] * [\sqrt{2.480}] = 0.68 \leq 3.0$, for 1g SAR

Thus, SAR for this device is not required.