



TEST REPORT

Product Name: TD-LTE wireless data terminal
FCC ID: 2BFCB-P6
Trademark: N/A
Model Number: P6, P7, P8, D12, X1, A5, A10, A7C
Prepared For: Shenzhen Xinchun Technology Co., Ltd
Address: 401, No. 89, Zone 1, Fifth Industrial Zone, Shangfen Community, Minzhi Street, Longhua District, Shenzhen, China
Manufacturer: Shenzhen Xinchun Technology Co., Ltd
Address: 401, No. 89, Zone 1, Fifth Industrial Zone, Shangfen Community, Minzhi Street, Longhua District, Shenzhen, China
Prepared By: Shenzhen CTB Testing Technology Co., Ltd.
Address: 1&2/F., Building A, No.26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China
Sample Received Date: Jan. 29, 2024
Sample tested Date: Jan. 29, 2024 to Mar. 07, 2024
Issue Date: Mar. 07, 2024
Report No.: CTB240307003RFX
Test Standards: FCC Part 2, 22, 24E, 27
Test Results: PASS
Remark: This is LTE radio test report.

Compiled by:

Zhou kui

Zhou Kui

Reviewed by:

Arron Liu

Arron Liu

Approved by:



Bin Mei / Director

Note: If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client. "*" indicates the testing items were fulfilled by subcontracted lab. "#" indicates the items are not in CNAS accreditation scope.

TABLE OF CONTENT

Test Report Declaration	Page
1. VERSION	3
2. TEST SUMMARY	4
3. MEASUREMENT UNCERTAINTY	5
4. PRODUCT INFORMATION AND TEST SETUP	6
4.1 Product Information	6
4.2 Test Setup Configuration	7
4.3 Support Equipment	7
4.4 Test Mode	7
4.5 Test Environment	7
5. TEST FACILITY AND TEST INSTRUMENT USED	8
5.1 Test Facility	8
5.2 Test Instrument Used	8
6. RF EXPOSURE	10
6.1 Standard Applicable	10
6.2 Test Result	10
7. RF OUTPUT POWER	11
7.1 Standard Applicable	11
7.2 Test Procedure	11
7.3 Summary of Test Results/Plots	12
8. PEAK-TO-AVERAGE RATIO (PAR) OF TRANSMITTER	23
8.1 Standard Applicable	23
8.2 Test Procedure	23
8.3 Summary of Test Results	23
9. EMISSION BANDWIDTH	24
9.1 Standard Applicable	24
9.2 Test Procedure	24
9.3 Summary of Test Results/Plots	24
10. OUT OF BAND EMISSIONS AT ANTENNA TERMINAL	25
10.1 Standard Applicable	25
10.2 Test Procedure	25
10.3 Summary of Test Results/Plots	26
11. SPURIOUS RADIATED EMISSIONS	27
11.1 Standard Applicable	27
11.2 Test Procedure	28
11.3 Summary of Test Results/Plots	28
12. FREQUENCY STABILITY	44
12.1 Standard Applicable	44
12.2 Test Procedure	44
12.3 Summary of Test Results/Plots	44

(Note: N/A means not applicable)

1. VERSION

Report No.	Issue Date	Description	Approved
CTB240307003RFX	Mar. 07, 2024	Original	Valid

2. TEST SUMMARY

The Product has been tested according to the following specifications:

Test Item	Test Requirement	Test method	Result
Conducted output power	Part 2.1046(a)	TIA-603-E-2016 & KDB 971168 D01v03r01	PASS
Effective Radiated Power of Transmitter(EIRP)	Part 22.913(a)(5)/Part27.50(h)(2)	TIA-603-E-2016 & KDB 971168 D01v03r01	PASS
peak-to-average ratio	Part 27.50(d)	KDB 971168 D01v03r01	PASS
99% & 26dB Occupied Bandwidth	Part 2.1049(h)	KDB 971168 D01v03r01	PASS
Band Edge at antenna terminals	Part 2.1051/ Part 22.917(a)/Part 27.53(m) (4)	KDB 971168 D01v03r01	PASS
Spurious emissions at antenna terminals	Part 2.1051/ Part 22.917(a)/Part 27.53(m) (4)	TIA-603-E-2016 & KDB 971168 D01v03r01	PASS
Field strength of spurious radiation	Part 2.1053/ Part 22.917(a)/Part 27.53(m) (4)	TIA-603-E-2016 & KDB 971168 D01v03r01	PASS
Frequency stability	Part 2.1055/Part 27.54	TIA-603-E-2016 & KDB 971168 D01v03r01	PASS

3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Item	Uncertainty
Occupancy bandwidth	54.3kHz
Conducted output power Above 1G	0.9dB
Conducted output power below 1G	0.9dB
Power Spectral Density , Conduction	0.9dB
Conduction spurious emissions	2.0dB
Out of band emission	2.0dB
3m chamber Radiated spurious emission(30MHz-1GHz)	4.6dB
3m chamber Radiated spurious emission(1GHz-18GHz)	5.1dB
3m chamber Radiated spurious emission(18GHz-40GHz)	3.4dB
Receiver Reference Sensitivity level	1.9dB
humidity uncertainty	5.5%
Temperature uncertainty	0.63°C
frequency	1×10 ⁻⁷

4. PRODUCT INFORMATION AND TEST SETUP

4.1 Product Information

Model(s):	P6, P7, P8, D12, X1, A5, A10, A7C
Model Description:	All the model are the same circuit and RF module, only different for model name. Test sample model: P6
Hardware Version:	V1.0
Software Version:	V1.0
Operation Frequency:	FDD-LTE BAND 2:1850-1910MHz FDD-LTE BAND 4:1710-1755MHz FDD-LTE BAND 5:824-849MHz FDD-LTE BAND 7:2500-2570MHz TDD-LTE BAND 66:1710-1780MHz
Max. RF output power:	FDD-LTE BAND 2: 21.59dBm FDD-LTE BAND 4: 21.84dBm FDD-LTE BAND 5: 22.85dBm FDD-LTE BAND 7: 22.24dBm TDD-LTE BAND 66: 22.30dBm
Type of Modulation:	QPSK, 16QAM
Antenna installation:	FPC antenna
Antenna Gain:	FDD-LTE BAND 2:0.45dBi FDD-LTE BAND 4: 1.12dBi FDD-LTE BAND 5: -5.61dBi FDD-LTE BAND 7: 2.08dBi TDD-LTE BAND 66: 1.12dBi
Ratings:	DC 5V=2.4A

4.2 Test Setup Configuration

See test photographs attached in EUT TEST SETUP PHOTOGRAPHS for the actual connections between Product and support equipment.

4.3 Support Equipment

No.	Device Type	Brand	Model	Series No.	Note
/	/	/	/	/	/

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.4 Test Mode

Test Mode List		
Test Mode	Description	Remark
TM1	FDD-LTE BAND 2	Low, Middle, High Channels
TM2	FDD-LTE BAND 4	Low, Middle, High Channels
TM3	FDD-LTE BAND 5	Low, Middle, High Channels
TM4	FDD-LTE BAND 7	Low, Middle, High Channels
TM5	FDD-LTE BAND 66	Low, Middle, High Channels

4.5 Test Environment

Humidity(%):	54
Atmospheric Pressure(kPa):	101
Normal Voltage(DC):	5V
Normal Temperature(°C)	23
Low Temperature(°C)	0
High Temperature(°C)	40

5. TEST FACILITY AND TEST INSTRUMENT USED

5.1 Test Facility

All measurement facilities used to collect the measurement data are located at 1&2F., Building A, No. 26, Xinghe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

5.2 Test Instrument Used

Item	Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	Agilent	N9020A	MY52090073	2024.07.05
2	Power Sensor	Agilent	U2021XA	MY56120032	2024.07.05
3	Power Sensor	Agilent	U2021XA	MY56120034	2024.07.05
4	Communication test set	R&S	CMW500	108058	2024.07.05
5	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	2024.07.05
6	Signal Generator	Agilent	N5181A	MY50140365	2024.07.05
7	Vector signal generator	Agilent	N5182A	MY47420195	2024.07.05
8	Communication test set	Agilent	E5515C	MY50102567	2024.07.06
9	2.4 GHz Filter	Shenxiang	MSF2400-2483.5MS-1154	20181015001	2024.07.05
10	5 GHz Filter	Shenxiang	MSF5150-5850 MS-1155	20181015001	2024.07.06
11	Filter	Xingbo	XBLBQ-DZA120	190821-1-1	2024.07.06
12	BT&WI-FI Automatic test software	Microwave	MTS8000	Ver. 2.0.0.0	/
13	Rohde & Schwarz SFU Broadcast Test System	R&S	SFU	101017	2024.10.30
14	Temperature humidity chamber	Hongjing	TH-80CH	DG-15174	2024.07.05
15	234G Automatic test software	Microwave	MTS8200	Ver. 2.0.0.0	/
16	966 chamber	C.R.T.	966	/	2024.08.11
17	Receiver	R&S	ESPI	100362	2024.07.05
18	Amplifier	HP	8447E	2945A02747	2024.07.05
19	Amplifier	Agilent	8449B	3008A01838	2024.07.05
20	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	00869	2024.07.08

21	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA9120D	01911	2024.07.08
22	EMI test software	Fala	EZ-EMC	FA-03A2 RE	/
23	Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-224	2024.07.08
24	loop antenna	ZHINAN	ZN30900A	GTS534	/
25	40G Horn antenna	A/H/System	SAS-574	588	2024.10.30
26	Amplifier	AEROFLEX	Aeroflex	097	2024.07.05

6. RF EXPOSURE

6.1 Standard Applicable

According to §1.1307 and §2.1091, §2.1093, the portable transmitter must comply the RF exposure requirements.

6.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF Exposure report.

7. RF OUTPUT POWER

7.1 Standard Applicable

According to §22.913(a)(2), the ERP of mobile and portable stations transmitters and auxiliary test transmitters must not exceed 7 Watts.


According to §24.232(c), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

According to §27.50(d)(4), fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP.

According to §27.50(c)(10), portable stations (hand-held devices) in the 698-746 MHz band are limited to 3 watts ERP.

7.2 Test Procedure

Conducted output power test method:



Radiated power test method:

1. The setup of EUT is according with per ANSI/TIA Standard 603E and ANSI C63.26 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

7.3 Summary of Test Results/Plots

Max. Radiated Power:

FDD-LTE Band 2

Channel Bandwidth: 1.4 MHz					
Modulation	Channel	Antenna Polar	EIRP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	20.61	<33.00	PASS
		H	19.58		
	MCH	V	21.36		PASS
		H	19.53		
	HCH	V	21.41		PASS
		H	21.02		
16QAM	LCH	V	19.61	<33.00	PASS
		H	19.91		
	MCH	V	21.23		PASS
		H	20.66		
	HCH	V	21.00		PASS
		H	19.61		
Channel Bandwidth: 3 MHz					
Modulation	Channel	Antenna Polar	EIRP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	20.98	<33.00	PASS
		H	19.95		
	MCH	V	19.49		PASS
		H	19.69		
	HCH	V	20.18		PASS
		H	20.15		
16QAM	LCH	V	19.97	<33.00	PASS
		H	20.21		
	MCH	V	20.49		PASS
		H	20.58		
	HCH	V	20.42		PASS
		H	19.96		
Channel Bandwidth: 5 MHz					
Modulation	Channel	Antenna Polar	EIRP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	20.91	<33.00	PASS
		H	20.99		
	MCH	V	19.98		PASS
		H	19.45		

	HCH	V	20.79		PASS
		H	20.85		
16QAM	LCH	V	20.48	<33.00	PASS
		H	19.31		
	MCH	V	20.59		PASS
		H	19.00		
	HCH	V	20.94		PASS
		H	19.21		
Channel Bandwidth: 10 MHz					
Modulation	Channel	Antenna Polar	EIRP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	21.10	<33.00	PASS
		H	20.78		
	MCH	V	20.63		PASS
		H	21.16		
	HCH	V	20.11		PASS
		H	20.02		
16QAM	LCH	V	20.43	<33.00	PASS
		H	19.82		
	MCH	V	20.06		PASS
		H	21.08		
	HCH	V	19.92		PASS
		H	19.84		
Channel Bandwidth: 15 MHz					
Modulation	Channel	Antenna Polar	EIRP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	21.34	<33.00	PASS
		H	19.77		
	MCH	V	20.44		PASS
		H	20.47		
	HCH	V	20.09		PASS
		H	21.21		
16QAM	LCH	V	20.63	<33.00	PASS
		H	20.82		
	MCH	V	21.22		PASS
		H	20.25		
	HCH	V	20.46		PASS
		H	20.40		

Channel Bandwidth: 20 MHz					
Modulation	Channel	Antenna Polar	EIRP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	21.59	<33.00	PASS
		H	21.42		
	MCH	V	20.03		PASS
		H	20.37		
	HCH	V	20.47		PASS
		H	20.25		
16QAM	LCH	V	21.57	<33.00	PASS
		H	19.74		
	MCH	V	19.83		PASS
		H	19.97		
	HCH	V	19.58		PASS
		H	20.47		

FDD-LTE Band 4

Channel Bandwidth: 1.4 MHz					
Modulation	Channel	Antenna Polar	EIRP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	18.76	<30.00	PASS
		H	20.16		
	MCH	V	18.84		PASS
		H	19.38		
	HCH	V	19.58		PASS
		H	19.32		
16QAM	LCH	V	20.14	<30.00	PASS
		H	19.78		
	MCH	V	20.07		PASS
		H	19.50		
	HCH	V	19.20		PASS
		H	20.47		
Channel Bandwidth: 3 MHz					
Modulation	Channel	Antenna Polar	EIRP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	20.30	<30.00	PASS
		H	20.81		
	MCH	V	20.47		PASS
		H	20.08		

	HCH	V	19.72		PASS
		H	20.01		
16QAM	LCH	V	19.66	<30.00	PASS
		H	19.21		
	MCH	V	19.85		PASS
		H	19.22		
	HCH	V	20.19		PASS
		H	20.17		
Channel Bandwidth: 5 MHz					
Modulation	Channel	Antenna Polar	EIRP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	18.99	<30.00	PASS
		H	20.26		
	MCH	V	19.66		PASS
		H	19.60		
	HCH	V	19.02		PASS
		H	18.77		
16QAM	LCH	V	19.34	<30.00	PASS
		H	20.48		
	MCH	V	19.08		PASS
		H	19.69		
	HCH	V	20.27		PASS
		H	19.78		
Channel Bandwidth: 10 MHz					
Modulation	Channel	Antenna Polar	EIRP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	21.09	<30.00	PASS
		H	20.87		
	MCH	V	20.99		PASS
		H	20.64		
	HCH	V	19.63		PASS
		H	20.55		
16QAM	LCH	V	19.56	<30.00	PASS
		H	21.02		
	MCH	V	20.01		PASS
		H	20.58		
	HCH	V	20.93		PASS
		H	21.10		

Channel Bandwidth: 15 MHz					
Modulation	Channel	Antenna Polar	EIRP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	21.28	<30.00	PASS
		H	19.57		
	MCH	V	19.99		PASS
		H	20.18		
	HCH	V	19.57		PASS
		H	20.60		
16QAM	LCH	V	21.02	<30.00	PASS
		H	20.18		
	MCH	V	19.72		PASS
		H	20.89		
	HCH	V	20.33		PASS
		H	21.12		
Channel Bandwidth: 20 MHz					
Modulation	Channel	Antenna Polar	EIRP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	21.84	<30.00	PASS
		H	20.17		
	MCH	V	20.37		PASS
		H	21.50		
	HCH	V	20.57		PASS
		H	20.65		
16QAM	LCH	V	21.82	<30.00	PASS
		H	21.46		
	MCH	V	19.74		PASS
		H	20.67		
	HCH	V	20.83		PASS
		H	19.56		

FDD-LTE Band 5

Channel Bandwidth: 1.4 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	21.05	<34.77	PASS
		H	21.98		
	MCH	V	21.38		PASS
		H	21.85		
	HCH	V	20.64		PASS

		H	21.82		
16QAM	LCH	V	22.07	<34.77	PASS
		H	22.42		
	MCH	V	20.75		PASS
		H	20.61		
	HCH	V	21.73		PASS
		H	22.34		
Channel Bandwidth: 3 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	21.99	<34.77	PASS
		H	20.25		
	MCH	V	21.43		PASS
		H	20.59		
	HCH	V	22.21		PASS
		H	22.45		
16QAM	LCH	V	20.73	<34.77	PASS
		H	21.81		
	MCH	V	22.25		PASS
		H	20.85		
	HCH	V	22.43		PASS
		H	21.93		
Channel Bandwidth: 5 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	21.24	<34.77	PASS
		H	21.24		
	MCH	V	22.44		PASS
		H	20.61		
	HCH	V	22.06		PASS
		H	20.89		
16QAM	LCH	V	21.36	<34.77	PASS
		H	20.55		
	MCH	V	22.29		PASS
		H	20.74		
	HCH	V	21.47		PASS
		H	20.73		

Channel Bandwidth: 10 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	22.85	<34.77	PASS
		H	20.90		
	MCH	V	21.29		PASS
		H	21.70		
	HCH	V	22.03		PASS
		H	20.74		
16QAM	LCH	V	22.78	<34.77	PASS
		H	21.72		
	MCH	V	20.88		PASS
		H	22.38		
	HCH	V	22.02		PASS
		H	22.24		

FDD-LTE Band 7

Channel Bandwidth: 5 MHz					
Modulation	Channel	Antenna Polar	EIRP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	20.23	<33	PASS
		H	20.92		
	MCH	V	19.59		PASS
		H	21.48		
	HCH	V	20.91		PASS
		H	21.00		
16QAM	LCH	V	20.83	<33	PASS
		H	21.21		
	MCH	V	20.13		PASS
		H	20.68		
	HCH	V	19.90		PASS
		H	20.86		

Channel Bandwidth: 10 MHz					
Modulation	Channel	Antenna Polar	EIRP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	20.61	<33	PASS
		H	19.24		
	MCH	V	19.35		PASS
		H	19.59		
	HCH	V	19.22		PASS
		H	20.70		
16QAM	LCH	V	20.21	<33	PASS
		H	20.86		
	MCH	V	19.50		PASS
		H	20.12		
	HCH	V	20.85		PASS
		H	19.24		

Channel Bandwidth: 15 MHz					
Modulation	Channel	Antenna Polar	EIRP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	19.23	<33	PASS
		H	20.57		
	MCH	V	19.81		PASS
		H	19.40		
	HCH	V	20.70		PASS
		H	20.62		
16QAM	LCH	V	20.35	<33	PASS
		H	19.65		
	MCH	V	19.71		PASS
		H	20.48		
	HCH	V	19.92		PASS
		H	19.54		

Channel Bandwidth: 20 MHz					
Modulation	Channel	Antenna Polar	EIRP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	22.24	<33	PASS
		H	20.99		
	MCH	V	19.98		PASS
		H	20.66		
	HCH	V	19.60		PASS
		H	19.93		
16QAM	LCH	V	22.22	<33	PASS
		H	19.45		
	MCH	V	19.48		PASS
		H	20.87		
	HCH	V	19.83		PASS
		H	19.89		

TDD-LTE Band 66

DD EYE Band 66

Channel Bandwidth: 1.4 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	19.68	<30.00	PASS
		H	21.44		
	MCH	V	19.92		PASS
		H	21.30		
	HCH	V	21.13		PASS
		H	20.02		
16QAM	LCH	V	19.73	<30.00	PASS
		H	20.07		
	MCH	V	19.82		PASS
		H	19.65		
	HCH	V	20.22		PASS
		H	20.51		
Channel Bandwidth: 3 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	20.68	<30.00	PASS
		H	21.16		
	MCH	V	21.50		PASS
		H	21.18		
	HCH	V	21.21		PASS

		H	20.92		
16QAM	LCH	V	20.34	<30.00	PASS
		H	20.44		
	MCH	V	19.56		PASS
		H	19.58		
	HCH	V	20.62		PASS
		H	20.61		
Channel Bandwidth: 5 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	21.15	<30.00	PASS
		H	19.69		
	MCH	V	19.74		PASS
		H	21.20		
	HCH	V	20.61		PASS
		H	20.42		
16QAM	LCH	V	19.52	<30.00	PASS
		H	20.78		
	MCH	V	20.80		PASS
		H	20.76		
	HCH	V	20.35		PASS
		H	21.31		
Channel Bandwidth: 10 MHz					
Modulation	Channel	Antenna Polar	ERP [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	21.15	<30.00	PASS
		H	21.39		
	MCH	V	20.05		PASS
		H	21.14		
	HCH	V	20.46		PASS
		H	20.21		
16QAM	LCH	V	20.57	<30.00	PASS
		H	20.24		
	MCH	V	20.71		PASS
		H	19.81		
	HCH	V	20.28		PASS
		H	21.13		

Channel Bandwidth: 15 MHz					
Modulation	Channel	Antenna Polar	E.i.r.p [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	20.31	<30.00	PASS
		H	21.93		
	MCH	V	21.77		PASS
		H	20.98		
	HCH	V	21.95		PASS
		H	20.13		
16QAM	LCH	V	20.36	<30.00	PASS
		H	20.63		
	MCH	V	20.08		PASS
		H	21.19		
	HCH	V	21.02		PASS
		H	20.81		
Channel Bandwidth: 20 MHz					
Modulation	Channel	Antenna Polar	E.i.r.p [dBm]	Limit (dBm)	Verdict
QPSK	LCH	V	22.30	<30.00	PASS
		H	21.34		
	MCH	V	21.07		PASS
		H	20.97		
	HCH	V	19.71		PASS
		H	20.69		
16QAM	LCH	V	22.29	<30.00	PASS
		H	19.53		
	MCH	V	21.29		PASS
		H	19.78		
	HCH	V	21.27		PASS

Max. Conducted Output Power

Please refer to Appendix A: Average Power Output Data

Test result: Pass

8. PEAK-TO-AVERAGE RATIO (PAR) OF TRANSMITTER

8.1 Standard Applicable

According to §24.232(d), power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51, in measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

According to §27.50(B), the peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB. The PAPR measurements should be made using either an instrument with complementary cumulative distribution function (CCDF) capabilities to determine that PAPR will not exceed 13 dB for more than 0.1 percent of the time or other Commission approved procedure. The measurement must be performed using a signal


corresponding to the highest PAPR expected during periods of continuous transmission.

8.2 Test Procedure

According with KDB 971168

1. The signal analyzer's CCDF measurement profile is enabled
2. Frequency = carrier center frequency
3. Measurement BW > Emission bandwidth of signal
4. The signal analyzer was set to collect one million samples to generate the CCDF curve
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

Test Configuration for the emission bandwidth testing:



8.3 Summary of Test Results

Please refer to Appendix 3: Peak-to-Average Ratio

Test result: Pass

9. EMISSION BANDWIDTH

9.1 Standard Applicable

According to §22.917(b), the emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


According to §24.238(b), the emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

According to §27.53, the emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

9.2 Test Procedure

According to §22.917(b), the emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

Test Configuration for the emission bandwidth testing:



9.3 Summary of Test Results/Plots

Please refer to Appendix 4: 26dB Bandwidth and Occupied Bandwidth
Test result: Pass

10. OUT OF BAND EMISSIONS AT ANTENNA TERMINAL

10.1 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §27.53 (c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB;

(2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB;

(3) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $76 + 10 \log(P)$ dB in a 6.25 kHz band segment, for base and fixed stations;

(4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $65 + 10 \log(P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;

(5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;

(6) Compliance with the provisions of paragraphs (c)(3) and (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

According to §27.53 (f) For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

According to §27.53(h), the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.


According to §27.53(g), for operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log(P)$ dB.

According to §27.53(m)(4), for mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz.

10.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 100kHz and 1MHz for the scan frequency from 30MHz to 1GHz and the scan frequency from 1GHz to up to 10 th harmonic.

Test Configuration for the out of band emissions testing:



10.3 Summary of Test Results/Plots

Please refer to Appendix 5 & 6: Band Edge & Conducted Spurious Emission

Test result: Pass

11. SPURIOUS RADIATED EMISSIONS

11.1 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §27.53 (c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB;

(2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB;

(3) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $76 + 10 \log(P)$ dB in a 6.25 kHz band segment, for base and fixed stations;

(4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $65 + 10 \log(P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;

(5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;

(6) Compliance with the provisions of paragraphs (c)(3) and (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

According to §27.53 (f) For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

According to §27.53(h), the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log(P)$ dB.

According to §27.53(g) the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log(P)$ dB.

11.2 Test Procedure

1. The setup of EUT is according with per ANSI/TIA-603-E and ANSI C63.4-2014 measurement procedure.
 2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
 3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
 4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.
- Spurious attenuation limit in dB = $43 + 10 \log_{10}(\text{power out in Watts})$

11.3 Summary of Test Results/Plots

Note: 1. this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

2. All test modes (different bandwidth and different modulation) are performed, but only the worst case is recorded in this report.

Test Data:
QPSK

Band 2 18607 channel/BW1.4(lowest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1276.14	141	349	-59.76	-13	-46.76	Pass	H
1728.91	151	36	-49.78	-13	-36.78	Pass	H
3988.91	156	288	-48.72	-13	-35.72	Pass	H
5881.06	148	277	-42.06	-13	-29.06	Pass	H
6602.68	151	327	-44.68	-13	-31.68	Pass	H
8111.21	153	318	-41.84	-13	-28.84	Pass	H
1296.45	141	297	-55.49	-13	-42.49	Pass	V
1449.87	143	123	-58.72	-13	-45.72	Pass	V
3607.54	149	219	-50.24	-13	-37.24	Pass	V
3816.31	141	126	-49.01	-13	-36.01	Pass	V
5708.62	145	57	-48.11	-13	-35.11	Pass	V
6561.40	160	72	-46.85	-13	-33.85	Pass	V
Band 2 18900 channel/BW1.4(middle channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1243.05	150	226	-58.48	-13	-45.48	Pass	H
1619.77	146	39	-49.30	-13	-36.30	Pass	H
3918.40	150	316	-52.70	-13	-39.70	Pass	H
5785.95	146	39	-46.69	-13	-33.69	Pass	H
6394.65	149	18	-48.81	-13	-35.81	Pass	H
8113.21	151	97	-46.28	-13	-33.28	Pass	H
1325.55	149	106	-51.43	-13	-38.43	Pass	V
1464.01	148	143	-58.96	-13	-45.96	Pass	V
3627.88	147	160	-50.89	-13	-37.89	Pass	V
3880.64	148	181	-51.78	-13	-38.78	Pass	V
5832.99	150	154	-50.07	-13	-37.07	Pass	V
6447.33	150	289	-50.25	-13	-37.25	Pass	V

Band 2 19193 channel/BW1.4(highest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1417.01	146	72	-56.45	-13	-43.45	Pass	H
1690.62	151	184	-54.08	-13	-41.08	Pass	H
3766.48	153	141	-47.95	-13	-34.95	Pass	H
5821.59	153	65	-38.55	-13	-25.55	Pass	H
6560.04	154	21	-40.98	-13	-27.98	Pass	H
8019.78	149	337	-44.58	-13	-31.58	Pass	H
1174.65	147	331	-55.68	-13	-42.68	Pass	V
1350.94	150	171	-59.05	-13	-46.05	Pass	V
3598.58	154	129	-49.84	-13	-36.84	Pass	V
3977.13	151	31	-49.52	-13	-36.52	Pass	V
5869.36	153	98	-42.43	-13	-29.43	Pass	V
6554.86	151	339	-47.78	-13	-34.78	Pass	V

16QAM

Band 2 18607 channel/BW1.4(lowest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1264.89	153	10	-57.80	-13	-44.80	Pass	H
1784.56	154	244	-47.84	-13	-34.84	Pass	H
3864.44	145	158	-48.09	-13	-35.09	Pass	H
5975.91	154	227	-43.39	-13	-30.39	Pass	H
6597.00	150	315	-42.22	-13	-29.22	Pass	H
7909.44	153	182	-39.76	-13	-26.76	Pass	H
1184.36	145	2	-51.47	-13	-38.47	Pass	V
1453.87	151	354	-55.50	-13	-42.50	Pass	V
3557.26	151	26	-49.46	-13	-36.46	Pass	V
3945.78	155	321	-53.60	-13	-40.60	Pass	V
5843.00	148	34	-43.22	-13	-30.22	Pass	V
6586.20	154	321	-50.78	-13	-37.78	Pass	V

Band 2 18900 channel/BW1.4(middle channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1403.41	151	82	-52.26	-13	-41.45	Pass	H
1817.67	149	347	-50.28	-13	-37.85	Pass	H
3867.47	154	256	-49.01	-13	-35.2	Pass	H
5855.55	145	53	-43.28	-13	-30.39	Pass	H
6580.84	148	245	-46.33	-13	-32.24	Pass	H
8124.21	148	151	-43.82	-13	-30.22	Pass	H
1174.08	152	162	-60.63	-13	-44.9	Pass	V
1373.30	146	341	-56.46	-13	-43.63	Pass	V
3502.67	152	100	-50.55	-13	-35.94	Pass	V
3914.69	149	323	-45.16	-13	-36.01	Pass	V
5759.66	146	88	-45.94	-13	-33.75	Pass	V
6427.87	148	302	-47.33	-13	-32.41	Pass	V
Band 2 19193 channel/BW1.4(highest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1310.29	149	201	-57.39	-13	-44.39	Pass	H
1688.46	147	133	-52.26	-13	-39.26	Pass	H
3958.96	155	47	-44.28	-13	-31.28	Pass	H
5941.31	147	27	-42.59	-13	-29.59	Pass	H
6579.81	152	227	-39.84	-13	-26.84	Pass	H
8118.60	153	180	-45.65	-13	-32.65	Pass	H
1283.04	153	178	-52.38	-13	-39.38	Pass	V
1483.80	151	115	-62.00	-13	-49.00	Pass	V
3526.91	147	79	-50.30	-13	-37.30	Pass	V
3872.56	148	106	-47.41	-13	-34.41	Pass	V
5727.97	152	226	-47.18	-13	-34.18	Pass	V
6474.39	154	186	-45.39	-13	-32.39	Pass	V

Note:

- 1) Scan from 9kHz to 40GHz, the disturbance above 13GHz and below 1GHz are attenuated more than 20 dB below the applicable limit and not required to be reported, the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
- 2) Tested with all kind of bandwidth, RB Size and RB Offset, Found the 1.4MHz with full RB were the worst case; and then Only the worst case is recorded in the report.

QPSK

Band 4 19957 channel/BW1.4(lowest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1296.10	155	106	-58.31	-13	-45.31	Pass	H
1702.33	159	68	-48.90	-13	-35.90	Pass	H
3853.90	156	79	-48.58	-13	-35.58	Pass	H
5802.23	140	245	-42.54	-13	-29.54	Pass	H
6488.54	152	359	-44.72	-13	-31.72	Pass	H
8134.35	158	251	-42.24	-13	-29.24	Pass	H
1206.72	150	133	-55.49	-13	-42.49	Pass	V
1361.65	150	295	-60.00	-13	-47.00	Pass	V
3602.35	150	221	-49.40	-13	-36.40	Pass	V
3769.55	141	3	-50.63	-13	-37.63	Pass	V
5741.99	148	313	-46.14	-13	-33.14	Pass	V
6498.94	147	279	-45.48	-13	-32.48	Pass	V
Band 4 20175 channel/BW1.4(middle channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1279.72	150	302	-55.23	-13	-42.23	Pass	H
1693.11	146	229	-53.55	-13	-40.55	Pass	H
3850.36	150	161	-48.41	-13	-35.41	Pass	H
5819.62	146	100	-42.61	-13	-29.61	Pass	H
6416.30	149	300	-47.46	-13	-34.46	Pass	H
8051.69	151	334	-50.07	-13	-37.07	Pass	H
1313.88	149	230	-54.91	-13	-41.91	Pass	V
1316.60	148	311	-61.10	-13	-48.10	Pass	V
3576.04	147	221	-53.84	-13	-40.84	Pass	V
3936.44	148	317	-49.32	-13	-36.32	Pass	V
5772.54	150	327	-50.77	-13	-37.77	Pass	V
6532.37	150	224	-50.40	-13	-37.40	Pass	V

Band 4 20393 channel/BW1.4(highest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1431.70	155	281	-55.11	-13	-42.11	Pass	H
1637.37	153	324	-50.87	-13	-37.87	Pass	H
3835.31	153	159	-45.29	-13	-32.29	Pass	H
5897.09	152	336	-38.29	-13	-25.29	Pass	H
6617.94	152	125	-42.15	-13	-29.15	Pass	H
8071.10	148	228	-46.34	-13	-33.34	Pass	H
1182.03	147	263	-53.64	-13	-40.64	Pass	V
1386.46	155	91	-56.74	-13	-43.74	Pass	V
3522.39	146	129	-50.04	-13	-37.04	Pass	V
3898.27	153	83	-50.31	-13	-37.31	Pass	V
5878.71	151	15	-45.43	-13	-32.43	Pass	V
6670.41	153	244	-47.36	-13	-34.36	Pass	V

16QAM

Band 4 19957 channel/BW1.4(lowest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1255.94	148	300	-61.20	-13	-48.20	Pass	H
1781.57	154	184	-45.81	-13	-32.81	Pass	H
3815.44	152	175	-46.71	-13	-33.71	Pass	H
5866.32	154	238	-47.85	-13	-34.85	Pass	H
6598.50	154	114	-43.83	-13	-30.83	Pass	H
8065.46	151	185	-43.10	-13	-30.10	Pass	H
1083.61	151	284	-54.99	-13	-41.99	Pass	V
1448.70	154	77	-57.55	-13	-44.55	Pass	V
3686.21	150	210	-50.73	-13	-37.73	Pass	V
3861.84	154	285	-54.31	-13	-41.31	Pass	V
5790.87	152	119	-46.01	-13	-33.01	Pass	V
6495.76	146	321	-48.20	-13	-35.20	Pass	V

Band 4 20175 channel/BW1.4(middle channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1315.68	148	13	-52.80	-13	-41.45	Pass	H
1808.89	150	329	-47.49	-13	-37.85	Pass	H
3886.96	152	158	-50.32	-13	-35.2	Pass	H
5898.38	152	285	-45.21	-13	-30.39	Pass	H
6599.26	155	252	-47.67	-13	-32.24	Pass	H
8153.02	147	198	-39.80	-13	-30.22	Pass	H
1133.04	155	53	-58.89	-13	-44.9	Pass	V
1437.46	149	316	-55.23	-13	-43.63	Pass	V
3551.33	146	32	-46.01	-13	-35.94	Pass	V
3757.84	150	222	-45.67	-13	-36.01	Pass	V
5733.59	155	350	-48.09	-13	-33.75	Pass	V
6590.67	147	269	-46.90	-13	-32.41	Pass	V
Band 4 20393 channel/BW1.4(highest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1296.94	146	259	-53.28	-13	-40.28	Pass	H
1750.60	154	157	-45.97	-13	-32.97	Pass	H
3982.61	148	69	-45.13	-13	-32.13	Pass	H
5926.70	149	274	-43.63	-13	-30.63	Pass	H
6498.08	151	268	-38.52	-13	-25.52	Pass	H
8107.85	154	316	-47.48	-13	-34.48	Pass	H
1151.67	151	336	-55.45	-13	-42.45	Pass	V
1555.81	147	330	-58.41	-13	-45.41	Pass	V
3478.54	149	246	-51.11	-13	-38.11	Pass	V
3854.64	147	325	-48.27	-13	-35.27	Pass	V
5790.04	155	228	-46.59	-13	-33.59	Pass	V
6459.69	153	95	-45.09	-13	-32.09	Pass	V

Note:

3) Scan from 9kHz to 40GHz, the disturbance above 13GHz and below 1GHz are attenuated more than 20 dB below the applicable limit and not required to be reported, the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.

4) Tested with all kind of bandwidth, RB Size and RB Offset, Found the 1.4MHz with full RB were the worst case; and then Only the worst case is recorded in the report.

QPSK

Band 5 20407 channel/BW1.4(lowest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1309.81	141	188	-55.27	-13	-42.27	Pass	H
1656.57	148	220	-49.59	-13	-36.59	Pass	H
3929.03	141	103	-46.25	-13	-33.25	Pass	H
5833.56	151	217	-42.54	-13	-29.54	Pass	H
6452.03	148	270	-41.91	-13	-28.91	Pass	H
8081.56	147	51	-41.55	-13	-28.55	Pass	H
1215.66	140	234	-54.50	-13	-41.50	Pass	V
1480.25	153	45	-55.64	-13	-42.64	Pass	V
3523.00	145	309	-52.03	-13	-39.03	Pass	V
3877.50	141	39	-51.20	-13	-38.20	Pass	V
5745.40	160	350	-46.43	-13	-33.43	Pass	V
6562.40	152	310	-46.69	-13	-33.69	Pass	V

Band 5 20525 channel/BW1.4(middle channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1389.22	150	63	-57.57	-13	-44.57	Pass	H
1763.71	146	255	-53.07	-13	-40.07	Pass	H
3828.29	150	258	-52.86	-13	-39.86	Pass	H
5844.23	146	258	-48.31	-13	-35.31	Pass	H
6503.55	149	88	-50.33	-13	-37.33	Pass	H
8083.62	151	278	-48.52	-13	-35.52	Pass	H
1143.35	149	219	-56.72	-13	-43.72	Pass	V
1420.99	148	157	-57.92	-13	-44.92	Pass	V
3642.09	147	104	-54.93	-13	-41.93	Pass	V
3987.15	148	126	-49.45	-13	-36.45	Pass	V
5828.24	150	107	-46.75	-13	-33.75	Pass	V
6509.18	150	68	-46.88	-13	-33.88	Pass	V

Band 5 20643 channel/BW1.4(highest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1361.52	152	5	-57.97	-13	-44.97	Pass	H
1674.31	152	81	-52.98	-13	-39.98	Pass	H
3808.39	154	354	-43.31	-13	-30.31	Pass	H
5964.93	145	71	-42.50	-13	-29.50	Pass	H
6464.32	152	298	-41.44	-13	-28.44	Pass	H
8000.03	146	119	-46.36	-13	-33.36	Pass	H
1187.99	151	167	-55.50	-13	-42.50	Pass	V
1400.46	150	199	-54.97	-13	-41.97	Pass	V
3612.76	149	291	-52.62	-13	-39.62	Pass	V
3932.06	145	132	-49.30	-13	-36.30	Pass	V
5865.06	155	236	-42.07	-13	-29.07	Pass	V
6641.55	147	358	-46.02	-13	-33.02	Pass	V

16QAM

Band 5 20407 channel/BW1.4(lowest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1332.87	151	158	-60.25	-13	-47.25	Pass	H
1705.71	151	93	-46.77	-13	-33.77	Pass	H
3829.71	153	333	-51.69	-13	-38.69	Pass	H
5832.92	148	171	-42.81	-13	-29.81	Pass	H
6654.24	149	184	-41.65	-13	-28.65	Pass	H
7905.61	150	332	-43.92	-13	-30.92	Pass	H
1153.89	150	111	-50.68	-13	-37.68	Pass	V
1409.01	149	56	-58.01	-13	-45.01	Pass	V
3608.27	150	49	-49.27	-13	-36.27	Pass	V
3828.22	150	280	-51.99	-13	-38.99	Pass	V
5924.62	146	199	-46.81	-13	-33.81	Pass	V
6634.46	146	337	-49.48	-13	-36.48	Pass	V

Band 5 20525 channel/BW1.4(middle channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1420.14	150	336	-52.12	-13	-41.45	Pass	H
1798.81	147	325	-51.33	-13	-37.85	Pass	H
3933.08	146	282	-46.92	-13	-35.2	Pass	H
6017.69	152	102	-43.38	-13	-30.39	Pass	H
6560.72	152	317	-47.44	-13	-32.24	Pass	H
8125.34	150	193	-41.80	-13	-30.22	Pass	H
1149.90	148	251	-55.39	-13	-44.9	Pass	V
1369.77	152	348	-59.03	-13	-43.63	Pass	V
3501.67	150	165	-46.80	-13	-35.94	Pass	V
3899.94	148	13	-48.53	-13	-36.01	Pass	V
5881.78	146	214	-49.12	-13	-33.75	Pass	V
6519.55	151	175	-41.79	-13	-32.41	Pass	V

Band 5 20643 channel/BW1.4(highest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1426.82	147	75	-58.26	-13	-45.26	Pass	H
1618.12	151	347	-51.19	-13	-38.19	Pass	H
3907.22	148	76	-42.00	-13	-29.00	Pass	H
5989.06	145	206	-41.53	-13	-28.53	Pass	H
6463.06	154	259	-39.58	-13	-26.58	Pass	H
7993.82	154	319	-41.98	-13	-28.98	Pass	H
1281.46	153	260	-54.99	-13	-41.99	Pass	V
1407.72	151	258	-55.58	-13	-42.58	Pass	V
3459.69	149	328	-51.48	-13	-38.48	Pass	V
3787.42	154	289	-52.78	-13	-39.78	Pass	V
5891.15	151	111	-45.81	-13	-32.81	Pass	V
6539.66	146	103	-43.16	-13	-30.16	Pass	V

Note:

5) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 1GHz are attenuated more than 20 dB below the applicable limit and not required to be reported, the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.

6) Tested with all kind of bandwidth, RB Size and RB Offset, Found the 1.4MHz with full RB were the worst case; and then Only the worst case is recorded in the report.

QPSK

Band 7 20775 channel/BW 5(lowest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1252.46	147	77	-59.89	-13	-46.89	Pass	H
1654.99	146	161	-47.52	-13	-34.52	Pass	H
3858.88	147	165	-51.85	-13	-38.85	Pass	H
5972.70	145	102	-42.48	-13	-29.48	Pass	H
6532.09	152	196	-44.23	-13	-31.23	Pass	H
8091.70	154	9	-42.50	-13	-29.50	Pass	H
1096.88	154	114	-54.46	-13	-41.46	Pass	V
1397.52	150	337	-58.23	-13	-45.23	Pass	V
3566.08	151	287	-50.28	-13	-37.28	Pass	V
3948.65	155	299	-53.28	-13	-40.28	Pass	V
5916.53	155	124	-45.54	-13	-32.54	Pass	V
6653.66	147	275	-48.54	-13	-35.54	Pass	V

Band 7 21100 channel/BW 5 (middle channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1389.93	151	45	-53.49	-13	-40.49	Pass	H
1655.24	149	140	-51.78	-13	-38.78	Pass	H
3850.98	153	214	-44.64	-13	-31.64	Pass	H
5991.97	150	131	-41.71	-13	-28.71	Pass	H
6559.59	151	38	-43.73	-13	-30.73	Pass	H
8084.85	152	112	-47.66	-13	-34.66	Pass	H
1273.31	154	87	-59.62	-13	-46.62	Pass	V
1399.17	151	96	-60.38	-13	-47.38	Pass	V
3466.81	152	278	-51.27	-13	-38.27	Pass	V
3879.93	152	78	-50.67	-13	-37.67	Pass	V
5871.19	155	109	-45.16	-13	-32.16	Pass	V
6435.27	153	307	-48.60	-13	-35.60	Pass	V

Band 7 21425 channel/BW 5 (highest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1311.91	149	165	-54.14	-13	-41.14	Pass	H
1703.98	146	208	-49.37	-13	-36.37	Pass	H
3820.88	146	4	-45.98	-13	-32.98	Pass	H
5974.21	150	198	-38.56	-13	-25.56	Pass	H
6553.18	146	341	-40.19	-13	-27.19	Pass	H
8043.76	150	235	-40.98	-13	-27.98	Pass	H
1122.25	146	292	-54.27	-13	-41.27	Pass	V
1384.88	150	158	-56.95	-13	-43.95	Pass	V
3571.11	149	55	-49.91	-13	-36.91	Pass	V
3864.99	150	319	-47.89	-13	-34.89	Pass	V
5789.01	146	118	-49.11	-13	-36.11	Pass	V
6577.67	150	155	-49.70	-13	-36.70	Pass	V

16QAM

Band 7 20775 channel/BW 5 (lowest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1309.32	150	78	-58.60	-13	-45.60	Pass	H
1789.74	149	291	-53.79	-13	-40.79	Pass	H
3837.64	151	213	-49.75	-13	-36.75	Pass	H
5916.48	150	89	-47.14	-13	-34.14	Pass	H
6420.84	151	329	-45.97	-13	-32.97	Pass	H
7998.64	148	138	-47.38	-13	-34.38	Pass	H
1165.69	149	99	-55.11	-13	-42.11	Pass	V
1499.44	148	217	-56.02	-13	-43.02	Pass	V
3647.63	150	12	-51.26	-13	-38.26	Pass	V
3752.15	150	137	-49.42	-13	-36.42	Pass	V
5881.93	146	356	-44.44	-13	-31.44	Pass	V
6489.01	146	95	-46.43	-13	-33.43	Pass	V

Band 7 21100 channel/BW 5 (middle channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1224.80	150	142	-58.74	-13	-45.74	Pass	H
1748.65	146	280	-54.62	-13	-41.62	Pass	H
3786.65	150	330	-49.55	-13	-36.55	Pass	H
5940.69	146	194	-41.98	-13	-28.98	Pass	H
6513.38	149	260	-53.19	-13	-40.19	Pass	H
7964.98	151	31	-45.77	-13	-32.77	Pass	H
1230.89	149	4	-53.79	-13	-40.79	Pass	V
1430.28	148	257	-60.34	-13	-47.34	Pass	V
3571.16	147	55	-49.05	-13	-36.05	Pass	V
3857.78	148	273	-53.60	-13	-40.60	Pass	V
5733.53	150	136	-52.50	-13	-39.50	Pass	V
6454.07	150	16	-50.86	-13	-37.86	Pass	V

Band 7 21425 channel/BW 5 (highest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1305.08	149	156	-53.61	-13	-40.61	Pass	H
1613.71	149	170	-53.65	-13	-40.65	Pass	H
3769.34	149	127	-49.42	-13	-36.42	Pass	H
5889.30	146	42	-39.36	-13	-26.36	Pass	H
6441.92	147	69	-41.09	-13	-28.09	Pass	H
7961.77	151	110	-44.75	-13	-31.75	Pass	H
1215.91	148	61	-53.97	-13	-40.97	Pass	V
1377.12	147	266	-51.24	-13	-38.24	Pass	V
3488.45	148	303	-50.96	-13	-37.96	Pass	V
3823.89	149	195	-47.96	-13	-34.96	Pass	V
5776.30	147	323	-44.67	-13	-31.67	Pass	V
6505.03	146	325	-46.23	-13	-33.23	Pass	V

Note:

7) Scan from 9kHz to 40GHz, the disturbance above 13GHz and below 1GHz are attenuated more than 20 dB below the applicable limit and not required to be reported, the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.

8) Tested with all kind of bandwidth, RB Size and RB Offset, Found the 1.4MHz with full RB were the worst case; and then Only the worst case is recorded in the report.

QPSK

Band 66 131979 channel/BW1.4(lowest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1404.23	145	138	-53.82	-13	-40.82	Pass	H
1704.66	150	252	-47.02	-13	-34.02	Pass	H
3870.87	147	48	-50.81	-13	-37.81	Pass	H
6000.01	147	178	-44.73	-13	-31.73	Pass	H
6620.15	153	95	-46.63	-13	-33.63	Pass	H
8000.98	147	1	-42.97	-13	-29.97	Pass	H
1141.42	147	123	-55.67	-13	-42.67	Pass	V
1449.41	148	60	-56.41	-13	-43.41	Pass	V
3573.98	154	31	-47.94	-13	-34.94	Pass	V
3956.26	146	68	-48.56	-13	-35.56	Pass	V
5798.39	148	9	-47.74	-13	-34.74	Pass	V
6594.60	151	69	-47.44	-13	-34.44	Pass	V

Band 66 132322 channel/BW1.4(middle channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1279.54	151	81	-57.56	-13	-44.56	Pass	H
1763.06	149	66	-48.96	-13	-35.96	Pass	H
3786.46	148	293	-47.16	-13	-34.16	Pass	H
5905.38	146	80	-42.61	-13	-29.61	Pass	H
6569.82	154	122	-41.21	-13	-28.21	Pass	H
8155.94	145	211	-43.12	-13	-30.12	Pass	H
1266.62	152	61	-59.56	-13	-46.56	Pass	V
1285.18	149	231	-56.88	-13	-43.88	Pass	V
3621.04	153	45	-46.33	-13	-33.33	Pass	V
3897.41	153	185	-43.95	-13	-30.95	Pass	V
5749.85	147	7	-41.25	-13	-28.25	Pass	V
6616.95	154	308	-48.81	-13	-35.81	Pass	V

Band 66 132665 channel/BW1.4(highest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1255.75	149	165	-50.71	-13	-37.71	Pass	H
1737.65	146	208	-49.43	-13	-36.43	Pass	H
3867.19	146	4	-42.93	-13	-29.93	Pass	H
5985.39	150	198	-44.00	-13	-31.00	Pass	H
6543.76	146	341	-42.27	-13	-29.27	Pass	H
8082.74	150	235	-40.09	-13	-27.09	Pass	H
1112.59	146	292	-54.20	-13	-41.20	Pass	V
1457.39	150	158	-53.73	-13	-40.73	Pass	V
3448.18	149	55	-50.94	-13	-37.94	Pass	V
3887.45	150	319	-45.11	-13	-32.11	Pass	V
5798.02	146	118	-44.68	-13	-31.68	Pass	V
6485.71	150	155	-48.95	-13	-35.95	Pass	V

16QAM

Band 66 131979 channel/BW1.4(lowest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1238.71	150	78	-56.01	-13	-43.01	Pass	H
1747.66	149	291	-53.25	-13	-40.25	Pass	H
3874.16	151	213	-51.91	-13	-38.91	Pass	H
5924.05	150	89	-43.86	-13	-30.86	Pass	H
6459.93	151	329	-44.51	-13	-31.51	Pass	H
8028.45	148	138	-45.85	-13	-32.85	Pass	H
1121.08	149	99	-58.97	-13	-45.97	Pass	V
1395.52	148	217	-55.13	-13	-42.13	Pass	V
3660.91	150	12	-50.04	-13	-37.04	Pass	V
3877.67	150	137	-48.17	-13	-35.17	Pass	V
5707.43	146	356	-43.71	-13	-30.71	Pass	V
6470.25	146	95	-48.20	-13	-35.20	Pass	V

Band 66 132322 channel/BW1.4(middle channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1391.13	150	142	-55.52	-13	-42.52	Pass	H
1653.17	146	280	-56.30	-13	-43.30	Pass	H
3914.29	150	330	-50.65	-13	-37.65	Pass	H
5869.76	146	194	-46.30	-13	-33.30	Pass	H
6403.72	149	260	-49.07	-13	-36.07	Pass	H
8056.32	151	31	-46.66	-13	-33.66	Pass	H
1226.16	149	4	-55.02	-13	-42.02	Pass	V
1426.58	148	257	-61.91	-13	-48.91	Pass	V
3679.85	147	55	-49.55	-13	-36.55	Pass	V
3993.88	148	273	-52.93	-13	-39.93	Pass	V
5848.73	150	136	-48.70	-13	-35.70	Pass	V
6486.37	150	16	-50.33	-13	-37.33	Pass	V

Band 66 132665 channel/BW1.4(highest channel)							
Frequency (MHz)	Height (cm)	Azimuth (deg)	Spurious Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result	Antenna Polaxis.
1263.76	149	156	-53.69	-13	-40.69	Pass	H
1668.31	149	170	-50.34	-13	-37.34	Pass	H
3807.21	149	127	-45.88	-13	-32.88	Pass	H
5821.60	146	42	-39.19	-13	-26.19	Pass	H
6491.73	147	69	-43.67	-13	-30.67	Pass	H
7956.15	151	110	-49.20	-13	-36.20	Pass	H
1207.11	148	61	-56.25	-13	-43.25	Pass	V
1373.34	147	266	-54.80	-13	-41.80	Pass	V
3434.32	148	303	-54.41	-13	-41.41	Pass	V
3883.43	149	195	-48.50	-13	-35.50	Pass	V
5783.94	147	323	-45.08	-13	-32.08	Pass	V
6517.53	146	325	-45.02	-13	-32.02	Pass	V

Note:

9) Scan from 9kHz to 40GHz, the disturbance above 13GHz and below 1GHz are attenuated more than 20 dB below the applicable limit and not required to be reported, the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.

10) Tested with all kind of bandwidth, RB Size and RB Offset, Found the 1.4MHz with full RB were the worst case; and then Only the worst case is recorded in the report.

12. FREQUENCY STABILITY

12.1 Standard Applicable

According to §22.355, §24.235, §27.54 the limit is 2.5ppm.

12.2 Test Procedure

According to §2.1055, the following test procedure was performed.

The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode

12.3 Summary of Test Results/Plots

Note: 1.Normal Voltage NV= DC5V; Low Voltage LV=DC4.5V; High Voltage HV=DC5.5V.

Test result: Pass

LTE Band 2

Test Frequency:1880.0MHz QPSK 1.4MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	-12	-0.0066	2.5
40		-10	-0.0051	2.5
30		-6	-0.0034	2.5
20		-5	-0.0025	2.5
10		-7	-0.0037	2.5
0		-7	-0.0036	2.5
-10		-10	-0.0054	2.5
-20		-7	-0.0037	2.5
-30		-9	-0.0045	2.5
20	4.5	-10	-0.0051	2.5
20	5.5	-7	-0.0036	2.5

Test Frequency:1880.0MHz 16QAM 1.4MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	-11	-0.0060	2.5
40		-10	-0.0053	2.5
30		-6	-0.0034	2.5
20		-4	-0.0022	2.5
10		-6	-0.0033	2.5
0		-8	-0.0044	2.5
-10		-11	-0.0060	2.5
-20		-7	-0.0037	2.5
-30		-10	-0.0051	2.5
20	4.5	-10	-0.0053	2.5
20	5.5	-8	-0.0043	2.5

LTE Band 2

Test Frequency:1880.0MHz QPSK 3MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	-13	-0.0067	2.5
40		-9	-0.0048	2.5
30		-7	-0.0037	2.5
20		-6	-0.0030	2.5
10		-8	-0.0041	2.5
0		-8	-0.0043	2.5
-10		-10	-0.0054	2.5
-20		-8	-0.0042	2.5
-30		-8	-0.0045	2.5
20	4.5	-10	-0.0052	2.5
20	5.5	-8	-0.0041	2.5

Test Frequency:1880.0MHz 16QAM 3MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	-11	-0.0060	2.5
40		-9	-0.0046	2.5
30		-7	-0.0038	2.5
20		-5	-0.0024	2.5
10		-6	-0.0034	2.5
0		-7	-0.0036	2.5
-10		-11	-0.0061	2.5
-20		-7	-0.0040	2.5
-30		-8	-0.0045	2.5
20	4.5	-10	-0.0055	2.5
20	5.5	-6	-0.0034	2.5

LTE Band 2

Test Frequency:1880.0MHz QPSK 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	-11	-0.0058	2.5
40		-8	-0.0044	2.5
30		-8	-0.0042	2.5
20		-5	-0.0029	2.5
10		-7	-0.0035	2.5
0		-8	-0.0044	2.5
-10		-11	-0.0060	2.5
-20		-9	-0.0046	2.5
-30		-9	-0.0046	2.5
20	4.5	-9	-0.0049	2.5
20	5.5	-7	-0.0039	2.5

Test Frequency:1880.0MHz 16QAM 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	-12	-0.0065	2.5
40		-10	-0.0053	2.5
30		-7	-0.0037	2.5
20		-4	-0.0022	2.5
10		-6	-0.0031	2.5
0		-8	-0.0043	2.5
-10		-10	-0.0054	2.5
-20		-8	-0.0045	2.5
-30		-8	-0.0044	2.5
20	4.5	-9	-0.0050	2.5
20	5.5	-8	-0.0041	2.5

LTE Band 2

Test Frequency:1880.0MHz QPSK 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	-12	-0.0066	2.5
40		-9	-0.0048	2.5
30		-7	-0.0040	2.5
20		-4	-0.0021	2.5
10		-7	-0.0039	2.5
0		-7	-0.0036	2.5
-10		-12	-0.0062	2.5
-20		-9	-0.0045	2.5
-30		-8	-0.0045	2.5
20	4.5	-11	-0.0056	2.5
20	5.5	-8	-0.0042	2.5

Test Frequency:1880.0MHz 16QAM 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	-12	-0.0063	2.5
40		-10	-0.0053	2.5
30		-7	-0.0036	2.5
20		-5	-0.0028	2.5
10		-6	-0.0034	2.5
0		-7	-0.0039	2.5
-10		-11	-0.0056	2.5
-20		-8	-0.0043	2.5
-30		-8	-0.0045	2.5
20	4.5	-11	-0.0056	2.5
20	5.5	-8	-0.0041	2.5

LTE Band 2

Test Frequency:1880.0MHz QPSK 15MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	-13	-0.0067	2.5
40		-9	-0.0048	2.5
30		-8	-0.0040	2.5
20		-4	-0.0021	2.5
10		-7	-0.0035	2.5
0		-8	-0.0042	2.5
-10		-11	-0.0058	2.5
-20		-8	-0.0040	2.5
-30		-8	-0.0044	2.5
20	4.5	-10	-0.0051	2.5
20	5.5	-7	-0.0040	2.5

Test Frequency:1880.0MHz 16QAM 15MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	-12	-0.0063	2.5
40		-9	-0.0046	2.5
30		-6	-0.0033	2.5
20		-6	-0.0030	2.5
10		-7	-0.0035	2.5
0		-8	-0.0045	2.5
-10		-10	-0.0055	2.5
-20		-7	-0.0038	2.5
-30		-9	-0.0046	2.5
20	4.5	-10	-0.0051	2.5
20	5.5	-7	-0.0037	2.5

LTE Band 2

Test Frequency:1880.0MHz QPSK 20MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	-11	-0.0061	2.5
40		-8	-0.0045	2.5
30		-7	-0.0035	2.5
20		-5	-0.0029	2.5
10		-7	-0.0040	2.5
0		-8	-0.0041	2.5
-10		-10	-0.0052	2.5
-20		-7	-0.0036	2.5
-30		-10	-0.0052	2.5
20	4.5	-10	-0.0055	2.5
20	5.5	-7	-0.0035	2.5

Test Frequency:1880.0MHz 16QAM 20MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	-13	-0.0067	2.5
40		-10	-0.0052	2.5
30		-7	-0.0039	2.5
20		-5	-0.0025	2.5
10		-6	-0.0033	2.5
0		-7	-0.0036	2.5
-10		-10	-0.0053	2.5
-20		-8	-0.0045	2.5
-30		-8	-0.0045	2.5
20	4.5	-9	-0.0047	2.5
20	5.5	-7	-0.0037	2.5

LTE Band 4

Test Frequency:1732.5MHz QPSK 1.4MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	-1	-0.0007	2.5
40		-7	-0.0042	2.5
30		-3	-0.0020	2.5
20		-3	-0.0015	2.5
10		2	0.0010	2.5
0		4	0.0026	2.5
-10		-5	-0.0026	2.5
-20		1	0.0006	2.5
-30		-1	-0.0003	2.5
20	4.5	1	0.0007	2.5
20	5.5	-2	-0.0013	2.5

Test Frequency:1732.5MHz 16QAM 1.4MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	-1	-0.0007	2.5
40		-7	-0.0040	2.5
30		-4	-0.0021	2.5
20		-3	-0.0019	2.5
10		0	0.0003	2.5
0		4	0.0024	2.5
-10		-4	-0.0023	2.5
-20		1	0.0006	2.5
-30		-1	-0.0004	2.5
20	4.5	0	-0.0001	2.5
20	5.5	-2	-0.0010	2.5

LTE Band 4

Test Frequency:1732.5MHz QPSK 3MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	0	0.0001	2.5
40		-9	-0.0050	2.5
30		-3	-0.0016	2.5
20		-4	-0.0023	2.5
10		0	0.0001	2.5
0		4	0.0023	2.5
-10		-4	-0.0024	2.5
-20		2	0.0014	2.5
-30		-1	-0.0004	2.5
20	4.5	0	0.0001	2.5
20	5.5	-2	-0.0009	2.5

Test Frequency:1732.5MHz 16QAM 3MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	-1	-0.0003	2.5
40		-8	-0.0047	2.5
30		-2	-0.0012	2.5
20		-3	-0.0015	2.5
10		1	0.0005	2.5
0		5	0.0031	2.5
-10		-4	-0.0024	2.5
-20		2	0.0011	2.5
-30		0	-0.0001	2.5
20	4.5	-1	-0.0003	2.5
20	5.5	-2	-0.0013	2.5

LTE Band 4

Test Frequency:1732.5MHz QPSK 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	-1	-0.0004	0
40		-8	-0.0044	6
30		-3	-0.0015	-3
20		-4	-0.0023	-2
10		2	0.0012	-7
0		5	0.0026	-3
-10		-3	-0.0019	-4
-20		2	0.0014	2
-30		1	0.0003	4
20	4.5	0	-0.0002	-3
20	5.5	-2	-0.0010	2

Test Frequency:1732.5MHz 16QAM 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	-1	-0.0006	2.5
40		-8	-0.0046	2.5
30		-2	-0.0012	2.5
20		-3	-0.0020	2.5
10		2	0.0010	2.5
0		5	0.0029	2.5
-10		-3	-0.0017	2.5
-20		1	0.0005	2.5
-30		0	0.0002	2.5
20	4.5	0	-0.0001	2.5
20	5.5	-2	-0.0012	2.5

LTE Band 4

Test Frequency:1732.5MHz QPSK 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	0	-0.0001	2.5
40		-7	-0.0043	2.5
30		-3	-0.0017	2.5
20		-4	-0.0024	2.5
10		2	0.0012	2.5
0		5	0.0032	2.5
-10		-4	-0.0023	2.5
-20		1	0.0006	2.5
-30		-1	-0.0003	2.5
20	4.5	1	0.0003	2.5
20	5.5	-2	-0.0013	2.5

Test Frequency:1732.5MHz 16QAM 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	0	-0.0002	2.5
40		-7	-0.0043	2.5
30		-2	-0.0012	2.5
20		-3	-0.0015	2.5
10		1	0.0008	2.5
0		5	0.0031	2.5
-10		-3	-0.0020	2.5
-20		1	0.0008	2.5
-30		-1	-0.0004	2.5
20	4.5	1	0.0008	2.5
20	5.5	-3	-0.0015	2.5

LTE Band 4

Test Frequency:1732.5MHz QPSK 15MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	-1	-0.0003	2.5
40		-8	-0.0047	2.5
30		-2	-0.0014	2.5
20		-3	-0.0018	2.5
10		1	0.0004	2.5
0		5	0.0028	2.5
-10		-3	-0.0017	2.5
-20		2	0.0014	2.5
-30		0	0.0001	2.5
20	4.5	0	-0.0001	2.5
20	5.5	-1	-0.0004	2.5

Test Frequency:1732.5MHz 16QAM 15MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	-1	-0.0004	2.5
40		-8	-0.0045	2.5
30		-3	-0.0017	2.5
20		-4	-0.0020	2.5
10		2	0.0011	2.5
0		5	0.0031	2.5
-10		-5	-0.0027	2.5
-20		0	0.0002	2.5
-30		0	-0.0003	2.5
20	4.5	1	0.0003	2.5
20	5.5	-2	-0.0012	2.5

LTE Band 4

Test Frequency:1732.5MHz QPSK 20MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	-1	-0.0005	2.5
40		-9	-0.0050	2.5
30		-2	-0.0011	2.5
20		-4	-0.0023	2.5
10		0	0.0003	2.5
0		5	0.0029	2.5
-10		-4	-0.0021	2.5
-20		2	0.0009	2.5
-30		1	0.0004	2.5
20	3.33	0	0.0001	2.5
20	4.07	-2	-0.0014	2.5

Test Frequency:1732.5MHz 16QAM 20MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	-1	-0.0005	2.5
40		-8	-0.0045	2.5
30		-4	-0.0021	2.5
20		-3	-0.0015	2.5
10		1	0.0007	2.5
0		5	0.0029	2.5
-10		-4	-0.0024	2.5
-20		1	0.0003	2.5
-30		-1	-0.0006	2.5
20	4.5	1	0.0007	2.5
20	5.5	-1	-0.0008	2.5

LTE Band 5

Test Frequency:836.5MHz QPSK 1.4MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	19	0.0225	2.5
40		-3	-0.0035	2.5
30		-4	-0.0046	2.5
20		-1	-0.0011	2.5
10		-1	-0.0014	2.5
0		-3	-0.0038	2.5
-10		-6	-0.0066	2.5
-20		-12	-0.0142	2.5
-30		-10	-0.0118	2.5
20	4.5	11	0.0127	2.5
20	5.5	3	0.0036	2.5

Test Frequency:836.5MHz 16QAM 1.4MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	19	0.0224	2.5
40		-2	-0.0027	2.5
30		-4	-0.0044	2.5
20		-1	-0.0016	2.5
10		0	-0.0001	2.5
0		-4	-0.0048	2.5
-10		-6	-0.0075	2.5
-20		-12	-0.0143	2.5
-30		-9	-0.0111	2.5
20	4.5	11	0.0131	2.5
20	5.5	2	0.0026	2.5

LTE Band 5

Test Frequency:836.5MHz QPSK 3MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	18	0.0219	2.5
40		-3	-0.0040	2.5
30		-3	-0.0036	2.5
20		0	-0.0003	2.5
10		0	0.0004	2.5
0		-3	-0.0037	2.5
-10		-6	-0.0077	2.5
-20		-12	-0.0144	2.5
-30		-11	-0.0129	2.5
20	4.5	11	0.0126	2.5
20	5.5	3	0.0034	2.5

Test Frequency:836.5MHz 16QAM 3MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	19	0.0224	2.5
40		-3	-0.0037	2.5
30		-4	-0.0042	2.5
20		-1	-0.0016	2.5
10		0	0.0003	2.5
0		-4	-0.0050	2.5
-10		-5	-0.0065	2.5
-20		-13	-0.0150	2.5
-30		-10	-0.0116	2.5
20	4.5	12	0.0140	2.5
20	5.5	3	0.0031	2.5

LTE Band 5

Test Frequency:836.5MHz QPSK 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	19	0.0223	2.5
40		-2	-0.0020	2.5
30		-4	-0.0045	2.5
20		-1	-0.0016	2.5
10		0	0.0002	2.5
0		-5	-0.0056	2.5
-10		-7	-0.0087	2.5
-20		-11	-0.0128	2.5
-30		-10	-0.0123	2.5
20	4.5	11	0.0127	2.5
20	5.5	2	0.0022	2.5

Test Frequency:836.5MHz 16QAM 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	18	0.0220	2.5
40		-3	-0.0038	2.5
30		-4	-0.0053	2.5
20		-1	-0.0017	2.5
10		-1	-0.0007	2.5
0		-3	-0.0038	2.5
-10		-5	-0.0063	2.5
-20		-11	-0.0130	2.5
-30		-11	-0.0128	2.5
20	4.5	10	0.0123	2.5
20	5.5	2	0.0021	2.5

LTE Band 5

Test Frequency:836.5MHz QPSK 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	18	0.0217	2.5
40		-2	-0.0025	2.5
30		-4	-0.0046	2.5
20		0	-0.0006	2.5
10		0	-0.0004	2.5
0		-3	-0.0036	2.5
-10		-6	-0.0073	2.5
-20		-12	-0.0138	2.5
-30		-10	-0.0118	2.5
20	4.5	10	0.0121	2.5
20	5.5	2	0.0025	2.5

Test Frequency:836.5MHz 16QAM 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	19	0.0231	2.5
40		-3	-0.0037	2.5
30		-4	-0.0042	2.5
20		-1	-0.0006	2.5
10		0	-0.0001	2.5
0		-3	-0.0037	2.5
-10		-6	-0.0068	2.5
-20		-11	-0.0137	2.5
-30		-10	-0.0122	2.5
20	4.5	12	0.0143	2.5
20	5.5	2	0.0024	2.5

LTE Band 66

Test Frequency:1755MHz QPSK 1.4MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	5	0.0029	2.5
40		-2	-0.0012	2.5
30		-3	-0.0015	2.5
20		0	0.0002	2.5
10		-9	-0.0049	2.5
0		-1	-0.0007	2.5
-10		-3	-0.0019	2.5
-20		-10	-0.0056	2.5
-30		-7	-0.0040	2.5
20	4.5	-2	-0.0014	2.5
20	5.5	-1	-0.0007	2.5

Test Frequency:1755MHz 16QAM 1.4MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	5	0.0028	2.5
40		-2	-0.0010	2.5
30		-3	-0.0016	2.5
20		0	0.0001	2.5
10		-9	-0.0052	2.5
0		-1	-0.0008	2.5
-10		-3	-0.0019	2.5
-20		-10	-0.0058	2.5
-30		-6	-0.0037	2.5
20	4.5	-3	-0.0015	2.5
20	5.5	-1	-0.0004	2.5

LTE Band 66

Test Frequency:1755MHz QPSK 3MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	6	0.0031	2.5
40		-1	-0.0007	2.5
30		-2	-0.0012	2.5
20		1	0.0008	2.5
10		-9	-0.0050	2.5
0		0	-0.0002	2.5
-10		-3	-0.0018	2.5
-20		-10	-0.0058	2.5
-30		-7	-0.0041	2.5
20	4.5	-4	-0.0021	2.5
20	5.5	-2	-0.0009	2.5

Test Frequency:1755MHz 16QAM 3MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	5	0.0027	2.5
40		-2	-0.0013	2.5
30		-2	-0.0011	2.5
20		1	0.0004	2.5
10		-10	-0.0058	2.5
0		-1	-0.0007	2.5
-10		-3	-0.0019	2.5
-20		-10	-0.0054	2.5
-30		-7	-0.0042	2.5
20	4.5	-3	-0.0015	2.5
20	5.5	0	-0.0002	2.5

LTE Band 66

Test Frequency:1755MHz QPSK 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	5	0.0027	2.5
40		-1	-0.0005	2.5
30		-3	-0.0016	2.5
20		0	-0.0001	2.5
10		-10	-0.0055	2.5
0		0	-0.0001	2.5
-10		-4	-0.0022	2.5
-20		-10	-0.0057	2.5
-30		-7	-0.0037	2.5
20	4.5	-4	-0.0020	2.5
20	5.5	-1	-0.0005	2.5

Test Frequency:1755MHz 16QAM 5MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	4	0.0023	2.5
40		-2	-0.0013	2.5
30		-2	-0.0012	2.5
20		1	0.0007	2.5
10		-10	-0.0054	2.5
0		0	-0.0003	2.5
-10		-2	-0.0012	2.5
-20		-9	-0.0051	2.5
-30		-7	-0.0041	2.5
20	4.5	-4	-0.0024	2.5
20	5.5	0	-0.0002	2.5

LTE Band 66

Test Frequency:1755MHz QPSK 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	4	0.0023	2.5
40		-2	-0.0011	2.5
30		-2	-0.0014	2.5
20		1	0.0007	2.5
10		-9	-0.0053	2.5
0		0	-0.0001	2.5
-10		-3	-0.0016	2.5
-20		-9	-0.0050	2.5
-30		-6	-0.0037	2.5
20	4.5	-2	-0.0014	2.5
20	5.5	0	-0.0001	2.5

Test Frequency:1755MHz 16QAM 10MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	4	0.0021	2.5
40		-1	-0.0004	2.5
30		-2	-0.0013	2.5
20		0	-0.0002	2.5
10		-9	-0.0054	2.5
0		0	-0.0002	2.5
-10		-2	-0.0014	2.5
-20		-10	-0.0059	2.5
-30		-7	-0.0037	2.5
20	4.5	-4	-0.0024	2.5
20	5.5	0	-0.0002	2.5

LTE Band 66

Test Frequency:1755MHz QPSK 15MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	5	0.0031	2.5
40		-2	-0.0010	2.5
30		-3	-0.0018	2.5
20		1	0.0005	2.5
10		-9	-0.0051	2.5
0		-1	-0.0008	2.5
-10		-3	-0.0014	2.5
-20		-9	-0.0052	2.5
-30		-7	-0.0042	2.5
20	4.5	-3	-0.0014	2.5
20	5.5	-2	-0.0010	2.5

Test Frequency:1755MHz 16QAM 15MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	5	0.0027	2.5
40		-2	-0.0009	2.5
30		-2	-0.0009	2.5
20		1	0.0004	2.5
10		-10	-0.0055	2.5
0		-1	-0.0005	2.5
-10		-4	-0.0021	2.5
-20		-10	-0.0055	2.5
-30		-7	-0.0040	2.5
20	4.5	-4	-0.0024	2.5
20	5.5	-1	-0.0008	2.5

LTE Band 66

Test Frequency:1755MHz QPSK 20MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	5	0.0031	2.5
40		-2	-0.0010	2.5
30		-3	-0.0020	2.5
20		0	-0.0002	2.5
10		-10	-0.0058	2.5
0		0	0.0000	2.5
-10		-3	-0.0014	2.5
-20		-10	-0.0054	2.5
-30		-7	-0.0041	2.5
20	4.5	-4	-0.0024	2.5
20	5.5	-1	-0.0008	2.5

Test Frequency:1755MHz 16QAM 20MHz				
Temperature (°C)	Power Supply (VDC)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	5	4	0.0026	2.5
40		-2	-0.0010	2.5
30		-2	-0.0011	2.5
20		1	0.0004	2.5
10		-10	-0.0054	2.5
0		-1	-0.0008	2.5
-10		-3	-0.0014	2.5
-20		-9	-0.0051	2.5
-30		-7	-0.0039	2.5
20	4.5	-3	-0.0019	2.5
20	5.5	-2	-0.0009	2.5

***** END OF REPORT *****