

FCC ID: 2BFCM-C35

RF exposure evaluation

§ 2.1093 Radiofrequency radiation exposure evaluation: Portable Devices.

According to § 15.247(i) and § 1.1307b(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the commission's guidance.

The 1-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- When the minimum test separation distance is < 5 mm, a distance of 5 mm according is applied to determine SAR test exclusion.
- The result is rounded to one decimal place for comparison

Modulation	Frequency (MHz)	Max. Power (dBm)	Tune-up Power (dBm)	Tune-up Power (mW)	Test distance (mm)	Result	Exclusion Thresholds for 1-g SAR
pi/4-DQPSK	2402	2.80	3.0	2.00	5	0.62	3.0
BLE 2M	2402	2.12	2.5	1.78	5	0.55	3.0