

# Testing Report

Customer Name: CANDY HOUSE JAPAN Inc.


Product Name: BLE Remote nano

Sample Model: CANDY HOUSE Remote nano

Reference Standard: *GB/T 9410-2008; ANSI/IEEE Std 149-1979*

Issue Date: 2023.12.26

|                 |                  |
|-----------------|------------------|
| Engineer: Zkmis | Date: 2023.12.25 |
| Auditor: Eason  | Date: 2023.12.26 |
| Approver: Jaron | Date: 2023.12.26 |



## Version

| Version No. | Date       | Description                   | Formulate | Approval |
|-------------|------------|-------------------------------|-----------|----------|
| A0          | 2023.12.26 | For the first time, formulate | Zkris     | Eason    |
|             |            |                               |           |          |
|             |            |                               |           |          |

## Contents


|                                                       |   |
|-------------------------------------------------------|---|
| 1.General Information .....                           | 3 |
| 1.1 General information of testing institutions ..... | 3 |
| 1.2 Testing principle .....                           | 3 |
| 1.3 Test equipment .....                              | 4 |
| 1.4 Test environment .....                            | 4 |
| 1.5 Statement .....                                   | 4 |
| 2.Sample Information .....                            | 5 |
| 2.1 Client information .....                          | 5 |
| 2.2 Description of EUT(S) .....                       | 5 |
| 2.3 EUT appearance .....                              | 6 |
| 2.4 EUT setup photo of free space OTA testing .....   | 6 |
| 3.Test Results .....                                  | 7 |
| 3.1 Test standard .....                               | 7 |
| 3.2 Test uncertainty .....                            | 7 |
| 3.3 Test data .....                                   | 7 |
| 3.3.1 Typical free space efficiency and gain .....    | 7 |
| 3.3.2 Typical free space radiation pattern .....      | 8 |
| (The following is blank) .....                        | 9 |

## 1.General Information

## 1.1 General information of testing institutions

|                  |                                                                                                                                                                                            |
|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Name</b>      | Shenzhen RFI-LAB Communication Technology Co., Ltd.                                                                                                                                        |
| <b>Address</b>   | 103 Building 1 Tingwei Industrial Park,No.6, Liufang Road, Zone 67Xingdong,Xin'an Subdistrict,Bao'an District, Shenzhen, Guangdong, China                                                  |
| <b>Tel</b>       | 13682621346                                                                                                                                                                                |
| <b>E-mail</b>    | rfi-lab@tech-now.com                                                                                                                                                                       |
| <b>Equipment</b> | All the equipment used in the report is fixed in 103 Building 1 Tingwei Industrial Park,No.6, Liufang Road, Zone 67Xingdong,Xin'an Subdistrict,Bao'an District, Shenzhen, Guangdong, China |

## 1.2 Testing principle



### 1.3 Test equipment

| Equipment        | Model No.    | Serial No.     | Manufacturer | Calibration date | Next calibration date |
|------------------|--------------|----------------|--------------|------------------|-----------------------|
| OTA Test System  | RayZone-5000 | RFI-LAB-RF-D00 | GTS          | 2023.3.14        | 2025.3.13             |
| Network Analyzer | E5071C       | RFI-LAB-RF-D01 | KEYSIGHT     | 2023.5.11        | 2024.5.10             |
| Network Analyzer | E5071C       | RFI-LAB-RF-C02 | KEYSIGHT     | 2023.5.11        | 2024.5.10             |

### 1.4 Test environment

|             |           |
|-------------|-----------|
| Temperature | 23.1°C    |
| Humidity    | 57%RH     |
| Pressure    | 100.19kPa |

### 1.5 Statement

- (1) The test results in the report are only applicable to the tested samples and the tested samples work under the environment described in the report.
- (2) Only Shenzhen RFI-LAB Communication Technology Co., Ltd. have the right to modify the report, and the modification information shall be annotated in the revision form.
- (3) Any objection to this report shall be raised within 30 days after formal confirmation of the report.
- (4) This report is invalid if there is any evidence that the sample information provided is falsified.
- (5) The report is invalid without the signature of the auditor and approver.

## 2.Sample Information



### 2.1 Client information

|                     |                                                             |
|---------------------|-------------------------------------------------------------|
| <b>Name</b>         | CANDY HOUSE JAPAN Inc.                                      |
| <b>Address</b>      | Pienoa-ku Irifune 5F,1-9-8 Irifune,Chuo,Tokyo 1040042 japan |
| <b>Contacts</b>     | /                                                           |
| <b>Tel</b>          | /                                                           |
| <b>E-mail</b>       | /                                                           |
| <b>Manufacturer</b> | CANDY HOUSE JAPAN Inc.                                      |

### 2.2 Description of EUT(S)


|                        |                                             |
|------------------------|---------------------------------------------|
| <b>Product Name</b>    | BLE Remote nano                             |
| <b>Sample Model</b>    | CANDY HOUSE Remote nano                     |
| <b>Antenna Size</b>    | /                                           |
| <b>Antenna Type</b>    | PCB Antenna                                 |
| <b>Test Item</b>       | Antenna gain; Efficiency; Radiation pattern |
| <b>Frequency Range</b> | 2400MHz-2500MHz                             |
| <b>Received Date</b>   | 2023.12.21                                  |
| <b>Test Date</b>       | 2023.12.25                                  |
| <b>Remark</b>          | /                                           |

## 2.3 EUT appearance




## 2.4 EUT setup photo of free space OTA testing

Planform



Front view



## 3. Test Results

### 3.1 Test standard

| Name                         | Parameter            | Method                                                               | Standard no.           |
|------------------------------|----------------------|----------------------------------------------------------------------|------------------------|
| Mobile communication antenna | Antenna gain         | Generic specification for antennas used in the mobile communications | GB/T 9410-2008         |
|                              | Radiation pattern    |                                                                      |                        |
| Antenna                      | Radiation efficiency | IEEE Standard Test Procedures for Antennas                           | ANSI/IEEE Std 149-1979 |
|                              | Gain and directivity |                                                                      |                        |

### 3.2 Test uncertainty

The uncertainty was calculated on the basis of the GUM published by ISO, using the inclusion factor of K=2 and the 95% confidence level to express the extended uncertainty.

| Item                 | Uncertainty         |
|----------------------|---------------------|
| Antenna gain         | $\pm 0.72\text{dB}$ |
| Radiation efficiency | $\pm 0.72\text{dB}$ |


### 3.3 Test data

#### 3.3.1 Typical free space efficiency and gain


| Frequency/MHz | 2400  | 2410  | 2420  | 2430  | 2440  | 2450  | 2460  | 2470  | 2480  | 2490  | 2500  |
|---------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Peak Gain/dBi | -2.65 | -2.69 | -2.65 | -2.57 | -2.70 | -2.88 | -2.85 | -2.75 | -2.98 | -3.20 | -3.28 |
| Efficiency/%  | 20.72 | 21.31 | 21.54 | 22.12 | 22.30 | 21.91 | 22.34 | 22.29 | 21.10 | 20.67 | 20.05 |

### 3.3.2 Typical free space radiation pattern


(1) X-Z Plane(unit:dBi):




(2) Y-Z Plane(unit:dBi):



(3) X-Y Plane(unit:dBi):



(4) Typical Free Space 3D Radiation Pattern at 2.43GHz(unit:dBi):



End

(The following is blank)