

# FCC RF EXPOSURE REPORT

## FCC ID: 2BFDS-DCS140

Test Report No.....: RF260527001-01-002

Product(s) Name.....: Smart Camera

Model(s).....: DCD101, DCD110, DCD111, DCD112, DCD120, DCD210, DCD130,  
DCD131, DCD132, DCD133, DCD134, DCD135 DCD136, DCS141,  
DCS142, DCS143, DCS140, DCS145, DCS149, DCS150

Trade Mark.....: N/A

Applicant.....: Hangzhou Denghong Technology Co.,Ltd.

Address.....: Paradise Software Park, No.3 Xidomen, Xihu District, Hangzhou,  
Zhejiang, China

Receipt Date.....: 2026.06.05

Test Date.....: 2026.06.08 ~ 2026.06.25

Issued Date.....: 2026.06.26

Standards.....: FCC Guidelines for Human Exposure IEEE C95.1  
FCC Title 47 Part 2.1091  
KDB 447498 D01 General RF Exposure Guidance v06

Testing Laboratory.....: Shenzhen Haiyun Standard Technical Co., Ltd.

| Prepared By:    | Checked By:       | Approved By:     |  |
|-----------------|-------------------|------------------|---------------------------------------------------------------------------------------|
| Lemon He        | Black Ding        | Tim Zhang        |                                                                                       |
| <i>Lemon He</i> | <i>Black Ding</i> | <i>Tim Zhang</i> |                                                                                       |

## History of this test report

Original Report Issue Date: 2026.06.26

- ☒ No additional attachment
- ☐ Additional attachments were issued following record

| Attachment No. | Issue Date | Description |
|----------------|------------|-------------|
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |

## 1. MPE CALCULATION METHOD

### Radio Frequency Exposure Limit

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) |
|-----------------------|-------------------------------|-------------------------------|-------------------------------------|
| 300-1,500             | --                            | --                            | f/1500                              |
| 1,500-100,000         | --                            | --                            | 1.0                                 |

### Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

### Table for Filed Antenna

For 2.4GHz\_WiFi:

| Antenna gain | Antenna Type |
|--------------|--------------|
| 3.24dBi      | FPC Antenna  |

## 2. TEST RESULTS

Worst case as below

| Operating Mode | Freq.     | Maximum conducted output power | Directional Antenna Gain | Calculated maximum EIRP |       | MPE Limit             | MPE Value |
|----------------|-----------|--------------------------------|--------------------------|-------------------------|-------|-----------------------|-----------|
|                | (MHz)     | (dBm)                          | (dBi)                    | (dBm)                   | (mW)  | (mW/cm <sup>2</sup> ) |           |
| 2.4G Wifi      | 2412-2462 | 15.55                          | 3.24                     | 18.79                   | 75.68 | 1                     | 0.015     |

Note: 1. The calculated distance is 20 cm.

Result: Complies

## Statement

1. The report is invalid without the official seal or special seal of Shenzhen Haiyun Standard Technical Co., Ltd. (hereinafter referred to as the unit).
2. The report is invalid without the signature of the approver.
3. The report is invalid if altered arbitrarily.
4. The report shall not be partially copied without the written approval of the unit.
5. The reported test results are only valid for the tested samples.
6. If there is any objection to the test report, it shall be submitted to the test unit within 15 days from the date of receiving the report, and the overdue shall not be accepted.

## Shenzhen Haiyun Standard Technical Co., Ltd.

Address: Room 110, 111, 112, 113, 115, 116, Block B, Jinyuan Business Building, No. 302, Xixiang Avenue, Labor Community, Xixiang Street, Baoan District, Shenzhen, China

---

(END OF REPORT)