

FCC Test Report

Test Report

On Behalf of

ALGAM

For

600W CONNECTED COLUMN SPEAKER

Model No.: CMIX600

FCC ID: 2BFGG-CMIX600

Prepared For: **ALGAM**

2 rue de Milan, 44470 THOUARE SUR LOIRE, France

Prepared By: **Shenzhen HUAKE Testing Technology Co., Ltd.**

1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

Date of Test: **Jun. 15, 2026 ~ Jul. 28, 2026**

Date of Report: **Jul. 28, 2026**

Report Number: **HK260615077-1E**

Test Result Certification

Applicant's Name : ALGAM

Address : 2 rue de Milan, 44470 THOUARE SUR LOIRE, France

Manufacturer's Name : ALGAM

Address : 2 rue de Milan, 44470 THOUARE SUR LOIRE, France

Product Description

Trade Mark : OFFSHORE

Product Name : 600W CONNECTED COLUMN SPEAKER

Model and/or Type Reference .. : CMIX600

47 CFR FCC Part 15 Subpart C 15.247

Standards : **KDB 558074 D01 15.247 Meas Guidance v05r02**

ANSI C63.10: 2020

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAKE Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAKE Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.


Date of Test :

Date (s) of Performance of Tests : **Jun. 15, 2026 ~ Jul. 28, 2026**

Date of Issue : **Jul. 28, 2026**

Test Result : **Pass**

Testing Engineer



Len Liao

Technical Manager



Sliver Wan

Authorized Signatory



Jason Zhou



Contents

Page

1	Summary	5
1.1	Test Procedures and Results	5
1.2	Measurement Uncertainty	6
1.3	Information of the Test Laboratory	6
2	General Information	7
2.1	General Description of EUT	7
2.2	Description of Test Conditions	9
2.3	Description of Test Setup	10
2.4	Description of Support Units	11
2.5	The Worst Case Power Setting Parameter	11
3	Equipments List for All Test Items	12
4	Test Result	13
4.1	Antenna Requirement	13
4.2	AC Conduction Emissions Measurement	14
4.3	Radiated Emissions Measurement	18
4.4	Maximum Peak Output Power Measurement	26
4.5	Power Spectral Density	27
4.6	6dB Bandwidth	30
4.7	Band Edge	33
4.8	Conducted Spurious Emissions	35
5	Test Setup Photos of the EUT	39
6	Photos of the EUT	41

**** Issued History ****

Revision	Description	Issued Date	Remark
Revision 1.0	Initial Test Report Release	Jul. 28, 2026	Jason Zhou



HUAK TESTING

1 Summary

1.1 Test Procedures and Results

Test Item	Standard Section	Result
Antenna Requirement	§15.203/§15.247(b)(4)	PASS
AC Conducted Emission	FCC Part 15.207	PASS
Radiated Emissions	FCC Part 15.205/15.209	PASS
Maximum Peak Output Power	FCC Part 15.247(b)	PASS
Power Spectral Density	FCC Part 15.247(e)	PASS
6dB Bandwidth	FCC Part 15.247(a)(2)/ FCC Part 15.215	PASS
Spurious RF Conducted Emission	FCC Part 15.247(d)	PASS
Band Edge	FCC Part 15.247(d)	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.



1.2 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

No.	Item	MU
1	Conducted Emission 0.15~30MHz	$\pm 2.22\text{dB}$
2	All Emissions, Radiated(<1G)	$\pm 3.60\text{dB}$
3	All Emissions, Radiated(1-18G)	$\pm 3.86\text{dB}$
4	All Emissions, Radiated(18-40G)	$\pm 4.76\text{dB}$
5	Transmitter Power Conducted	$\pm 0.37\text{dB}$
6	Conducted Spurious Emission	$\pm 2.20\text{dB}$
7	Occupied Bandwidth	$\pm 3.68\%$
8	Temperature	$\pm 0.1^{\circ}\text{C}$
9	Humidity	$\pm 1.0\%$

1.3 Information of the Test Laboratory

Shenzhen HUAKE Testing Technology Co., Ltd.

Add.: 1-2/F., Building B2, Junfeng Zhongcheng Zhizao Innovation Park, Heping, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

**HUAK TESTING**

2 General Information

2.1 General Description of EUT

EUT Name:	600W CONNECTED COLUMN SPEAKER
Model No:	CMIX600
Series Model(s):	N/A
Model Difference:	N/A
Operation Frequency:	2402 MHz to 2480 MHz
Channel Separation:	2MHz
Number of Channel:	40
Modulation Technology:	GFSK
Hardware Version:	V4
Software Version:	V1.0
Antenna Type:	PCB Antenna
Antenna Gain:	3.38dBi
Power Supply:	100-240V AC/50-60Hz
Note: 1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual. 2. Antenna gain Refer to the antenna specifications. 3. The cable loss data is obtained from the supplier. 4. The test results in the report only apply to the tested sample.	



Description of Channel					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	14	2430	28	2458
1	2404	15	2432	29	2460
2	2406	16	2434	30	2462
3	2408	17	2436	31	2464
4	2410	18	2438	32	2466
5	2412	19	2440	33	2468
6	2414	20	2442	34	2470
7	2416	21	2444	35	2472
8	2418	22	2446	36	2474
9	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454		
13	2428	27	2456		

The EUT has been operated in modulations: GFSK independently.

No.	Test Mode Description
1	Low channel TX
2	Middle channel TX
3	High channel TX

Note:

1. All the test modes can be supply by serial port, only the result of the worst case was recorded in the report if no any records.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.

2.2 Description of Test Conditions

(1) E.U.T. test conditions:

For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.


(2) Frequency range of radiated measurements:

The test range will be up to the tenth harmonic of the highest fundamental frequency.

(3) Pre-test the EUT in all transmitting mode at the lowest (2402 MHz), middle (2440 MHz) and highest (2480 MHz) channel with different data packet and conducted to determine the worst-case mode, only the worst-case results are recorded in this report.

(4) Mode Test Duty Cycle


Mode	Duty Cycle
BT-LE(1Mbps)	0.8760





2.3 Description of Test Setup

Operation of EUT during AC Conducted and Radiation testing:



Operation of EUT during RF Conducted testing:



The sample was placed (0.1m below 1GHz, 0.1m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. The worst case is X position.



2.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Trade Mark	Model Name	Specification	Remark
1	600W CONNECTED COLUMN SPEAKER	OFFSHORE	CMIX600	N/A	EUT
2	Cable	N/A	N/A	Length: 150cm	

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

2.5 The Worst Case Power Setting Parameter

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the end product.

Test Software Version	bt_tool_v1.1.4
Transmit Antenna Number	1
Test Software setting value	7



3 Equipments List for All Test Items

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N.	R&S	ENV216	HKE-002	2026/02/11	1 Year
2	L.I.S.N.	R&S	ENV216	HKE-059	2026/02/04	1 Year
3	EMI Test Receiver	R&S	ESR-7	HKE-005	2026/02/06	1 Year
4	Spectrum analyzer	Agilent	N9020A	HKE-025	2026/02/06	1 Year
5	Spectrum analyzer	KEYSIGHT	N9020A	HKE-117	2026/02/06	1 Year
6	Spectrum analyzer	R&S	FSV3044	HKE-126	2026/02/06	1 Year
7	Preamplifier	Schwarzbeck	EMC051845SE	HKE-006	2026/02/04	1 Year
8	Preamplifier	Agilent	83051A	HKE-016	2026/02/04	1 Year
9	Preamplifier	QJD	QJD18-40-50	HKE-030	2026/02/05	1 Year
10	6dB Attenuator	Pasternack	6dB	HKE-152	2026/02/06	1 Year
11	EMI Test Receiver	R&S	ESR-7	HKE-010	2026/02/06	1 Year
12	Broadband Antenna	Schwarzbeck	VULB9168	HKE-167	2026/02/06	2 Year
13	Loop Antenna	COM-POWER	AL-130R	HKE-014	2026/02/06	2 Year
14	Horn Antenna	Schwarzbeck	9120D	HKE-013	2026/02/06	2 Year
15	Broadband Horn Antenna	A-INFO	LB-180400-KF	HKE-031	2026/02/06	2 Year
16	EMI Test Software	Tonscend	JS32-CE 2.5.0.6	HKE-081	/	/
17	EMI Test Software	Tonscend	JS32-RE 5.0.0	HKE-082	/	/
18	RF Automatic control unit	Tonscend	JS0806-2	HKE-060	2026/02/06	1 Year
19	High pass filter unit	Tonscend	JS0806-F	HKE-055	2026/02/06	1 Year
20	Wireless Communication Test Set	R&S	CMW500	HKE-027	2026/02/06	1 Year
21	High-low temperature chamber	Guangke	HT-80L	HKE-118	2026/02/06	1 Year
22	Temperature and humidity meter	Boyang	HTC-1	HKE-075	2026/03/06	1 Year
23	RF Test Software	Tonscend	JS1120-3 Version 3.6.21	HKE-083	/	/
24	10dB Attenuator	Schwarzbeck	VTSD9561F	HKE-153	2026/02/04	1 Year
25	RSE Test Software	Tonscend	JS36-RSE 5.0.0	HKE-184	/	/

4 Test Result

4.1 Antenna Requirement

4.1.1 Standard Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247, if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.


Refer to statement below for compliance.

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction

The antenna used in this product is a PCB Antenna, is a permanently attached antenna on the PCB. It conforms to the standard requirements. The directional gains of antenna used for transmitting is 3.38dBi.

4.1.2 EUT Antenna



4.2 AC Conduction Emissions Measurement

4.2.1 Applied Procedures / Limit

According to FCC CFR Title 47 Part 15 Subpart C Section 15.207, AC Power Line Conducted Emissions Limits for Licence-Exempt Radio Apparatus as below:


Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

4.2.2 Test Procedure

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.1 meters is used and is placed on the ground plane as per ANSI C63.10.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. The adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

4.2.3 Test Setup



Remark:

E.U.T: Equipment Under Test


LISN: Line Impedance Stabilization Network

Test table height=0.1m

4.2.4 Test Results

All the test modes completed for test. Only the worst result was reported as below:

Test Specification: Line



Suspected List


NO.	Freq. [MHz]	Level [dBμV]	Factor [dB]	Limit [dBμV]	Margin [dB]	Reading [dBμV]	Detector	Type
1	0.2490	43.85	19.77	61.79	17.94	24.08	PK	L
2	0.5100	39.27	19.86	56.00	16.73	19.41	PK	L
3	0.8520	40.19	19.91	56.00	15.81	20.28	PK	L
4	1.5315	40.58	19.98	56.00	15.42	20.60	PK	L
5	2.7780	42.03	20.12	56.00	13.97	21.91	PK	L
6	5.0460	42.25	20.23	60.00	17.75	22.02	PK	L

Remark: Margin = Limit – Level

Correction factor = Cable lose + LISN insertion loss

Level=Test receiver reading + correction factor

Test Specification: Neutral



Suspected List

NO.	Freq. [MHz]	Level [dBμV]	Factor [dB]	Limit [dBμV]	Margin [dB]	Reading [dBμV]	Detector	Type
1	0.1725	40.76	19.86	64.84	24.08	20.90	PK	N
2	0.2535	44.45	19.79	61.64	17.19	24.66	PK	N
3	0.7350	40.52	19.95	56.00	15.48	20.57	PK	N
4	2.2110	40.89	20.17	56.00	15.11	20.72	PK	N
5	5.4960	42.39	20.45	60.00	17.61	21.94	PK	N
6	15.3555	45.79	22.03	60.00	14.21	23.76	PK	N

Remark: Margin = Limit – Level

Correction factor = Cable lose + LISN insertion loss

Level=Test receiver reading + correction factor

4.3 Radiated Emissions Measurement

4.3.1 Applied Procedures / Limit

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission out of authorized band shall not exceed the following table at a 3 meters measurement distance.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

Except when the requirements applicable to a given device state otherwise, emissions from license-exempt transmitters shall comply with the field strength limits shown in table below. Additionally, the level of any transmitter emission shall not exceed the level of the transmitter's fundamental emission.


Radiated Emission Limits

Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500


4.3.2 Test Setup

Test Configuration:


- 1) 9 kHz to 30 MHz emissions:



2) 30 MHz to 1 GHz emissions:



3) 1 GHz to 26 GHz emissions:



Test Procedure


1. The EUT was placed on turn table which is 0.1m above ground plane for below 1GHz test, and on a low permittivity and low loss tangent turn table which is 0.1m above ground plane for above 1GHz test.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0 degrees to 360 degrees to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.

4.3.3 Test Result

Below 1GHz Test Results

All modes have been tested, only the worst mode of GFSK Low channel TX is reflected.


Antenna polarity: Horizontal



Suspected List									
NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	67.868	-16.14	35.05	18.91	40.00	21.09	100	258	Horizontal
2	109.620	-14.69	37.65	22.96	43.50	20.54	100	61	Horizontal
3	168.849	-17.13	48.50	31.37	43.50	12.13	100	100	Horizontal
4	254.294	-12.96	42.02	29.06	46.00	16.94	100	272	Horizontal
5	426.156	-9.24	32.11	22.87	46.00	23.13	100	14	Horizontal
6	691.231	-4.41	37.37	32.96	46.00	13.04	100	178	Horizontal

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

Antenna polarity: Vertical



Suspected List

NO.	Freq. [MHz]	Factor [dB]	Reading [dBμV/m]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	33.884	-15.39	47.35	31.96	40.00	8.04	100	19	Vertical
2	39.710	-13.68	37.20	23.52	40.00	16.48	100	193	Vertical
3	55.245	-13.35	38.82	25.47	40.00	14.53	100	158	Vertical
4	94.084	-15.49	39.58	24.09	43.50	19.41	100	183	Vertical
5	168.849	-17.13	45.87	28.74	43.50	14.76	100	97	Vertical
6	252.352	-13.04	34.82	21.78	46.00	24.22	100	214	Vertical

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

Harmonics and Spurious Emissions

Frequency Range (9kHz-30MHz)

Frequency (MHz)	Level@3m (dBμV/m)	Limit@3m (dBμV/m)
--	--	--
--	--	--
--	--	--
--	--	--

Note: 1. Emission Level=Reading+ Cable loss+ Antenna factor-Amp factor.


2. The emission levels are 20 dB below the limit value, which are not reported. It is deemed to comply with the requirement.

Above 1GHz Test Results

All the test modes completed for test. only the worst mode of GFSK Low channel TX is reflected.

For 1GHz to 18GHz

Antenna polarity: Horizontal




Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	PK Level [dBμV/m]	Factor [dB]	PK Limit [dBμV/m]	PK Margin [dB]	Height [cm]	Angle [°]	Polarity
1	2210.121	63.83	49.14	-14.69	74.00	24.86	150	81	Horizontal
2	2258.126	69.20	54.66	-14.54	74.00	19.34	150	70	Horizontal
3	2305.731	68.22	53.73	-14.49	74.00	20.27	150	70	Horizontal
4	2497.750	65.74	51.31	-14.43	74.00	22.69	150	70	Horizontal
5	2545.955	64.01	49.75	-14.26	74.00	24.25	150	63	Horizontal
6	17917.492	45.87	52.25	6.38	74.00	21.75	150	359	Horizontal

AV Final Data List								
NO	Freq. [MHz]	Factor [dB]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	2210.121	-14.69	47.34	54.00	6.66	150	81	Horizontal
2	2258.013	-14.54	52.90	54.00	1.10	150	70	Horizontal
3	2306.007	-14.49	51.98	54.00	2.02	150	70	Horizontal
4	2497.750	-14.43	49.84	54.00	4.16	150	70	Horizontal
5	2545.955	-14.26	47.53	54.00	6.47	150	63	Horizontal
6	17917.492	6.38	42.37	54.00	11.63	150	359	Horizontal

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor;

Margin = Limit – Level

Antenna polarity: Vertical




Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	PK Level [dBμV/m]	Factor [dB]	PK Limit [dBμV/m]	PK Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1008.001	62.68	42.43	-20.25	74.00	31.57	150	117	Vertical
2	2306.131	60.37	45.88	-14.49	74.00	28.12	150	159	Vertical
3	9267.627	51.73	50.76	-0.97	74.00	23.24	150	355	Vertical
4	11642.364	48.73	51.35	2.62	74.00	22.65	150	31	Vertical
5	14702.670	47.67	51.42	3.75	74.00	22.58	150	13	Vertical
6	17963.996	45.07	52.03	6.96	74.00	21.97	150	230	Vertical

AV Final Data List								
NO	Freq. [MHz]	Factor [dB]	AV Value [dBμV/m]	AV Limit [dBμV/m]	AV Margin [dB]	Height [cm]	Angle [°]	Polarity
1	1008.001	-20.25	35.64	54.00	18.36	150	117	Vertical
2	2306.131	-14.49	41.28	54.00	12.72	150	159	Vertical
3	9267.627	-0.97	39.77	54.00	14.23	150	355	Vertical
4	11642.364	2.62	40.59	54.00	13.41	150	31	Vertical
5	14702.670	3.75	41.21	54.00	12.79	150	13	Vertical
6	17963.996	6.96	41.36	54.00	12.64	150	230	Vertical

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor;
Margin = Limit – Level

For 18GHz to 26GHz


Antenna polarity: Horizontal



Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	PK Level [dBμV/m]	Factor [dB]	PK Limit [dBμV/m]	PK Margin [dB]	Height [cm]	Angle [°]	Polarity
1	19561.756	39.21	45.31	6.10	74.00	28.69	150	180	Horizontal
2	20145.815	39.40	45.51	6.11	74.00	28.49	150	360	Horizontal
3	20647.465	40.24	46.06	5.82	74.00	27.94	150	140	Horizontal
4	21929.993	41.71	47.39	5.68	74.00	26.61	150	240	Horizontal
5	22468.447	42.78	48.43	5.65	74.00	25.57	150	110	Horizontal
6	23280.528	41.34	47.01	5.67	74.00	26.99	150	60	Horizontal

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level

Antenna polarity: Vertical



Suspected Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	PK Level [dBμV/m]	Factor [dB]	PK Limit [dBμV/m]	PK Margin [dB]	Height [cm]	Angle [°]	Polarity
1	18683.268	39.15	44.61	5.46	74.00	29.39	150	40	Vertical
2	19488.149	38.87	44.96	6.09	74.00	29.04	150	160	Vertical
3	20166.617	39.47	45.57	6.10	74.00	28.43	150	250	Vertical
4	21100.310	40.72	46.04	5.32	74.00	27.96	150	280	Vertical
5	21933.193	41.92	47.60	5.68	74.00	26.40	150	220	Vertical
6	23343.734	41.23	46.90	5.67	74.00	27.10	150	80	Vertical

Remark: Factor = Cable loss + Antenna factor + Attenuator – Preamplifier; Level = Reading + Factor; Margin = Limit – Level