



TEST REPORT

Test item description: Projector
FCC ID: 2BFIZ-GIMBALA5
Trademark(s): N/A
Model/Type reference: Gimbal A5, X3AR, SMOON 350, SMOON 360, TP300, TP300 NTV, X3AR100, X3AR200, X3AR300, CR100, CR200, CR300, X3BR, HY310X, X3CR, Gimbal N5, X3AQ, X3AA, X3, HY310X NTC, CI1003, AC1066, X3 One, X3 Pro, X3 Max, X3 Plus, C3, D3, L600, L600D, L600G, L600X, X3 Ultra
Applicant's name: Chengdu Hotack Technology Co., Ltd.
Address: 501-502, Unit 3, Building 13, No. 666 Jinfenghuang Avenue, High-tech Industry Park, Jinniu District, Chengdu City, Si Chuan Province, China.
Manufacturer: Chengdu Hotack Technology Co., Ltd.
Address: 501-502, Unit 3, Building 13, No. 666 Jinfenghuang Avenue, High-tech Industry Park, Jinniu District, Chengdu City, Si Chuan Province, China.
Prepared By: Shenzhen CTB Testing Technology Co., Ltd.
Address: 1&2/F., Building A, No.26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China
Sample Received Date: Nov. 15, 2025
Sample tested Date: Nov. 15, 2025 to Dec. 05, 2025
Issue Date: Dec. 05, 2025
Report No.: CTB25111500206RF04
Test Standards: FCC CFR Title 47 Part 15 Subpart E Section 15.407
KDB 789033 V02r01
Test Results: PASS
Remark: This is WIFI-5GHz band radio test report.

Compiled by:

Reviewed by:

Approved by:

Kai Chen

Kai Chen

Martin Feng

Martin FengBin Mei / Director

Note: If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client. "*" indicates the testing items were fulfilled by subcontracted lab. "#" indicates the items are not in CNAS accreditation scope.

TABLE OF CONTENT

Test Report Declaration	Page
1. VERSION.....	3
2. TEST SUMMARY	4
3. MEASUREMENT UNCERTAINTY	5
4. PRODUCT INFORMATION AND TEST SETUP	6
4.1 Product Information	6
4.2 Test Setup Configuration.....	6
4.3 Support Equipment.....	6
4.5 Test Mode	8
4.6 Test Environment	8
5. TEST FACILITY AND TEST INSTRUMENT USED	9
5.1 Test Facility	9
5.2 Test Instrument Used	9
6. AC POWER LINE CONDUCTED EMISSION.....	12
6.1 Block Diagram Of Test Setup.....	12
6.2 Limit.....	12
6.3 Test procedure	12
6.4 Test Result	14
7. RADIATED SPURIOUS EMISSIONS.....	18
7.1 Block Diagram Of Test Setup.....	18
7.2 Limit.....	18
7.3 Test procedure	19
7.4 Test Result	20
8. BAND EDGE	28
8.1 Block Diagram Of Test Setup.....	28
8.2 Limit.....	28
8.3 Test procedure	28
8.4 Test Result	29
9. CONDUCTED OUTPUT POWER.....	35
9.1 Block Diagram Of Test Setup.....	35
9.2 Limit.....	35
9.3 Test procedure	36
9.4 Test Result	37
10. EMISSION BANDWIDTH& OCCUPIED BANDWIDTH.....	45
10.1 Block Diagram Of Test Setup.....	45
10.2 Limits.....	45
10.3 Test Procedure.....	45
10.4 Test Results	47
11. POWER SPECTRAL DENSITY.....	54
11.1 Block Diagram Of Test Setup.....	54
11.2 Limit.....	54
11.3 Test procedure	54
11.4 Test Result	56
12. FREQUENCY STABILITY	63
12.1 Block Diagram Of Test Setup.....	63
12.2 Limit.....	63
12.3 Test procedure	63
12.4 Test Result	64
13. OPERATION IN THE ABSENCE OF INFORMATION TO THE TRANSMIT.....	70
13.1 Requirement.....	70
13.2 Test Results	70
14. ANTENNA REQUIREMENT	71
15. EUT TEST SETUP PHOTOGRAPHS.....	72

(NOTE: N/A MEANS NOT APPLICABLE)

1. VERSION

Report No.	Issue Date	Description	Approved
CTB25111500206RF04	Dec. 05, 2025	Original	Valid

2. TEST SUMMARY

The Product has been tested according to the following specifications:

Test Item	Test Requirement	Test method	Result
AC Power Line Conducted Emission	47 CFR Part 15 Subpart E Section 15.407 (b)(9)	ANSI C63.10-2020	PASS
Radiated Spurious emissions	47 CFR Part 15 Subpart E Section 15.205/15.407(b)	KDB789033v02r01	PASS
Band edge	47 CFR Part 15 Subpart E Section 15.205/15.407(b)	KDB789033v02r01	PASS
Conducted Peak Output Power	47 CFR Part 15 Subpart E Section 15.407 (a)	KDB789033v02r01	PASS
Emission Bandwidth & Occupied Bandwidth	47 CFR Part 15 Subpart E Section 15.407 (a)(e)	KDB789033v02r01	PASS
Power Spectral Density	47 CFR Part 15 Subpart E Section 15.407 (a)	KDB789033v02r01	PASS
Frequency stability	47 CFR Part 15 Subpart E Section 15.407 (g)	KDB789033v02r01	PASS
Operation in the absence of information to the transmit	47 CFR Part 15 Subpart E Section 15.407 (c)	47 CFR Part 15 Subpart E	PASS
Antenna Requirement	47 CFR Part 15 Subpart E Section 15.203	ANSI C63.10-2020	PASS

Remark:

Test according to ANSI C63.10-2020.

3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Uncertainty
1	Occupancy bandwidth	$U=\pm 54.3\text{Hz}$
2	Adjacent channel power	$U=\pm 1.3\text{dB}$
3	Conducted Adjacent channel power	$U=\pm 1.38\text{dB}$
4	Conducted output power above 1G	$U=\pm 1.0\text{dB}$
5	Conducted output power below 1G	$U=\pm 0.9\text{dB}$
6	Power Spectral Density, Conduction	$U=\pm 1.0\text{dB}$
7	Conduction spurious emissions	$U=\pm 2.8\text{dB}$
8	Out of band emission	$U=\pm 54\text{Hz}$
9	3m chamber Radiated spurious emission(30MHz-1GHz)	$U=\pm 4.3\text{dB}$
10	3m chamber Radiated spurious emission(1GHz-18GHz)	$U=\pm 4.5\text{dB}$
11	Humidity uncertainty	$U=\pm 5.3\%$
12	Temperature uncertainty	$U=\pm 0.59^{\circ}\text{C}$
13	Supply volyages	$U=\pm 3\%$
14	Time	$U=\pm 5\%$
15	Conducted Emission(150kHz-30MHz)	3.2 dB
16	3m camber Radiated spurious emission(9kHz-30MHz)	4.8dB
17	3m chamber Radiated spurious emission(18GHz-40GHz)	3.4dB

4. PRODUCT INFORMATION AND TEST SETUP

4.1 Product Information

Model/Type reference:	Gimbal A5, X3AR, SMOON 350, SMOON 360, TP300, TP300 NTV, X3AR100, X3AR200, X3AR300, CR100, CR200, CR300, X3BR, HY310X, X3CR, Gimbal N5, X3AQ, X3AA, X3, HY310X NTC, CI1003, AC1066, X3 One, X3 Pro, X3 Max, X3 Plus, C3, D3, L600, L600D, L600G, L600X, X3 Ultra
Model Description:	All the model are the same circuit and RF module, only the model names, colors and appearances are different. Test sample model: Gimbal A5
Wi-Fi Specification:	IEEE 802.11a/n/ac/ax
Hardware Version:	LCD H726 68156A
Software Version:	Android 14
Operation Frequency:	IEEE 802.11a/n/ac/ax(20M): 5150MHz ~5250MHz/ 4 channel IEEE 802.11n/ac/ax(40M): 5150MHz ~5250MHz/ 2 channel IEEE 802.11a/n/ac/ax(20M): 5725MHz ~5850MHz/ 5 channel IEEE 802.11n/ac/ax(40M): 5725MHz ~5850MHz/ 2 channel
Max. RF output power:	WiFi (5G):14.749dBm
Type of Modulation:	WiFi (5G): OFDM, OFDMA
Antenna installation:	WiFi (5G): FPC antenna
Antenna Gain:	WiFi (5.2G): 1.57dBi WiFi (5.8G): 2.4dBi
Ratings:	Input:45V=0.85A,12V=0.7A (Simultaneous Input)

4.2 Test Setup Configuration

See test photographs attached in EUT TEST SETUP PHOTOGRAPHS for the actual connections between Product and support equipment.

4.3 Support Equipment

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1.	Laptop	DELL	Vostro 5490	N/A	AE
2.	AC adapter	Dongguan Yuanhong Electronic Technologies Co.,Ltd.	HYP317-4500850US	N/A	N/A
3.	AC adapter	Guangdong Mingxin Power Technologies Co.,Ltd.	MX60WB-4500850U-1200700U	N/A	N/A

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the

test.

2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.4 Channel List

For 802.11a/n/ac/ax(20M) Operation in the 5180MHz ~5240 MHz band			
Channel	Frequency	Channel	Frequency
36	5180MHz	44	5220MHz
40	5200MHz	48	5240MHz
For 802.11a/n/ac/ax(20M) Operation in the 5745MHz ~5825 MHz band			
Channel	Frequency	Channel	Frequency
149	5745MHz	161	5805MHz
153	5765MHz	165	5825MHz
157	5785MHz	NA	NA

For 802.11n/ac/ax(40M) Operation in the 5190MHz ~5230 MHz band			
Channel	Frequency	Channel	Frequency
38	5190MHz	46	5230MHz
For 802.11n/ac/ax(40M) Operation in the 5755MHz ~5795 MHz band			
Channel	Frequency	Channel	Frequency
151	5755MHz	159	5795MHz

NOTE: Duty cycle>98%.

Test mode	Rate
802.11a	54M
802.11n	500M
802.11ac/ax	500M

4.5 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests, the worst data were recorded and reported.

Test Mode	Tx/Rx	RF Channel		
		Low(L)	Middle(M)	High(H)
802.11a/n/ac/ax(20M)	5180MHz ~5240 MHz	Channel 36	Channel 40	Channel 48
		5180MHz	5200MHz	5240MHz
802.11n/ac/ax(40M)	5180MHz ~5240 MHz	Channel 38	N/A	Channel 46
		5190MHz	N/A	5230MHz
802.11a/n/ac/ax(20M)	5745MHz ~5825MHz	Channel 149	Channel 157	Channel 165
		5745MHz	5785MHz	5825MHz
802.11n/ac/ax(40M)	5745MHz ~5825MHz	Channel 151	N/A	Channel 159
		5755MHz	N/A	5795MHz

4.6 Test Environment

Humidity(%):	54
Atmospheric Pressure(kPa):	101
Normal Voltage(AC):	120V
Normal Temperature(°C):NT	23
Low Temperature(°C):LT	0
High Temperature(°C):HT	40

5. TEST FACILITY AND TEST INSTRUMENT USED

5.1 Test Facility

All measurement facilities used to collect the measurement data are located at 1&2F., Building A, No. 26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

FCC Test Firm Registration Number: CN1276

5.2 Test Instrument Used

No.	Equipment	Manufacturer	Type No.	Serial No.	Firmware Version	Calibrated Date	Calibrated until
1	Spectrum Analyzer	Agilent	N9020A	MY52090073	A.14.16	2025/5/23	2026/5/22
2	Power Sensor	Agilent	U2021XA	MY56120032	/	2025/5/23	2026/5/22
3	Power Sensor	Agilent	U2021XA	MY56120034	/	2025/5/23	2026/5/22
4	Communication test set	R&S	CMW500	108058	V3.5.80	2025/5/23	2026/5/22
5	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	A.14.16	2025/5/23	2026/5/22
6	Signal Generator	Agilent	N5181A	MY50140365	A.01.60	2025/5/22	2026/5/21
7	Vector signal generator	Agilent	N5182A	MY47420195	A.01.87	2025/5/22	2026/5/21
8	Communication test set	Agilent	E5515C	MY50102567	B.19.07 (E1962B)	2025/5/22	2026/5/21
9	2.4 GHz Filter	Shenxiang	MSF2400-2483.5MS-1154	20181015001	/	2025/6/18	2026/6/17
10	5 GHz Filter	Shenxiang	MSF5150-5850 MS-1155	20181015001	/	2025/6/18	2026/6/17
11	Filter	Xingbo	XBLBQ-DZA120	190821-1-1	/	2025/5/24	2026/5/23
12	BT&Wi-Fi Automatic test software	Microwave	MTS8310	Ver. 2.0.0.0	/	/	/
13	Rohde & Schwarz SFU Broadcast Test System	R&S	SFU	101017	/	2025/10/20	2026/10/19
14	Temperature humidity chamber	Hongjing	TH-80CH	DG-15174	/	2025/5/22	2026/5/21
15	234G Automatic test software	Microwave	MTS8200	Ver. 2.0.0.0	/	/	/
16	966 chamber	C.R.T.	966	/	/	2024/6/23	2027/6/22
17	Receiver	R&S	ESPI	100362	RF_ATTEN_7	2025/5/23	2026/5/22

					(104489/003)		
18	Amplifier	HP	8447E	2945A02747	/	2025/5/23	2026/5/22
19	Amplifier	Agilent	8449B	3008A01838	/	2025/6/2	2026/6/1
20	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	00869	/	2025/6/29	2026/6/28
21	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA9120D	01911	/	2025/6/1	2026/5/31
22	EMI test software	Fala	EZ-EMC	FA-03A2 RE	/	/	/
23	Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-224	/	2025/6/2	2026/6/1
24	loop antenna	ZHINAN	ZN30900A	GTS534	/	/	/
25	40G Horn antenna	A/H/System	SAS-574	588	/	2025/6/2	2026/6/1
26	Amplifier	AEROFLEX	Aeroflex	097	/	2025/6/2	2026/6/1
27	Power Meter	KEYSIGHT	N1912AP	N/A	A.05.00	2025/6/2	2026/6/1


Continuous disturbance							
No.	Equipment	Manufacturer	Model No.	Serial No.	Firmware version	Calibrated Date	Calibrated until
1	843 Shield Room	C/ R/ T	843	/	/	2024/6/22	2027/6/21
2	LISN	ROHDE&SCHWARZ	ESH3-Z5	831551852	/	2025/5/22	2026/5/21
3	EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100428	V4.42.SP3	2025/5/22	2026/5/21
4	Coaxial cable	ZDECL	Z302S	18091904	/	2025/5/22	2026/5/21
5	ISN	Schwarzbeck	NTFM8158	183	/	2025/6/18	2026/6/17
6	Voltage sensor	Schwarzbeck	TK 9420	01189	/	2025/9/19	2026/9/18
7	EZ-EMC	Frad	EMC-con3A1.1	/	/	/	/
8	Current Probe	FCC	F-52B	199453	/	2025/5/24	2026/5/23
9	Communication test set	R&S	CMW500	108058	B.19.07 (E1962B)	2025/5/23	2026/5/22
10	Communication test set	Agilent	E5515C	MY50102567	V3.5.80	2025/5/23	2026/5/22

Radiated emission(No.2 Chamber)							
No.	Equipment	Manufacturer	Model No.	Serial No.	Firmware version	Calibrated Date	Calibrated until
1	966 Chamber	C/ R/ T	966	/	/	2024/6/8	2027/6/7
2	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA 9120 D	01911	/	2025/6/1	2026/5/31
3	Broadband Antenna	Schwarzbeck	VULB 9168	1471	/	2025/9/19	2026/9/18
4	Amplifier	Agilent	8449B	3008A01838	/	2025/6/3	2026/6/2

5	Preamplifier	Schwarzbeck	BBV 9743 B	00500	/	2025/5/30	2026/5/29
6	EMI TEST RECEIVER	R&S	ESCI7	100861	/	2025/9/19	2026/9/18
7	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	A.14.16	2025/5/23	2026/5/22
8	EMI test software	Farad	EZ-EMC	/	Ver. FARAD-3A1+	/	/
9	Coaxial cable	Rosenberg	8m	/	/	2025/9/19	2026/9/18
10	Coaxial cable	Times	2m	/	/	2025/9/19	2026/9/18
11	Coaxial cable	Times	2m	/	/	2025/9/19	2026/9/18
12	Coaxial cable	Times	1m	/	/	2025/9/19	2026/9/18
13	loop antenna	Schwarzbeck	FMZB 1519B	1519B-224	/	2025/6/2	2026/6/1
14	Communication test set	R&S	CMW500	108058	B.19.07 (E1962B)	2025/5/23	2026/5/22
15	Communication test set	Agilent	E5515C	MY50102567	V3.5.80	2025/5/23	2026/5/22

6. AC POWER LINE CONDUCTED EMISSION

6.1 Block Diagram Of Test Setup



6.2 Limit

Table 4 – AC power-line conducted emissions limits

Frequency (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 ^{Note 1}	56 to 46 ^{Note 1}
0.5 - 5	56	46
5 - 30	60	50

Note 1: The level decreases linearly with the logarithm of the frequency.

* Decreasing linearly with the logarithm of the frequency

6.3 Test procedure

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane.

This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0,8 m from the LISN 2.


- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

6.4 Test Result

MX60W-4500850U-1200700U

Modulation: 802.11a (the worst data)

L:




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.2151	45.20	10.18	55.38	63.01	-7.63	QP
2		0.2151	18.91	10.18	29.09	53.01	-23.92	AVG
3		0.4778	36.47	10.20	46.67	56.38	-9.71	QP
4		0.4778	14.86	10.20	25.06	46.38	-21.32	AVG
5		1.3260	33.41	10.37	43.78	56.00	-12.22	QP
6		1.3260	6.69	10.37	17.06	46.00	-28.94	AVG
7		2.8260	32.06	10.83	42.89	56.00	-13.11	QP
8		2.8260	5.81	10.83	16.64	46.00	-29.36	AVG
9		5.1977	24.07	11.72	35.79	60.00	-24.21	QP
10		5.1977	8.01	11.72	19.73	50.00	-30.27	AVG
11		18.8338	34.29	18.10	52.39	60.00	-7.61	QP
12	*	18.8338	26.17	18.10	44.27	50.00	-5.73	AVG

Remark:

Factor = Cable loss + LISN factor, Margin = Measurement – Limit

N:



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
		MHz	Level	Factor	ment			Detector
			dBuV	dB	dBuV	dBuV	dB	
1		0.3260	41.28	10.19	51.47	59.55	-8.08	QP
2		0.3260	26.19	10.19	36.38	49.55	-13.17	AVG
3		0.5700	36.93	10.21	47.14	56.00	-8.86	QP
4		0.5700	21.42	10.21	31.63	46.00	-14.37	AVG
5		1.4536	33.27	10.40	43.67	56.00	-12.33	QP
6		1.4536	13.59	10.40	23.99	46.00	-22.01	AVG
7		2.0859	34.03	10.56	44.59	56.00	-11.41	QP
8		2.0859	14.29	10.56	24.85	46.00	-21.15	AVG
9		3.0859	32.19	10.93	43.12	56.00	-12.88	QP
10		3.0859	14.90	10.93	25.83	46.00	-20.17	AVG
11		21.2056	34.09	19.28	53.37	60.00	-6.63	QP
12	*	21.2056	25.66	19.28	44.94	50.00	-5.06	AVG


Remark:

1. Factor = Cable loss + LISN factor, Margin = Limit – Level
2. All modes were tested at AC 120V and 240V, only the worst result of AC 120V 60Hz was reported.
3. All the test modes completed for test. Only the worst result of was reported.

HYP317-450085US

Modulation: 802.11a (the worst data)

L:




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1945	43.11	10.18	53.29	63.84	-10.55	QP
2		0.1945	32.95	10.18	43.13	53.84	-10.71	AVG
3		0.4138	36.81	10.19	47.00	57.57	-10.57	QP
4	*	0.4138	28.26	10.19	38.45	47.57	-9.12	AVG
5		1.0300	31.49	10.31	41.80	56.00	-14.20	QP
6		1.0300	21.27	10.31	31.58	46.00	-14.42	AVG
7		2.7378	33.72	10.80	44.52	56.00	-11.48	QP
8		2.7378	22.56	10.80	33.36	46.00	-12.64	AVG
9		5.3418	29.37	11.79	41.16	60.00	-18.84	QP
10		5.3418	19.99	11.79	31.78	50.00	-18.22	AVG
11		24.0060	25.25	20.80	46.05	60.00	-13.95	QP
12		24.0060	15.62	20.80	36.42	50.00	-13.58	AVG

Remark:

Factor = Cable loss + LISN factor, Margin = Measurement – Limit

N:



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1945	41.62	10.18	51.80	63.84	-12.04	QP
2		0.1945	27.60	10.18	37.78	53.84	-16.06	AVG
3		0.4060	35.18	10.19	45.37	57.73	-12.36	QP
4		0.4060	25.79	10.19	35.98	47.73	-11.75	AVG
5		0.9060	31.75	10.28	42.03	56.00	-13.97	QP
6		0.9060	19.53	10.28	29.81	46.00	-16.19	AVG
7		1.9416	27.43	10.52	37.95	56.00	-18.05	QP
8		1.9416	16.27	10.52	26.79	46.00	-19.21	AVG
9	*	3.9580	33.56	11.25	44.81	56.00	-11.19	QP
10		3.9580	21.31	11.25	32.56	46.00	-13.44	AVG
11		24.2179	25.77	20.91	46.68	60.00	-13.32	QP
12		24.2179	17.38	20.91	38.29	50.00	-11.71	AVG

Remark:

- Factor = Cable loss + LISN factor, Margin = Limit – Level
- All modes were tested at AC 120V and 240V, only the worst result of AC 120V 60Hz was reported.
- All the test modes completed for test. Only the worst result of was reported.

7. RADIATED SPURIOUS EMISSIONS

7.1 Block Diagram Of Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1GHz

7.2 Limit

Spurious Emissions:

Frequency	Field strength (dB μ V/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	$20\log 2400/F \text{ (kHz)} + 80$	Quasi-peak	3
0.490MHz-1.705MHz	$20\log 24000/F \text{ (kHz)} + 40$	Quasi-peak	3
1.705MHz-30MHz	$20\log 30 + 40$	Quasi-peak	3
30MHz-88MHz	40.0	Quasi-peak	3
88MHz-216MHz	43.5	Quasi-peak	3
216MHz-960MHz	46.0	Quasi-peak	3
960MHz-1GHz	54.0	Quasi-peak	3
Above 1GHz	54.0	Average	3

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

If radiated measurements are performed, field strength is then converted to EIRP as follows:

$$(i) \text{ EIRP} = ((E \cdot d)^2) / 30$$

where:

- E is the field strength in V/m;
- d is the measurement distance in meters;
- EIRP is the equivalent isotropically radiated power in watts.

(ii) Working in dB units, the above equation is equivalent to:

$$\text{EIRP[dBm]} = E[\text{dB}\mu\text{V/m}] + 20 \log(d[\text{meters}]) - 104.77$$

(iii) Or, if d is 3 meters:

$$\text{EIRP[dBm]} = E[\text{dB}\mu\text{V/m}] - 95.2$$

7.3 Test procedure

Below 1GHz test procedure as below:

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rota table table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter(Above 18GHz the distance is 1 meter and table is 1.5 meter).

h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

j. Repeat above procedures until all frequencies measured was complete.

Receiver set:

Frequency	Detector	RBW	VBW	Remark
0.009MHz-0.090MHz	Peak	10kHz	30KHz	Peak
0.009MHz-0.090MHz	Average	10kHz	30KHz	Average
0.090MHz-0.110MHz	Quasi-peak	10kHz	30KHz	Quasi-peak
0.110MHz-0.490MHz	Peak	10kHz	30KHz	Peak
0.110MHz-0.490MHz	Average	10kHz	30KHz	Average
0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
30MHz-1GHz	Quasi-peak	120 kHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.

7.4 Test Result


MX60W-4500850U-1200700U

30MHz-1GHzTest Results:

Modulation: 802.11a (the worst data)

Test Channel: 5180MHz

Antenna polarity: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	75.9771	49.41	-16.20	33.21	40.00	-6.79	QP
2	192.4183	52.08	-15.55	36.53	43.50	-6.97	QP
3	298.2681	44.88	-12.22	32.66	46.00	-13.34	QP
4 *	522.7180	47.77	-7.41	40.36	46.00	-5.64	QP
5 !	750.1082	42.99	-2.92	40.07	46.00	-5.93	QP
6	900.1472	35.49	-0.79	34.70	46.00	-11.30	QP

Antenna polarity: V



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	49.3594	44.69	-13.17	31.52	40.00	-8.48	QP
2 !	60.0690	47.76	-13.73	34.03	40.00	-5.97	QP
3 *	75.4462	51.11	-16.12	34.99	40.00	-5.01	QP
4 !	171.3925	50.70	-13.07	37.63	43.50	-5.87	QP
5	522.7180	46.87	-7.41	39.46	46.00	-6.54	QP
6	750.1082	42.14	-2.92	39.22	46.00	-6.78	QP

Remark: Factor = Cable lose + Antenna factor - Pre-amplifier; Margin = Measurement – Limit

- The margin of 9k-30MH measurement exceeds 20dB, so the test chart is not included. Test Mode: 802.11a20 (the worst)


HYP317-450085US

30MHz-1GHzTest Results:

Modulation: 802.11a (the worst data)


Test Channel: 5180MHz

Antenna polarity: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	76.2442	51.22	-16.24	34.98	40.00	-5.02	QP
2	191.7450	49.48	-15.53	33.95	43.50	-9.55	QP
3	243.3771	50.57	-14.23	36.34	46.00	-9.66	QP
4	522.7180	43.67	-7.41	36.26	46.00	-9.74	QP
5 !	750.1082	43.00	-2.92	40.08	46.00	-5.92	QP
6	929.0081	40.22	-0.38	39.84	46.00	-6.16	QP

Antenna polarity: V



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	30.4237	47.24	-13.63	33.61	40.00	-6.39	QP
2	60.2800	47.63	-13.77	33.86	40.00	-6.14	QP
3 !	76.7806	51.24	-16.32	34.92	40.00	-5.08	QP
4 *	175.0365	52.61	-13.65	38.96	43.50	-4.54	QP
5	522.7180	46.16	-7.41	38.75	46.00	-7.25	QP
6	929.0081	40.26	-0.38	39.88	46.00	-6.12	QP

Remark: Factor = Cable lose + Antenna factor - Pre-amplifier; Margin = Measurement – Limit

- The margin of 9k-30MH measurement exceeds 20dB, so the test chart is not included. Test Mode: 802.11a20 (the worst)

MX60W-4500850U-1200700U

Radiated Spurious Emission (Above 1GHz):

Modulation: 802.11(a) (the worst data)

Freq (MHz)	Rd_level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	detector	Height	Degree	Antenna polarization
Channel:5180MHz									
10360	39.43	16.39	55.82	74	-18.18	PK	1.36	86	H
10360	26.54	16.39	42.93	54	-11.07	AV	1.47	288	H
10360	39.21	16.39	55.60	74	-18.40	PK	1.34	335	V
10360	26.75	16.39	43.14	54	-10.86	AV	1.39	327	V
Channel:5240MHz									
10480	39.86	16.11	55.97	74	-18.03	PK	1.27	77	H
10480	26.14	16.11	42.25	54	-11.75	AV	1.39	336	H
10480	40.25	16.11	56.36	74	-17.64	PK	1.70	73	V
10480	26.84	16.11	42.95	54	-11.05	AV	1.38	139	V
Channel:5745MHz									
11490	40.31	17.46	57.77	74	-16.23	PK	1.04	147	H
11490	25.67	17.46	43.13	54	-10.87	AV	1.62	219	H
11490	41.57	17.46	59.03	74	-14.97	PK	1.56	15	V
11490	27.04	17.46	44.50	54	-9.50	AV	1.73	298	V
Channel:5825MHz									
11650	40.31	17.46	57.77	74	-16.23	PK	1.04	147	H
11650	25.67	17.46	43.13	54	-10.87	AV	1.62	219	H
11650	41.57	17.46	59.03	74	-14.97	PK	1.56	15	V
11650	27.04	17.46	44.50	54	-9.50	AV	1.73	298	V

Modulation: 802.11(n40) (the worst data)

Freq (MHz)	Rd_level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	detector	Height	Degree	Antenna polarization
Channel:5190MHz									
10380	39.02	16.34	55.36	74	-18.64	PK	1.74	210	H
10380	27.15	16.34	43.49	54	-10.51	AV	1.49	202	H
10380	41.26	16.34	57.60	74	-16.40	PK	1.31	231	V
10380	25.63	16.34	41.97	54	-12.03	AV	1.74	267	V
Channel:5230MHz									
10460	40.51	16.15	56.66	74	-17.34	PK	1.61	174	H
10460	26.33	16.15	42.48	54	-11.52	AV	1.25	314	H
10460	41.24	16.15	57.39	74	-16.61	PK	1.63	123	V
10460	27.55	16.15	43.70	54	-10.30	AV	1.86	200	V
Channel:5755MHz									
11510	41.71	17.49	59.20	74	-14.80	PK	1.81	53	H
11510	27.60	17.49	45.09	54	-8.91	AV	1.84	83	H
11510	41.67	17.49	59.16	74	-14.84	PK	1.12	274	V
11510	26.04	17.49	43.53	54	-10.47	AV	1.67	321	V
Channel:5795MHz									
11590	41.25	17.52	58.77	74	-16.61	PK	1.65	51	H
11590	27.49	17.52	45.01	54	-15.23	AV	1.47	20	H
11590	40.42	17.52	57.94	74	-16.06	PK	1.83	163	V
11590	27.72	17.52	45.24	54	-8.76	AV	1.35	344	V

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier. Emission level = Reading Result + Factor, Margin = Emission level - Limits

2. The EUT was tested in the low, high channel and the worst case position data was reported.

3. Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

HYP317-450085US

Radiated Spurious Emission (Above 1GHz):

Modulation: 802.11(a) (the worst data)

Freq (MHz)	Rd_level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	detector	Height	Degree	Antenna polarization
Channel:5180MHz									
10360	39.71	16.39	56.10	74	-17.90	PK	1.27	7	H
10360	26.44	16.39	42.83	54	-11.17	AV	1.14	183	H
10360	41.89	16.39	58.28	74	-15.72	PK	1.22	258	V
10360	26.31	16.39	42.70	54	-11.30	AV	1.21	275	V
Channel:5240MHz									
10480	39.71	16.11	55.82	74	-18.18	PK	1.24	101	H
10480	25.24	16.11	41.35	54	-12.65	AV	1.53	138	H
10480	41.69	16.11	57.80	74	-16.20	PK	1.63	224	V
10480	26.31	16.11	42.42	54	-11.58	AV	1.63	92	V
Channel:5745MHz									
11490	40.84	17.46	58.30	74	-15.70	PK	1.80	234	H
11490	27.07	17.46	44.53	54	-9.47	AV	1.64	34	H
11490	39.78	17.46	57.24	74	-16.76	PK	1.19	80	V
11490	25.90	17.46	43.36	54	-10.64	AV	1.18	255	V
Channel:5825MHz									
11650	40.41	17.57	57.98	74	-16.02	PK	1.36	105	H
11650	25.97	17.57	43.54	54	-10.46	AV	1.18	271	H
11650	40.40	17.57	57.97	74	-16.03	PK	1.77	137	V
11650	26.57	17.57	44.14	54	-9.86	AV	1.20	347	V

Modulation: 802.11(n40) (the worst data)

Freq (MHz)	Rd_level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	detector	Height	Degree	Antenna polarization
Channel:5190MHz									
10380	41.38	16.34	57.72	74	-16.28	PK	1.63	261	H
10380	25.84	16.34	42.18	54	-11.82	AV	1.61	316	H
10380	41.19	16.34	57.53	74	-16.47	PK	1.59	213	V
10380	26.22	16.34	42.56	54	-11.44	AV	1.22	207	V
Channel:5230MHz									
10460	41.52	16.15	57.67	74	-16.33	PK	1.82	191	H
10460	25.19	16.15	41.34	54	-12.66	AV	1.63	109	H
10460	40.56	16.15	56.71	74	-17.29	PK	1.48	108	V
10460	25.72	16.15	41.87	54	-12.13	AV	1.25	139	V
Channel:5755MHz									
11510	41.54	17.49	59.03	74	-14.97	PK	1.80	184	H
11510	27.98	17.49	45.47	54	-8.53	AV	1.04	217	H
11510	40.39	17.49	57.88	74	-16.12	PK	1.70	180	V
11510	27.89	17.49	45.38	54	-8.62	AV	1.60	198	V
Channel:5795MHz									
11590	40.39	17.52	57.91	74	-17.09	PK	1.03	38	H
11590	27.63	17.52	45.15	54	-16.09	AV	1.46	66	H
11590	41.47	17.52	58.99	74	-15.01	PK	1.17	30	V
11590	25.05	17.52	42.57	54	-11.43	AV	1.38	114	V

Remark:


1. Factor = Antenna Factor + Cable Loss – Pre-amplifier. Emission level = Reading Result + Factor, Margin = Emission level - Limits

2. The EUT was tested in the low, high channel and the worst case position data was reported.

3. Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

8. BAND EDGE

8.1 Block Diagram Of Test Setup



8.2 Limit

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of -17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (5) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
- (6) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.


8.3 Test procedure


1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

8.4 Test Result


Test Graph

5180-5240MHz







802.11n(HT40)-5190





802.11n(HT40)-5230




802.11ax(HE20)-5180




802.11ax(HE20)-5240



802.11ax(HE40)-5190



802.11ax(HE40)-5230



5745-5825MHz


802.11a-5745




802.11a-5825




802.11ac(VHT20)-5745




802.11ac(VHT20)-5825



802.11ac(VHT40)-5755



802.11ac(VHT40)-5795




802.11(n20)-5745




802.11(n20)-5825






802.11(n40)-5755



802.11(n40)-5795



802.11ax(HE20)-5745



802.11ax(HE20)-5825



802.11ax(HE40)-5755




802.11ax(HE40)-5795



9. CONDUCTED OUTPUT POWER

9.1 Block Diagram Of Test Setup



9.2 Limit

(1) For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p.

at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(4) The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.

(5) The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less.

Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

(h) Transmit Power Control (TPC) and Dynamic Frequency Selection (DFS).

(1) Transmit power control (TPC). U-NII devices operating in the 5.25-5.35 GHz band and the 5.47-5.725 GHz band shall employ a TPC mechanism. The U-NII device is required to have the capability to operate at least 6 dB below the mean EIRP value of 30 dBm. A TPC mechanism is not required for systems with an e.i.r.p. of less than 500 mW.

9.3 Test procedure

According to KDB789033 D02v02r01 sectionE, the following is the measurement procedure.

(i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.

(ii) Set RBW = 1 MHz.

(iii) Set VBW $\geq$ 3 MHz.

(iv) Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$. (This ensures that bin-to-bin spacing is $\leq \text{RBW}/2$, so that narrowband signals are not lost between frequency bins.)

(v) Sweep time = auto.

(vi) Detector = power averaging (rms), if available. Otherwise, use sample detector mode.

(vii) If transmit duty cycle $< 98\%$, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq 98\%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run."

(viii) Trace average at least 100 traces in power averaging (rms) mode.

(ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.

9.4 Test Result

Test mode1	Test Channel (MHz)	Output Power dBm	Limit dBm
802.11a20	5180	8.867	23.98
	5200	9.95	23.98
	5240	7.968	23.98
802.11ac20	5180	10.362	23.98
	5200	11.286	23.98
	5240	9.383	23.98
802.11ac40	5190	10.387	23.98
	5230	9.016	23.98
802.11n(HT20)	5180	8.78	23.98
	5200	9.734	23.98
	5240	7.693	23.98
802.11n(HT40)	5190	8.408	23.98
	5230	7.468	23.98
802.11ax20	5180	7.981	23.98
	5200	9.133	23.98
	5240	6.963	23.98
802.11ax40	5190	8.21	23.98
	5230	7.37	23.98


Test mode1	Test Channel (MHz)	Output Power dBm	Limit dBm
802.11a20	5745	10.782	30
	5785	13.715	30
	5825	14.321	30
802.11ac20	5745	12.745	30
	5785	14.64	30
	5825	14.749	30
802.11ac40	5755	12.628	30
	5795	14.256	30
802.11n(HT20)	5745	10.711	30
	5785	13.458	30
	5825	14.327	30
802.11n(HT40)	5755	10.998	30
	5795	13.493	30
802.11ax20	5745	10.343	30
	5785	12.697	30
	5825	12.467	30
802.11ax40	5755	10.644	30
	5795	12.366	30

5180-5240MHz-Power


802.11a-5180



802.11a-5200




802.11a-5240




802.11ac(VHT20)-5180



802.11ac(VHT20)-5200




802.11ac(VHT20)-5240




802.11ac(VHT40)-5190


802.11ac(VHT40)-5230




802.11n(HT20)-5180




802.11n(HT20)-5200




802.11n(HT20)-5240




802.11n(HT40)-5190




802.11n(HT40)-5230




802.11ax(HE20)-5180




802.11ax(HE20)-5200




802.11ax(HE20)-5240



802.11ax(HE40)-5190




802.11ax(HE40)-5230




5745-5825MHz-Power


802.11a-5745



802.11a-5785




802.11a-5825




802.11ac(VHT20)-5745



802.11ac(VHT20)-5785



802.11ac(VHT20)-5825




802.11ac(VHT40)-5755



802.11ac(VHT40)-5795







802.11n(HT20)-5745




802.11n(HT20)-5785




802.11n(HT20)-5825




5802.11n(HT40)-5755




802.11n(HT40)-5795




802.11ax(HE20)-5745




802.11ax(HE20)-5785



802.11ax(HE20)-5825



802.11ax(HE40)-5755



802.11ax(HE40)-5795

