

RF TEST REPORT

For

Chengdu Hotack Technology Co., Ltd.

Product Name: PROJECTOR

Test Model(s): X5AR

Report Reference No. : DACE260225003RL003

FCC ID : 2BFIZ-X5AR

Applicant's Name : Chengdu Hotack Technology Co., Ltd.

Address : 501-502, Unit 3, Building 13, No. 666 Jinfenghuang Avenue, High-tech Industry Park, Jinniu District, Chengdu City, Si Chuan Province, China

Testing Laboratory : Shenzhen DACE Testing Technology Co., Ltd.

Address : 102, Building H1, & 1/F., Building H, Hongfa Science & Technology Park, Tangtou Community, Shiyan Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Test Specification Standard : 47 CFR Part 15.247

Date of Receipt : February 25, 2026

Date of Test : February 25, 2026 to April 20, 2026

Date of Issue : April 20, 2026

Result : **Pass**

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen DACE Testing Technology Co., Ltd. This document may be altered or revised by Shenzhen DACE Testing Technology Co., Ltd. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample



Apply for company information

Applicant's Name	:	Chengdu Hotack Technology Co., Ltd.
Address	:	501-502, Unit 3, Building 13, No. 666 Jinfenghuang Avenue, High-tech Industry Park, Jinniu District, Chengdu City, Si Chuan Province, China
Product Name	:	PROJECTOR
Test Model(s)	:	X5AR
Series Model(s)	:	X5, X5Pro, X5MAX, X5Plus, X5A, X5B, X5C, X5D, X5BR, X5CR, X5DR, TP500, XPH6, HT1, HT2, HT3, HT4, HT5, HT6, HT7, HT8, HT9, Gimbal A7, Gimbal N7, Gimbal A7 Go, Gimbal N7 Go, Gimbal A7 Cine, Gimbal N7 Cine, X5AD, X5Max, X5GTV, AC1069
Test Specification Standard(s)	:	47 CFR Part 15.247

NOTE1:

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

Compiled by:

Lucy Mo

Lucy Mo / Test Engineer

April 20, 2026

Supervised by:

Arron Liu

Arron Liu / Project Engineer

April 20, 2026

Approved by:

Tom Chen

Tom Chen / Manager

April 20, 2026

Revision History Of Report

Version	Description	REPORT No.	Issue Date
V1.0	Original	DACE260225003RL003	April 20, 2026

CONTENTS

1	TEST SUMMARY	6
1.1	TEST STANDARDS	6
1.2	SUMMARY OF TEST RESULT	6
2	GENERAL INFORMATION	7
2.1	CLIENT INFORMATION	7
2.2	DESCRIPTION OF DEVICE (EUT)	7
2.3	DESCRIPTION OF TEST MODES	7
2.4	DESCRIPTION OF SUPPORT UNITS	7
2.5	OPERATION FREQUENCY EACH OF CHANNEL	8
2.6	EQUIPMENTS USED DURING THE TEST	9
2.7	STATEMENT OF THE MEASUREMENT UNCERTAINTY	11
2.8	IDENTIFICATION OF TESTING LABORATORY	11
2.9	ANNOUNCEMENT	11
3	EVALUATION RESULTS (EVALUATION)	12
3.1	ANTENNA REQUIREMENT	12
3.1.1	Conclusion:	12
4	RADIO SPECTRUM MATTER TEST RESULTS (RF)	13
4.1	CONDUCTED EMISSION AT AC POWER LINE	13
4.1.1	E.U.T. Operation:	13
4.1.2	Test Setup Diagram:	13
4.1.3	Test Data:	14
4.2	6DB BANDWIDTH	16
4.2.1	E.U.T. Operation:	16
4.2.2	Test Setup Diagram:	16
4.2.3	Test Data:	17
4.3	MAXIMUM CONDUCTED OUTPUT POWER	18
4.3.1	E.U.T. Operation:	18
4.3.2	Test Setup Diagram:	18
4.3.3	Test Data:	18
4.4	POWER SPECTRAL DENSITY	19
4.4.1	E.U.T. Operation:	19
4.4.2	Test Setup Diagram:	19
4.4.3	Test Data:	19
4.5	EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS	20
4.5.1	E.U.T. Operation:	20
4.5.2	Test Setup Diagram:	20
4.5.3	Test Data:	20
4.6	BAND EDGE EMISSIONS (RADIATED)	21
4.6.1	E.U.T. Operation:	21
4.6.2	Test Data:	22
4.7	EMISSIONS IN FREQUENCY BANDS (BELOW 1GHz)	26
4.7.1	E.U.T. Operation:	27
4.7.2	Test Data:	28
4.8	EMISSIONS IN FREQUENCY BANDS (ABOVE 1GHz)	30
4.8.1	E.U.T. Operation:	31
4.8.2	Test Data:	32

5	TEST SETUP PHOTOS	38
6	PHOTOS OF THE EUT	40
	APPENDIX	41
	1. -6dB Bandwidth	42
	2. 99% Occupied Bandwidth	49
	3. Duty Cycle	56
	4. MAX. Output Power	63
	5. Power Spectral Density	64
	6. Bandedge	71
	7. Spurious Emission	80

1 TEST SUMMARY

1.1 Test Standards

The tests were performed according to following standards:

47 CFR Part 15.247: Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

1.2 Summary of Test Result

Item	Standard	Method	Requirement	Result
Antenna requirement	47 CFR Part 15.247	---	47 CFR 15.203	Pass
Conducted Emission at AC power line	47 CFR Part 15.247	ANSI C63.10-2020 section 6.2	47 CFR 15.207(a)	Pass
6dB Bandwidth	47 CFR Part 15.247	ANSI C63.10-2020, section 11.8 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(a)(2)	Pass
Maximum Conducted Output Power	47 CFR Part 15.247	ANSI C63.10-2020, section 11.9.2 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(b)(3)	Pass
Power Spectral Density	47 CFR Part 15.247	ANSI C63.10-2020, section 11.10 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(e)	Pass
Emissions in non-restricted frequency bands	47 CFR Part 15.247	ANSI C63.10-2020 section 11.11 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d)	Pass
Band edge emissions (Radiated)	47 CFR Part 15.247	ANSI C63.10-2020 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (below 1GHz)	47 CFR Part 15.247	ANSI C63.10-2020 section 6.5.4 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (above 1GHz)	47 CFR Part 15.247	ANSI C63.10-2020 section 6.5.4 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d), 15.209, 15.205	Pass

2 GENERAL INFORMATION

2.1 Client Information

Applicant's Name : Chengdu Hotack Technology Co., Ltd.
Address : 501-502, Unit 3, Building 13, No. 666 Jinfenghuang Avenue, High-tech Industry Park, Jinniu District, Chengdu City, Si Chuan Province, China

Manufacturer : Chengdu Hotack Technology Co., Ltd.
Address : 501-502, Unit 3, Building 13, No. 666 Jinfenghuang Avenue, High-tech Industry Park, Jinniu District, Chengdu City, Si Chuan Province, China

2.2 Description of Device (EUT)

Product Name:	PROJECTOR
Model/Type reference:	X5AR
Series Model:	X5, X5Pro, X5MAX, X5Plus, X5A, X5B, X5C, X5D, X5BR, X5CR, X5DR, TP500, XPH6, HT1, HT2, HT3, HT4, HT5, HT6, HT7, HT8, HT9, Gimbal A7, Gimbal N7, Gimbal A7 Go, Gimbal N7 Go, Gimbal A7 Cine, Gimbal N7 Cine, X5AD, X5Max, X5GTV, AC1069
Model Difference:	All the model are the same circuit and RF module, only the model name and appearance color are different. Test sample model: X5AR
Trade Mark:	N/A
Power Supply:	100-240V~, 50/60Hz, 2.5A
Operation Frequency:	2412-2462MHz
Number of Channels:	802.11b/g/n(HT20): 11 Channels; 802.11n(HT40): 7 Channels
Modulation Type:	802.11b: DSSS(CCK, DQPSK, DBPSK); 802.11g: OFDM(BPSK, QPSK, 16QAM, 64QAM); 802.11n(HT20 and HT40): OFDM (BPSK, QPSK, 16QAM, 64QAM)
Antenna Type:	FPC Antenna
Antenna Gain:	3.19dBi
Hardware Version:	LCD H726 68156A
Software Version:	Android 14

2.3 Description of Test Modes

No	Title	Description
TM1	2.4GWIFI TX Mode	Keep the EUT in 802.11b/g/n20/n40 transmitting mode at lowest, middle and highest channel.
Test Environment		Normal Voltage(AC): 120V

2.4 Description of Support Units

The EUT was tested as an independent device.

2.5 Operation Frequency each of channel

CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)
1	2412	2	2417	3	2422	4	2427
5	2432	6	2437	7	2442	8	2447
9	2462	10	2457	11	2462	/	/

Note: In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	802.11b/g/n(HT20)	802.11n(HT40)
	Frequency (MHz)	Frequency (MHz)
Lowest channel	2412MHz	2422MHz
Middle channel	2437MHz	2437MHz
Highest channel	2462MHz	2452MHz

2.6 Equipments Used During The Test

Conducted Emission at AC power line					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Power absorbing clamp	SCHWARZ BECK	MESS-ELEKTRONIK	/	2026-04-14	2027-04-13
Electric Network	SCHWARZ BECK	CAT5 8158	CAT5 8158#207	2026-04-14	2027-04-13
Cable	SCHWARZ BECK	/	/	2026-04-14	2027-04-13
Pulse Limiter	SCHWARZ BECK	VTSD 9561-F Pulse limiter 10dB Attenuation	561-G071	2025-12-02	2026-12-01
Test Receiver	Rohde & Schwarz	ESPI TEST RECEIVER	1164.6607K03 -102109-MH	2026-04-14	2027-04-13
L.I.S.N	R&S	ESH3-Z5	831.5518.52	2026-04-14	2027-04-13
L.I.S.N	SCHWARZ BECK	NSLK 8126	05055	2026-04-14	2027-04-13
Pulse Limiter	CYBERTEK	EM5010A	/	2026-04-14	2027-04-13
EMI test software	EZ -EMC	EZ	V1.1.42	/	/

Emissions in non-restricted frequency bands 6dB Bandwidth Maximum Conducted Output Power Power Spectral Density					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
RF Test Software	Tachoy Information Technology(she nzen) Co.,Ltd.	RTS-01	V1.0.0	/	/
RF Sensor Unit	Tachoy Information Technology(she nzen) Co.,Ltd.	TR1029-2	000001	/	/
Wideband radio communication tester	R&S	CMW500	113410	2026-04-14	2027-04-13
Vector Signal Generator	Keysight	N5181A	MY50143455	2025-12-02	2026-12-01
Signal Generator	Keysight	N5182A	MY48180415	2025-12-02	2026-12-01
Spectrum Analyzer	Keysight	N9020A	MY53420323	2025-12-02	2026-12-01

Band edge emissions (Radiated)
Emissions in frequency bands (below 1GHz)
Emissions in frequency bands (above 1GHz)

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test software	Farad	EZ -EMC	V1.1.42	/	/
Positioning Controller	MF	MF-7802	/	/	/
Amplifier(18-40G)	COM-POWER	AH-1840	10100008-1	2024-04-26	2027-04-25
Horn antenna	COM-POWER	AH-1840 (18-40G)	10100008	2024-04-26	2027-04-25
Loop antenna	ZHINAN	ZN30900C	ZN30900C	2026-04-14	2027-04-13
Cable(LF)#2	Schwarzbeck	/	/	2026-04-13	2027-04-12
Cable(LF)#1	Schwarzbeck	/	/	2026-04-14	2027-04-13
Cable(HF)#2	Schwarzbeck	AK9515E	96250	2026-04-14	2027-04-13
Cable(HF)#1	Schwarzbeck	SYV-50-3-1	/	2026-04-14	2027-04-13
Power amplifier(LF)	Schwarzbeck	BBV9743	9743-151	2026-04-14	2027-04-13
Power amplifier(HF)	Schwarzbeck	BBV9718	9718-282	2026-04-14	2027-04-13
Wideband radio communication tester	R&S	CMW500	113410	2026-04-14	2027-04-13
Spectrum Analyzer	R&S	FSP30	1321.3008K40-101729-jR	2026-04-14	2027-04-13
Test Receiver	R&S	ESCI 3	1166.5950K03-101431-Jq	2026-04-14	2027-04-13
Horn Antenna	Sunol Sciences	DRH-118	A091114	2026-04-14	2027-04-13
Broadband Antenna	Sunol Sciences	JB6 Antenna	A090414	2024-09-28	2026-09-27

2.7 Statement Of The Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Disturbance (0.15~30MHz)	$\pm 3.41\text{dB}$
Occupied Bandwidth	$\pm 3.63\%$
RF conducted power	$\pm 0.733\text{dB}$
RF power density	$\pm 0.234\%$
Conducted Spurious emissions	$\pm 1.98\text{dB}$
Radiated Emission (Above 1GHz)	$\pm 5.46\text{dB}$
Radiated Emission (Below 1GHz)	$\pm 5.79\text{dB}$
Note: (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.	

2.8 Identification of Testing Laboratory

Company Name:	Shenzhen DACE Testing Technology Co., Ltd.
Address:	102, Building H1, & 1/F., Building H, Hongfa Science & Technology Park, Tangtou Community, Shiyao Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Phone Number:	+86-13267178997
Fax Number:	86-755-29113252

Identification of the Responsible Testing Location

Company Name:	Shenzhen DACE Testing Technology Co., Ltd.
Address:	102, Building H1, & 1/F., Building H, Hongfa Science & Technology Park, Tangtou Community, Shiyao Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Phone Number:	+86-13267178997
Fax Number:	86-755-29113252
FCC Registration Number:	0032847402
Designation Number:	CN1342
Test Firm Registration Number:	778666
A2LA Certificate Number:	6270.01

2.9 Announcement


- (1) The test report reference to the report template version v0.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing, reviewing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) This document may not be altered or revised in any way unless done so by DACE and all revisions are duly noted in the revisions section.
- (5) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
- (6) We hereby declare that the laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant. the laboratory is not responsible for the accuracy of the information provided by the client(item 2.2). When the information provided by the customer may affect the effectiveness of the results, the responsibility lies with the customer, and the laboratory does not assume any responsibility.

3 Evaluation Results (Evaluation)

3.1 Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
Test Method:	---

3.1.1 Conclusion:



4.1 Conducted Emission at AC power line


4.1.1 E.U.T. Operation:

4.1.2 Test Setup Diagram:




4.1.3 Test Data:

TM1 / Line: Line / Band: 2400-2483.5 MHz / BW: 20 / CH: L



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1500	43.59	10.11	53.70	66.00	-12.30	QP	
2		0.1500	9.85	10.11	19.96	56.00	-36.04	AVG	
3		0.3020	38.44	10.09	48.53	60.19	-11.66	QP	
4		0.3020	34.13	10.09	44.22	50.19	-5.97	AVG	
5		0.9060	33.52	10.10	43.62	56.00	-12.38	QP	
6	*	0.9060	30.31	10.10	40.41	46.00	-5.59	AVG	
7		1.5100	34.58	10.06	44.64	56.00	-11.36	QP	
8		1.5100	30.13	10.06	40.19	46.00	-5.81	AVG	
9		2.7220	32.60	10.05	42.65	56.00	-13.35	QP	
10		2.7220	27.01	10.05	37.06	46.00	-8.94	AVG	
11		4.5300	32.89	10.17	43.06	56.00	-12.94	QP	
12		4.5300	26.20	10.17	36.37	46.00	-9.63	AVG	

TM1 / Line: Neutral / Band: 2400-2483.5 MHz / BW: 20 / CH: L



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1500	43.39	10.08	53.47	66.00	-12.53	QP	
2		0.1500	9.25	10.08	19.33	56.00	-36.67	AVG	
3		0.3020	38.34	10.08	48.42	60.19	-11.77	QP	
4	*	0.3020	33.90	10.08	43.98	50.19	-6.21	AVG	
5		0.9060	33.33	10.08	43.41	56.00	-12.59	QP	
6		0.9060	29.32	10.08	39.40	46.00	-6.60	AVG	
7		1.5100	32.64	10.05	42.69	56.00	-13.31	QP	
8		1.5100	28.90	10.05	38.95	46.00	-7.05	AVG	
9		3.3220	32.90	10.11	43.01	56.00	-12.99	QP	
10		3.3220	29.33	10.11	39.44	46.00	-6.56	AVG	
11		4.5260	31.43	10.18	41.61	56.00	-14.39	QP	
12		4.5260	25.98	10.18	36.16	46.00	-9.84	AVG	

NOTE:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor, Over = Limit - Measurement

4.2 6dB Bandwidth


Test Requirement:	47 CFR 15.247(a)(2)
Test Limit:	Refer to 47 CFR 15.247(a)(2), Systems using digital modulation techniques may operate in the 902-928 MHz, and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
Test Method:	ANSI C63.10-2020, section 11.8 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	11.8.1 Option 1 The steps for the first option are as follows: a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz. b) Set the VBW $\geq [3 \times \text{RBW}]$. c) Detector = peak. d) Trace mode = max-hold. e) Sweep = No faster than coupled (auto) time. f) Allow the trace to stabilize. g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value. 11.8.2 Option 2 The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., RBW = 100 kHz, VBW $\geq 3 \times \text{RBW}$, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

4.2.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.4 °C	Humidity:	50 %	Atmospheric Pressure:	101.4 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.2.2 Test Setup Diagram:

--



4.2.3 Test Data:

Please Refer to Appendix for Details.


4.3 Maximum Conducted Output Power

Test Requirement:	47 CFR 15.247(b)(3)
Test Limit:	Refer to 47 CFR 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
Test Method:	ANSI C63.10-2020, section 11.9.2 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020, section 11.9.2 Maximum conducted (average) output power

4.3.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.8 °C	Humidity:	50 %	Atmospheric Pressure:	101.4 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.3.2 Test Setup Diagram:



4.3.3 Test Data:

Please Refer to Appendix for Details.


4.4 Power Spectral Density

Test Requirement:	47 CFR 15.247(e)
Test Limit:	Refer to 47 CFR 15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.
Test Method:	ANSI C63.10-2020, section 11.10 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020+Cor 1-2023, section 11.10, Maximum power spectral density level in the fundamental emission

4.4.1 E.U.T. Operation:

Operating Environment:					
Temperature:	23.8 °C	Humidity:	47 %	Atmospheric Pressure:	101.4 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.4.2 Test Setup Diagram:



4.4.3 Test Data:

Please Refer to Appendix for Details.


4.5 Emissions in non-restricted frequency bands

Test Requirement:	47 CFR 15.247(d)
Test Limit:	Refer to 47 CFR 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Test Method:	ANSI C63.10-2020 section 11.11 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020 Section 11.11.1, Section 11.11.2, Section 11.11.3

4.5.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.1 °C	Humidity:	53 %	Atmospheric Pressure:	101.4 kPa
Pretest mode:	TM1				
Final test mode:	TM1				

4.5.2 Test Setup Diagram:



4.5.3 Test Data:

Please Refer to Appendix for Details.

4.6 Band edge emissions (Radiated)


Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2020 section 6.10.5.2		

4.6.1 E.U.T. Operation:

Operating Environment:			
Temperature:	22.5 °C	Humidity:	48 %
Atmospheric Pressure:	101.4 kPa		
Pretest mode:	TM1		
Final test mode:	TM1		


4.6.2 Test Data:

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector		P/F	Remark
1	2310.000	41.61	-6.63	34.98	74.00	-39.02	peak		P	
2 *	2310.000	31.51	-6.63	24.88	54.00	-29.12	AVG		P	
3	2390.000	41.09	-6.42	34.67	74.00	-39.33	peak		P	
4	2390.000	29.61	-6.42	23.19	54.00	-30.81	AVG		P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	2310.000	39.37	-6.63	32.74	74.00	-41.26	peak			P	
2	2310.000	29.81	-6.63	23.18	54.00	-30.82	AVG			P	
3	2390.000	41.21	-6.42	34.79	74.00	-39.21	peak			P	
4 *	2390.000	31.12	-6.42	24.70	54.00	-29.30	AVG			P	

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	2483.500	41.20	-6.17	35.03	74.00	-38.97	peak			P	
2 *	2483.500	30.32	-6.17	24.15	54.00	-29.85	AVG			P	
3	2510.000	40.89	-6.11	34.78	74.00	-39.22	peak			P	
4	2510.000	29.82	-6.11	23.71	54.00	-30.29	AVG			P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	2483.500	41.01	-6.17	34.84	74.00	-39.16	peak			P	
2 *	2483.500	30.33	-6.17	24.16	54.00	-29.84	AVG			P	
3	2510.000	41.07	-6.11	34.96	74.00	-39.04	peak			P	
4	2510.000	29.88	-6.11	23.77	54.00	-30.23	AVG			P	

Remark: Margin = Level - Limit, Level = Test receiver reading + correction factor

The test software will only record the worst test angle and height, and only the worst case will be recorded in the test report.

4.7 Emissions in frequency bands (below 1GHz)

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
	** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.		
Test Method:	ANSI C63.10-2020 section 6.5.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. h. Test the EUT in the lowest channel, the middle channel, the Highest channel. i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. j. Repeat above procedures until all frequencies measured was complete. Remark: 1) For emission below 1GHz, through pre-scan found the worst case is the lowest		


	channel. Only the worst case is recorded in the report. 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows: Final Test Level =Receiver Reading + Antenna Factor + Cable Factor +C Preamplifier Factor 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. Fundamental frequency is blocked by filter, and only spurious emission is shown.
--	---

4.7.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.9 °C	Humidity:	48 %	Atmospheric Pressure:	101.4 kPa
Pretest mode:	TM1				
Final test mode:	TM1				


4.7.2 Test Data:

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	64.6594	38.46	-13.75	24.71	40.00	-15.29	QP	100		P	
2	148.9625	39.55	-7.73	31.82	43.50	-11.68	QP	100		P	
3	318.8170	45.93	-7.93	38.00	46.00	-8.00	QP	100		P	
4	595.1329	37.63	-1.58	36.05	46.00	-9.95	QP	100		P	
5 *	744.8661	41.43	1.17	42.60	46.00	-3.40	QP	100		P	
6	893.8567	35.16	3.60	38.76	46.00	-7.24	QP	100		P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 !	51.1209	49.08	-13.88	35.20	40.00	-4.80	QP	100		P	
2 !	65.1145	47.83	-13.55	34.28	40.00	-5.72	QP	100		P	
3	119.8556	42.71	-6.79	35.92	43.50	-7.58	QP	100		P	
4	150.0108	42.27	-8.14	34.13	43.50	-9.37	QP	100		P	
5	446.4141	40.98	-4.63	36.35	46.00	-9.65	QP	100		P	
6 *	744.8661	40.78	1.08	41.86	46.00	-4.14	QP	100		P	

Remark: Margin=Level - Limit, Level=Test receiver reading + correction factor

All modes have been tested, and the test results show that b-mode data is the worst, only b-mode test chart is put. Test Mode: 802.11b low channel (the worst)

4.8 Emissions in frequency bands (above 1GHz)

Test Requirement:	Refer to 47 CFR 15.247(d), in addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.			
Test Method:	ANSI C63.10-2020 section 6.5.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. h. Test the EUT in the lowest channel, the middle channel, the Highest channel. i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. j. Repeat above procedures until all frequencies measured was complete. Remark:		


	1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report. 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows: Final Test Level = Receiver Reading + Antenna Factor + Cable Factor + Preamplifier Factor 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. Fundamental frequency is blocked by filter, and only spurious emission is shown.
--	--

4.8.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.7 °C	Humidity:	52 %	Atmospheric Pressure:	101.4 kPa
Pretest mode:	TM1				
Final test mode:	TM1				


4.8.2 Test Data:

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: L




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector		P/F	Remark
1	4818.750	56.03	-0.65	55.38	74.00	-18.62	peak		P	
2 *	4818.750	42.87	-0.65	42.22	54.00	-11.78	AVG		P	
3	8414.250	37.58	7.31	44.89	74.00	-29.11	peak		P	
4	8414.250	25.95	7.31	33.26	54.00	-20.74	AVG		P	
5	11528.000	40.24	9.68	49.92	74.00	-24.08	peak		P	
6	11528.000	28.68	9.68	38.36	54.00	-15.64	AVG		P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: L




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	4818.750	44.62	-0.65	43.97	74.00	-30.03	peak			P	
2	4818.750	31.60	-0.65	30.95	54.00	-23.05	AVG			P	
3	8414.250	38.83	7.31	46.14	74.00	-27.86	peak			P	
4	8414.250	26.05	7.31	33.36	54.00	-20.64	AVG			P	
5	11410.500	42.38	9.61	51.99	74.00	-22.01	peak			P	
6 *	11410.500	29.09	9.61	38.70	54.00	-15.30	AVG			P	

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: M




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	4877.500	58.28	-0.45	57.83	74.00	-16.17	peak			P	
2 *	4877.500	42.73	-0.45	42.28	54.00	-11.72	AVG			P	
3	7309.750	40.26	4.55	44.81	74.00	-29.19	peak			P	
4	7309.750	29.97	4.55	34.52	54.00	-19.48	AVG			P	
5	10458.750	41.13	8.92	50.05	74.00	-23.95	peak			P	
6	10458.750	29.05	8.92	37.97	54.00	-16.03	AVG			P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: M




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	4877.500	48.07	-0.45	47.62	74.00	-26.38	peak			P	
2	4877.500	33.31	-0.45	32.86	54.00	-21.14	AVG			P	
3	9565.750	40.71	8.09	48.80	74.00	-25.20	peak			P	
4	9565.750	27.32	8.09	35.41	54.00	-18.59	AVG			P	
5	11539.750	40.55	9.70	50.25	74.00	-23.75	peak			P	
6 *	11539.750	28.42	9.70	38.12	54.00	-15.88	AVG			P	

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	4924.500	61.25	-0.30	60.95	74.00	-13.05	peak			P	
2 *	4924.500	48.36	-0.30	48.06	54.00	-5.94	AVG			P	
3	7920.750	38.44	6.40	44.84	74.00	-29.16	peak			P	
4	7920.750	25.85	6.40	32.25	54.00	-21.75	AVG			P	
5	10729.000	41.11	9.17	50.28	74.00	-23.72	peak			P	
6	10729.000	28.31	9.17	37.48	54.00	-16.52	AVG			P	

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 20 / CH: H



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector			P/F	Remark
1	4824.500	62.83	-0.64	62.19	74.00	-11.81	peak			P	
2 *	4824.500	49.84	-0.64	49.20	54.00	-4.80	AVG			P	
3	7280.250	43.80	4.49	48.29	74.00	-25.71	peak			P	
4	7280.250	30.54	4.49	35.03	54.00	-18.97	AVG			P	
5	10429.250	40.92	8.87	49.79	74.00	-24.21	peak			P	
6	10429.250	28.92	8.87	37.79	54.00	-16.21	AVG			P	

Remark: Margin = Level - Limit, Level = Test receiver reading + correction factor


The test software will only record the worst test angle and height, and only the worst case will be recorded in the test report.

5 TEST SETUP PHOTOS


Conducted Emission at AC power line



Emissions in frequency bands (below 1GHz)



Emissions in frequency bands (above 1GHz)



6 PHOTOS OF THE EUT


Refer to Appendix - EUT Photos for EUT External Photo and Internal Photo.

Appendix



1. -6dB Bandwidth



Condition	Antenna	Modulation	Frequency (MHz)	-6dB BW(MHz)	limit(kHz)	Result
NVNT	ANT1	802.11b	2412.00	8.11	500	Pass
NVNT	ANT1	802.11b	2437.00	8.11	500	Pass
NVNT	ANT1	802.11b	2462.00	8.11	500	Pass
NVNT	ANT1	802.11g	2412.00	16.23	500	Pass
NVNT	ANT1	802.11g	2437.00	16.25	500	Pass
NVNT	ANT1	802.11g	2462.00	16.41	500	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	17.52	500	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	17.55	500	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	17.46	500	Pass
NVNT	ANT1	802.11n(HT40)	2422.00	35.40	500	Pass
NVNT	ANT1	802.11n(HT40)	2437.00	35.38	500	Pass
NVNT	ANT1	802.11n(HT40)	2452.00	35.39	500	Pass


-6dB_Bandwidth_NVNT_ANT1_802_11b_2412




-6dB_Bandwidth_NVNT_ANT1_802_11b_2437









-6dB_Bandwidth_NVNT_ANT1_802_11n(HT20)_2412





-6dB_Bandwidth_NVNT_ANT1_802_11n(HT20)_2437




-6dB_Bandwidth_NVNT_ANT1_802_11n(HT20)_2462



-6dB_Bandwidth_NVNT_ANT1_802_11n(HT40)_2422







2. 99% Occupied Bandwidth

Condition	Antenna	Modulation	Frequency (MHz)	99% BW (MHz)
NVNT	ANT1	802.11b	2412.00	12.715
NVNT	ANT1	802.11b	2437.00	12.725
NVNT	ANT1	802.11b	2462.00	12.723
NVNT	ANT1	802.11g	2412.00	16.483
NVNT	ANT1	802.11g	2437.00	16.496
NVNT	ANT1	802.11g	2462.00	16.504
NVNT	ANT1	802.11n(HT20)	2412.00	17.597
NVNT	ANT1	802.11n(HT20)	2437.00	17.704
NVNT	ANT1	802.11n(HT20)	2462.00	17.659
NVNT	ANT1	802.11n(HT40)	2422.00	36.017
NVNT	ANT1	802.11n(HT40)	2437.00	36.030
NVNT	ANT1	802.11n(HT40)	2452.00	35.926


99%_Occupied_Bandwidth_NVNT_ANT1_802_11b_2412




99%_Occupied_Bandwidth_NVNT_ANT1_802_11b_2437




99%_Occupied_Bandwidth_NVNT_ANT1_802_11b_2462




99%_Occupied_Bandwidth_NVNT_ANT1_802_11g_2412




99%_Occupied_Bandwidth_NVNT_ANT1_802_11g_2437




99%_Occupied_Bandwidth_NVNT_ANT1_802_11g_2462




99%_Occupied_Bandwidth_NVNT_ANT1_802_11n(HT20)_2412




99%_Occupied_Bandwidth_NVNT_ANT1_802_11n(HT20)_2437




99%_Occupied_Bandwidth_NVNT_ANT1_802_11n(HT20)_2462




99%_Occupied_Bandwidth_NVNT_ANT1_802_11n(HT40)_2422



99%_Occupied_Bandwidth_NVNT_ANT1_802_11n(HT40)_2437




99%_Occupied_Bandwidth_NVNT_ANT1_802_11n(HT40)_2452




3. Duty Cycle

Condition	Antenna	Modulation	Frequency (MHz)	Duty cycle(%)	Duty factor(dB)
NVNT	ANT1	802.11b	2412.00	99.08	0.00
NVNT	ANT1	802.11b	2437.00	98.63	0.00
NVNT	ANT1	802.11b	2462.00	99.08	0.00
NVNT	ANT1	802.11g	2412.00	91.67	0.38
NVNT	ANT1	802.11g	2437.00	83.33	0.79
NVNT	ANT1	802.11g	2462.00	75.00	1.25
NVNT	ANT1	802.11n(HT20)	2412.00	97.06	0.13
NVNT	ANT1	802.11n(HT20)	2437.00	98.53	0.00
NVNT	ANT1	802.11n(HT20)	2462.00	97.06	0.13
NVNT	ANT1	802.11n(HT40)	2422.00	94.29	0.26
NVNT	ANT1	802.11n(HT40)	2437.00	94.29	0.26
NVNT	ANT1	802.11n(HT40)	2452.00	88.89	0.51


Duty_Cycle_NVNT_ANT1_802_11b_2412





Duty_Cycle_NVNT_ANT1_802_11b_2437








Duty_Cycle_NVNT_ANT1_802_11b_2462





Duty_Cycle_NVNT_ANT1_802_11g_2412








Duty_Cycle_NVNT_ANT1_802_11n(HT40)_2422



Duty_Cycle_NVNT_ANT1_802_11n(HT40)_2452




4. MAX. Output Power

Condition	Antenna	Modulation	Frequency (MHz)	Detector	Total Power(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11b	2412.00	Peak	16.44	30	Pass
NVNT	ANT1	802.11b	2437.00	Peak	16.11	30	Pass
NVNT	ANT1	802.11b	2462.00	Peak	16.15	30	Pass
NVNT	ANT1	802.11g	2412.00	Peak	15.52	30	Pass
NVNT	ANT1	802.11g	2437.00	Peak	15.83	30	Pass
NVNT	ANT1	802.11g	2462.00	Peak	15.82	30	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	Peak	14.62	30	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	Peak	14.87	30	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	Peak	14.85	30	Pass
NVNT	ANT1	802.11n(HT40)	2422.00	Peak	13.41	30	Pass
NVNT	ANT1	802.11n(HT40)	2437.00	Peak	13.76	30	Pass
NVNT	ANT1	802.11n(HT40)	2452.00	Peak	13.51	30	Pass


5. Power Spectral Density

Condition	Antenna	Modulation	Frequency (MHz)	SA_PSD(dBm/30kHz)	Duty factor(dB)	RB factor(dB)	PSD(dBm/3kHz)	limit(dBm/3kHz)	Result
NVNT	ANT1	802.11b	2412.00	0.28	N/A	-10.00	-9.72	8	Pass
NVNT	ANT1	802.11b	2437.00	1.42	N/A	-10.00	-8.58	8	Pass
NVNT	ANT1	802.11b	2462.00	0.92	N/A	-10.00	-9.08	8	Pass
NVNT	ANT1	802.11g	2412.00	-8.51	N/A	-10.00	-18.51	8	Pass
NVNT	ANT1	802.11g	2437.00	-7.86	N/A	-10.00	-17.86	8	Pass
NVNT	ANT1	802.11g	2462.00	-7.38	N/A	-10.00	-17.38	8	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	-5.49	N/A	-10.00	-15.48	8	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	-7.75	N/A	-10.00	-17.75	8	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	-8.28	N/A	-10.00	-18.28	8	Pass
NVNT	ANT1	802.11n(HT40)	2422.00	-10.77	N/A	-10.00	-20.77	8	Pass
NVNT	ANT1	802.11n(HT40)	2437.00	-11.55	N/A	-10.00	-21.55	8	Pass
NVNT	ANT1	802.11n(HT40)	2452.00	-11.39	N/A	-10.00	-21.39	8	Pass

Power_Spectral_Density_NVNT_ANT1_802_11b_2412




Power_Spectral_Density_NVNT_ANT1_802_11b_2437




Power_Spectral_Density_NVNT_ANT1_802_11b_2462




Power_Spectral_Density_NVNT_ANT1_802_11g_2412




Power_Spectral_Density_NVNT_ANT1_802_11g_2437





Power_Spectral_Density_NVNT_ANT1_802_11g_2462





Power_Spectral_Density_NVNT_ANT1_802_11n(HT20)_2412




Power_Spectral_Density_NVNT_ANT1_802_11n(HT20)_2437



Power_Spectral_Density_NVNT_ANT1_802_11n(HT40)_2422




Power_Spectral_Density_NVNT_ANT1_802_11n(HT40)_2452




6. Bandedge

Condition	Antenna	Modulation	TX_Frequency (MHz)	Max. Mark_freq(MHz)	Ref_level(dBm)	Spurious level(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11b	2412.00	2398.368	4.585	-46.491	-15.415	Pass
NVNT	ANT1	802.11b	2462.00	2493.376	4.661	-52.779	-15.339	Pass
NVNT	ANT1	802.11g	2412.00	2396.912	-4.111	-55.032	-24.111	Pass
NVNT	ANT1	802.11g	2462.00	2495.968	-3.326	-60.202	-23.326	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	2398.480	-1.683	-55.158	-21.683	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	2486.320	-3.374	-60.321	-23.374	Pass
NVNT	ANT1	802.11n(HT40)	2422.00	2399.760	-6.416	-56.768	-26.416	Pass
NVNT	ANT1	802.11n(HT40)	2452.00	2484.496	-6.414	-57.360	-26.414	Pass


1_Reference_Level_NVNT_ANT1_802_11b_2412



2_Bandedge_NVNT_ANT1_802_11b_2412




1_Reference_Level_NVNT_ANT1_802_11b_2462




2_Bandedge_NVNT_ANT1_802_11b_2462




1_Reference_Level_NVNT_ANT1_802_11g_2412




2_Bandedge_NVNT_ANT1_802_11g_2412



1_Reference_Level_NVNT_ANT1_802_11g_2462




2_Bandedge_NVNT_ANT1_802_11g_2462




1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2412




2_Bandedge_NVNT_ANT1_802_11n(HT20)_2412




1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2462




2_Bandedge_NVNT_ANT1_802_11n(HT20)_2462



1_Reference_Level_NVNT_ANT1_802_11n(HT40)_2422




2_Bandedge_NVNT_ANT1_802_11n(HT40)_2422



1_Reference_Level_NVNT_ANT1_802_11n(HT40)_2452



2_Bandedge_NVNT_ANT1_802_11n(HT40)_2452




7. Spurious Emission

Condition	Antenna	Modulation	TX_Frequency (MHz)	Max. Mark_freq(MHz)	Ref_level(dBm)	Spurious level(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11b	2412.00	24970.036	4.585	-43.045	-15.415	Pass
NVNT	ANT1	802.11b	2437.00	24530.564	4.163	-44.246	-15.837	Pass
NVNT	ANT1	802.11b	2462.00	24987.515	4.661	-39.338	-15.339	Pass
NVNT	ANT1	802.11g	2412.00	25000.000	-4.111	-51.095	-24.111	Pass
NVNT	ANT1	802.11g	2437.00	24932.581	-3.274	-51.546	-23.274	Pass
NVNT	ANT1	802.11g	2462.00	24453.157	-3.326	-51.799	-23.326	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	24415.702	-1.683	-50.456	-21.683	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	24905.114	-3.053	-48.194	-23.053	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	24990.012	-3.374	-51.533	-23.374	Pass
NVNT	ANT1	802.11n(HT40)	2422.00	24955.054	-6.416	-53.054	-26.416	Pass
NVNT	ANT1	802.11n(HT40)	2437.00	24488.115	-6.204	-50.345	-26.204	Pass
NVNT	ANT1	802.11n(HT40)	2452.00	24925.090	-6.414	-50.112	-26.414	Pass


1_Reference_Level_NVNT_ANT1_802_11b_2412




2_Spurious_Emission_NVNT_ANT1_802_11b_2412




1_Reference_Level_NVNT_ANT1_802_11b_2437




2_Spurious_Emission_NVNT_ANT1_802_11b_2437




1_Reference_Level_NVNT_ANT1_802_11b_2462




2_Spurious_Emission_NVNT_ANT1_802_11b_2462




1_Reference_Level_NVNT_ANT1_802_11g_2412




2_Spurious_Emission_NVNT_ANT1_802_11g_2412




1_Reference_Level_NVNT_ANT1_802_11g_2437




2_Spurious_Emission_NVNT_ANT1_802_11g_2437




1_Reference_Level_NVNT_ANT1_802_11g_2462




2_Spurious_Emission_NVNT_ANT1_802_11g_2462




1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2412




2_Spurious_Emission_NVNT_ANT1_802_11n(HT20)_2412




1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2437




2_Spurious_Emission_NVNT_ANT1_802_11n(HT20)_2437




1_Reference_Level_NVNT_ANT1_802_11n(HT20)_2462




2_Spurious_Emission_NVNT_ANT1_802_11n(HT20)_2462




1_Reference_Level_NVNT_ANT1_802_11n(HT40)_2422




2_Spurious_Emission_NVNT_ANT1_802_11n(HT40)_2422



1_Reference_Level_NVNT_ANT1_802_11n(HT40)_2437




2_Spurious_Emission_NVNT_ANT1_802_11n(HT40)_2437



1_Reference_Level_NVNT_ANT1_802_11n(HT40)_2452



2_Spurious_Emission_NVNT_ANT1_802_11n(HT40)_2452



***** End of Report *****