



This product consists of three parts: charging case, microphone transmitter and receiver(as shown in the figure below, some models have no charging case, Based on the actual object)



① Windproof Net
 ② Transmitter indicator light
 ③ Transmitter type-c charging port
 ④ Transmitter switch key
 ⑤ Transmitter multi-function key
 ⑥ External MIC 3.5mm audio input port
 ⑦ Receiver switch key
 ⑧ Receiver multi-function key
 ⑨ Receiver indicator light
 ⑩ Receiver type-c charging port
 ⑪ Charging pin
 ⑫ Charging case display screen
 ⑬ Charging case type-c charging port

Function	Operate	LED
Power on	1 Take out from charging case will turn on automatically 2 Long press ① switch key	The 2th connection LED icon will flash and then remains on after paired successfully
Power off	Long press ③ switch key	Indicator light goes off
Noise reduction	Press ② multi-function key	1st level: the 4th indicator light remains on
Default noise reduction after turn on	1st level: Press the first time 2nd level: Press the second time 3rd level: Press the third time	2nd level: the 4th indicator light flash 2 times, then remains on 3rd level: the 4th indicator light flash 3 times, then remains on
Silent mode on/off	Press ③ switch key	On: The 3rd silent indicator light remains on Off: The 3rd silent indicator light goes off
Reverberation	Double press ② multi-function key	On: The 4th indicator light flash Off: Under noise reduction mode, the 4th indicator light is on and under non-noise mode, the 4th indicator light is off

Function	Operate	LED
Power on	1.Take out from the charging case will turn on automatically 2.Long press "7" switch key	The indicator light flashing
Power off	Long press;"7" switch key	Indicator light goes off
Paired		The indicator light remains on after paired
Silent mode on/off	Press "8" multi-function key	On:The indicator light flashing Off:The indicator light remain on

- (1) Microphone transmitter
- (2) Receiver
- (3) Charging case
- (4) Type-C Charging Cable
- (5) USB-C to Lightning Cable
- (6) USB-C to USB-C Cable
- (7) 3.5 mm jack cable
- (8) User manual

Frequency:2.4GHz Digital Frequency
Frequency response:20Hz-20kHz
Sampling frequency:48kHz
Transmission range:up to 20m(w/o any obstacle)
Signal to noise ratio: ≥ 75 dB
Sensitivity:-38dB $\pm$ 3dB
Battery capacity:80mAh(transmitter)
900mAh(charging case)
Working duration:up to 7h
Charging case charge times: 3.5 times
Interface:USB-C
Weight:119 G
Dimension:84.8*42*50.9 mm

FCC Warning Statement: Changes or modifications to this unit not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

FCC Radiation Exposure Statement

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.