FCC RADIO TEST REPORT
FCC ID: 2BFKR-R1

Product : Smart Ring

Trade Mark :

Model Name : Even R1

Family Model : N/A

Report No. : N25080700247E

Issue Date: Sept. 16, 2025

Prepared for

Even Realities Ltd.

Building West 2603, LEPU TOWER, Nanshan District, Shenzhen, 518055 China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

No. 24 Xinfa East Road, Xiangshan Community, Xinqiao Street,
Baoan District, Shenzhen, Guangdong, People's Republic of China

Tel. 0755-23200050 Website: http://www.ntek.org.cn

TEST RESULT CERTIFICATION

Applicant's name ..... : Even Realities Ltd.

Address ..... : Building West 2603, LEPU TOWER, Nanshan District, Shenzhen, 518055 China

Manufacturer's Name ..... : Even Realities Ltd.

Address ..... : Building West 2603, LEPU TOWER, Nanshan District, Shenzhen, 518055 China

Product description

Product name..... : Smart Ring

Model and/or type reference : Even R1

Family Model ..... :

Test Sample number..... : S2508200095-1#

Standards ..... : FCC Part15.225

Test procedure ..... ANSI C63.10-2020

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

Date of Test ..... :

Date (s) of performance of tests..... : Aug. 07, 2025 ~Sept. 16, 2025

Date of Issue..... : Sept. 16, 2025

Test Result..... : **Pass**

Prepared By	Reviewed By	Approved By
Mary Hu	Aaron Cheng	Alex Li
(Project Engineer)	(Supervisor)	(Manager)

Table of Contents **Page**

1 . SUMMARY OF TEST RESULTS 4
1.1 TEST FACILITY 5
1.2 MEASUREMENT UNCERTAINTY 5
2 . GENERAL INFORMATION 6
2.1 GENERAL DESCRIPTION OF EUT 6
2.2 DESCRIPTION OF TEST MODES 7
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 8
2.4 DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE) 9
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS 10
3 . ANTENNA REQUIREMENT 11
3.1 STANDARD REQUIREMENT 11
3.2 EUT ANTENNA 11
4 . EMC EMISSION TEST 12
4.1 CONDUCTED EMISSION MEASUREMENT 12
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS 12
4.1.2 TEST CONFIGURATION 12
4.1.3 TEST PROCEDURE 12
4.1.4 TEST RESULT 13
4.2 RADIATED EMISSION MEASUREMENT 15
4.2.1 RADIATED EMISSION LIMITS 15
4.2.2 TEST PROCEDURE 16
4.2.3 DEVIATION FROM TEST STANDARD 16
4.2.4 TEST SETUP 17
4.2.5 TEST RESULTS (BELOW 30MHZ) 18
4.2.6 TEST RESULTS (BETWEEN 30 – 1000 MHZ) 22
5 . BANDWIDTH TEST 24
5.1 TEST PROCEDURE 24
5.2 DEVIATION FROM STANDARD 24
5.3 TEST SETUP 24
5.4 TEST RESULTS 25
6. FREQUENCY TOLERANCE 26

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15, Subpart C (15.225)			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	Pass	
15.205(a) 15.209 15.225(abcd)	Radiated Spurious Emission	Pass	
15.225 15.215(c)	20dB Bandwidth	Pass	
15.225(e)	Frequency Tolerance	Pass	
15.203	Antenna Requirement	Pass	

NOTE:
(1) ” N/A” denotes test is not applicable in this Test Report.

1.1 TEST FACILITY

All measurement facilities used to collect the measurement data are located at
No. 24 Xinfa East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China.
The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

Site Description

CNAS-Lab.	:	The Certificate Registration Number is L5516.
IC-Registration		The Certificate Registration Number is 9270A. CAB identifier:CN0074
FCC- Accredited		Test Firm Registration Number: 463705. Designation Number: CN1184
A2LA-Lab.		The Certificate Registration Number is 4298.01 This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).
Name of Firm	:	Shenzhen NTEK Testing Technology Co., Ltd.
Site Location	:	No. 24 Xinfa East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China.

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement **y** ± **U** , where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2** , providing a level of confidence of approximately **95** %。

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power,conducted	±0.16dB
3	Spurious emissions,conducted	±0.21dB
4	All emissions,radiated(<1G)	±4.68dB
5	All emissions,radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%
8	Radio Frequency	$\pm 1\times 10^{-6}$
9	Occupied bandwidth	±4.7dB

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Smart Ring
Trade Mark	
Model Name	Even R1
Family Model	N/A
Model Difference	N/A
Product Description	The EUT is a Smart Ring Operation Frequency: 13.56MHz Modulation Type: ASK Number Of Channel 1CH. Antenna Designation: Induction coil
Adapter	N/A
Battery	Ring: Cell 1): JL136235 3.8V,21mAh, 79.8mWh Cell 2): JL136228 3.8V,16mAh, 60.8mwh
Power supply	Smart Ring Input : AC 5-35V, 1W Smart Ring Capacity: Cell 1): JL136235 3.8V,21mAh, 79.8mWh Cell 2): JL136228 3.8V,16mAh, 60.8mwh
HW Version	N/A
FW Version	N/A
SW Version	N/A

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX-13.56MHz

For Conducted Emission	
Final Test Mode	Description
Mode 1	TX-13.56MHz

For Radiated Emission	
Final Test Mode	Description
Mode 1	TX-13.56MHz

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note:1.The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.
2.EUT built-in battery-powered, the battery is fully-charged.

2.4 DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
AE-1	Adapter	ADP65S-1903420	N/A	Peripherals
AE-2	Smart Ring Charger	Even R1 Charger	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length	Note
C-1	USB Cable	YES	NO	1.0m	
C-2	RF Cable	YES	NO	0.1m	

Note:

(1) The support equipment was authorized by Declaration of Confirmation.

(2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation& Conducted Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Aglient	E4440A	MY41000130	2025.04.24	2026.04.23	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2025.04.17	2026.04.16	1 year
3	Spectrum Analyzer	R&S	FSV40	101417	2025.04.17	2026.04.16	1 year
4	Test Receiver	R&S	ESPI7	101318	2025.04.17	2026.04.16	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2025.04.17	2026.04.16	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2024.04.26	2027.04.25	3 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2024.05.12	2027.05.11	3 year
8	Active Loop Antenna	SCHWARZBECK	FMZB 1519 B	055	2024.05.17	2027.05.16	3 year
9	LF Cable	N/A	R-03	N/A	2023.06.17	2026.06.16	3 year
10	MXG Vector Signal Generator	Agilent	N5182A	MY47070317	2025.04.17	2026.04.16	1 year
11	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2023.05.06	2026.05.05	3 year
12	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2023.05.06	2026.05.05	3year

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2025.04.17	2026.04.16	1 year
2	LISN	R&S	ENV216	101313	2025.04.16	2026.04.15	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2025.04.16	2026.04.15	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2024.04.26	2027.04.25	3 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2023.05.06	2026.05.05	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2023.05.06	2026.05.05	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2023.05.06	2026.05.05	3 year

Note:

1.We will use the temporary antenna connector (soldered on the PCB board) When conducted test And this temporary antenna connector is listed within the instrument list

2. Each piece of equipment is scheduled for calibration once a year except the Test Cable& Aux Equipment which is scheduled for calibration every 3 years.

3. ANTENNA REQUIREMENT

3.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

3.2 EUT ANTENNA

The EUT antenna is permanent attached antenna. It comply with the standard requirement.

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
2. The lower limit shall apply at the transition frequencies
3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.1.2 TEST CONFIGURATION



4.1.3 TEST PROCEDURE

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2020 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.4 TEST RESULT

EUT：	Smart Ring	Model Name ：	Even R1
Temperature：	20.9 ℃	Relative Humidity：	60.3%
Pressure：	1010hPa	Phase：	L
Test Voltage ：	DC 5V from Adapter AC 120V/60Hz	Test Mode：	Mode 1

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.4300	18.71	19.56	38.27	57.25	-18.98	QP
0.4300	7.62	19.56	27.18	47.25	-20.07	AVG
0.9180	18.11	19.59	37.70	56.00	-18.30	QP
0.9180	6.79	19.59	26.38	46.00	-19.62	AVG
1.5300	17.11	19.62	36.73	56.00	-19.27	QP
1.5300	6.08	19.62	25.70	46.00	-20.30	AVG
13.5617	32.00	8.50	40.50	60.00	-19.50	QP
13.5617	31.04	8.50	39.54	50.00	-10.46	AVG
17.0016	16.40	22.25	38.65	60.00	-21.35	QP
17.0016	5.50	22.25	27.75	50.00	-22.25	AVG
26.8100	16.09	22.86	38.95	60.00	-21.05	QP
26.8100	7.79	22.86	30.65	50.00	-19.35	AVG

Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



EUT：	Smart Ring	Model Name ：	Even R1
Temperature：	20.9 ℃	Relative Humidity：	60.3%
Pressure：	1010hPa	Phase：	N
Test Voltage ：	DC 5V from Adapter AC 120V/60Hz	Test Mode：	Mode 1

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.3780	15.39	19.54	34.93	58.32	-23.39	QP
0.3780	6.54	19.54	26.08	48.32	-22.24	AVG
0.6540	17.01	19.61	36.62	56.00	-19.38	QP
0.6540	6.51	19.61	26.12	46.00	-19.88	AVG
1.3260	16.73	19.64	36.37	56.00	-19.63	QP
1.3260	6.46	19.64	26.10	46.00	-19.90	AVG
2.4420	15.39	19.71	35.10	56.00	-20.90	QP
2.4420	5.31	19.71	25.02	46.00	-20.98	AVG
13.5617	33.37	8.27	41.64	60.00	-18.36	QP
13.5617	32.40	8.27	40.67	50.00	-9.33	AVG
27.9020	17.74	23.08	40.82	60.00	-19.18	QP
27.9020	7.58	23.08	30.66	50.00	-19.34	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 Radiated Emission Limits (FCC 15.209)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note:

(1) The tighter limit applies at the band edges.

(2) Emission level (dBuV/m)=20log Emission level (uV/m).

(3) The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

According to FCC Part15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

LIMITS OF RADIATED EMISSION MEASUREMENT (FCC 15.225)

(a)The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters, equal to 124dBuV/m at 3 meters.

(b) Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters, equal to 90.5dBuV/m at 3 meters.

(c) Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters, equal to 80.5dBuV/m at 3 meters..

(d) The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in § 15.209.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1MHz / 1MHz for Peak

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.2.2 TEST PROCEDURE

a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz And above 1GHz,
b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3m meter. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m.
d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD

No deviation

4.2.4 TEST SETUP

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



4.2.5 TEST RESULTS (BELOW 30MHz)

EUT :	Smart Ring	Model Name. :	Even R1
Temperature :	20 ℃	Relative Humidtity :	54%
Pressure :	1010 hPa	Test Voltage :	DC 3.8V from Battery
Test Mode :	TX-13.56MHz		

Measurement Plot (Polarity: X):



Measurement Result:

Frequency (MHz)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
13.5618	53.10	53.10	124	-70.90

Measurement Plot (Polarity: Y):



Measurement Result:

Frequency (MHz)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
13.5609	56.98	56.98	124	-67.02

Measurement Plot (Polarity: Z):



Measurement Result:

Frequency (MHz)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
13.5609	58.48	58.48	124.00	-65.52

Spurious emissions at 9KHz~13.110MHz & 14.010MHz~30MHz

Frequency(MHz)	Ant.Pol.	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
0.0165	X	54.23	143.25	-89.02	PK
0.0165	X	41.34	123.25	-81.91	Avg
0.0849	X	52.41	129.03	-76.62	PK
0.0849	X	41.26	109.03	-67.77	Avg
0.135	X	45.34	105.00	-59.66	PK
0.135	X	31.68	85	-53.32	Avg
1.389	X	46.26	63.93	-17.67	QP
2.634	X	38.79	69.54	-30.75	QP
3.523	X	38.49	69.54	-31.05	QP

Note:

Below 30MHz, Pre-test the X, Y, Z axis to find X axis is worst case, so only record X axis test data.

X: Field strength which this device generates since the position of the loop antenna differ by 0 degrees.

Y: Field strength which this device generates since the position of the loop antenna differ by 90 degrees.

Z: Field strength which this device generates since the position of the loop antenna differ by 180 degrees

4.2.6 TEST RESULTS (BETWEEN 30 – 1000 MHZ)

EUT :	Smart Ring	Model Name :	Even R1
Temperature :	25.3 ℃	Relative Humidity :	53%
Pressure :	1010 hPa	Test Voltage :	DC 3.8V from Battery
Test Mode :	TX	Polarization :	Horizontal

Frequency (MHz)	Reading (dBμV/m)	Factor (dB)	Measurement (dBμV/m)	Limit (dBμV/m)	Over (dB)	Detector
52.5752	2.80	19.84	22.64	40.00	-17.36	QP
94.7600	8.24	16.71	24.95	43.50	-18.55	QP
255.6230	10.66	19.06	29.72	46.00	-16.28	QP
325.5957	7.10	20.75	27.85	46.00	-18.15	QP
434.0650	6.28	22.56	28.84	46.00	-17.16	QP
948.7610	3.90	30.17	34.07	46.00	-11.93	QP

Remark:
Factor = Antenna Factor + Cable Loss.



EUT :	Smart Ring	Model Name :	Even R1
Temperature :	25.3℃	Relative Humidity :	53%
Pressure :	1010 hPa	Test Voltage :	DC 3.8V from Battery
Test Mode :	TX	Polarization :	Vertical

Frequency (MHz)	Reading (dBμV/m)	Factor (dB)	Measurement (dBμV/m)	Limit (dBμV/m)	Over (dB)	Detector
40.7016	9.43	19.02	28.45	40.00	-11.55	QP
51.4807	9.17	19.90	29.07	40.00	-10.93	QP
94.7600	10.22	16.71	26.93	43.50	-16.57	QP
187.7530	9.83	16.75	26.58	43.50	-16.92	QP
261.9752	10.15	19.33	29.48	46.00	-16.52	QP
948.7610	3.67	30.17	33.84	46.00	-12.16	QP

Remark:
Factor = Antenna Factor + Cable Loss.



5. BANDWIDTH TEST

5.1 TEST PROCEDURE

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak mode.
2. 20dB Bandwidth the resolution bandwidth of 1 kHz and the video bandwidth of 1 kHz were used.
3. Measured the spectrum width with power higher than 20dB below carrier.

5.2 DEVIATION FROM STANDARD

15.215
(c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated

FCC Part15.225
Operation within the band 13.110 – 14.010MHz

5.3 TEST SETUP



5.4 TEST RESULTS

EUT :	Smart Ring	Model Name :	Even R1
Temperature :	26 ℃	Relative Humidity :	54%
Pressure :	1020 hPa	Test Power :	DC 3.8V from Battery
Test Mode :	TX		

Test Channel	Frequency (MHz)	20 dBc Bandwidth (kHz)
CH01	13.56	0.753



6. FREQUENCY TOLERANCE

6.1 Requirement:

Test Requirement:	FCC Part15.225
Test Method:	ANSI C63.10-2020
Requirement:	The frequency towlerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency over a temperature variation of –20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

6.2 Test Procedure

1.The EUT was placed on a turn table which is 0.8m above ground plane.

2.Set EUT as normal operation

3.Set SPA Center Frequency = fundamental frequency, RBW, VBW= 10kHz, Span =100kHz.

4.Set SPA Max hold. Mark peak.

Test Result

Power Supply	Temperature (℃)	Measured Frequency (MHz)	Frequency Error (MHz)	Result (ppm)	Part 15.225 Limit
DC 5.5V	-20	13.56011	0.00011	8.11	+/- 0.01%(100ppm)
	20	13.56014	0.00014	10.32	+/- 0.01%(100ppm)
	50	13.56013	0.00013	9.59	+/- 0.01%(100ppm)
DC 5V	-20	13.56004	0.00004	2.95	+/- 0.01%(100ppm)
	20	13.56003	0.00003	2.21	+/- 0.01%(100ppm)
	50	13.56006	0.00006	4.42	+/- 0.01%(100ppm)
DC 4.5V	-20	13.56003	0.00003	2.21	+/- 0.01%(100ppm)
	20	13.56004	0.00004	2.95	+/- 0.01%(100ppm)
	50	13.56007	0.00007	5.16	+/- 0.01%(100ppm)

END REPORT

`