

Test report

Number T251-0301/25

Project file: C20240241

Date: 2025-11-24

Pages: 9

Product: Activity sensor

Type reference: SENS motion PLUS, model A016

Ratings: 3 V d.c.
Class: |||

Trademark: 

Applicant: SENS Innovation ApS
Nannasgade 28, Copenhagen, Denmark

Manufacturer: SENS Innovation ApS
Nannasgade 28, Copenhagen, Denmark

Place of manufacture: SENS Innovation ApS
Nannasgade 28, Copenhagen, Denmark

Summary of testing

Testing method: Antenna pattern measurements

Testing location: SIQ Ljubljana
Mašera-Spasičeva ulica 10, SI-1000 Ljubljana, Slovenia

Remarks: Date of receipt of test items: 2025-03-13
Number of items tested: 3
Date of performance of tests: 2025-03-19
The test results presented in this report relate only to the items tested.
The test items were tested in the condition as received.
The product complies with the requirements of the testing methods.

Tested by: Luka Cvajnar

Approved by: Marjan Mak



The report shall not be reproduced except in full.



CONTENTS		page
<u>1</u>	<u>GENERAL</u>	<u>3</u>
1.1	EQUIPMENT UNDER TEST	3
1.2	ANTENNA PATTERN MEASUREMENT	4
1.3	TEST RESULTS BLE ANTENNA	5
1.4	MAXIMUM BLE ANTENNA GAIN	8
<u>2</u>	<u>USED TEST EQUIPMENT</u>	<u>9</u>

1 GENERAL

History sheet			
Date	Report No.	Change	Revision
2025-11-24	T251-0301/25	Initial Test Report issued.	--

Environmental conditions:

Ambient temperature: 15 °C to 35 °C

Relative humidity: 30 % to 60 %


Atmospheric pressure: 860 mbar to 1060 mbar

1.1 Equipment under test

Activity sensor

Type: **SENS motion PLUS**, model **A016**

Tested was antenna pattern of the sample below.



Picture of test sample

Copy of marking plate

The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective NCBs that own these marks.

**1.2 Antenna pattern measurement****1.2.1 Test procedure**

The radiation pattern for BLE antenna implemented to PCB reference design has been measured in an anechoic chamber with 3 meters test distance. Test results show radiation patterns for two planes, measured with vertical and horizontal polarization of measuring antenna. All measurements were performed at 2402, 2440 and 2480 MHz frequency.

1.3 Test results BLE Antenna

EUT Information

EUT:

Operating mode:


SENS motion

TX 2402


AziChart_MinMax_Eval

Frequency (MHz)	Max. Value (dBm)	Azimuth max. (deg)	Pol max.	Min. Value (dBm)	Azimuth min. (deg)	Pol min.
2402.000000	3.68	161	H	-31.31	336	V

Azimuth Chart: Horizontal



Azimuth Chart: Vertical






EUT Information

EUT: SENS motion
Operating mode: TX 2440


AziChart MinMax Eval

Frequency (MHz)	Max. Value (dBm)	Azimuth max. (deg)	Pol max.	Min. Value (dBm)	Azimuth min. (deg)	Pol min.
2440.000000	-6.85	279	H	-35.53	200	V

Azimuth Chart: Horizontal



Azimuth Chart: Vertical



EUT Information

EUT:

SENS motion


Operating mode:

TX 2480


AziChart MinMax Eval

Frequency (MHz)	Max. Value (dBm)	Azimuth max. (deg)	Pol max.	Min. Value (dBm)	Azimuth min. (deg)	Pol min.
2480.000000	-11.01	212	H	-43.02	192	V

Azimuth Chart: Horizontal



Azimuth Chart: Vertical





1.4 Maximum BLE antenna gain

DUT Frequency (MHz)	Maximum antenna gain (dBi)
2402.000000	3.68
2440.000000	-6.85
2480.000000	-11.01

2 USED TEST EQUIPMENT

Antenna pattern measurement

Manufacturer	Model No.	Used	Calibrated	Calibrated until
Comtest engineering, SAC2 (together with controlling equipment)	SAC 3m	X	2022-04-14	2025-04-14
Maturo, Turn table (2 m diameter)	TT 2.0 SI	X	/	/
Maturo, Bore-sight antenna mast	BAM-4.0-P	X	/	/
Maturo, positioning equipment	NCD	X	/	/
Rohde & Schwarz, RFI receiver	ESW 44	X	2024-09-26	2026-03-26
R&S, Ultra Broadband Antenna	HL562E		2023-09-26	2026-09-26
R&S, Horn Antenna	HF907	X	2023-08-22	2026-08-22

-----END OF TEST REPORT-----