RF TEST REPORT

Product Name: Smart watch

Model Name: SMRTW01

FCC ID: 2BFPH-SMRTW01

Issued For : Face Wheels(JiangSu) Co., Ltd.

Room 603, Building 3, Ziyuan Mansion, No. 158, Zhuangpai Road, Moling Street, Jiangning District, Nanjing

Issued By : Shenzhen LGT Test Service Co., Ltd.

Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China

Report Number:	LGT24E026HA01
Sample Received Date:	May 09, 2024
Date of Test:	May 09, 2024 – May 28, 2024
Date of Issue:	May 28, 2024

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.

TEST REPORT CERTIFICATION

Applicant:	Face Wheels(JiangSu) Co., Ltd.
Address:	Room 603, Building 3, Ziyuan Mansion, No. 158, Zhuangpai Road, Moling Street, Jiangning District, Nanjing
Manufacture:	Face Wheels(JiangSu) Co., Ltd.
Address:	Room 603, Building 3, Ziyuan Mansion, No. 158, Zhuangpai Road, Moling Street, Jiangning District, Nanjing
Product Name:	Smart watch
Trademark:	N/A
Model Name:	SMRTW01
Sample Status:	Normal

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47CFR §2.1093 KDB 447498 D01 General RF Exposure Guidance v06	PASS

Prepared by:

Zane Shan

Zane Shan
Engineer

Approved by:

Vita Li
Technical Director

SHENZHEN LGT TEST SERVICE CO., LTD.
LGT
领冠检测

TABLE OF CONTENTS

1 . GENERAL INFORMATION **5**

1.1 GENERAL DESCRIPTION OF THE EUT 5

1.2 TEST LABORATORY 5

2 . FCC 47CFR §2.1093 REQUIREMENT **6**

2.1 TEST STANDARDS 6

2.2 LIMIT 6

2.3 TEST RESULT 8

APPENDIX I - PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS **9**

Revision History

Rev.	Issue Date	Revisions
00	May 28 2024	Initial Issue

1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF THE EUT

Product Name:	Smart watch
Trademark:	N/A
Model Name:	SMRTW01
Series Model:	N/A
Model Difference:	N/A
Frequency Bands:	Bluetooth: 2402-2480MHz
Rating	Input: USB DC 5V 1A
Battery:	Rated Capacity: 50mAh Rated Voltage: 3.7V
Hardware Version:	N/A
Software Version:	N/A

1.2 TEST LABORATORY

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China
Accreditation Certificate	A2LA Certificate No.: 6727.01
	FCC Registration No.: 746540
	CAB ID: CN0136

2. FCC 47CFR §2.1093 REQUIREMENT

2.1 TEST STANDARDS

The limit for Maximum Permissible Exposure (MPE) specified in KDB 447498 D01 General RF Exposure Guidance v06 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.
Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

2.2 LIMIT

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	*SAR Test Exclusion Threshold* (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

MHz	30	35	40	45	50	mm
150	232	271	310	349	387	*SAR Test Exclusion Threshold* (mW)
300	164	192	219	246	274	
450	134	157	179	201	224	
835	98	115	131	148	164	
900	95	111	126	142	158	
1500	73	86	98	110	122	
1900	65	76	87	98	109	
2450	57	67	77	86	96	
3600	47	55	63	71	79	
5200	39	46	53	59	66	
5400	39	45	52	58	65	
5800	37	44	50	56	62	

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • [√f(GHz)] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,where f(GHz) is the RF channel transmit frequency in GHz.

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

2.3 TEST RESULT

Turn up Result

Mode	Turn up Power
BLE-GFSK	3±1dBm

The MPE result of worst mode:

RF Function	Frequency (MHz)	Max Turn up Power (dBm)	Max Turn up Power (mW)	Estimated SAR	Limit	Ratio	Result
BLE	2440	4.00	2.51	0.785	3	0.262	Pass

Note:

1. The estimated SAR≤ 3.0 for 1-g SAR, Separation distance ≤ 5mm, complies with the exemption requirements.

APPENDIX I - PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS

Note: Please refer to the attached SMRTW01_External Photos and SMRTW01_Internal Photos.

※※※※※END OF THE REPORT※※※※※