

Manufacturer: SHENZHEN GOBETTER TECHNOLOGY CO.,LTD

Address: 3F,Building B, Hengchao Industrial Zone, Zhoushi Road,Shiyan Town,Bao'an District,
Shenzhen City, China


Antenna model: 9026W

Product specification

Quick Reference

	Antenna model information	
Antenna Type	PCB	
Frequency	2.44GHz	
Ant. Port Input Pwr.(dBm)	0(Typ.BT class 2 output power)	
Tot.Rad.Pwr.(dBm)	-5.8(Input pwrloss pwr)	
Peak EIRP(dBm)	-2.9	
Directivity(dBi)	1(all direction antenna)	
Efficiency(dB)	-5.8(26.03%)	
Gain(dBi)	-2.9(Peak Gain XY-plane)	
MaximumPower(dBm)	-2.9(XY -plane)	
MinimumPower(dBm)	-7.9(XY -plane)	
AveragePower(dBm)	-4.5(XY -plane)	
Max/Min Ratio(dB)	5(XY -plane)	
Max/Avg Ratio(dB)	1.6(XY -plane)	
Min/Avg Ratio(dB)	-3.4(XY -plane)	
Average Gain(dB)	-4.5(Avg Gain XY-plane)	


Antenna module & Size




AntennaGain

Gain Table


Unit in dB@ 2.44 GHz z	XY -plane		XZ -plane		YZ -plane		Efficiency
	Peak	Avg	Peak	Avg	Peak	Avg	
	-2.9	-4.5	-3.7	-6.9	-2.9	-6.1	
							26.03%




Return Loss




3D radiation pattern diagram



XY-plane



XZ-plane



YZ-plane

