

FCC RF EXPOSURE REPORT

FCC ID: 2BFQX-RC860M

Project No. : 2405C265
Equipment : Bluetooth remote control
Brand Name : N/A
Test Model : RC860M
Series Model : RC*****(* can be A-Z,0-9 or“-” or blank)
Applicant : Moka Technology (Guangdong) Co., Ltd
Address : NO.1 Qiaoguang Road,Chenjiang Street,Zhongkai Hi-tech Industrial Zone,Huizhou City,Guangdong Province,P.R.China
Factory : Moka Technology (Guangdong) Co., Ltd
Address : NO.1 Qiaoguang Road,Chenjiang Street,Zhongkai Hi-tech Industrial Zone,Huizhou City,Guangdong Province,P.R.China
Date of Receipt : Jun. 03, 2024
Date of Test : Jun. 05, 2024 ~ Jun. 20, 2024
Issued Date : Jul. 17, 2024
Report Version : R00
Test Sample : Engineering Sample No.: DG20240603290
Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & KDB447498 D01

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Prepared by : Vincent. Tan
Vincent Tan

Approved by : Chay. Cai
Chay Cai

Room 108, Building 2, No.1, Yile Road, Songshan Lake Zone, Dongguan City, Guangdong,
People's Republic of China.

Tel: +86-769-8318-3000 Web: www.newbtl.com Service mail: btl_qa@newbtl.com

REPORT ISSUED HISTORY

Report No.	Version	Description	Issued Date	Note
BTL-FCCP-2-2405C265	R00	Original Report.	Jul. 17, 2024	Valid

1. TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No.3, Jinshagang 1st Road, Dalang, Dongguan City, Guangdong People's Republic of China.

2. GENERAL CONCLUSION

According to FCC KDB447498 D01, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$
 ≤ 3.0 for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Appendix A - SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and ≤ 50 mm											
MHz	5	10	15	20	25	30	35	40	45	50	mm
150	39	77	116	155	194	232	271	310	349	387	SAR Test Exclusion Thresholds (mW)
300	27	55	82	110	137	164	192	219	246	274	
450	22	45	67	89	112	134	157	179	201	224	
835	16	33	49	66	82	98	115	131	148	164	
900	16	32	47	63	79	95	111	126	142	158	
1500	12	24	37	49	61	73	86	98	110	122	
1900	11	22	33	44	54	65	76	87	98	109	
2450	10	19	29	38	48	57	67	77	86	96	
3600	8	16	24	32	40	47	55	63	71	79	
5200	7	13	20	26	33	39	46	53	59	66	
5400	6	13	19	26	32	39	45	52	58	65	
5800	6	12	19	25	31	37	44	50	56	62	

3. TABLE FOR FILED ANTENNA

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain (dBi)
1	Huizhou yin Baoshan new science and technology co., ltd	N/A	PCB	N/A	-0.83

Note: The antenna gain is provided by the manufacturer.

4. TEST RESULTS

Frequency (MHz)	Max Tune-up power (dBm)	Max Tune-up power (mW)	Distance(mm)	Result	Limit
2480	5.11	3.243	5	1.022	3

Note:

(1) Output power including tune up tolerance.

(2) No SAR evaluation required since transmitter power is below FCC threshold.

End of Test Report