






99% Bandwidth:






GFSK DH5 Channel 0




GFSK DH5 Channel 39




GFSK DH5 Channel 78


 $\pi/4$ DQPSK 2-DH5 Channel 0 $\pi/4$ DQPSK 2-DH5 Channel 39 $\pi/4$ DQPSK 2-DH5 Channel 78



8DPSK_3-DH5_Channel 0



8DPSK_3-DH5_Channel 39



8DPSK_3-DH5_Channel 78



20dB Bandwidth:



CTC Laboratories, Inc.




2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China




Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : <http://yz.cnca.cn>

 $\pi/4$ DQPSK_2-DH5_Channel 0 $\pi/4$ DQPSK_2-DH5_Channel 39 $\pi/4$ DQPSK_2-DH5_Channel 78

**8DPSK 3-DH5 Channel 0****8DPSK 3-DH5 Channel 39****8DPSK 3-DH5 Channel 78**

CTC Laboratories, Inc.

2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : <http://yz.cnca.cn>




3.6. Channel Separation

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1)

Test Item	Limit	Frequency Range (MHz)
Channel Separation	>25kHz or >two-thirds of the 20 dB bandwidth Which is greater	2400~2483.5

Test Configuration



Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
2. Spectrum Setting:
 - (1) Set RBW = 100 kHz.
 - (2) Set the video bandwidth (VBW) ≥ 3 RBW.
 - (3) Detector = Peak.
 - (4) Trace mode = Max hold.
 - (5) Sweep = Auto couple.

Test Mode

Please refer to the clause 2.4.

Test Result

Test Mode	Frequency (MHz)	Carrier Frequencies Separation (MHz)	Limit (MHz)	Verdict
GFSK	Hop_2441	0.9886	0.689	Pass
$\pi/4$ -DQPSK	Hop_2441	0.9937	0.879	Pass
8-DPSK	Hop_2441	1.1452	0.866	Pass



Test plot as follows:



CTC Laboratories, Inc.

2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn

For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : <http://yz.cnca.cn>




3.7. Number of Hopping Channel

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(iii)

Section	Test Item	Limit
15.247 (a)(iii) RSS-247 5.1 d	Number of Hopping Channel	≥ 15

Test Configuration



Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
2. Spectrum Setting:
 - (1) Peak Detector: RBW=100 kHz, VBW $\geq$ RBW, Sweep time= Auto.

Test Mode


Please refer to the clause 2.4.

Test Result


Test Mode	Channel Number	Limit	Verdict
GFSK	79	≥ 15	Pass
$\pi/4$ -DQPSK	79	≥ 15	Pass
8-DPSK	79	≥ 15	Pass




Test plot as follows:



Hopping Plot
GFSK



Hopping Plot
 $\pi/4$ DQPSK



Hopping Plot
8DPSK

CTC Laboratories, Inc.

2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059



Fax: (86)755-27521011 Http://www.sz-ctc.org.cn
For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : <http://yz.cnca.cn>




3.8. Dwell Time

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(iii)

Section	Test Item	Limit
15.247 (a)(iii) RSS-247 5.1 d	Average Time of Occupancy	0.4 sec

Test Configuration



Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
2. Spectrum Setting:
 - (1) Spectrum Setting: RBW=1MHz, VBW $\geq$ RBW.
 - (2) Use video trigger with the trigger level set to enable triggering only on full pulses.
 - (3) Sweep Time is more than once pulse time.
 - (4) Set the center frequency on any frequency would be measure and set the frequency span to zero.
 - (5) Measure the maximum time duration of one single pulse.
 - (6) Set the EUT for packet transmitting.

Test Mode

Please refer to the clause 2.4.

**Test Result**

Test Mode	Channel	Frequency (MHz)	Pulse Time (ms)	Number of Pulses in 31.6 seconds	Total of Dwell (ms)	Period Time (ms)	Limit (second)	Verdict
GFSK	DH1	2441	0.3840	100	122.9	31.60	≤0.40	Pass
	DH3	2441	1.632	55	261.1	31.60		
	DH5	2441	2.880	34	307.2	31.60		
π /4-DQPSK	2DH1	2441	0.3920	101	125.4	31.60	≤0.40	Pass
	2DH3	2441	1.648	56	263.7	31.60		
	2DH5	2441	2.888	47	308.1	31.60		
8-DPSK	3DH1	2441	0.3840	99	122.9	31.60	≤0.40	Pass
	3DH3	2441	1.640	53	262.4	31.60		
	3DH5	2441	2.892	30	308.5	31.60		




Note: 1DH1/2DH1/3DH1 Total of Dwell = Pulse Time*(1600/2)*31.6/79


1DH3/2DH3/3DH3 Total of Dwell = Pulse Time*(1600/4)*31.6/79

1DH5/2DH5/3DH5 Total of Dwell = Pulse Time*(1600/6)*31.6/79




Test plot as follows:


Pulse Width
GFSK_DH1Number of Pulses in 31.6 seconds
GFSK_DH1Pulse Width
GFSK_DH3




Number of Pulses in 31.6 seconds
GFSK DH3



Pulse Width
GFSK DH5




Number of Pulses in 31.6 seconds
GFSK DH5




Pulse Width
 $\pi/4$ DQPSK 2-DH1




Number of Pulses in 31.6 seconds
 $\pi/4$ DQPSK 2-DH1




Pulse Width
 $\pi/4$ DQPSK 2-DH3






Number of Pulses in 31.6 seconds
 $\pi/4$ DQPSK 2-DH3




Pulse Width
 $\pi/4$ DQPSK 2-DH5




Number of Pulses in 31.6 seconds
 $\pi/4$ DQPSK 2-DH5


Pulse Width
8DPSK_3-DH1Number of Pulses in 31.6 seconds
8DPSK_3-DH1Pulse Width
8DPSK_3-DH3



Number of Pulses in 31.6 seconds
8DPSK_3-DH3



Pulse Width
8DPSK_3-DH5



Number of Pulses in 31.6 seconds
8DPSK_3-DH5




3.9. Peak Output Power

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(1)

Section	Test Item	Limit	Frequency Range (MHz)
FCC CFR 47 Part15.247 (b)(1)	Maximum Conducted Output Power	Hopping Channels $\geq$ 75, Power <1W(30dBm); Others <125mW(21dBm)	2400~2483.5

Test Configuration



Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
2. Spectrum Setting:
 - (1) Set RBW > 20dB Bandwidth.
 - (2) Set VBW $\geq$ RBW.
 - (3) Detector = Peak.
 - (4) Trace mode = Max hold.
 - (5) Sweep = Auto couple.
 - (6) Span = Approximately five times the 20dB bandwidth, centered on a hopping channel.

Test Mode


Please refer to the clause 2.4.

Test Result

Test Mode	Frequency (MHz)	Conducted Output Power (dBm)	FCC Limit (dBm)	Verdict
GFSK	2402	-6.379	≤ 30	Pass
	2441	-4.747	≤ 30	Pass
	2480	-3.929	≤ 30	Pass
$\pi/4$ -DQPSK	2402	-5.546	≤ 30	Pass
	2441	-4.105	≤ 30	Pass
	2480	-3.480	≤ 30	Pass
8-DPSK	2402	-6.666	≤ 30	Pass
	2441	-6.561	≤ 30	Pass
	2480	-5.387	≤ 30	Pass



Test plot as follows:



CTC Laboratories, Inc.

2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China


Tel.: (86)755-27521059

Fax: (86)755-27521011


Http://www.sz-ctc.org.cn




For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : <http://yz.cnca.cn>




Peak Output Power
 $\pi/4$ DQPSK Channel 0




Peak Output Power
 $\pi/4$ DQPSK Channel 39




Peak Output Power
 $\pi/4$ DQPSK Channel 78



Peak Output Power
8DPSK Channel 0



Peak Output Power
8DPSK Channel 39



Peak Output Power
8DPSK Channel 78




3.10. Duty Cycle

Limit

None, for report purposes only.

Test Configuration



Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
2. The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 DTS Meas Guidance v05r02.
3. Spectrum Setting:
Set analyzer center frequency to test channel center frequency.
Set the span to 0Hz.
Set the RBW to 10MHz.
Set the VBW to 10MHz.
Detector: Peak.
Sweep time: Auto.
Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.

Test Mode


Please refer to the clause 2.4.




Test Result


Test Mode	Frequency (MHz)	Transmission Duration (ms)	Transmission Period (ms)	Duty Cycle (%)	1/T Minimum VBW (kHz)	Final Setting for VBW (kHz)
GFSK	2402	2.890	3.732	77.42	0.35	1
	2441	2.890	3.732	77.42	0.35	1
	2480	2.870	3.732	76.88	0.35	1
$\pi/4$ -DQPSK	2402	2.870	3.712	77.30	0.35	1
	2441	2.890	3.732	77.42	0.35	1
	2480	2.890	3.732	77.42	0.35	1
8-DPSK	2402	2.890	3.732	77.42	0.35	1
	2441	2.890	3.732	77.42	0.35	1
	2480	2.890	3.732	77.42	0.35	1




Test plot as follows:




 $\pi/4$ DQPSK(2-DH5) Channel 0 $\pi/4$ DQPSK(2-DH5) Channel 39 $\pi/4$ DQPSK(2-DH5) Channel 78



8DPSK(3-DH5) Channel 0



8DPSK(3-DH5) Channel 39



8DPSK(3-DH5) Channel 78



3.11. Antenna Requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i)

(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

Test Result

The directional gain of the antenna is less than 6dBi, please refer to the EUT internal photographs antenna photo.

*****THE END*****