

**FCC ID: 2BFVZ-CRYSTALSUPER**

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

BLE:

| Modulation | Channel Freq. (GHz) | Conduct ed power (dBm) | Conducte d power (mW) | Tune-up power (dBm) | Max tune-up power (dBm) | Max tune-up power (mW) | Distance (mm) | Result calculation | SAR Exclusion threshold | SAR test exclusion |
|------------|---------------------|------------------------|-----------------------|---------------------|-------------------------|------------------------|---------------|--------------------|-------------------------|--------------------|
| BLE(1M)    | 2.402               | -5.35                  | 0.29                  | -5±1                | -4                      | 0.40                   | <5            | 0.12340            | 3.00                    | YES                |
|            | 2.440               | -5.27                  | 0.30                  | -5±1                | -4                      | 0.40                   | <5            | 0.12437            | 3.00                    | YES                |
|            | 2.480               | -5.04                  | 0.31                  | -5±1                | -4                      | 0.40                   | <5            | 0.12539            | 3.00                    | YES                |
| BLE(2M)    | 2.402               | -5.33                  | 0.29                  | -5±1                | -4                      | 0.40                   | <5            | 0.12340            | 3.00                    | YES                |
|            | 2.440               | -5.26                  | 0.30                  | -5±1                | -4                      | 0.40                   | <5            | 0.12437            | 3.00                    | YES                |
|            | 2.480               | -5.01                  | 0.32                  | -5±1                | -4                      | 0.40                   | <5            | 0.12539            | 3.00                    | YES                |

**Conclusion:**

For the max result :  $0.12539 \leq 3.0$  for 1g SAR, SAR is not required.

Signature:



Date: 2025-05-28

**NAME AND TITLE** (Please print or type): Alex li /Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China