

TEST REPORT

Application No.: SZCR2509004228AT
Applicant: Shenzhen Mammotion Innovation Co., Limited
Address of Applicant: 9th Floor, Building A3, Nanshan Zhiyuan, Changyuan Community, Nanshan District, Shenzhen, China
Manufacturer: Shenzhen Mammotion Innovation Co., Limited
Address of Manufacturer: 9th Floor, Building A3, Nanshan Zhiyuan, No.1001 Xueyuan Avenue, Changyuan Community, Taoyuan Street, Nanshan District, Shenzhen
Factory: NK (Dongguan) Co., Ltd
Address of Factory: Room 101, Building 6, No. 770, Xie Cao Road, Xiegang Town, Dongguan City, Guangdong, P.R.China
Equipment Under Test (EUT):
EUT Name: Robotic Lawn Mower
Model No.: LUB3S1, LUB3S2, LUB3S3, LUB3H1, LUB3H2, LUB3H3 ♣
♣ Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.
Trade Mark: MAMMOTION
FCC ID: 2BFWS-LUBA3SH
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2025-09-25
Date of Test: 2025-10-20 to 2025-12-30
Date of Issue: 2025-12-30

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Keny Xu

Keny Xu
EMC Laboratory Manager



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR250900422803

Page: 2 of 93

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2025-12-30		Original

Authorized for issue by:				
		Donjon . Huang		
		Donjon Huang/Project Engineer		
		Eric Fu		
		Eric Fu/Reviewer		



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2020) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2020) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2020) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2020) Section 6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Conducted Peak Output Power		ANSI C63.10 (2020) Section 11.9.2	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2020) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2020) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2020) Section 6.10.4	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2020) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR250900422803

Page: 4 of 93

Remark:

Model No.: LUB3S1, LUB3S2, LUB3S3, LUB3H1, LUB3H2, LUB3H3

Only the models LUB3H3 was tested. According to the applicant, the circuit design, layout, components used, internal wiring, and functionality of the above models are identical, with the difference as the below.

Model	LUB3S1	LUB3H1	LUB3S2	LUB3H2	LUB3S3	LUB3H3
LiDAR	AK1		MID-360S			
Battery	MWBT06S04P-02 (21.6V 9.4Ah 203Wh)		MWBT06S04P-01 (21.6V 12.0Ah 259.2Wh)		MWBT06S05P-01 (21.6V 15.0Ah 324Wh)	
GNSS	TD1050 and Antenna		UM960 and Antenna			
Mowing Size	1500		3000		5000	
Cutting Height	25-70mm	55-100mm	25-70mm	55-100mm	25-70mm	55-100mm
Motor for blade	SL5870B024(24V 88W)		SL5870B021.6-001(24V 165W)			

Note: LiDAR is an infrared detector and does not have wireless transmission capabilities.



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (SZEMC) Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	5
4 General Information	7
4.1 Details of E.U.T.	7
4.2 Description of Support Units	8
4.3 Measurement Uncertainty	8
4.4 Test Location	9
4.5 Test Facility	9
4.6 Deviation from Standards	9
4.7 Abnormalities from Standard Conditions	9
5 Equipment List	10
6 Radio Spectrum Technical Requirement	12
6.1 Antenna Requirement	12
6.1.1 Test Requirement:	12
6.1.2 Conclusion	12
7 Radio Spectrum Matter Test Results	13
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)	13
7.1.1 E.U.T. Operation	13
7.1.2 Test Mode Description	13
7.1.3 Test Setup Diagram	14
7.1.4 Measurement Procedure and Data	14
7.2 Radiated Emissions which fall in the restricted bands	17
7.2.1 E.U.T. Operation	17
7.2.2 Test Mode Description	17
7.2.3 Test Setup Diagram	18
7.2.4 Measurement Procedure and Data	19
7.3 Radiated Spurious Emissions Below 1GHz	28
7.3.1 E.U.T. Operation	28
7.3.2 Test Mode Description	28
7.3.3 Test Setup Diagram	29
7.3.4 Measurement Procedure and Data	29
7.4 Radiated Spurious Emissions Above 1GHz	32
7.4.1 E.U.T. Operation	32
7.4.2 Test Mode Description	32
7.4.3 Test Setup Diagram	33
7.4.4 Measurement Procedure and Data	34
7.5 Conducted Peak Output Power	40
7.5.1 E.U.T. Operation	40



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR250900422803

Page: 6 of 93

7.5.2	Test Mode Description	40
7.5.3	Test Setup Diagram	41
7.5.4	Measurement Procedure and Data.....	41
7.6	Minimum 6dB Bandwidth	42
7.6.1	E.U.T. Operation	42
7.6.2	Test Mode Description	42
7.6.3	Test Setup Diagram	42
7.6.4	Measurement Procedure and Data.....	42
7.7	Power Spectrum Density	43
7.7.1	E.U.T. Operation	43
7.7.2	Test Mode Description	43
7.7.3	Test Setup Diagram	43
7.7.4	Measurement Procedure and Data.....	43
7.8	Conducted Band Edges Measurement	44
7.8.1	E.U.T. Operation	44
7.8.2	Test Mode Description	44
7.8.3	Test Setup Diagram	45
7.8.4	Measurement Procedure and Data.....	45
7.9	Conducted Spurious Emissions	46
7.9.1	E.U.T. Operation	46
7.9.2	Test Mode Description	46
7.9.3	Test Setup Diagram	47
7.9.4	Measurement Procedure and Data.....	47
8	Test Setup Photo	48
9	EUT Constructional Details (EUT Photos)	48
10	Appendix.....	49



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4 General Information

4.1 Details of E.U.T.

Power supply:	Powered by Rechargeable Li-ion Battery. Battery 1 information: Model: MWBT06S04P-01 Nominal Voltage: 21.6Vdc Rated Capacity: 12.0Ah/259.2Wh Battery 2 information: Model: MWBT06S05P-01 Nominal Voltage: 21.6Vdc Rated Capacity: 15.0Ah/324Wh Battery 3 information: Model: MWBT06S04P-02 Nominal Voltage: 21.6Vdc Rated Capacity: 9.4Ah/203Wh Charging station information Model 1: CHG4402 Model 2: CHG4403 Input: 28VDC,210W Output: 28VDC,7.5A Charging station information Adapter1 Model: TS-A210-2807501 Input: 100-240VAC, 50/60Hz 3.0A Max Output: 28.0VDC, 7.5A, 210.0W Adapter2 Model: E210-1C280750M6 Input: 100-240VAC, 50/60Hz 3.0A Max Output: 28.0VDC, 7.5A
Cable(s):	AC cable of adapter: 85cm unshielded DC cable of adapter to charge station: 1040cm unshielded DC cable of station to RTK: 213cm unshielded
Cable Loss (for RF conducted test):	0.7dB
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz 802.11n(HT40): 2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
Number of Channels:	802.11b/g/n(HT20):11 802.11n(HT40):7
Channel Spacing:	5MHz



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR250900422803

Page: 8 of 93

Antenna Type:	PIFA Antenna
Antenna Gain:	2.9dBi

Remark: The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
--	--	--	--

The EUT has been tested as an independent unit.

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	$\pm 3.2\text{dB}$
Radiated Emissions which fall in the restricted bands	$\pm 6.0\text{dB}$ (Below 1GHz); $\pm 4.6\text{dB}$ (Above 1GHz)
Radiated Spurious Emissions Below 1GHz	$\pm 6.0\text{dB}$ for 3m; $\pm 5.0\text{dB}$ for 10m
Radiated Spurious Emissions Above 1GHz	$\pm 4.6\text{dB}$ (1-18GHz); $\pm 4.8\text{dB}$ (18-40GHz)
Conducted Peak Output Power	$\pm 0.4\text{dB}$
Minimum 6dB Bandwidth	$\pm 0.3\%$
Power Spectrum Density	$\pm 0.4\text{dB}$
Conducted Band Edges Measurement	$\pm 2.7\text{dB}$
Conducted Spurious Emissions	$\pm 2.7\text{dB}$

Remark:

The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR250900422803

Page: 9 of 93

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2025-05-07	2028-05-06
EMI Test Receiver	Rohde&Schwarz	ESR	SZ-WRG-M-047	2025-01-08	2026-01-07
Measurement Software	AUDIX	e3 V8.2014-6-27a	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2025-07-05	2026-07-04
LISN	Rohde&Schwarz	ENV216	SEM007-01	2025-07-25	2026-07-24
LISN	ETS-LINDGREN	3816/2	SEM007-02	2025-03-03	2026-03-02

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Signal & Spectrum Analyzer	Rohde & Schwarz	FSV	SZ-WRG-M-048	2025-01-07	2026-01-06
Low Noise Amplifier 30M-8GHz	Tonscend	TAP30M8G30	SZ-WRG-M-050	2025-01-07	2026-01-06
Double Ridge Horn Antenna 1GHz-18GHz	SCHWARZBECK	BBHA 9120 D	SZ-WRG-M-055	2023-12-21 2025-12-13	2025-12-20 2026-12-12
RSE Test Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Chamber	CRTSGSSAC966	N/A	SZ-WRG-C-063	2025-01-06	2028-01-05
Humidity and Temperature Indicator	deli	8838	SEM002-46	2025-07-23	2026-07-22

Radiated Spurious Emissions Below 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2023-11-20 2025-11-17	2025-11-19 2027-11-16
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2023-06-19	2026-06-18
MXE EMI Receiver	Agilent Technologies	N9038A	SEM004-15	2025-07-25	2026-07-24
BiConiLog Antenna	ETS-LINDGREN	3142C	SEM003-01	2025-08-29	2027-08-28
Pre-Amplifier	Agilent Technologies	8447D	SEM005-01	2025-03-04	2026-03-03
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM025-01	2025-07-05	2026-07-04



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR250900422803

Page: 11 of 93

Radiated Spurious Emissions Above 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Signal & Spectrum Analyzer	Rohde & Schwarz	FSV	SZ-WRG-M-048	2025-01-07	2026-01-06
Low Noise Amplifier 1G-18GHz	Tonscend	TAP01018050	SZ-WRG-M-051	2025-01-07	2026-01-06
Low Noise Amplifier 18G-40GHz	Tonscend	TAP18040048	SZ-WRG-M-052	2025-01-08	2026-01-07
Double Ridge Horn Antenna 1GHz-18GHz	SCHWARZBECK	BBHA 9120 D	SZ-WRG-M-055	2023-12-21 2025-12-13	2025-12-20 2026-12-12
SHF-EHF Horn 15GHz-40GHz	SCHWARZBECK	BBHA 9170	SZ-WRG-M-056	2023-12-25 2025-12-13	2025-12-24 2026-12-12
RSE Test Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Chamber	CRTSGSSAC966	N/A	SZ-WRG-C-063	2025-01-06	2028-01-05
Humidity and Temperature Indicator	deli	8838	SEM002-46	2025-07-23	2026-07-22

RF Conducted Test					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Power Sensor	TST PASS	TSPS2023R	SEM009-26	2025-03-04	2026-03-03
Power Sensor	KEYSIGHT	U2021XA	SEM009-16	2025-03-04	2026-03-03
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2025-07-24	2026-07-23
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2025-03-04	2026-03-03
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2025-07-05	2026-07-04
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2025-03-03	2026-03-02

General used equipment					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	deli	8838	SEM002-32	2025-07-23	2026-07-22
Humidity/ Temperature Indicator	deli	8838	SEM002-33	2025-07-23	2026-07-22
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2025-03-03	2026-03-02



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.9dBi.

Antenna location: Refer to internal photos



7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207
 Test Method: ANSI C63.10 (2020) Section 6.2
 Test Engineer: Wade Li

Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		
Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz		

7.1.1 E.U.T. Operation

Operating Environment:


Temperature: 25.3 °C Humidity: 40.5 % RH Atmospheric Pressure: 1020 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	05	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



7.1.3 Test Setup Diagram




7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: Level=Read Level+ Cable Loss+ LISN Factor



Test Mode: 05; Line: Live line




Site : Shielding Room
Condition: Line
Job No. : 04228AT/04229AT
Test mode: 05

	Freq	Cable Loss	LISN Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.2106	0.07	10.09	38.32	48.48	63.18	-14.70	QP
2 *	0.2106	0.07	10.09	36.04	46.20	53.18	-6.98	Average
3	0.3410	0.08	9.77	34.67	44.52	59.18	-14.66	QP
4	0.3410	0.08	9.77	31.92	41.77	49.18	-7.41	Average
5	1.0997	0.11	9.58	27.17	36.86	56.00	-19.14	QP
6	1.0997	0.11	9.58	18.67	28.36	46.00	-17.64	Average
7	1.9489	0.12	9.58	24.04	33.74	56.00	-22.26	QP
8	1.9489	0.12	9.58	14.72	24.42	46.00	-21.58	Average
9	4.9519	0.14	9.66	30.68	40.48	56.00	-15.52	QP
10	4.9519	0.14	9.66	24.64	34.44	46.00	-11.56	Average
11 *	6.3859	0.14	9.67	36.02	45.83	60.00	-14.17	QP
12	6.3859	0.14	9.67	30.55	40.36	50.00	-9.64	Average



Test Mode: 05; Line: Neutral Line



Site : Shielding Room
Condition: Neutral
Job No. : 04228AT/04229AT
Test mode: 05

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.2220	0.07	10.00	36.72	46.79	62.74	-15.95	QP
2	0.2220	0.07	10.00	30.02	40.09	52.74	-12.65	Average
3 *	0.3446	0.08	9.75	35.30	45.13	59.09	-13.96	QP
4 *	0.3446	0.08	9.75	32.60	42.43	49.09	-6.66	Average
5	0.9381	0.11	9.56	27.34	37.01	56.00	-18.99	QP
6	0.9381	0.11	9.56	14.93	24.60	46.00	-21.40	Average
7	1.9906	0.12	9.55	22.27	31.94	56.00	-24.06	QP
8	1.9906	0.12	9.55	14.67	24.34	46.00	-21.66	Average
9	4.9782	0.14	9.56	31.13	40.83	56.00	-15.17	QP
10	4.9782	0.14	9.56	25.45	35.15	46.00	-10.85	Average
11	6.3186	0.14	9.62	36.19	45.95	60.00	-14.05	QP
12	6.3186	0.14	9.62	30.46	40.22	50.00	-9.78	Average



7.2 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.10.5
 Measurement Distance: 3m
 Test Engineer: Xing Guo

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.2.1 E.U.T. Operation

Operating Environment:


Temperature: 24.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1020 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	04	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.
Final test	05	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



7.2.3 Test Setup Diagram



30MHz-1GHz

Above 1GHz



7.2.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor


Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Remark 3: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.

Remark 4: For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.




11b_TX_CH_01_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Factor	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB		dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.847	6.83	27.46	30.69	61.82	65.42	74.00	-8.58	peak	
2	2390.000	6.83	27.46	30.69	61.41	65.01	74.00	-8.99	peak	
3 pp	2412.000	6.91	27.52	30.69	104.72	108.46	74.00	34.46	peak	


11b_TX_CH_01_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Factor	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB		dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2386.461	6.82	27.45	30.69	40.80	44.38	54.00	-9.62	Average	
2	2390.000	6.83	27.46	30.69	38.49	42.09	54.00	-11.91	Average	
3 pp	2412.000	6.91	27.52	30.69	101.34	105.08	54.00	51.08	Average	


11b_TX_CH_01_Vertical-Peak



Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Factor	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB		dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2388.516	6.82	27.45	30.69	57.36	60.94	74.00	-13.06	peak	
2	2390.000	6.83	27.46	30.69	55.79	59.39	74.00	-14.61	peak	
3 pp	2412.000	6.91	27.52	30.69	100.85	104.59	74.00	30.59	peak	

11b_TX_CH_01_Vertical-Avg



Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Factor	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB		dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2386.340	6.82	27.45	30.69	38.11	41.69	54.00	-12.31	Average	
2	2390.000	6.83	27.46	30.69	35.66	39.26	54.00	-14.74	Average	
3 pp	2412.000	6.91	27.52	30.69	97.58	101.32	54.00	47.32	Average	




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch, Shenzhen, P.R. China, Laboratory.

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


11b_TX_CH_11_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2462 Band edge
: 2.4G Wi-Fi 11b

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp 2462.000	7.25	27.67	30.70	104.34	108.56	74.00	34.56	peak
2 2483.500	7.40	27.80	30.71	44.12	48.61	74.00	-25.39	peak
3 2485.295	7.41	27.81	30.71	54.04	58.55	74.00	-15.45	peak


11b_TX_CH_11_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2462 Band edge
: 2.4G Wi-Fi 11b

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp 2462.000	7.25	27.67	30.70	101.21	105.43	54.00	51.43	Average
2 2483.500	7.40	27.80	30.71	39.09	43.58	54.00	-10.42	Average
3 2487.656	7.43	27.83	30.71	40.79	45.34	54.00	-8.66	Average


11b_TX_CH_11_Vertical-Peak



Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2462 Band edge
: 2.4G Wi-Fi 11b

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp 2462.000	7.25	27.67	30.70	99.87	104.09	74.00	30.09	peak
2 2483.500	7.40	27.80	30.71	39.60	44.09	74.00	-29.91	peak
3 2491.630	7.45	27.85	30.71	45.92	50.51	74.00	-23.49	peak

11b_TX_CH_11_Vertical-Avg




Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2462 Band edge
: 2.4G Wi-Fi 11b

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp 2462.000	7.25	27.67	30.70	96.75	100.97	54.00	46.97	Average
2 2483.500	7.40	27.80	30.71	35.22	39.71	54.00	-14.29	Average
3 2487.656	7.43	27.83	30.71	36.31	40.86	54.00	-13.14	Average




11g_TX_CH_01_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11g

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	6.83	27.46	30.69	64.78	68.38	74.00	-5.62	peak
2	2390.000	6.83	27.46	30.69	64.78	68.38	74.00	-5.62	peak
3 pp	2412.000	6.91	27.52	30.69	107.04	110.78	74.00	36.78	peak


11g_TX_CH_01_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11g

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	6.83	27.46	30.69	42.95	46.55	54.00	-7.45	Average
2	2390.000	6.83	27.46	30.69	42.95	46.55	54.00	-7.45	Average
3 pp	2412.000	6.91	27.52	30.69	96.47	100.21	54.00	46.21	Average


11g_TX_CH_01_Vertical-Peak



Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11g

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	6.83	27.46	30.69	59.73	63.33	74.00	-10.67	peak
2	2390.000	6.83	27.46	30.69	59.73	63.33	74.00	-10.67	peak
3 pp	2412.000	6.91	27.52	30.69	103.25	106.99	74.00	32.99	peak

11g_TX_CH_01_Vertical-Avg




Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11g

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.847	6.83	27.46	30.69	39.33	42.93	54.00	-11.07	Average
2	2390.000	6.83	27.46	30.69	39.23	42.83	54.00	-11.17	Average
3 pp	2412.000	6.91	27.52	30.69	92.48	96.22	54.00	42.22	Average




11g_TX_CH_11_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2462 Band edge
: 2.4G Wi-Fi 11g

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2462.000	7.25	27.67	30.70	106.71	110.93	74.00	36.93	peak
2	2483.500	7.40	27.80	30.71	63.66	68.15	74.00	-5.85	peak
3	2484.944	7.41	27.81	30.71	69.10	73.61	74.00	-0.39	peak


11g_TX_CH_11_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2462 Band edge
: 2.4G Wi-Fi 11g

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2462.000	7.25	27.67	30.70	95.96	100.18	54.00	46.18	Average
2	2483.500	7.40	27.80	30.71	45.50	49.99	54.00	-4.01	Average
3	2483.840	7.40	27.80	30.71	45.04	49.53	54.00	-4.47	Average


11g_TX_CH_11_Vertical-Peak



Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2462 Band edge
: 2.4G Wi-Fi 11g

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2462.000	7.25	27.67	30.70	102.42	106.64	74.00	32.64	peak
2	2483.500	7.40	27.80	30.71	58.74	63.23	74.00	-10.77	peak
3	2484.693	7.41	27.81	30.71	64.12	68.63	74.00	-5.37	peak

11g_TX_CH_11_Vertical-Avg




Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2462 Band edge
: 2.4G Wi-Fi 11g

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2462.000	7.25	27.67	30.70	91.60	95.82	54.00	41.82	Average
2	2483.500	7.40	27.80	30.71	40.77	45.26	54.00	-8.74	Average
3	2483.790	7.40	27.80	30.71	40.40	44.89	54.00	-9.11	Average




11n_HT(20M)_TX_CH_01_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11n20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.363	6.82	27.46	30.69	67.66	71.25	74.00	-2.75	peak
2	2390.000	6.83	27.46	30.69	67.48	71.08	74.00	-2.92	peak
3 pp	2412.000	6.91	27.52	30.69	106.23	109.97	74.00	35.97	peak


11n_HT(20M)_TX_CH_01_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11n20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.847	6.83	27.46	30.69	44.05	47.65	54.00	-6.35	Average
2	2390.000	6.83	27.46	30.69	44.03	47.63	54.00	-6.37	Average
3 pp	2412.000	6.91	27.52	30.69	95.95	99.69	54.00	45.69	Average


11n_HT(20M)_TX_CH_01_Vertical-Peak



Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11n20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	6.83	27.46	30.69	61.43	65.03	74.00	-8.97	peak
2	2390.000	6.83	27.46	30.69	61.43	65.03	74.00	-8.97	peak
3 pp	2412.000	6.91	27.52	30.69	102.43	106.17	74.00	32.17	peak

11n_HT(20M)_TX_CH_01_Vertical-Avg




Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11n20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.726	6.82	27.46	30.69	39.91	43.50	54.00	-10.50	Average
2	2390.000	6.83	27.46	30.69	39.81	43.41	54.00	-10.59	Average
3 pp	2412.000	6.91	27.52	30.69	92.04	95.78	54.00	41.78	Average




11n_HT(20M)_TX_CH_11_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2462 Band edge
: 2.4G Wi-Fi 11n20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB		dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2462.000	7.25	27.67	30.70	106.07	110.29	74.00	36.29 peak
2	2483.500	7.40	27.80	30.71	68.96	73.45	74.00	-0.55 peak
3	2483.890	7.40	27.80	30.71	68.12	72.61	74.00	-1.39 peak


11n_HT(20M)_TX_CH_11_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2462 Band edge
: 2.4G Wi-Fi 11n20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB		dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2462.000	7.25	27.67	30.70	95.89	100.11	54.00	46.11 Average
2	2483.500	7.40	27.80	30.71	47.77	52.26	54.00	-1.74 Average
3	2483.940	7.40	27.80	30.71	47.41	51.90	54.00	-2.10 Average


11n_HT(20M)_TX_CH_11_Vertical-Peak



Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2462 Band edge
: 2.4G Wi-Fi 11n20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB		dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2462.000	7.25	27.67	30.70	101.72	105.94	74.00	31.94 peak
2	2483.500	7.40	27.80	30.71	63.07	67.56	74.00	-6.44 peak
3	2483.790	7.40	27.80	30.71	62.59	67.08	74.00	-6.92 peak

11n_HT(20M)_TX_CH_11_Vertical-Avg



Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2462 Band edge
: 2.4G Wi-Fi 11n20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB		dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2462.000	7.25	27.67	30.70	91.52	95.74	54.00	41.74 Average
2	2483.500	7.40	27.80	30.71	42.81	47.30	54.00	-6.70 Average
3	2483.790	7.40	27.80	30.71	42.47	46.96	54.00	-7.04 Average




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


11n_HT(40M)_TX_CH_03_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2422 Band edge
: 2.4G Wi-Fi 11n40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.677	6.82	27.46	30.69	69.34	72.93	74.00	-1.07 peak
2	2390.000	6.83	27.46	30.69	69.14	72.74	74.00	-1.26 peak
3	2422.000	6.98	27.54	30.69	102.71	106.54	74.00	32.54 peak


11n_HT(40M)_TX_CH_03_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2422 Band edge
: 2.4G Wi-Fi 11n40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.677	6.82	27.46	30.69	45.16	48.75	54.00	-5.25 Average
2	2390.000	6.83	27.46	30.69	45.54	49.14	54.00	-4.86 Average
3	2422.000	6.98	27.54	30.69	92.42	96.25	54.00	42.25 Average


11n_HT(40M)_TX_CH_03_Vertical-Peak



Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2422 Band edge
: 2.4G Wi-Fi 11n40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.526	6.82	27.46	30.69	62.74	66.33	74.00	-7.67 peak
2	2390.000	6.83	27.46	30.69	62.56	66.16	74.00	-7.84 peak
3	2422.000	6.98	27.54	30.69	98.65	102.48	74.00	28.48 peak

11n_HT(40M)_TX_CH_03_Vertical-Avg




Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2422 Band edge
: 2.4G Wi-Fi 11n40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.827	6.83	27.46	30.69	39.05	42.65	54.00	-11.35 Average
2	2390.000	6.83	27.46	30.69	38.87	42.47	54.00	-11.53 Average
3	2422.000	6.98	27.54	30.69	88.29	92.12	54.00	38.12 Average




11n_HT(40M)_TX_CH_09_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2452 Band edge
: 2.4G Wi-Fi 11n40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2452.000	7.19	27.61	30.70	102.30	106.40	74.00	32.40	peak
2	2483.500	7.40	27.80	30.71	67.58	72.07	74.00	-1.93	peak
3	2483.935	7.40	27.80	30.71	67.54	72.03	74.00	-1.97	peak


11n_HT(40M)_TX_CH_09_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2452 Band edge
: 2.4G Wi-Fi 11n40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2452.000	7.19	27.61	30.70	92.25	96.35	54.00	42.35	Average
2	2483.500	7.40	27.80	30.71	48.06	52.55	54.00	-1.45	Average
3	2483.865	7.40	27.80	30.71	48.03	52.52	54.00	-1.48	Average


11n_HT(40M)_TX_CH_09_Vertical-Peak



Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2452 Band edge
: 2.4G Wi-Fi 11n40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2452.000	7.19	27.61	30.70	97.96	102.06	74.00	28.06	peak
2	2483.500	7.40	27.80	30.71	63.59	68.08	74.00	-5.92	peak
3	2483.935	7.40	27.80	30.71	63.55	68.04	74.00	-5.96	peak

11n_HT(40M)_TX_CH_09_Vertical-Avg



Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2452 Band edge
: 2.4G Wi-Fi 11n40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2452.000	7.19	27.61	30.70	87.93	92.03	54.00	38.03	Average
2	2483.500	7.40	27.80	30.71	44.99	49.48	54.00	-4.52	Average
3	2483.935	7.40	27.80	30.71	44.85	49.34	54.00	-4.66	Average



7.3 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.4,6.5
 Measurement Distance: 3m
 Test Engineer: Kaito Zeng

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

7.3.1 E.U.T. Operation

Operating Environment:


Temperature: 23.5 °C Humidity: 46.8 % RH Atmospheric Pressure: 1020 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	04	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.
Final test	05	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data


- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.



Test Mode: 05; Polarity: Horizontal



Site : chamber

Condition: 3m HORIZONTAL


Job No. : 04228AT/04229AT

Test Mode: 05

		Ant	Cable	Preamp	Read		Limit	Over	
	Freq	Factor	Loss	Factor	Level	Level	Line	Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	36.381	18.09	0.79	27.64	33.89	25.13	40.00	-14.87	QP
2	68.391	10.70	0.97	27.62	41.32	25.37	40.00	-14.63	QP
3 q	204.955	14.54	1.72	27.78	47.14	35.62	43.50	-7.88	QP
4	240.830	17.08	1.89	27.66	46.02	37.33	46.00	-8.67	QP
5	625.078	25.06	3.18	28.03	30.03	30.24	46.00	-15.76	QP
6	721.726	26.25	3.47	27.78	29.20	31.14	46.00	-14.86	QP



Test Mode: 05; Polarity: Vertical



Site : chamber

Condition: 3m VERTICAL

Job No. : 04228AT/04229AT

Test Mode: 05

		Ant	Cable	Preamp	Read		Limit	Over	
	Freq	Factor	Loss	Factor	Level	Level	Line	Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	q	42.900	14.99	0.85	27.64	48.17	36.37	40.00	-3.63 QP
2		51.662	12.51	0.90	27.63	47.07	32.85	40.00	-7.15 QP
3		167.824	13.17	1.58	27.75	43.33	30.33	43.50	-13.17 QP
4		263.819	17.11	1.98	27.60	37.96	29.45	46.00	-16.55 QP
5		473.835	22.43	2.73	27.90	32.81	30.07	46.00	-15.93 QP
6		875.247	27.67	3.91	27.12	26.72	31.18	46.00	-14.82 QP



7.4 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.6
 Measurement Distance: 3m
 Test Engineer: Xing Guo

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

7.4.1 E.U.T. Operation

Operating Environment:


Temperature: 24.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1020 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	04	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.
Final test	05	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data


- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
- 4: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.
- 5:For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle<98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.




11b_TX_CH_01_Horizontal



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4818.016	8.92	31.97	55.42	67.12	52.59	74.00	-21.41	peak
2	7898.049	11.48	37.59	56.53	53.03	45.57	74.00	-28.43	peak
3	11044.130	14.18	39.44	55.47	48.89	47.04	74.00	-26.96	peak
4	13173.560	15.77	40.23	54.78	35.78	37.00	54.00	-17.00	Average
5	13173.560	15.77	40.23	54.78	48.69	49.91	74.00	-24.09	peak
6	16891.040	19.64	39.60	54.09	31.48	36.63	54.00	-17.37	Average
7	16891.040	19.64	39.60	54.09	44.21	49.36	74.00	-24.64	peak
8	pp17948.050	18.75	43.44	54.20	32.27	40.26	54.00	-13.74	Average
9	pk17948.050	18.75	43.44	54.20	45.10	53.09	74.00	-20.91	peak


11b_TX_CH_01_Vertical



Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4818.016	8.92	31.97	55.42	60.36	45.83	74.00	-28.17	peak
2	7898.049	11.48	37.59	56.53	52.72	45.26	74.00	-28.74	peak
3	11906.070	14.62	39.71	55.23	47.60	46.70	74.00	-27.30	peak
4	14325.370	17.03	39.75	54.37	33.97	36.38	54.00	-17.62	Average
5	14325.370	17.03	39.75	54.37	46.32	48.73	74.00	-25.27	peak
6	16891.040	19.64	39.60	54.09	32.95	38.10	54.00	-15.90	Average
7	16891.040	19.64	39.60	54.09	44.97	50.12	74.00	-23.88	peak
8	pp18000.000	18.64	43.80	54.20	31.85	40.09	54.00	-13.91	Average
9	pk18000.000	18.64	43.80	54.20	45.15	53.39	74.00	-20.61	peak


11b_TX_CH_06_Horizontal



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4874.043	8.97	32.15	55.44	61.60	47.28	74.00	-26.72	peak
2	7673.034	11.17	36.90	56.59	54.35	45.83	74.00	-28.17	peak
3	11940.540	14.52	39.74	55.22	47.82	46.86	74.00	-27.14	peak
4	14575.970	16.46	39.35	54.27	35.26	36.80	54.00	-17.20	Average
5	14575.970	16.46	39.35	54.27	48.15	49.69	74.00	-24.31	peak
6	16891.040	19.64	39.60	54.09	33.56	38.71	54.00	-15.29	Average
7	16891.040	19.64	39.60	54.09	45.62	50.77	74.00	-23.23	peak
8	pp17844.590	19.02	42.77	54.19	32.95	40.55	54.00	-13.45	Average
9	pk17844.590	19.02	42.77	54.19	44.94	52.54	74.00	-21.46	peak

11b_TX_CH_06_Vertical




Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4874.043	8.97	32.15	55.44	57.00	42.68	74.00	-31.32	peak
2	7898.049	11.48	37.59	56.53	53.80	46.34	74.00	-27.66	peak
3	11335.190	14.29	39.70	55.39	48.57	47.17	74.00	-26.83	peak
4	14242.800	16.83	39.80	54.40	35.90	38.13	54.00	-15.87	Average
5	14242.800	16.83	39.80	54.40	47.17	49.40	74.00	-24.60	peak
6	16891.040	19.64	39.60	54.09	32.84	37.99	54.00	-16.01	Average
7	16891.040	19.64	39.60	54.09	44.35	49.50	74.00	-24.50	peak
8	pp17948.050	18.75	43.44	54.20	32.97	40.96	54.00	-13.04	Average
9	pk17948.050	18.75	43.44	54.20	44.66	52.65	74.00	-21.35	peak




11b_TX_CH_11_Horizontal



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11g

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4818.016	8.92	31.97	55.42	64.89	50.36	74.00	-23.64	peak
2	7762.260	11.22	37.05	56.57	53.71	45.41	74.00	-28.59	peak
3	11302.480	14.39	39.70	55.40	48.28	46.97	74.00	-27.03	peak
4	12984.540	15.26	40.32	54.84	36.73	37.47	54.00	-16.53	Average
5	12984.540	15.26	40.32	54.84	48.27	49.01	74.00	-24.99	peak
6	16891.040	19.64	39.60	54.09	32.23	37.38	54.00	-16.62	Average
7	16891.040	19.64	39.60	54.09	44.42	49.57	74.00	-24.43	peak
8	pp17896.250	18.87	43.08	54.19	33.72	41.48	54.00	-12.52	Average
9	pk17896.250	18.87	43.08	54.19	45.55	53.31	74.00	-20.69	peak


11b_TX_CH_11_Vertical



Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4916.490	9.02	32.20	55.46	61.35	47.11	74.00	-26.89	peak
2	7739.857	11.22	36.98	56.57	53.96	45.59	74.00	-28.41	peak
3	11667.600	14.42	39.53	55.29	48.29	46.95	74.00	-27.05	peak
4	13997.930	16.53	39.90	54.50	34.48	36.41	54.00	-17.59	Average
5	13997.930	16.53	39.90	54.50	47.13	49.06	74.00	-24.94	peak
6	16891.040	19.64	39.60	54.09	32.17	37.32	54.00	-16.68	Average
7	16891.040	19.64	39.60	54.09	44.49	49.64	74.00	-24.36	peak
8	pp18000.000	18.64	43.80	54.20	31.23	39.47	54.00	-14.53	Average
9	pk18000.000	18.64	43.80	54.20	43.78	52.02	74.00	-21.98	peak


11g_TX_CH_01_Horizontal



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11g

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4818.016	8.92	31.97	55.42	64.89	50.36	74.00	-23.64	peak
2	7762.260	11.22	37.05	56.57	53.71	45.41	74.00	-28.59	peak
3	11302.480	14.39	39.70	55.40	48.28	46.97	74.00	-27.03	peak
4	12984.540	15.26	40.32	54.84	36.73	37.47	54.00	-16.53	Average
5	12984.540	15.26	40.32	54.84	48.27	49.01	74.00	-24.99	peak
6	16891.040	19.64	39.60	54.09	32.23	37.38	54.00	-16.62	Average
7	16891.040	19.64	39.60	54.09	44.42	49.57	74.00	-24.43	peak
8	pp17896.250	18.87	43.08	54.19	33.72	41.48	54.00	-12.52	Average
9	pk17896.250	18.87	43.08	54.19	45.55	53.31	74.00	-20.69	peak

11g_TX_CH_01_Vertical




Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11g

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4831.962	8.93	32.03	55.42	58.01	43.55	74.00	-30.45	peak
2	7966.832	11.47	37.73	56.51	52.73	45.42	74.00	-28.58	peak
3	11237.330	14.30	39.64	55.42	48.24	46.76	74.00	-27.24	peak
4	13249.930	15.91	40.25	54.75	35.54	36.95	54.00	-17.05	Average
5	13249.930	15.91	40.25	54.75	47.51	48.92	74.00	-25.08	peak
6	16842.290	18.46	39.60	54.09	33.03	37.00	54.00	-17.00	Average
7	16842.290	18.46	39.60	54.09	46.03	50.00	74.00	-24.00	peak
8	pp18000.000	18.64	43.80	54.20	33.38	41.62	54.00	-12.38	Average
9	pk18000.000	18.64	43.80	54.20	44.52	52.76	74.00	-21.24	peak




11g_TX_CH_06_Horizontal



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11g

	Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB		dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4874.043	8.97	32.15	55.44	66.29	51.97	74.00	-22.03	peak	
2	7966.832	11.47	37.73	56.51	53.27	45.96	74.00	-28.04	peak	
3	11906.070	14.62	39.71	55.23	48.10	47.20	74.00	-26.80	peak	
4	14284.030	17.00	39.80	54.38	33.60	36.02	54.00	-17.98	Average	
5	14284.030	17.00	39.80	54.38	46.89	49.31	74.00	-24.69	peak	
6	16891.040	19.64	39.60	54.09	33.23	38.38	54.00	-15.62	Average	
7	16891.040	19.64	39.60	54.09	45.03	50.18	74.00	-23.82	peak	
8	pp18000.000	18.64	43.80	54.20	32.06	40.30	54.00	-13.70	Average	
9	pk18000.000	18.64	43.80	54.20	45.07	53.31	74.00	-20.69	peak	


11g_TX_CH_06_Vertical



Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11g

	Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB		dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4874.043	8.97	32.15	55.44	60.28	45.96	74.00	-28.04	peak	
2	7966.832	11.47	37.73	56.51	52.70	45.39	74.00	-28.61	peak	
3	11335.190	14.29	39.70	55.39	48.32	46.92	74.00	-27.08	peak	
4	14533.910	16.36	39.43	54.28	34.55	36.06	54.00	-17.94	Average	
5	14533.910	16.36	39.43	54.28	47.80	49.31	74.00	-24.69	peak	
6	16939.940	19.22	39.64	54.10	33.54	38.30	54.00	-15.70	Average	
7	16939.940	19.22	39.64	54.10	44.98	49.74	74.00	-24.26	peak	
8	pp17948.050	18.75	43.44	54.20	31.50	39.49	54.00	-14.51	Average	
9	pk17948.050	18.75	43.44	54.20	44.63	52.62	74.00	-21.38	peak	


11g_TX_CH_11_Horizontal



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11g

	Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB		dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pk 4916.490	9.02	32.20	55.46	67.36	53.12	74.00	-20.88	peak	
2	7920.911	11.48	37.64	56.52	52.83	45.43	74.00	-28.57	peak	
3	11667.600	14.42	39.53	55.29	48.38	47.04	74.00	-26.96	peak	
4	14242.800	16.83	39.80	54.40	33.92	36.15	54.00	-17.85	Average	
5	14242.800	16.83	39.80	54.40	46.84	49.07	74.00	-24.93	peak	
6	16891.040	19.64	39.60	54.09	31.89	37.04	54.00	-16.96	Average	
7	16891.040	19.64	39.60	54.09	44.36	49.51	74.00	-24.49	peak	
8	pp18000.000	18.64	43.80	54.20	33.94	42.18	54.00	-11.82	Average	
9	18000.000	18.64	43.80	54.20	44.65	52.89	74.00	-21.11	peak	

11g_TX_CH_11_Vertical




Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11g

	Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB		dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4916.490	9.02	32.20	55.46	63.33	49.09	74.00	-24.91	peak	
2	7784.729	11.21	37.14	56.56	54.04	45.83	74.00	-28.17	peak	
3	8866.062	12.30	38.53	56.18	52.16	46.81	74.00	-27.19	peak	
4	13249.930	15.91	40.25	54.75	34.33	35.74	54.00	-18.26	Average	
5	13249.930	15.91	40.25	54.75	47.63	49.04	74.00	-24.96	peak	
6	16891.040	19.64	39.60	54.09	34.25	39.40	54.00	-14.60	Average	
7	16891.040	19.64	39.60	54.09	45.62	50.77	74.00	-23.23	peak	
8	pp17896.250	18.87	43.08	54.19	33.77	41.53	54.00	-12.47	Average	
9	pk17896.250	18.87	43.08	54.19	45.07	52.83	74.00	-21.17	peak	




11n_20M_TX_CH_01_Horizontal



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11n20

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4818.016	8.92	31.97	55.42	61.71	47.18	74.00	-26.82	peak
2	7966.832	11.47	37.73	56.51	53.12	45.81	74.00	-28.19	peak
3	8489.882	12.08	38.32	56.31	52.61	46.70	74.00	-27.30	peak
4	13326.750	15.92	40.30	54.72	37.05	38.55	54.00	-15.45	Average
5	13326.750	15.92	40.30	54.72	47.78	49.28	74.00	-24.72	peak
6	16891.040	19.64	39.60	54.09	32.65	37.80	54.00	-16.20	Average
7	16891.040	19.64	39.60	54.09	44.43	49.58	74.00	-24.42	peak
8	pp17896.250	18.87	43.08	54.19	33.70	41.46	54.00	-12.54	Average
9	pk17896.250	18.87	43.08	54.19	45.00	52.76	74.00	-21.24	peak


11n_20M_TX_CH_01_Vertical



Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11n20

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4818.016	8.92	31.97	55.42	57.61	43.08	74.00	-30.92	peak
2	7966.262	11.23	37.23	56.55	53.98	45.89	74.00	-28.11	peak
3	11940.540	14.52	39.74	55.22	48.25	47.29	74.00	-26.71	peak
4	13365.320	15.79	40.30	54.71	35.13	36.51	54.00	-17.49	Average
5	13365.320	15.79	40.30	54.71	47.99	49.37	74.00	-24.63	peak
6	16891.040	19.64	39.60	54.09	31.98	37.13	54.00	-16.87	Average
7	16891.040	19.64	39.60	54.09	44.61	49.76	74.00	-24.24	peak
8	pp18000.000	18.64	43.80	54.20	32.01	40.25	54.00	-13.75	Average
9	pk18000.000	18.64	43.80	54.20	44.82	53.06	74.00	-20.94	peak


11n_20M_TX_CH_06_Horizontal



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11n20

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4874.043	8.97	32.15	55.44	65.67	51.35	74.00	-22.65	peak
2	7943.838	11.48	37.69	56.52	52.52	45.17	74.00	-28.83	peak
3	11871.710	14.63	39.67	55.24	47.86	46.92	74.00	-27.08	peak
4	14038.450	16.47	39.90	54.48	37.26	39.15	54.00	-14.85	Average
5	14038.450	16.47	39.90	54.48	48.27	50.16	74.00	-23.84	peak
6	16891.040	19.64	39.60	54.09	31.31	36.46	54.00	-17.54	Average
7	16891.040	19.64	39.60	54.09	44.44	49.59	74.00	-24.41	peak
8	pp17896.250	18.87	43.08	54.19	31.50	39.26	54.00	-14.74	Average
9	pk17896.250	18.87	43.08	54.19	44.91	52.67	74.00	-21.33	peak

11n_20M_TX_CH_06_Vertical




Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11n20

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4859.975	8.96	32.12	55.44	58.66	44.30	74.00	-29.70	peak
2	7920.911	11.48	37.64	56.52	53.06	45.66	74.00	-28.34	peak
3	11906.070	14.62	39.71	55.23	47.73	46.83	74.00	-27.17	peak
4	14408.430	16.90	39.59	54.33	34.97	37.13	54.00	-16.87	Average
5	14408.430	16.90	39.59	54.33	46.93	49.09	74.00	-24.91	peak
6	16793.680	17.45	39.59	54.08	33.68	36.64	54.00	-17.36	Average
7	16793.680	17.45	39.59	54.08	47.15	50.11	74.00	-23.89	peak
8	pp17896.250	18.87	43.08	54.19	34.53	42.29	54.00	-11.71	Average
9	pk17896.250	18.87	43.08	54.19	45.15	52.91	74.00	-21.09	peak




11n_20M_TX_CH_11_Horizontal



Condition: 3m HORIZONTAL
Job No : 04228AT/04229AT
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11n20

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pk 4916.490	9.02	32.20	55.46	67.71	53.47	74.00	-20.53	peak
2 7966.832	11.47	37.73	56.51	53.51	46.20	74.00	-27.80	peak
3 11076.100	14.14	39.48	55.46	48.86	47.02	74.00	-26.98	peak
4 13326.750	15.92	40.30	54.72	34.78	36.28	54.00	-17.72	Average
5 13326.750	15.92	40.30	54.72	48.18	49.68	74.00	-24.32	peak
6 16891.040	19.64	39.60	54.09	32.35	37.50	54.00	-16.50	Average
7 16891.040	19.64	39.60	54.09	44.59	49.74	74.00	-24.26	peak
8 pp17896.250	18.87	43.08	54.19	32.27	40.03	54.00	-13.97	Average
9 17896.250	18.87	43.08	54.19	44.84	52.60	74.00	-21.40	peak

11n_20M_TX_CH_11_Vertical



Condition: 3m VERTICAL
Job No : 04228AT/04229AT
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11n20

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 4916.490	9.02	32.20	55.46	61.55	47.31	74.00	-26.69	peak
2 7966.832	11.47	37.73	56.51	52.85	45.54	74.00	-28.46	peak
3 11044.130	14.18	39.44	55.47	49.22	47.37	74.00	-26.63	Peak
4 14618.170	16.62	39.28	54.25	35.58	37.23	54.00	-16.77	Average
5 14618.170	16.62	39.28	54.25	46.96	48.61	74.00	-25.39	peak
6 16891.040	19.64	39.60	54.09	31.29	36.44	54.00	-17.56	Average
7 16891.040	19.64	39.60	54.09	44.48	49.63	74.00	-24.37	peak
8 pp17948.050	18.75	43.44	54.20	31.63	39.62	54.00	-14.38	Average
9 pk17948.050	18.75	43.44	54.20	44.64	52.63	74.00	-21.37	peak



7.5 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)
 Test Method: ANSI C63.10 (2020) Section 11.9.2
 Test Engineer: Byron Liang

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.5.1 E.U.T. Operation

Operating Environment:


Temperature: 21.8 °C Humidity: 59.3 % RH Atmospheric Pressure: 1020 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details



7.6 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)
 Test Method: ANSI C63.10 (2020) Section 11.8.1
 Test Engineer: Byron Liang

Limit:
 ≥500 kHz


7.6.1 E.U.T. Operation

Operating Environment:
 Temperature: 21.8 °C Humidity: 59.3 % RH Atmospheric Pressure: 1020 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

Please Refer to Appendix for Details



7.7 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)
 Test Method: ANSI C63.10 (2020) Section 11.10.2
 Test Engineer: Byron Liang

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.7.1 E.U.T. Operation


Operating Environment:

Temperature: 21.8 °C Humidity: 59.3 % RH Atmospheric Pressure: 1020 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
 Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.8 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
 Test Method: ANSI C63.10 (2020) Section 6.10.4
 Test Engineer: Byron Liang

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.1 E.U.T. Operation

Operating Environment:


Temperature: 21.8 °C Humidity: 59.3 % RH Atmospheric Pressure: 1020 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data

Please Refer to Appendix for Details



7.9 Conducted Spurious Emissions

Test Requirement: 47 CFR Part 15, Subpart C 15.247(d)
 Test Method: ANSI C63.10 (2020) Section 11.11
 Test Engineer: Byron Liang

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.9.1 E.U.T. Operation

Operating Environment:


Temperature: 21.8 °C Humidity: 59.3 % RH Atmospheric Pressure: 1020 mbar

7.9.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



7.9.3 Test Setup Diagram



7.9.4 Measurement Procedure and Data

Please Refer to Appendix for Details



8 Test Setup Photo

Refer to Appendix - Test Setup Photo for SZCR2509004228AT

9 EUT Constructional Details (EUT Photos)

Refer to External and Internal Photos for SZCR2509004228AT



10 Appendix

1. Duty Cycle


1.1 Test Result

1.1.1 Ant1

Ant1							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11b	SISO	2412	8.193	8.210	99.79	0.01	0.04
		2437	8.190	8.206	99.81	0.01	0.04
		2462	8.193	8.210	99.79	0.01	0.04
802.11g	SISO	2412	1.361	1.413	96.32	0.16	0.06
		2437	1.361	1.413	96.32	0.16	0.03
		2462	1.361	1.412	96.39	0.16	0.03
802.11n (HT20)	SISO	2412	1.273	1.325	96.08	0.17	0.07
		2437	1.273	1.324	96.15	0.17	0.04
		2462	1.273	1.324	96.15	0.17	0.04
802.11n (HT40)	SISO	2422	0.633	0.684	92.54	0.34	0.04
		2437	0.632	0.684	92.40	0.34	0.03
		2452	0.633	0.684	92.54	0.34	0.03

1.2 Test Graph


1.2.1 Ant1




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV



802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV



802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV



2. Bandwidth

2.1 Test Result

2.1.1 OBW

Mode	TX Type	Frequency (MHz)	ANT	99% Occupied Bandwidth (MHz)		Verdict
				Result	Limit	
802.11b	SISO	2412	1	13.973	/	Pass
		2437	1	13.976	/	Pass
		2462	1	13.981	/	Pass
802.11g	SISO	2412	1	17.364	/	Pass
		2437	1	17.321	/	Pass
		2462	1	17.330	/	Pass
802.11n (HT20)	SISO	2412	1	18.427	/	Pass
		2437	1	18.398	/	Pass
		2462	1	18.416	/	Pass
802.11n (HT40)	SISO	2422	1	36.004	/	Pass
		2437	1	35.995	/	Pass
		2452	1	35.990	/	Pass


2.1.2 6dB BW

Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
802.11b	SISO	2412	1	10.162	≥ 0.5	Pass
		2437	1	10.169	≥ 0.5	Pass
		2462	1	10.171	≥ 0.5	Pass
802.11g	SISO	2412	1	16.426	≥ 0.5	Pass
		2437	1	16.383	≥ 0.5	Pass
		2462	1	16.338	≥ 0.5	Pass
802.11n (HT20)	SISO	2412	1	17.737	≥ 0.5	Pass
		2437	1	17.748	≥ 0.5	Pass
		2462	1	17.722	≥ 0.5	Pass
802.11n (HT40)	SISO	2422	1	36.031	≥ 0.5	Pass
		2437	1	35.997	≥ 0.5	Pass
		2452	1	35.954	≥ 0.5	Pass




2.2 Test Graph


2.2.1 OBW




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV




2.2.2 6dB BW




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV



802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV



802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR250900422803

Page: 69 of 93

3. Maximum Conducted Output Power

3.1 Test Result

3.1.1 Power

Mode	TX Type	Frequency (MHz)	Maximum Average Conducted Output Power (dBm)		Verdict
			ANT1	Limit	
802.11b	SISO	2412	15.75	<=30	Pass
		2437	15.73	<=30	Pass
		2462	15.07	<=30	Pass
802.11g	SISO	2412	13.96	<=30	Pass
		2437	14.38	<=30	Pass
		2462	13.73	<=30	Pass
802.11n (HT20)	SISO	2412	13.81	<=30	Pass
		2437	14.24	<=30	Pass
		2462	13.60	<=30	Pass
802.11n (HT40)	SISO	2422	13.82	<=30	Pass
		2437	14.07	<=30	Pass
		2452	13.43	<=30	Pass

Note1: Antenna Gain: Ant1: 2.90dBi;



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4. Maximum Power Spectral Density

4.1 Test Result


4.1.1 PSD

Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm)		Verdict
			ANT1	Limit	
802.11b	SISO	2412	-1.74	<=8	Pass
		2437	-1.77	<=8	Pass
		2462	-2.21	<=8	Pass
802.11g	SISO	2412	-6.00	<=8	Pass
		2437	-5.65	<=8	Pass
		2462	-6.33	<=8	Pass
802.11n (HT20)	SISO	2412	-6.25	<=8	Pass
		2437	-5.91	<=8	Pass
		2462	-6.24	<=8	Pass
802.11n (HT40)	SISO	2422	-9.04	<=8	Pass
		2437	-8.46	<=8	Pass
		2452	-8.61	<=8	Pass


Note1: Antenna Gain: Ant1: 2.90dBi;

4.2 Test Graph


4.2.1 PSD




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV



802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV



802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV



5. Unwanted Emissions In Non-restricted Frequency Bands

5.1 Test Result

5.1.1 Ref


Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)
802.11b	SISO	2412	1	6.71
		2437	1	6.65
		2462	1	6.01
802.11g	SISO	2412	1	3.03
		2437	1	3.39
		2462	1	2.63
802.11n (HT20)	SISO	2412	1	2.90
		2437	1	3.33
		2462	1	2.12
802.11n (HT40)	SISO	2422	1	-0.12
		2437	1	0.13
		2452	1	-0.45

5.1.2 CSE


Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
802.11b	SISO	2412	1	6.71	-23.29	Pass
		2437	1	6.71	-23.29	Pass
		2462	1	6.71	-23.29	Pass
802.11g	SISO	2412	1	3.39	-26.61	Pass
		2437	1	3.39	-26.61	Pass
		2462	1	3.39	-26.61	Pass
802.11n (HT20)	SISO	2412	1	3.33	-26.67	Pass
		2437	1	3.33	-26.67	Pass
		2462	1	3.33	-26.67	Pass
802.11n (HT40)	SISO	2422	1	0.13	-29.87	Pass
		2437	1	0.13	-29.87	Pass
		2452	1	0.13	-29.87	Pass

5.2 Test Graph


5.2.1 Ref




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV




5.2.2 CSE




802.11b_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV



802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV



802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV



802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV

