TEST REPORT

Applicant Name:	JINGSHAN JINGYANG ELECTRONICS CO., LTD
Address:	Group 1, Sanyang Village, Sanyang Town, Jingshan City, Jingmen City, Hubei Province, China
Report Number:	2401U24989E-RF-00
FCC ID:	2BFYM-TWS108

Test Standard (s)

FCC PART 15.247

Sample Description

Product Type:	TRUE WIRELESS EARBUDS
Model No.:	PATW-1034-SV
Multiple Model(s) No.:	TWS108, PATW-1034-PK, PATW-1034-PR, PATW-1034-BL
Trade Mark:	Prime Audio
Date Received:	2024/07/01
Issue Date:	2024/07/31

Test Result:	Pass▲

▲ In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Jojo Guo
RF Engineer

Approved By:

Michelle Zeng
RF Supervisor

Note: The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.
This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.
This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.
This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY **4**

GENERAL INFORMATION **5**
- PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 5
- OBJECTIVE 5
- TEST METHODOLOGY 5
- MEASUREMENT UNCERTAINTY 6
- TEST FACILITY 6

SYSTEM TEST CONFIGURATION **7**
- DESCRIPTION OF TEST CONFIGURATION 7
- EUT EXERCISE SOFTWARE 7
- SPECIAL ACCESSORIES 7
- EQUIPMENT MODIFICATIONS 7
- SUPPORT EQUIPMENT LIST AND DETAILS 7
- EXTERNAL I/O CABLE 8
- BLOCK DIAGRAM OF TEST SETUP 8

SUMMARY OF TEST RESULTS **9**

TEST EQUIPMENT LIST **10**

FCC§15.247 (I), §1.1307 (B) (1) & §2.1093 - RF EXPOSURE **11**
- APPLICABLE STANDARD 11
- MEASUREMENT RESULT 11

FCC §15.203 - ANTENNA REQUIREMENT **12**
- APPLICABLE STANDARD 12
- ANTENNA CONNECTOR CONSTRUCTION 12

FCC §15.205, §15.209 & §15.247(D) - RADIATED EMISSIONS **13**
- APPLICABLE STANDARD 13
- EUT SETUP 13
- EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP 14
- TEST PROCEDURE 15
- FACTOR & OVER LIMIT/MARGIN CALCULATION 15
- TEST DATA 15

FCC §15.247(A) (1) - CHANNEL SEPARATION TEST **30**
- APPLICABLE STANDARD 30
- TEST PROCEDURE 30
- TEST DATA 30

FCC §15.247(A) (1) - 20 DB EMISSION BANDWIDTH **31**
- APPLICABLE STANDARD 31
- TEST PROCEDURE 31
- TEST DATA 32

FCC §15.247(A) (1) (III) - QUANTITY OF HOPPING CHANNEL TEST **33**
- APPLICABLE STANDARD 33
- TEST PROCEDURE 33
- TEST DATA 33

FCC §15.247(A) (1) (III) - TIME OF OCCUPANCY (DWELL TIME)....34
APPLICABLE STANDARD 34
TEST PROCEDURE 34
TEST DATA 35
FCC §15.247(B) (1) - PEAK OUTPUT POWER MEASUREMENT 36
APPLICABLE STANDARD 36
TEST PROCEDURE 36
TEST DATA 36
FCC §15.247(D) § 5.5 - BAND EDGES TESTING....37
APPLICABLE STANDARD 37
TEST PROCEDURE 37
TEST DATA 38
EUT PHOTOGRAPHS....39
TEST SETUP PHOTOGRAPHS 40
APPENDIX 41
APPENDIX A: 20DB EMISSION BANDWIDTH....41
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH 47
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER 53
APPENDIX D: CARRIER FREQUENCY SEPARATION 58
APPENDIX E: TIME OF OCCUPANCY....61
APPENDIX F: NUMBER OF HOPPING CHANNELS 71
APPENDIX G: BAND EDGE MEASUREMENTS 74

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	2401U24989E-RF-00	Original Report	2024/07/31

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	TRUE WIRELESS EARBUDS
Tested Model	PATW-1034-SV
Multiple Model(s)	TWS108, PATW-1034-PK, PATW-1034-PR, PATW-1034-BL
UPC Number	195207097257, 195207097264, 195207097271, 195207097288, 195207097240
SKU Number	9155769
Frequency Range	Bluetooth: 2402~2480MHz
Transmit Peak Power	0.8 dBm
Modulation Technique	Bluetooth: GFSK, π/4-DQPSK, 8DPSK
Antenna Specification#	2.499dBi (provided by the applicant)
Voltage Range	DC 3.7V from battery
Sample serial number	2NS8-1 for Radiated Emissions Test 2NS8-2 for RF Conducted Test (Assigned by BACL, Shenzhen)
Sample/EUT Status	Good condition
Adapter Information	N/A
Note 1: The multiple models are electrically identical with the test model except for model number and color. Please refer to the declaration letter# for more detail, which was provided by manufacturer. Note 2: The left earbuds and the right earbuds are electrically identical in RF schematics, the left earbuds was selected for test.	

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF output power, conducted		0.72 dB(k=2, 95% level of confidence)
AC Power Lines Conducted Emissions	9kHz-150kHz	3.94dB(k=2, 95% level of confidence)
	150kHz-30MHz	3.84dB(k=2, 95% level of confidence)
Radiated Emissions	9kHz - 30MHz	3.30dB(k=2, 95% level of confidence)
	30MHz~200MHz (Horizontal)	4.48dB(k=2, 95% level of confidence)
	30MHz~200MHz (Vertical)	4.55dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Horizontal)	4.85dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Vertical)	5.05dB(k=2, 95% level of confidence)
	1GHz - 6GHz	5.35dB(k=2, 95% level of confidence)
	6GHz - 18GHz	5.44dB(k=2, 95% level of confidence)
	18GHz - 40GHz	5.16dB(k=2, 95% level of confidence)
Temperature		±1℃
Humidity		±1%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2403	41	2443
2	2404	42	2444
…	…	…	…
…	…	…	…
36	2438	75	2477
37	2439	76	2478
38	2440	77	2479
39	2441	78	2480

EUT was tested with Channel 0, 39 and 78.

EUT Exercise Software

"BT-TOOL V1.1.2"# exercise software was used and the power level is 3#. The software and power level was provided by the applicant.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Length (m)	From Port	To
/	/	/	/

Block Diagram of Test Setup

For Radiated Emissions below 1GHz:



For Radiated Emissions above 1GHz:



SUMMARY OF TEST RESULTS

Rules	Description of Test	Result
FCC 15.247 (i), §1.1307 (b) (1) & §2.1093	RF Exposure	Compliant
FCC §15.203	Antenna Requirement	Compliant
FCC §15.207(a)	AC Line Conducted Emissions	Not Applicable
FCC §15.205, §15.209, §15.247(d)	Radiated Emissions	Compliant
FCC §15.247(a)(1)	20 dB Emission Bandwidth	Compliant
FCC §15.247(a)(1)	Channel Separation Test	Compliant
FCC §15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
FCC §15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
FCC §15.247(b)(1)	Peak Output Power Measurement	Compliant
FCC §15.247(d)	Band edges	Compliant

Not Applicable: The EUT is powered by battery.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test					
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2026/07/19
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2024/01/16	2025/01/15
BACL	Active Loop Antenna	1313-1A	4031911	2024/05/14	2027/05/13
Unknown	Cable	XH500C	J-10M-A	2024/06/18	2025/06/17
Unknown	Cable	Chamber Cable 1	F-03-EM236	2024/06/18	2025/06/17
Audix	EMI Test software	E3	19821b(V9)	NCR	NCR
Rohde&Schwarz	Spectrum Analyzer	FSV40	101605	2024/03/27	2025/03/26
COM-POWER	Pre-amplifier	PA-122	181919	2024/06/18	2025/06/17
Schwarzbeck	Horn Antenna	BBHA9120D(1201)	1143	2023/07/26	2026/07/25
Unknown	RF Cable	KMSE	0735	2024/06/18	2025/06/17
Unknown	RF Cable	UFA147	219661	2024/06/18	2025/06/17
Unknown	RF Cable	XH750A-N	J-10M	2024/06/18	2025/06/17
SNSD	2.4G Band Reject filter	BSF2402-2480MN-0898-001	2.4G filter	2024/06/27	2025/06/26
A.H.System	Pre-amplifier	PAM-1840VH	190	2024/06/18	2025/06/17
Electro-Mechanics Co	Horn Antenna	3116	9510-2270	2023/09/18	2026/09/17
RF Conducted Test					
MARCONI	10dB Attenuator	6534/3	2942	2024/06/27	2025/06/26
Rohde & Schwarz	Spectrum Analyzer	FSV40	101473	2024/01/16	2025/01/15
Tonscend	RF control Unit	JS0806-2	19D8060154	2023/09/06	2024/09/05

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 - RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] · [√f(GHz)] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where
1. f(GHz) is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Measurement Result

For worst case:

Mode	Frequency (MHz)	Max tune-up conducted power# (dBm)	Max tune-up conducted power# (mW)	Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
BT	2402-2480	1	1.26	5	0.4	3	Yes

Result: Compliant

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

Antenna Connector Construction

The EUT has a PCB antenna arrangement, which was permanently attached, the antenna gain# is 2.499dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliant

FCC §15.205, §15.209 & §15.247(d) - RADIATED EMISSIONS

Applicable Standard

FCC §15.205; §15.209; §15.247(d)

EUT Setup

9 kHz-30MHz:



30MHz-1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	/	/	200 Hz	QP
	300 Hz	1 kHz	/	PK
150 kHz – 30 MHz	/	/	9 kHz	QP
	10 kHz	30 kHz	/	PK
30 MHz – 1000 MHz	/	/	120 kHz	QP
	100 kHz	300 kHz	/	PK
Above 1 GHz	Harmonics & Band Edge			
	1MHz	3 MHz	/	PK
	Average Emission Level=Peak Emission Level+20*log(Duty cycle)			
	Other Emissions			
	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Average

For Duty cycle measurement:

Use the duty cycle factor correction factor method per 15.35(c).
Duty cycle=On time/100milliseconds, On time=N1*L1+N2*L2+…Nn-1*Ln-1+Nn*Ln,
Where N1 is number of type 1 pulses, L1 is length of type 1 pulse, etc.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

All emissions under the average limit and under the noise floor have not recorded in the report.

Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

Factor = Antenna Factor + Cable Loss - Amplifier Gain

The "**Over Limit/Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

Over Limit/Margin = Level/Corrected Amplitude – Limit
Level / Corrected Amplitude = Read Level + Factor

Test Data

Environmental Conditions

Temperature:	22-25.6 °C
Relative Humidity:	50-54%
ATM Pressure:	101 kPa

The testing was performed by Shy Jiang on 2024-07-16 for below 1GHz and Sadow Tan from 2024-07-17 to 2024-07-18 for above 1GHz.

Test mode: Transmitting

Note: After pre-scan in the X, Y and Z axes of orientation, the worst case Z-axis of orientation were recorded.

9 kHz-30MHz: *(Maximum output power mode, EDR Mode (8DPSK) Low channel)*

The amplitude of spurious emissions attenuated more than 20 dB below the limit was not recorded.

30MHz-1GHz: *(Maximum output power mode, EDR Mode (8DPSK) Low channel)*

Horizontal



Site : Chamber A
Condition : 3m Horizontal
Project Number: 2401U24989E-RF
Test Mode : BT
Tester : Shy Jiang

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	40.05	-11.55	24.26	12.71	40.00	-27.29	QP
2	99.35	-15.60	25.27	9.67	43.50	-33.83	QP
3	119.86	-12.38	25.97	13.59	43.50	-29.91	QP
4	385.79	-10.99	25.10	14.11	46.00	-31.89	QP
5	659.41	-6.62	26.49	19.87	46.00	-26.13	QP
6	769.09	-5.46	29.35	23.89	46.00	-22.11	QP

Vertical



Site : Chamber A
Condition : 3m Vertical
Project Number: 2401U24989E-RF
Test Mode : BT
Tester : Shy Jiang

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	40.35	-13.21	23.75	10.54	40.00	-29.46	QP
2	98.66	-17.20	24.81	7.61	43.50	-35.89	QP
3	115.37	-13.46	26.66	13.20	43.50	-30.30	QP
4	398.33	-10.84	26.05	15.21	46.00	-30.79	QP
5	685.95	-6.72	25.95	19.23	46.00	-26.77	QP
6	896.21	-4.85	27.58	22.73	46.00	-23.27	QP

Above 1GHz (Maximum output power mode):

Frequency (MHz)	Receiver		Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
	Reading (dBµV)	PK/AV					
8DPSK							
Low Channel 2402MHz							
2354.52	56.11	PK	H	-2.93	53.18	74	-20.82
2384.5	55.74	PK	V	-2.93	52.81	74	-21.19
4804	62.71	PK	H	1.69	64.4	74	-9.6
4804	56.65	PK	V	1.69	58.34	74	-15.66
Middle Channel 2441MHz							
4882	61.65	PK	H	1.69	63.34	74	-10.66
4882	56.22	PK	V	1.69	57.91	74	-16.09
High Channel 2480MHz							
2483.54	58.91	PK	H	-3.17	55.74	74	-18.26
2488.75	55.51	PK	V	-3.18	52.33	74	-21.67
4960	60.25	PK	H	2.77	63.02	74	-10.98
4960	54.36	PK	V	2.77	57.13	74	-16.87

Note:
Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
Corrected Amplitude/Level = Factor + Reading
Margin = Corrected Amplitude/Level - Limit
The other spurious emission which is in the noise floor level was not recorded.

Field Strength of Average							
Frequency (MHz)	**Peak Measurement @3m (dBµV/m)**	**Polar (H/V)**	**Duty Cycle Corrected Factor (dB)**	**Average Level (dBµV/m)**	**Limit (dBµV/m)**	**Margin (dB)**	**Comment**
Low Channel 2402MHz							
2354.52	53.18	H	-24.73	28.45	54	-25.55	Bandedge
2384.5	52.81	V	-24.73	28.08	54	-25.92	Bandedge
4804	64.4	H	-24.73	39.67	54	-14.33	Harmonic
4804	58.34	V	-24.73	33.61	54	-20.39	Harmonic
Middle Channel 2441MHz							
4882	63.34	H	-24.73	38.61	54	-15.39	Harmonic
4882	57.91	V	-24.73	33.18	54	-20.82	Harmonic
High Channel 2480MHz							
2483.54	55.74	H	-24.73	31.01	54	-22.99	Bandedge
2488.75	52.33	V	-24.73	27.6	54	-26.4	Bandedge
4960	63.02	H	-24.73	38.29	54	-15.71	Harmonic
4960	57.13	V	-24.73	32.4	54	-21.6	Harmonic

Note: Average level= Peak level+ Duty Cycle Corrected Factor
Margin = Average level - Limit

Worst case duty cycle:
Duty cycle = Ton/100ms = 2.899*2/100=0.05798
Duty Cycle Corrected Factor = 20lg (Duty cycle) = 20lg0.05798 = -24.73

Duty Cycle (100ms)	
Duty Cycle (1s)	

Test plots for example as below:

Band Edge Measurements (Radiated):

8DPSK			
Test Channel:	**2480MHz**	**Ant. Polar. :**	**Horizontal**



Condition : Horizontal
Project No.: 2401U24989E-RF
Tester : Sadow Tan
Note : BT_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2483.541	-3.17	58.91	55.74	74.00	-18.26	peak

8DPSK			
Test Channel:	**2480MHz**	**Ant. Polar. :**	**Vertical**



Condition : Vertical
Project No.: 2401U24989E-RF
Tester : Sadow Tan
Note : BT_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	2488.750	-3.18	55.51	52.33	74.00	-21.67	peak

Harmonic Measurements:

Horizontal

1-4GHz



Condition : Horizontal
Project No.: 2401U24989E-RF
Tester : Sadow Tan
Note : BT_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3892.000	-0.56	35.11	34.55	54.00	-19.45	Average
2	3892.000	-0.56	49.94	49.38	74.00	-24.62	Peak

Vertical

1-4GHz



Condition : Vertical
Project No.: 2401U24989E-RF
Tester : Sadow Tan
Note : BT_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	3926.125	-0.33	33.53	33.20	54.00	-20.80	Average
2	3926.125	-0.33	48.73	48.40	74.00	-25.60	Peak

Horizontal

4-18GHz



Condition : Horizontal
Project No.: 2401U24989E-RF
Tester : Sadow Tan
Note : BT_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4960.000	2.77	60.25	63.02	74.00	-10.98	Peak
2	17998.250	24.61	22.67	47.28	54.00	-6.72	Average
3	17998.250	24.61	37.33	61.94	74.00	-12.06	Peak

Vertical

4-18GHz



Condition : Vertical
Project No.: 2401U24989E-RF
Tester : Sadow Tan
Note : BT_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	4960.000	2.77	54.36	57.13	74.00	-16.87	Peak
2	17994.750	24.58	22.41	46.99	54.00	-7.01	Average
3	17994.750	24.58	37.31	61.89	74.00	-12.11	Peak

Horizontal

18-25GHz



Condition : Horizontal
Project No.: 2401U24989E-RF
Tester : Sadow Tan
Note : BT_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	24307.880	18.54	41.35	59.89	74.00	-14.11	Peak
2	24307.880	18.54	26.31	44.85	54.00	-9.15	Average

Vertical

18-25GHz



Condition : Vertical
Project No.: 2401U24989E-RF
Tester : Sadow Tan
Note : BT_2480

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	23374.250	17.40	26.11	43.51	54.00	-10.49	Average
2	23374.250	17.40	41.90	59.30	74.00	-14.70	peak

FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hoping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.2

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

a) Span: Wide enough to capture the peaks of two adjacent channels.
b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
c) Video (or average) bandwidth (VBW) ≥ RBW.
d) Sweep: Auto.
e) Detector function: Peak.
f) Trace: Max hold.
g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined.



Limit=20 dB bandwidth*2/3

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	55 %
ATM Pressure:	101 kPa

The testing was performed by Navilite Cai on 2024-07-18.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(a) (1) - 20 dB EMISSION BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.7 & Clause 6.9.2

a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.

b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.

c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than [10 log (OBW/RBW)] below the reference level.

d) Steps a) through c) might require iteration to adjust within the specified tolerances.

e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target "−xx dB down" requirement; that is, if the requirement calls for measuring the −20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.

f) Set detection mode to peak and trace mode to max hold.

g) Determine the reference value: Set the EUT to transmit an un-modulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).

h) Determine the "−xx dB down amplitude" using [(reference value) − xx]. Alternatively, this calculation may be made by using the marker-delta function of the instrument.

i) If the reference value is determined by an un-modulated carrier, then turn the EUT modulation on, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).

j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the "− xx dB down amplitude" determined in step h). If a marker is below this "−xx dB down amplitude" value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the "− xx dB down amplitude" determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.

k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).



Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	55 %
ATM Pressure:	101 kPa

The testing was performed by Navilite Cai on 2024-07-18.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that
a minimum of 15 channels are used.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.3

a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.

b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

c) VBW ≥ RBW.

d) Sweep: Auto.

e) Detector function: Peak.

f) Trace: Max hold.

It might prove necessary to break the span up into sub ranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	55 %
ATM Pressure:	101 kPa

The testing was performed by Navilite Cai on 2024-07-18.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.4

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

a) Span: Zero span, centered on a hopping channel.
b) RBW shall be ≤ channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel.
c) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
d) Detector function: Peak.
e) Trace: Max hold.

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

(Number of hops in the period specified in the requirements) =(number of hops on spectrum analyzer) × (period specified in the requirements / analyzer sweep time)

The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation.

The measured transmit time and time between hops shall be consistent with the values described in the operational description for the EUT.



Note 1: A period time=0.4*79=31.6(S), Result=Burst Width*Total hops
Note 2: Total hops=Hopping Number in 3.16s*10
Note 3: Hopping Number in 3.16s=Total of highest signals in 3.16s(Second high signals were other channel)

Test Data

Environmental Conditions

Temperature:	25 ℃
Relative Humidity:	55 %
ATM Pressure:	101 kPa

The testing was performed by Navilite Cai on 2024-07-18.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.5

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. The hopping shall be disabled for this test:

a) Use the following spectrum analyzer settings:

1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
2) RBW > 20 dB bandwidth of the emission being measured.
3) VBW ⩾ RBW.
4) Sweep: Auto.
5) Detector function: Peak.
6) Trace: Max hold.

b) Allow trace to stabilize.

c) Use the marker-to-peak function to set the marker to the peak of the emission.

d) The indicated level is the peak output power, after any corrections for external attenuators and cables.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	55 %
ATM Pressure:	101 kPa

The testing was performed by Navilite Cai on 2024-07-18.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(d) § 5.5 - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.6 & Clause 6.10

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	55 %
ATM Pressure:	101 kPa

The testing was performed by Navilite Cai on 2024-07-18.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

EUT PHOTOGRAPHS

Please refer to the attachment 2401U24989E-RF External photo and 2401U24989E-RF Internal photo.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2401U24989E-RF Test Setup photo.

APPENDIX

Appendix A: 20dB Emission Bandwidth

Test Result

Test Mode	Antenna	Freq(MHz)	20dB EBW[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH1	Ant1	2402	0.942	2401.52	2402.47	---	---
		2441	0.939	2440.52	2441.46	---	---
		2480	0.939	2479.52	2480.46	---	---
2DH1	Ant1	2402	1.254	2401.36	2402.61	---	---
		2441	1.254	2440.36	2441.61	---	---
		2480	1.257	2479.35	2480.61	---	---
3DH1	Ant1	2402	1.215	2401.39	2402.61	---	---
		2441	1.212	2440.39	2441.60	---	---
		2480	1.215	2479.39	2480.61	---	---

Test Graphs

DH1_Ant1_2402



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.401523 GHz	-23.55 dBm		
M2		1	2.401823 GHz	-2.76 dBm		
D3	M1	1	942.0 kHz	0.47 dB		

ProjectNo.:2401U24989E-RF Tester:Navilite.Cai
Date: 18.JUL.2024 14:04:20

DH1_Ant1_2441



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.440523 GHz	-23.67 dBm		
M2		1	2.44082 GHz	-3.41 dBm		
D3	M1	1	939.0 kHz	0.14 dB		

ProjectNo.:2401U24989E-RF Tester:Navilite.Cai
Date: 18.JUL.2024 14:05:16

DH1_Ant1_2480



2DH1_Ant1_2402



2DH1_Ant1_2441



2DH1_Ant1_2480



3DH1_Ant1_2402



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.401391 GHz	-23.59 dBm		
M2		1	2.401817 GHz	-3.00 dBm		
D3	M1	1	1.215 MHz	-0.14 dB		

ProjectNo.:2401U24989E-RF Tester:Navilite.Cai
Date: 18.JUL.2024 14:10:25

3DH1_Ant1_2441



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.440391 GHz	-23.82 dBm		
M2		1	2.440817 GHz	-3.55 dBm		
D3	M1	1	1.212 MHz	0.13 dB		

ProjectNo.:2401U24989E-RF Tester:Navilite.Cai
Date: 18.JUL.2024 14:11:18

3DH1_Ant1_2480



Appendix B: Occupied Channel Bandwidth

Test Result

Test Mode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH1	Ant1	2402	0.839	2401.5654	2402.4046	---	---
		2441	0.845	2440.5624	2441.4076	---	---
		2480	0.842	2479.5624	2480.4046	---	---
2DH1	Ant1	2402	1.145	2401.4066	2402.5514	---	---
		2441	1.145	2440.4066	2441.5514	---	---
		2480	1.145	2479.4066	2480.5514	---	---
3DH1	Ant1	2402	1.136	2401.4246	2402.5604	---	---
		2441	1.148	2440.4186	2441.5664	---	---
		2480	1.142	2479.4216	2480.5634	---	---

Test Graphs

DH1_Ant1_2402



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.4018232 GHz	-2.78 dBm		
T1		1	2.40156543 GHz	-22.23 dBm	Occ Bw	839.160839161 kHz
T2		1	2.4024046 GHz	-21.66 dBm		

ProjectNo.:2401U24989E-RF Tester:Navilite.Cai
Date: 18.JUL.2024 14:04:26

DH1_Ant1_2441



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.4408202 GHz	-3.40 dBm		
T1		1	2.44056244 GHz	-22.59 dBm	Occ Bw	845.154845155 kHz
T2		1	2.44140759 GHz	-22.45 dBm		

ProjectNo.:2401U24989E-RF Tester:Navilite.Cai
Date: 18.JUL.2024 14:05:22

DH1_Ant1_2480



2DH1_Ant1_2402



2DH1_Ant1_2441



2DH1_Ant1_2480



3DH1_Ant1_2402



3DH1_Ant1_2441



3DH1_Ant1_2480

Appendix C: Maximum conducted output power

Test Result Peak

Test Mode	Antenna	Freq(MHz)	Conducted Peak Power[dBm]	Conducted Limit[dBm]	Verdict
DH1	Ant1	2402	-0.50	≤20.97	PASS
		2441	-0.92	≤20.97	PASS
		2480	-1.31	≤20.97	PASS
2DH1	Ant1	2402	-0.02	≤20.97	PASS
		2441	-0.42	≤20.97	PASS
		2480	-0.78	≤20.97	PASS
3DH1	Ant1	2402	0.80	≤20.97	PASS
		2441	0.47	≤20.97	PASS
		2480	0.05	≤20.97	PASS

Test Graphs

DH1_Ant1_2402



DH1_Ant1_2441



DH1_Ant1_2480



ProjectNo.:2401U24989E-RF Tester:Navilite.Cai
Date: 18.JUL.2024 14:06:45

2DH1_Ant1_2402



ProjectNo.:2401U24989E-RF Tester:Navilite.Cai
Date: 18.JUL.2024 14:07:43

2DH1_Ant1_2441



2DH1_Ant1_2480



3DH1_Ant1_2402



3DH1_Ant1_2441



3DH1_Ant1_2480



Appendix D: Carrier frequency separation

Test Result

Test Mode	Antenna	Freq(MHz)	Result[MHz]	Limit[MHz]	Verdict
DH1	Ant1	Hop	1.003	≥0.626	PASS
2DH1	Ant1	Hop	1.000	≥0.836	PASS
3DH1	Ant1	Hop	1.003	≥0.808	PASS

Test Graphs

DH1_Ant1_Hop



ProjectNo.:2401U24989E-RF Tester:Navilite.Cai
Date: 18.JUL.2024 14:15:09

2DH1_Ant1_Hop



ProjectNo.:2401U24989E-RF Tester:Navilite.Cai
Date: 18.JUL.2024 14:20:39

3DH1_Ant1_Hop



Appendix E: Time of occupancy

Test Result

Test Mode	Antenna	Freq(MHz)	Burst Width [ms]	Total Hops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.401	320	0.128	≤0.4	PASS
DH3	Ant1	Hop	1.650	160	0.264	≤0.4	PASS
DH5	Ant1	Hop	2.890	110	0.318	≤0.4	PASS
2DH1	Ant1	Hop	0.413	330	0.136	≤0.4	PASS
2DH3	Ant1	Hop	1.658	160	0.265	≤0.4	PASS
2DH5	Ant1	Hop	2.897	130	0.377	≤0.4	PASS
3DH1	Ant1	Hop	0.414	330	0.137	≤0.4	PASS
3DH3	Ant1	Hop	1.656	150	0.248	≤0.4	PASS
3DH5	Ant1	Hop	2.899	110	0.319	≤0.4	PASS

Test Graphs

DH1_Ant1_Hop





DH3_Ant1_Hop


Spectrum
Ref Level 29.56 dBm Offset 19.56 dB RBW 1 MHz
Att 20 dB SWT 10 ms VBW 3 MHz
SGL Count 1/1 TRG:VID
1Pk Clrw
M1[1] -16.12 dBm
-6.23 µs
D2[1] 13.81 dB
1.65000 ms
20 dBm
10 dBm
0 dBm
TRG -3.240 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
CF 2.441 GHz 8000 pts 1.0 ms/
ProjectNo.:2401U24989E-RF Tester:Navilite.Cai
Date: 18.JUL.2024 14:17:19


Spectrum
Ref Level 29.56 dBm Offset 19.56 dB RBW 500 kHz
Att 20 dB SWT 3.2 s VBW 3 MHz
SGL Count 1/1 TRG:VID
1Pk Clrw
20 dBm
10 dBm
0 dBm
TRG -3.240 dBm
-10 dBm
-20 dBm
-30 dBm
-50 dBm
-60 dBm
CF 2.441 GHz 30000 pts 316.0 ms/
ProjectNo.:2401U24989E-RF Tester:Navilite.Cai
Date: 18.JUL.2024 14:17:24

DH5_Ant1_Hop


Spectrum
Ref Level 29.56 dBm Offset 19.56 dB RBW 1 MHz
Att 20 dB SWT 10 ms VBW 3 MHz
SGL Count 1/1 TRG:VID
1Pk Clrw
M1[1] -15.42 dBm
-4.98 µs
D2[1] 13.24 dB
2.89000 ms
20 dBm
10 dBm
0 dBm
TRG -3.340 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
CF 2.441 GHz 8000 pts 1.0 ms/
ProjectNo.:2401U24989E-RF Tester:Navilite.Cai
Date: 18.JUL.2024 14:17:57


Spectrum
Ref Level 29.56 dBm Offset 19.56 dB RBW 500 kHz
Att 20 dB SWT 3.2 s VBW 3 MHz
SGL Count 1/1 TRG:VID
1Pk Clrw
20 dBm
10 dBm
0 dBm
TRG -3.340 dBm
-10 dBm
-20 dBm
-30 dBm
-50 dBm
-60 dBm
CF 2.441 GHz 30000 pts 316.0 ms/
ProjectNo.:2401U24989E-RF Tester:Navilite.Cai
Date: 18.JUL.2024 14:18:02

2DH1_Ant1_Hop





2DH3_Ant1_Hop





2DH5_Ant1_Hop



ProjectNo.:2401U24989E-RF Tester:Navilite.Cai
Date: 18.JUL.2024 14:24:22



ProjectNo.:2401U24989E-RF Tester:Navilite.Cai
Date: 18.JUL.2024 14:24:27

3DH1_Ant1_Hop





3DH3_Ant1_Hop





3DH5_Ant1_Hop





Appendix F: Number of hopping channels

Test Result

Test Mode	Antenna	Freq(MHz)	Result[Num]	Limit[Num]	Verdict
DH1	Ant1	Hop	79	≥15	PASS
2DH1	Ant1	Hop	79	≥15	PASS
3DH1	Ant1	Hop	79	≥15	PASS

Test Graphs

DH1_Ant1_Hop



2DH1_Ant1_Hop



3DH1_Ant1_Hop



Appendix G: Band edge measurements

Test Graphs

DH1_Ant1_Low_2402



DH1_Ant1_High_2480



DH1_Ant1_Low_Hop_2402



DH1_Ant1_High_Hop_2480



2DH1_Ant1_Low_2402



2DH1_Ant1_High_2480



2DH1_Ant1_Low_Hop_2402



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.402174 GHz	-0.94 dBm		
M2		1	2.4 GHz	-44.57 dBm		
M3		1	2.39 GHz	-47.16 dBm		
M4		1	2.3960725 GHz	-44.22 dBm		

ProjectNo.:2401U24989E-RF Tester:Navilite.Cai
Date: 18.JUL.2024 14:19:55

2DH1_Ant1_High_Hop_2480



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.48013 GHz	-2.06 dBm		
M2		1	2.4835 GHz	-46.28 dBm		
M3		1	2.5 GHz	-47.36 dBm		
M4		1	2.488899 GHz	-44.32 dBm		

ProjectNo.:2401U24989E-RF Tester:Navilite.Cai
Date: 18.JUL.2024 14:22:46

3DH1_Ant1_Low_2402



3DH1_Ant1_High_2480



3DH1_Ant1_Low_Hop_2402



3DH1_Ant1_High_Hop_2480



******* END OF REPORT *******