Radio Test Report

FCC ID: 2BG38-MC605

Report No.	:	TBR-C-202406-0001-3
Applicant	:	Shenzhen XinWosen Technology Co., Ltd.
Equipment Under Test (EUT)		
EUT Name	:	Micro HiFi System
Model No.	:	MC-605
Series Model No.	:	item No.210332, MCD-60, MC-608, MC-609，MC-610, MC-612
Brand Name	:	Sharper Image
Sample ID	:	HC-C-202405-0001-01-01&HC-C-202405-0001-01-02
Receipt Date	:	2024-06-13
Test Date	:	2024-06-13 to 2024-06-24
Issue Date	:	2024-06-24
Standards	:	FCC Part 15 Subpart C 15.247
Test Method	:	ANSI C63.10: 2013 KDB 558074 D01 15.247 Meas Guidance v05r02
Conclusions	:	**PASS**
		In the configuration tested, the EUT complied with the standards specified above.
Test By	:	ZKN Zhou
Reviewed By	:	Henry Huang
Approved By	:	Ivan Su

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

1/F.,Building 6, Rundongsheng Industrial Zone, Longzhu, Xixiang, Bao'an District, Shenzhen, Guangdong, China
Tel: +86 75526509301 Fax: +86 75526509195

Contents

CONTENTS 2
1. GENERAL INFORMATION ABOUT EUT 5
1.1 Client Information 5
1.2 General Description of EUT (Equipment Under Test) 5
1.3 Block Diagram Showing the Configuration of System Tested 6
1.4 Description of Support Units 7
1.5 Description of Test Mode 7
1.6 Description of Test Software Setting 8
1.7 Measurement Uncertainty 8
1.8 Test Facility 9
2. TEST SUMMARY 10
3. TEST SOFTWARE 10
4. TEST EQUIPMENT AND TEST SITE 11
5. CONDUCTED EMISSION 12
5.1 Test Standard and Limit 12
5.2 Test Setup 12
5.3 Test Procedure 12
5.4 Deviation From Test Standard 12
5.5 EUT Operating Mode 13
5.6 Test Data 13
6. RADIATED AND CONDUCTED UNWANTED EMISSIONS 14
6.1 Test Standard and Limit 14
6.2 Test Setup 15
6.3 Test Procedure 16
6.4 Deviation From Test Standard 17
6.5 EUT Operating Mode 17
6.6 Test Data 17
7. RESTRICTED BANDS AND BAND EDGE REQUIREMENT 18
7.1 Test Standard and Limit 18
7.2 Test Setup 18
7.3 Test Procedure 19
7.4 Deviation From Test Standard 19
7.5 EUT Operating Mode 19
7.6 Test Data 19
8. 99% OCCUPIED AND 20DB BANDWIDTH 20
8.1 Test Standard and Limit 20
8.2 Test Setup 20
8.3 Test Procedure 20
8.4 Deviation From Test Standard 20
8.5 EUT Operating Mode 21
8.6 Test Data 21
9. PEAK OUTPUT POWER TEST 22

9.1 Test Standard and Limit 22
9.2 Test Setup 22
9.3 Test Procedure 22
9.4 Deviation From Test Standard 23
9.5 EUT Operating Mode 23
9.6 Test Data 23
10. CARRIER FREQUENCY SEPARATION 24
10.1 Test Standard and Limit 24
10.2 Test Setup 24
10.3 Test Procedure 24
10.4 Deviation From Test Standard 24
10.5 Antenna Connected Construction 25
10.6 Test Data 25
11. TIME OF OCCUPANCY (DWELL TIME) 26
11.1 Test Standard and Limit 26
11.2 Test Setup 26
11.3 Test Procedure 26
11.4 Deviation From Test Standard 27
11.5 Antenna Connected Construction 27
11.6 Test Data 27
12. NUMBER OF HOPPING FREQUENCIES 28
12.1 Test Standard and Limit 28
12.2 Test Setup 28
12.3 Test Procedure 28
12.4 Deviation From Test Standard 28
12.5 Antenna Connected Construction 29
12.6 Test Data 29
13. ANTENNA REQUIREMENT 30
13.1 Test Standard and Limit 30
13.2 Deviation From Test Standard 30
13.3 Antenna Connected Construction 30
13.4 Test Data 30
ATTACHMENT A-- CONDUCTED EMISSION TEST DATA 31
ATTACHMENT B--UNWANTED EMISSIONS DATA 33

Revision History

Report No.	Version	Description	Issued Date
TBR-C-202406-0001-3	Rev.01	Initial issue of report	2024-06-24

1. General Information about EUT

1.1 Client Information

Applicant	:	Shenzhen XinWosen Technology Co., Ltd.
Address	:	5th Floor, Building 4, Huangmabu Centennial Kitchenware Industrial Park, Hangcheng Street, Shenzhen, Guangdong, China
Manufacturer	:	Shenzhen XinWosen Technology Co., Ltd.
Address	:	5th Floor, Building 4, Huangmabu Centennial Kitchenware Industrial Park, Hangcheng Street, Shenzhen, Guangdong, China

1.2 General Description of EUT (Equipment Under Test)

EUT Name	:	Micro HiFi System	
Models No.	:	MC-605, item No.210332, MCD-60, MC-608, MC-609, MC-610, MC-612	
Model Different	:	All these models are identical in the same PCB, layout and electrical circuit, The only difference is model name, brand name and product name.	
Product Description	:	Operation Frequency:	Bluetooth(BR+EDR): 2402MHz~2480MHz
		Number of Channel:	79 channels
		Antenna Gain:	1.58dBi PCB Antenna
		Modulation Type:	GFSK(1Mbps) π/4-DQPSK(2Mbps) 8DPSK(3Mbps)
Power Rating	:	Adapter:(MR-AA0150500200US) Input: 100-240V~50/60Hz 0.3A Output: 5V⎓2.0A 10.0W	
Software Version	:	N/A	
Hardware Version	:	PZ-MC-605-M5677 REV6.0	

Remark:
(1)The antenna gain provided by the applicant, the adapter and the verified for the RF conduction test provided by TOBY test lab.
(2)The above antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.
(3)For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

(4) Channel List:

Bluetooth Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	**2402**	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	**39**	**2441**	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	**78**	**2480**
25	2427	52	2454		
26	2428	53	2455		

1.3 Block Diagram Showing the Configuration of System Tested



1.4 Description of Support Units

Equipment Information				
Name	**Model**	**S/N**	**Manufacturer**	**Used "√"**
Notebook	HYLR-WFQ9	AAMFPM1418000165	honour	√

1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test(AC POWER)	
Final Test Mode	**Description**
Mode 1	TX GFSK Mode Channel 00
For Radiated and RF Conducted Test	
Final Test Mode	**Description**
Mode 1	TX GFSK Mode Channel 00
Mode 2	TX Mode(GFSK) Channel 00/39/78
Mode 3	TX Mode(π/4-DQPSK) Channel 00/39/78
Mode 4	TX Mode(8DPSK) Channel 00/39/78
Mode 5	Hopping Mode(GFSK)
Mode 6	Hopping Mode(π/4-DQPSK)
Mode 7	Hopping Mode(8DPSK)

Note:

(1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate.

According to ANSI C63.10 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:

TX Mode: GFSK (1 Mbps)
TX Mode:π/4-DQPSK (2 Mbps)
TX Mode: 8DPSK (3 Mbps)

(2) During the testing procedure, the continuously transmitting with the maximum power mode was programmed by the customer.

(3) The EUT is considered a Mobile unit; in normal use it was positioned on X-plane. The worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.

1.6 Description of Test Software Setting

During testing channel& Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of RF setting.

Test Software Version	**BT_Tool**		
Frequency	2402 MHz	2441MHz	2480 MHz
GFSK	7	7	7
π/4-DQPSK	7	7	7
8DPSK	7	7	7

1.7 Measurement Uncertainty

The reported uncertainty of measurement y±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

Test Item	**Parameters**	**Expanded Uncertainty (U_{Lab})**
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	±3.50 dB ±3.10 dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	±4.60 dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	±4.50 dB
Radiated Emission	Level Accuracy: Above 1000MHz	±4.20 dB

1.8 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1/F.,Building 6, Rundongsheng Industrial Zone, Longzhu, Xixiang, Bao'an District, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)
The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

A2LA Certificate No.: 4750.01
The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01.FCC Accredited Test Site Number: 854351. Designation Number: CN1223.

IC Registration No.: (11950A)
The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A. CAB identifier: CN0056.

2. Test Summary

Standard Section		Test Item	Test Sample(s)	Judgment	Remark
FCC	IC				
FCC 15.207(a)	RSS-Gen 8.8	Conducted Emission	HC-C-202405-0001-01-02	PASS	N/A
FCC 15.209 & 15.247(d)	RSS-Gen 8.9 & RSS 247 5.5	Radiated Unwanted Emissions	HC-C-202405-0001-01-02	PASS	N/A
FCC 15.203	RSS-247 6.8	Antenna Requirement	HC-C-202405-0001-01-01	PASS	N/A
FCC 15.247(a)	RSS-Gen 6.7 RSS 247 5.1 (1)	99% Occupied Bandwidth & 20dB Bandwidth	HC-C-202405-0001-01-01	PASS	N/A
FCC 15.247(b)(1)	RSS 247 5.4 (2)	Peak Output Power	HC-C-202405-0001-01-01	PASS	N/A
FCC 15.247(a)(1)	RSS 247 5.1 (2)	Carrier frequency separation	HC-C-202405-0001-01-01	PASS	N/A
FCC 15.247(a)(1)	RSS 247 5.1 (4)	Time of occupancy	HC-C-202405-0001-01-01	PASS	N/A
FCC 15.247(b)(1)	RSS 247 5.1 (4)	Number of Hopping Frequency	HC-C-202405-0001-01-01	PASS	N/A
FCC 15.247(d)	RSS-Gen 8.10 RSS-247 5.5	Band Edge	HC-C-202405-0001-01-01	PASS	N/A
FCC 15.207(a)	RSS-247 5.5	Conducted Unwanted Emissions	HC-C-202405-0001-01-01	PASS	N/A
FCC 15.205	RSS-Gen 8.10	Emissions in Restricted Bands	HC-C-202405-0001-01-01	PASS	N/A
/	/	On Time and Duty Cycle	HC-C-202405-0001-01-01	/	N/A

Note: N/A is an abbreviation for Not Applicable.

3. Test Software

Test Item	Test Software	Manufacturer	Version No.
Conducted Emission	EZ-EMC	EZ	CDI-03A2
Radiation Emission	EZ-EMC	EZ	FA-03A2RE
Radiation Emission	EZ-EMC	EZ	FA-03A2RE+
RF Conducted Measurement	MTS-8310	MWRFtest	V2.0.0.0
RF Test System	JS1120	Tonscend	V3.2.22

4. Test Equipment and Test Site

Test Site				
No.	**Test Site**	**Manufacturer**	**Specification**	**Used**
TB-EMCSR001	Shielding Chamber #1	YIHENG	7.5*4.0*3.0 (m)	√
TB-EMCSR002	Shielding Chamber #2	YIHENG	8.0*4.0*3.0 (m)	√
TB-EMCCA001	3m Anechoic Chamber #A	ETS	9.0*6.0*6.0 (m)	X
TB-EMCCB002	3m Anechoic Chamber #B	YIHENG	9.0*6.0*6.0 (m)	√

Conducted Emission Test					
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Last Cal.**	**Cal. Due Date**
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jun. 17, 2024	Jun. 16, 2025
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jun. 17, 2024	Jun. 16, 2025
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jun. 17, 2024	Jun. 16, 2025
LISN	Rohde & Schwarz	ENV216	101131	Jun. 17, 2024	Jun. 16, 2025
Radiation Emission Test(B Site)					
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Last Cal.**	**Cal. Due Date**
Spectrum Analyzer	Agilent	N9020A	MY49100060	Aug. 30, 2023	Aug. 29, 2024
Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102197	Jun. 17, 2024	Jun. 16, 2025
EMI Test Receiver	Rohde & Schwarz	ESU-8	100472/008	Feb. 23, 2024	Feb.22, 2025
Bilog Antenna	SCHWARZBECK	VULB 9168	1225	Nov. 13, 2023	Nov. 12, 2025
Horn Antenna	SCHWARZBECK	BBHA 9120 D	2463	Jun. 14, 2024	Jun. 13, 2026
Horn Antenna	SCHWARZBECK	BBHA 9170	1118	Feb. 27, 2024	Feb.26, 2026
Loop Antenna	SCHWARZBECK	FMZB 1519 B	1519B-059	Jun. 14, 2024	Jun. 13, 2026
HF Amplifier	Tonscend	TAP9E6343	AP21C806117	Aug. 30, 2023	Aug. 29, 2024
HF Amplifier	Tonscend	TAP051845	AP21C806141	Aug. 30, 2023	Aug. 29, 2024
HF Amplifier	Tonscend	TAP0184050	AP21C806129	Aug. 30, 2023	Aug. 29, 2024
Highpass Filter	CD	HPM-6.4/18G	---	N/A	N/A
Highpass Filter	CD	HPM-2.8/18G	---	N/A	N/A
Highpass Filter	XINBO	XBLBQ-HTA67(8-25G)	22052702-1	N/A	N/A
Antenna Conducted Emission					
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Last Cal.**	**Cal. Due Date**
Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102197	Jun. 17, 2024	Jun. 16, 2025
MXA Signal Analyzer	KEYSIGHT	N9020B	MY60110172	Aug. 30, 2023	Aug. 29, 2024
MXA Signal Analyzer	Agilent	N9020A	MY47380425	Aug. 30, 2023	Aug. 29, 2024
RF Power Sensor	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO26	Aug. 30, 2023	Aug. 29, 2024
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO29	Aug. 30, 2023	Aug. 29, 2024
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO31	Aug. 30, 2023	Aug. 29, 2024
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO33	Aug. 30, 2023	Aug. 29, 2024
Temperature and Humidity Chamber	ZhengHang	ZH-QTH-1500	ZH2107264	Jun. 17, 2024	Jun. 16, 2025

5. Conducted Emission

5.1 Test Standard and Limit

5.1.1 Test Standard

RSS-Gen 8.8

FCC Part 15.207

5.1.2 Test Limit

Frequency	Maximum RF Line Voltage (dBμV)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Notes:

(1) *Decreasing linearly with logarithm of the frequency.

(2) The lower limit shall apply at the transition frequencies.

(3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.2 Test Setup



5.3 Test Procedure

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- The bandwidth of EMI test receiver is set at 9 kHz, and the test frequency band is from 0.15MHz to 30MHz.

5.4 Deviation From Test Standard

No deviation

5.5 EUT Operating Mode

Please refer to the description of test mode.

5.6 Test Data

Please refer to the Attachment A inside test report.

6. Radiated and Conducted Unwanted Emissions

6.1 Test Standard and Limit

6.1.1 Test Standard

RSS-Gen 8.9 & RSS 247 5.5

FCC Part 15.209 & FCC Part 15.247(d)

6.1.2 Test Limit

General field strength limits at frequencies Below 30MHz		
Frequency (MHz)	**Field Strength (microvolt/meter)****	**Measurement Distance (meters)**
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
Note: 1, The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.		

General field strength limits at frequencies above 30 MHz		
Frequency (MHz)	**Field strength (μV/m at 3 m)**	**Measurement Distance (meters)**
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

General field strength limits at frequencies Above 1000MHz		
Frequency (MHz)	**Distance of 3m (dBuV/m)**	
	Peak	**Average**
Above 1000	74	54
Note: (1) The tighter limit applies at the band edges. (2) Emission Level(dBuV/m)=20log Emission Level(uV/m)		

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB.

6.2 Test Setup

Radiated measurement



Below 30MHz Test Setup



Below 1000MHz Test Setup



Above 1GHz Test Setup

Conducted measurement



6.3 Test Procedure

---Radiated measurement

● The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.

● Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.

● The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.

● The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.

● If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Below 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.

● Testing frequency range 30MHz-1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection. Testing frequency range 9KHz-150Hz the measuring instrument use VBW=200Hz with Quasi-peak detection. Testing frequency range 9KHz-30MHz the measuring instrument use VBW=9kHz with Quasi-peak detection.

● Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

● For the actual test configuration, please see the test setup photo.

--- Conducted measurement

●Reference level measurement

Establish a reference level by using the following procedure:
a) Set instrument center frequency to DTS channel center frequency.
b) Set the span to≥1.5 times the DTS bandwidth.
c) Set the RBW = 100 kHz.
d) Set the VBW≥[3*RBW].
e) Detector = peak.
f) Sweep time = auto couple.
g) Trace mode = max hold.
h) Allow trace to fully stabilize.
i) Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

●Emission level measurement

Establish an emission level by using the following procedure:
a) Set the center frequency and span to encompass frequency range to be measured.
b) Set the RBW = 100 kHz.
c) Set the VBW≥[3*RBW].
d) Detector = peak.
e) Sweep time = auto couple.
f) Trace mode = max hold.
g) Allow trace to fully stabilize.
h) Use the peak marker function to determine the maximum amplitude level.
Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

6.4 Deviation From Test Standard

No deviation

6.5 EUT Operating Mode

Please refer to the description of test mode.

6.6 Test Data

Radiated measurement please refer to the Attachment B inside test report.
Conducted measurement please refer to the external appendix report of BT.

7. Restricted Bands and Band Edge Requirement

7.1 Test Standard and Limit

7.1.1 Test Standard

RSS-Gen 8.10 & RSS 247 5.5

FCC Part 15.205 & FCC Part 15.247(d)

7.1.2 Test Limit

Restricted Frequency Band (MHz)	Distance Meters(at 3m)	
	Peak (dBuV/m)	Average (dBuV/m)
2310 ~2390	74	54
2483.5 ~2500	74	54
	Peak (dBm)see 7.3 e)	Average (dBm) see 7.3 e)
2310 ~2390	-21.20	-41.20
2483.5 ~2500	-21.20	-41.20
Note: According the ANSI C63.10 11.12.2 antenna-port conducted measurements may also be used as an alternative to radiated measurements for determining compliance in the restricted frequency bands requirements. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test forcabinet/case emissions is required.		

7.2 Test Setup

Radiated measurement



Conducted measurement



7.3 Test Procedure

---Radiated measurement

● Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.

● The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.

●The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.

●The Peak Value and average value both need to comply with applicable limit above 1 GHz.

●Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

●For the actual test configuration, please see the test setup photo.

--- Conducted measurement

a) Measure the conducted output power (in dBm) using the detector specified by the appropriate regulatory agency (see 11.12.2.3 through 11.12.2.5 for guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).

b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP (see 11.12.2.6 for guidance on determining the applicable antenna gain).

c) Add the appropriate maximum ground reflection factor to the EIRP (6 dB for frequencies ≤30 MHz; 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive; and 0 dB for frequencies > 1000 MHz).

d) For MIMO devices, measure the power of each chain and sum the EIRP of all chains in linear terms (i.e., watts and mW).

e) Convert the resultant EIRP to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20 \log d + 104.8$$

where

E is the electric field strength in dBuV/m

EIRP is the equivalent isotropically radiated power in dBm

d is the specified measurement distance in m

f) Compare the resultant electric field strength level with the applicable regulatory limit.

g) Perform the radiated spurious emission test.

7.4 Deviation From Test Standard

No deviation

7.5 EUT Operating Mode

Please refer to the description of test mode.

7.6 Test Data

Remark: The test uses antenna-port conducted measurements as an alternative to radiated measurements for determining compliance in the restricted frequency bands requirements.

Please refer to the external appendix report of BT.

8. 99% Occupied and 20dB Bandwidth

8.1 Test Standard and Limit

8.1.1 Test Standard

RSS-Gen 6.7 & RSS 247 5.1(a)

FCC Part 15.205 & FCC Part 15.247(a)

8.1.2 Test Limit

For an FHSS system operating in the 2400 to 2483.5 MHz band, there are no limits for 20dB bandwidth and 99% occupied bandwidth.

8.2 Test Setup



8.3 Test Procedure

●The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.

b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.

c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than [10 log (OBW/RBW)] below the reference level. Specific guidance is given in 4.1.5.2.

d) Step a) through step c) might require iteration to adjust within the specified range.

e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.

f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.

g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.

h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

8.4 Deviation From Test Standard

No deviation

8.5 EUT Operating Mode

Please refer to the description of test mode.

8.6 Test Data

Please refer to the external appendix report of BT.

9. Peak Output Power Test

9.1 Test Standard and Limit

9.1.1 Test Standard

RSS 247 5.4(2)
FCC Part 15.247(b)(1)

9.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Peak Output Power	$P_{max\text{-}pk} \leq 1$ W $N_{ch} \geq 75$ f ≥ MAX { 25 kHz, BW_{20dB} } max. BW_{20dB} not specified $t_{ch} \leq 0.4$ s for $T = 0.4*N_{ch}$	2400~2483.5
	$P_{max\text{-}pk} \leq 0.125$ W $N_{ch} \geq 15$ f ≥ [MAX{25 kHz, 0.67*BW_{20dB}} OR MAX{25 kHz, BW_{20dB}}] max. BW_{20dB} not specified $t_{ch} \leq 0.4$ s for $T = 0.4*N_{ch}$	
t_{ch} = average time of occupancy; T = period; N_{ch} = # hopping frequencies; BW = bandwidth; f = hopping channel carrier frequency separation		

9.2 Test Setup



9.3 Test Procedure

●This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. The hopping shall be disabled for this test:

a) Use the following spectrum analyzer settings:
   1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
   2) RBW > 20 dB bandwidth of the emission being measured.
   3) VBW≥ RBW.
   4) Sweep: Auto.
   5) Detector function: Peak.
   6) Trace: Max hold.

b) Allow trace to stabilize.
c) Use the marker-to-peak function to set the marker to the peak of the emission.
d) The indicated level is the peak output power, after any corrections for external attenuators and cables.
e) A plot of the test results and setup description shall be included in the test report.

NOTE-A peak responding power meter may be used, where the power meter and sensor system video bandwidth is greater than the occupied bandwidth of the unlicensed wireless device, rather than a spectrum analyzer.

9.4 Deviation From Test Standard

No deviation

9.5 EUT Operating Mode

Please refer to the description of test mode.

9.6 Test Data

Please refer to the external appendix report of BT.

10. Carrier frequency separation

10.1 Test Standard and Limit

10.1.1 Test Standard

RSS 247 5.1(2)

FCC Part 15.247(a)(1)

10.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Carrier frequency separation	$P_{max\text{-}pk} \leq 1$ W $N_{ch} \geq 75$ f ≥ MAX { 25 kHz, BW_{20dB} } max. BW_{20dB} not specified $t_{ch} \leq 0.4$ s for $T = 0.4*N_{ch}$	2400~2483.5
	$P_{max\text{-}pk} \leq 0.125$ W $N_{ch} \geq 15$ f ≥ [MAX{25 kHz, 0.67*BW_{20dB}} OR MAX{25 kHz, BW_{20dB}}] max. BW_{20dB} not specified $t_{ch} \leq 0.4$ s for $T = 0.4*N_{ch}$	
t_{ch} = average time of occupancy; T = period; N_{ch} = # hopping frequencies; BW = bandwidth; f = hopping channel carrier frequency separation		

10.2 Test Setup



10.3 Test Procedure

●The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

a) Span: Wide enough to capture the peaks of two adjacent channels.
b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
c) Video (or average) bandwidth (VBW) ≥ RBW.
d) Sweep: Auto.
e) Detector function: Peak.
f) Trace: Max hold.
g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Compliance of an EUT with the appropriate regulatory limit shall be determined. A plot of the data shall be included in the test report.

10.4 Deviation From Test Standard

No deviation

10.5 Antenna Connected Construction

Please refer to the description of test mode.

10.6 Test Data

Please refer to the external appendix report of BT.

11. Time of occupancy (dwell time)

11.1 Test Standard and Limit

11.1.1 Test Standard

RSS 247 5.1(2)

FCC Part 15.247(a)(1)

11.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Time of occupancy (dwell time)	$P_{max\text{-}pk} \leq 1$ W $N_{ch} \geq 75$ f ≥ MAX { 25 kHz, BW_{20dB} } max. BW_{20dB} not specified $t_{ch} \leq 0.4$ s for $T = 0.4*N_{ch}$	2400~2483.5
	$P_{max\text{-}pk} \leq 0.125$ W $N_{ch} \geq 15$ f ≥ [MAX{25 kHz, 0.67*BW_{20dB}} OR MAX{25 kHz, BW_{20dB}}] max. BW_{20dB} not specified $t_{ch} \leq 0.4$ s for $T = 0.4*N_{ch}$	
t_{ch} = average time of occupancy; T = period; N_{ch} = # hopping frequencies; BW = bandwidth; □ f = hopping channel carrier frequency separation		

11.2 Test Setup



11.3 Test Procedure

●The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

a) Span: Zero span, centered on a hopping channel.

b) RBW shall be □ channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel.

c) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.

d) Detector function: Peak.

e) Trace: Max hold.

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Repeat the measurement using a longer sweep time to determine the number of hops

over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:
(Number of hops in the period specified in the requirements) =
(number of hops on spectrum analyzer)x(period specified in the requirements / analyzer sweep time)
The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation.
The measured transmit time and time between hops shall be consistent with the values described in the operational description for the EUT.

11.4 Deviation From Test Standard

No deviation

11.5 Antenna Connected Construction

Please refer to the description of test mode.

11.6 Test Data

Please refer to the external appendix report of BT.

12. Number of hopping frequencies

12.1 Test Standard and Limit

12.1.1 Test Standard

RSS 247 5.1(4)

FCC Part 15.247(b)(1)

12.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Carrier frequency separation	$P_{max\text{-}pk} \leq 1$ W $N_{ch} \geq 75$ f ≥ MAX { 25 kHz, BW_{20dB} } max. BW_{20dB} not specified $t_{ch} \leq 0.4$ s for $T = 0.4*N_{ch}$	2400~2483.5
	$P_{max\text{-}pk} \leq 0.125$ W $N_{ch} \geq 15$ f ≥ [MAX{25 kHz, 0.67*BW_{20dB}} OR MAX{25 kHz, BW_{20dB}}] max. BW_{20dB} not specified $t_{ch} \leq 0.4$ s for $T = 0.4*N_{ch}$	
t_{ch} = average time of occupancy; T = period; N_{ch} = # hopping frequencies; BW = bandwidth; f = hopping channel carrier frequency separation		

12.2 Test Setup



12.3 Test Procedure

●The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:
a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
c) VBW ≥ RBW.
d) Sweep: Auto.
e) Detector function: Peak.
f) Trace: Max hold.
g) Allow the trace to stabilize.
It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies.
Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.

12.4 Deviation From Test Standard

No deviation

12.5 Antenna Connected Construction

Please refer to the description of test mode.

12.6 Test Data

Please refer to the external appendix report of BT.

13. Antenna Requirement

13.1 Test Standard and Limit

11.1.1 Test Standard

RSS 247 6.8

FCC Part 15.203

11.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

13.2 Deviation From Test Standard

No deviation

13.3 Antenna Connected Construction

The gains of the antenna used for transmitting is 1.58dBi, and the antenna de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

13.4 Test Data

The EUT antenna is a PCB Antenna. It complies with the standard requirement.

Antenna Type
☒Permanent attached antenna
☐Unique connector antenna
☐Professional installation antenna

Attachment A-- Conducted Emission Test Data

Test Voltage:	AC 120V/60Hz
Terminal:	Line
Test Mode:	Mode 1
Remark:	Only worse case is reported.



Temperature: 23.4 (C) Humidity: 48 %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1660	18.35	10.39	28.74	65.15	-36.41	QP
2		0.1660	7.99	10.39	18.38	55.15	-36.77	AVG
3		0.6220	20.18	10.37	30.55	56.00	-25.45	QP
4	*	0.6220	13.02	10.37	23.39	46.00	-22.61	AVG
5		1.8340	11.74	10.15	21.89	56.00	-34.11	QP
6		1.8340	5.97	10.15	16.12	46.00	-29.88	AVG
7		3.9580	10.45	10.46	20.91	56.00	-35.09	QP
8		3.9580	5.44	10.46	15.90	46.00	-30.10	AVG
9		8.4500	9.51	11.00	20.51	60.00	-39.49	QP
10		8.4500	4.68	11.00	15.68	50.00	-34.32	AVG
11		25.6940	18.55	11.56	30.11	60.00	-29.89	QP
12		25.6940	7.82	11.56	19.38	50.00	-30.62	AVG

Remark:
1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Margin (dB) =QuasiPeak/Average (dBuV)-Limit (dBuV)

Test Voltage:	AC 120V/60Hz
Terminal:	Neutral
Test Mode:	Mode 1
Remark:	Only worse case is reported.



Temperature: 23.4 (C) Humidity: 48 %

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1539	16.14	10.42	26.56	65.78	-39.22	QP
2		0.1539	8.35	10.42	18.77	55.78	-37.01	AVG
3		0.2340	17.33	10.40	27.73	62.30	-34.57	QP
4		0.2340	11.61	10.40	22.01	52.30	-30.29	AVG
5	*	0.6100	24.04	10.33	34.37	56.00	-21.63	QP
6		0.6100	12.94	10.33	23.27	46.00	-22.73	AVG
7		1.2059	15.44	10.25	25.69	56.00	-30.31	QP
8		1.2059	7.74	10.25	17.99	46.00	-28.01	AVG
9		4.6940	13.02	10.43	23.45	56.00	-32.55	QP
10		4.6940	6.65	10.43	17.08	46.00	-28.92	AVG
11		26.0060	18.17	11.58	29.75	60.00	-30.25	QP
12		26.0060	8.29	11.58	19.87	50.00	-30.13	AVG

Remark:
1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)
2. Margin (dB) =QuasiPeak/Average (dBuV)-Limit (dBuV)

Attachment B--Unwanted Emissions Data

---Radiated Unwanted Emissions

9 KHz~30 MHz

From 9 KHz to 30 MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB Below the permissible value has no need to be reported.

30MHz~1GHz

Test Voltage:	AC 120V/60Hz
Ant. Pol.	Horizontal
Test Mode:	Mode 1
Remark:	Only worse case is reported.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	84.7020	57.63	-27.20	30.43	40.00	-9.57	peak	P
2 *	126.7723	62.59	-23.84	38.75	43.50	-4.75	peak	P
3 !	148.4410	59.52	-21.07	38.45	43.50	-5.05	peak	P
4 !	169.5990	60.09	-22.21	37.88	43.50	-5.62	peak	P
5 !	190.4050	62.43	-24.65	37.78	43.50	-5.72	peak	P
6	296.1836	58.54	-21.35	37.19	46.00	-8.81	peak	P

Remark:
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. QuasiPeak (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = QuasiPeak (dBμV/m)-Limit QPK(dBμV/m)

Test Voltage:	AC 120V/60Hz
Ant. Pol.	Vertical
Test Mode:	Mode 1
Remark:	Only worse case is reported.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 !	67.6751	62.04	-26.14	35.90	40.00	-4.10	peak	P
2 !	84.7020	61.70	-27.20	34.50	40.00	-5.50	peak	P
3 *	126.7723	64.36	-23.84	40.52	43.50	-2.98	peak	P
4 !	148.4410	58.92	-21.07	37.85	43.50	-5.65	peak	P
5	169.5990	59.38	-22.21	37.17	43.50	-6.33	peak	P
6	190.4050	56.78	-24.65	32.13	43.50	-11.37	peak	P

Remark:
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. QuasiPeak (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = QuasiPeak (dBμV/m)-Limit QPK(dBμV/m)

Above 1GHz

Temperature:	23.5℃	**Relative Humidity:**	49%
Test Voltage:	AC 120V/60Hz		
Test Mode:	DH5 Mode TX 2402 MHz		
Remark:	Only worse case is reported.		

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11633.500	43.91	0.94	44.85	74.00	-29.15	peak	P
2 *	13469.500	42.92	2.16	45.08	74.00	-28.92	peak	P

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11735.500	43.43	1.08	44.51	74.00	-29.49	peak	P
2 *	13418.500	42.58	2.12	44.70	74.00	-29.30	peak	P

Remark:
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value < average limit, So only show the peak value.

Temperature:	23.5℃	**Relative Humidity:**	49%
Test Voltage:	AC 120V/60Hz		
Test Mode:	DH5 Mode TX 2441 MHz		
Remark:	Only worse case is reported.		

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11404.000	42.38	0.61	42.99	74.00	-31.01	peak	P
2 *	13469.500	42.84	2.16	45.00	74.00	-29.00	peak	P

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	12092.500	42.64	1.48	44.12	74.00	-29.88	peak	P
2 *	13571.500	42.97	2.25	45.22	74.00	-28.78	peak	P

Remark:
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value < average limit, So only show the peak value.

Temperature:	23.5℃	**Relative Humidity:**	49%
Test Voltage:	AC 120V/60Hz		
Test Mode:	DH5 Mode TX 2480 MHz		
Remark:	Only worse case is reported.		

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	10945.000	46.38	-0.08	46.30	74.00	-27.70	peak	P
2	13393.000	43.33	2.10	45.43	74.00	-28.57	peak	P

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	10919.500	46.43	-0.13	46.30	74.00	-27.70	peak	P
2	13520.500	43.52	2.20	45.72	74.00	-28.28	peak	P

Remark:
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value < average limit, So only show the peak value.

Temperature:	23.5℃	**Relative Humidity:**	49%
Test Voltage:	AC 120V/60Hz		
Test Mode:	2DH5 Mode TX 2402 MHz		
Remark:	Only worse case is reported.		

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	10919.500	46.87	-0.13	46.74	74.00	-27.26	peak	P
2	13393.000	44.09	2.10	46.19	74.00	-27.81	peak	P

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	12118.000	44.60	1.49	46.09	74.00	-27.91	peak	P
2	13469.500	43.49	2.16	45.65	74.00	-28.35	peak	P

Remark:
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value < average limit, So only show the peak value.

Temperature:	23.5℃	**Relative Humidity:**	49%
Test Voltage:	AC 120V/60Hz		
Test Mode:	2DH5 Mode TX 2441 MHz		
Remark:	Only worse case is reported.		

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	10817.500	46.90	-0.36	46.54	74.00	-27.46	peak	P
2	12985.000	44.30	1.75	46.05	74.00	-27.95	peak	P

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11761.000	45.66	1.12	46.78	74.00	-27.22	peak	P
2 *	14566.000	43.78	3.21	46.99	74.00	-27.01	peak	P

Remark:
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value < average limit, So only show the peak value.

Temperature:	23.5℃	**Relative Humidity:**	49%
Test Voltage:	AC 120V/60Hz		
Test Mode:	2DH5 Mode TX 2480 MHz		
Remark:	Only worse case is reported.		

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11710.000	44.50	1.05	45.55	74.00	-28.45	peak	P
2 *	13240.000	43.60	1.96	45.56	74.00	-28.44	peak	P

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	12016.000	44.80	1.46	46.26	74.00	-27.74	peak	P
2 *	13520.500	44.45	2.20	46.65	74.00	-27.35	peak	P

Remark:
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value < average limit, So only show the peak value.

Temperature:	23.5℃	**Relative Humidity:**	49%
Test Voltage:	AC 120V/60Hz		
Test Mode:	3DH5 Mode TX 2402 MHz		
Remark:	Only worse case is reported.		

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11761.000	44.29	1.12	45.41	74.00	-28.59	peak	P
2 *	13520.500	43.59	2.20	45.79	74.00	-28.21	peak	P

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11276.500	44.61	0.45	45.06	74.00	-28.94	peak	P
2 *	13546.000	44.59	2.22	46.81	74.00	-27.19	peak	P

Remark:
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value < average limit, So only show the peak value.

Temperature:	23.5℃	**Relative Humidity:**	49%
Test Voltage:	AC 120V/60Hz		
Test Mode:	3DH5 Mode TX 2441 MHz		
Remark:	Only worse case is reported.		

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	10945.000	46.10	-0.08	46.02	74.00	-27.98	peak	P
2 *	13571.500	44.96	2.25	47.21	74.00	-26.79	peak	P

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	10486.000	47.14	-1.13	46.01	74.00	-27.99	peak	P
2	12832.000	44.03	1.71	45.74	74.00	-28.26	peak	P

Remark:
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value < average limit, So only show the peak value.

Temperature:	23.5℃	**Relative Humidity:**	49%
Test Voltage:	AC 120V/60Hz		
Test Mode:	3DH5 Mode TX 2480 MHz		
Remark:	Only worse case is reported.		

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1	11990.500	43.54	1.43	44.97	74.00	-29.03	peak	P
2 *	13495.000	43.75	2.18	45.93	74.00	-28.07	peak	P

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F
1 *	12092.500	44.67	1.48	46.15	74.00	-27.85	peak	P
2	14081.500	43.16	2.70	45.86	74.00	-28.14	peak	P

Remark:
1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Peak/AVG (dBμV/m)= Corr. (dB/m)+ Read Level (dBμV)
3. Margin (dB) = Peak/AVG (dBμV/m)-Limit PK/AVG(dBμV/m)
4. The tests evaluated 1-26.5GHz, The testing has been conformed to the 10th harmonic of the highest fundamental frequency. Test with highpass filter (Pass Frequency: 2.8-18G and 8-25G), and 18GHz-26.5GHz is the noise, No other signals were detected.
5. No report for the emission which below the prescribed limit.
6. The peak value < average limit, So only show the peak value.

-----END OF THE REPORT------