FCC TEST REPORT
FCC ID: 2BG3K-BT-3301

Report Number.....:	ZHT-240516027E-1
Date of Test..... :	May 16, 2024 to June 20, 2024
Date of issue.....:	June 20, 2024
Test Result .....:	PASS
Testing Laboratory.....:	Guangdong Zhonghan Testing Technology Co., Ltd.
Address ..... :	Room 104, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Applicant's name .....:	XUTHUS INT'L LOGISTICS LTD
Address ..... :	ROOM 419 BULDING 2, ZHIMEIIHUIZHI INDUSTRIAL PARK,FUZHOU ROAD,FUYONG,SHENZHEN,CHINA
Manufacturer's name .....:	XUTHUS INT'L LOGISTICS LTD
Address ..... :	ROOM 419 BULDING 2, ZHIMEIIHUIZHI INDUSTRIAL PARK,FUZHOU ROAD,FUYONG,SHENZHEN,CHINA
Test specification:	
Standard.....:	FCC CFR Title 47 Part 15 Subpart C Section 15.247
Test procedure..... :	ANSI C63.10:2013
Non-standard test method .....:	N/A

This device described above has been tested by ZHT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.
This report shall not be reproduced except in full, without the written approval of ZHT, this document may be altered or revised by ZHT, personal only, and shall be noted in the revision of the document.

Product name..... :	LED WIRELESS CHARGING SPEAKER
Trademark .....:	/
Model/Type reference..... :	BT-3301, BT-3302 BT-3303, BT-3304, BT-3305, BT-3306, BT-3307, BT-3308, BT-3309
Model difference..... :	BT-3301 is tested model, other models are derivative models .The models are identical in circuit, only different on the model names. So the test data of BT-3301 can represent the remaining models.
Ratings..... :	Input: Type-C: 5V, or 3.7V by Built-in Battery Wireless charging Output: 15W Max

Testing procedure and testing location:

Testing Laboratory.....:	Guangdong Zhonghan Testing Technology Co., Ltd.
Address..... :	Room 104, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Tested by (name + signature).....:	Leon Li
Reviewer (name + signature)..... :	Baret Wu
Approved (name + signature)..... :	Levi Lee

Table of Contents

Page
1. VERSION 5
2. TEST SUMMARY 6
2.1 TEST FACILITY 7
2.2 MEASUREMENT UNCERTAINTY 7
3. GENERAL INFORMATION 8
3.1 GENERAL DESCRIPTION OF EUT 8
3.2 Test Setup Configuration 9
3.3 Support Equipment 10
3.4 Test Mode 10
3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS 11
4. EMC EMISSION TEST 13
4.1 Conducted emissions 13
4.1.1 POWER LINE CONDUCTED EMISSION Limits 13
4.1.2 TEST PROCEDURE 13
4.1.3 DEVIATION FROM TEST STANDARD 13
4.1.4 TEST SETUP 14
4.1.5 EUT OPERATING CONDITIONS 14
4.1.6 Test Result 14
4.2 Radiated emissions 17
4.2.1 Radiated Emission Limits 17
4.2.2 TEST PROCEDURE 17
4.2.3 DEVIATION FROM TEST STANDARD 18
4.2.4 TEST SETUP 18
4.2.5 EUT OPERATING CONDITIONS 19
4.2.6 TEST RESULTS 20
5. RADIATED BAND EMISSION MEASUREMENT 28
5.1 Test Requirement: 28
5.2 TEST PROCEDURE 28
5.3 DEVIATION FROM TEST STANDARD 29
5.4 TEST SETUP 29
5.5 EUT OPERATING CONDITIONS 29
5.6 TEST RESULT 30
6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION 32
6.1 Limit 32
6.2 Test Setup 32
6.3 Test procedure 32
6.4 DEVIATION FROM STANDARD 32
6.5 Test Result 33
BAND EDGE 33
BAND EDGE(HOPPING) 40
CONDUCTED RF SPURIOUS EMISSION 47
7. 20DB&99% BANDWIDTH 57
7.1 Test Setup 57
7.2 Limit 57
7.3 Test procedure 57
7.4 DEVIATION FROM STANDARD 57
7.5 Test Result 57
8. MAXIMUM PEAK OUTPUT POWER 68
8.1 Block Diagram Of Test Setup 68
8.2 Limit 68
8.3 Test procedure 68
8.4 DEVIATION FROM STANDARD 68
8.5 Test Result 68
9. HOPPING CHANNEL SEPARATION 74
9.1 Test Setup 74
9.2 Test procedure 74

9.3 DEVIATION FROM STANDARD 74
9.4 Test Result 74
10.NUMBER OF HOPPING FREQUENCY 77
10.1 Test Setup 77
10.2 Test procedure 77
10.3 DEVIATION FROM STANDARD 77
10.4 Test Result 78
11. DWELL TIME 83
11.1 Test Setup 83
11.2 Test procedure 83
11.3 DEVIATION FROM STANDARD 83
11.4 Test Result 84
12. ANTENNA REQUIREMENT 94
13. TEST SETUP PHOTO 95
14. EUT CONSTRUCTIONAL DETAILS 95

1. VERSION

Report No.	Version	Description	Approved
ZHT-240516027E-1	Rev.01	Initial issue of report	June 20, 2024

2. TEST SUMMARY

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Result	Remark
FCC part 15.203/15.247 (b)(4)	Antenna Requirement	PASS	
15.207	AC Power Line Conducted Emission	PASS	
15.247 (b)(1)	Conducted Peak Output Power	PASS	
15.247 (a)(1)	20dB Occupied Bandwidth 99% OCB	PASS	
15.247 (a)(1)	Carrier Frequencies Separation	PASS	
15.247 (a)(1)(iii)	Hopping Channel Number	PASS	
15.247 (a)(1)(iii)	Dwell Time	PASS	
15.205/15.209	Radiated Emission and Restricted Band	PASS	
15.247(d)	Conducted Unwanted emissions and Band Edge	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

2.1 TEST FACILITY

Guangdong Zhonghan Testing Technology Co., Ltd.
Add. : Room 104, Building 1, Yibaolai Industrial Park, Qiaotou Community, Fuhai Street, Bao'an Distric Shenzhen, Guangdong, China

FCC Registration Number:255941
Designation Number: CN0325
IC Registered No.: 29832
CAB identifier: CN0143

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ± U，where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2，providing a level of confidence of approximately 95 %。

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF conducted power	±0.16dB
3	Conducted spurious emissions	±0.21dB
4	All radiated emissions (9k-30MHz)	±4.68dB
5	All radiated emissions (<1G)	±4.68dB
6	All radiated emissions (>1G)	±4.89dB
7	Temperature	±0.5°C
8	Humidity	±2%
9	Occupied Bandwidth	±4.96dB

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	LED WIRELESS CHARGING SPEAKER
Test Model No.:	BT-3301
Hardware Version:	V1.0
Software Version:	V1.0
Sample(s) Status:	Engineer sample
Channel numbers:	79
Channel separation:	2402MHz-2480MHz
Modulation technology:	GFSK, π/4DQPSK, 8DPSK
Antenna Type:	PCB Antenna
Antenna gain:	1.2dBi
Power supply:	Input: Type-C: 5V, or 3.7V by Built-in Battery Wireless charging Output: 15W Max
Sample Number:	240516027E-1#

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

3.2 Test Setup Configuration

Conducted Emission

AC Adapter — EUT

Radiated Emission

AC Adapter — EUT

3.3 Support Equipment

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note

Item	Shielded Type	Ferrite Core	Length	Note

Note:
(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in『Length』column.
(3) The test software is the Bluetooth RF Test Tool which can set the EUT into the individual test modes.TX Power:7

3.4 Test Mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Model	Serial No.	Last Cal.	Next Cal.
1	Receiver	R&S	ESCI	100874	May 10, 2024	May 09, 2025
2	Loop antenna	EMCI	LAP600	272	May 10, 2024	May 09, 2025
3	Amplifier	Schwarzbeck	BBV 9743 B	00378	May 10, 2024	May 09, 2025
4	Amplifier	Schwarzbeck	BBV 9718 B	00040	May 10, 2024	May 09, 2025
5	Bilog Antenna	Schwarzbeck	VULB9168	00498	Aug. 04, 2023	Aug. 03, 2024
6	Horn Antenna	Schwarzbeck	BBHA9120D	02623	May 16, 2024	May 15, 2025
7	Horn Antenna	A.H.SYSTEMS	SAS574	588	May 10, 2024	May 09, 2025
8	Amplifier	AEROFLEX	100KHz-40GHz	097	May 10, 2024	May 09, 2025
9	Spectrum Analyzer	R&S	FSV40	101413	May 10, 2024	May 09, 2025
10	966 Anechoic Chamber	EMToni	9m6m6m	/	Nov. 25, 2021	Nov. 24, 2024
11	Spectrum Analyzer	KEYSIGHT	N9020A	MY53420208	May 10, 2024	May 09, 2025
12	WIDBAND RADIO COMMUNICATION TESTER	R&S	CMW500	109863	May 10, 2024	May 09, 2025
13	Single Generator	Agilent	N5182A	MY48180575	May 10, 2024	May 09, 2025
14	Power Sensor	MWRFtest	MW100-RFCB	/	May 10, 2024	May 09, 2025
15	Power Amplifier Shielding Room	EMToni	2m3m3m	/	Nov. 25, 2021	Nov. 24, 2024

Conduction Test equipment

Equipment	Manufacturer	Model	Serial No.	Last Cal.	Next Cal.
Receiver	R&S	ESCI	100874	May 10, 2024	May 09, 2025
LISN	R&S	ENV216	102794	May 10, 2024	May 09, 2025
ISN CAT 6	Schwarzbeck	NTFM 8158	00318	May 10, 2024	May 09, 2025
ISN CAT 5	Schwarzbeck	CAT5 8158	00343	May 10, 2024	May 09, 2025
Capacitive Voltage Probe	Schwarzbeck	CVP 9222 C	00101	May 10, 2024	May 09, 2025
Current Transformer Clamp	Schwarzbeck	SW 9605	SW9605 #209	May 10, 2024	May 09, 2025
CE Shielding Room	EMToni	9m4m3m	/	Nov. 25, 2021	Nov. 24, 2024

Conducted Test equipment

Item	Equipment	Manufacturer	Model	Serial No.	Last Cal.	Next Cal.
1	Spectrum Analyzer	R&S	FSV40	101413	May 10, 2024	May 09, 2025
2	Spectrum Analyzer	KEYSIGHT	N9020A	MY53420208	May 10, 2024	May 09, 2025
3	Power Sensor	MWRFtest	MW100-RFCB	/	May 10, 2024	May 09, 2025

4. EMC EMISSION TEST

4.1 Conducted emissions

Test Requirement:	FCC Part15 C Section 15.207, RSS-Gen 8.8
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.

4.1.2 TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

4.1.6 Test Result

Temperature:	24.3℃	Relative Humidity :	50%
Pressure:	101kPa	Phase :	L
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.8664	25.53	10.05	35.58	56.00	-20.42	QP	P	
2 *	0.8664	24.59	10.05	34.64	46.00	-11.36	AVG	P	
3	1.7345	22.67	10.06	32.73	56.00	-23.27	QP	P	
4	1.7345	20.31	10.06	30.37	46.00	-15.63	AVG	P	
5	2.5945	19.49	10.06	29.55	56.00	-26.45	QP	P	
6	2.5945	17.38	10.06	27.44	46.00	-18.56	AVG	P	
7	3.0253	17.70	10.07	27.77	56.00	-28.23	QP	P	
8	3.0253	14.89	10.07	24.96	46.00	-21.04	AVG	P	
9	3.4722	18.87	10.08	28.95	56.00	-27.05	QP	P	
10	3.4722	16.04	10.08	26.12	46.00	-19.88	AVG	P	
11	3.9014	19.23	10.09	29.32	56.00	-26.68	QP	P	
12	3.9014	14.27	10.09	24.36	46.00	-21.64	AVG	P	

Notes:
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor

Temperature:	24.3℃	Relative Humidity :	50%
Pressure:	101kPa	Phase :	N
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.8700	24.66	10.05	34.71	56.00	-21.29	QP	P	
2 *	0.8700	24.58	10.05	34.63	46.00	-11.37	AVG	P	
3	1.7340	21.82	10.06	31.88	56.00	-24.12	QP	P	
4	1.7340	19.05	10.06	29.11	46.00	-16.89	AVG	P	
5	2.6070	19.32	10.06	29.38	56.00	-26.62	QP	P	
6	2.6070	17.14	10.06	27.20	46.00	-18.80	AVG	P	
7	3.4754	19.07	10.08	29.15	56.00	-26.85	QP	P	
8	3.4754	16.04	10.08	26.12	46.00	-19.88	AVG	P	
9	3.9120	19.32	10.09	29.41	56.00	-26.59	QP	P	
10	3.9120	14.22	10.09	24.31	46.00	-21.69	AVG	P	
11	7.3814	20.58	10.10	30.68	60.00	-29.32	QP	P	
12	7.3814	10.17	10.10	20.27	50.00	-29.73	AVG	P	

Notes:
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor

4.2 Radiated emissions

Test Requirement:	FCC Part15 C Section 15.209, RSS-Gen 8.9, RSS-Gen 8.10
Test Method:	ANSI C63.10:2013
Test Frequency Range:	9kHz to 25GHz
Test site:	Measurement Distance: 3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Average	1MHz	10Hz	Average

4.2.1 Radiated Emission Limits

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD

No deviation

4.2.4 TEST SETUP

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 TEST RESULTS

Between 9KHz – 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.

Between 30MHz – 1GHz

Temperature:	25.2℃	Relative Humidity:	50%
Pressure:	1010kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	132.2204	53.58	-16.14	37.44	43.50	-6.06	QP
2 !	151.0664	53.04	-15.26	37.78	43.50	-5.72	QP
3 !	175.0365	54.53	-16.65	37.88	43.50	-5.62	QP
4 *	185.1377	56.95	-17.25	39.70	43.50	-3.80	QP
5 !	207.1225	57.41	-17.87	39.54	43.50	-3.96	QP
6 !	211.5263	55.51	-17.68	37.83	43.50	-5.67	QP

Temperature:	25.2℃	Relative Humidity:	50%
Pressure:	1010kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	58.4074	34.43	-15.76	18.67	40.00	-21.33	QP
2	139.8506	42.83	-15.74	27.09	43.50	-16.41	QP
3	168.4137	50.24	-16.27	33.97	43.50	-9.53	QP
4	213.7632	46.67	-17.57	29.10	43.50	-14.40	QP
5 *	377.2590	57.08	-12.53	44.55	46.00	-1.45	QP
6	958.7943	28.89	-2.33	26.56	46.00	-19.44	QP

Remarks:
1.Final Level =Receiver Read level + Antenna Factor + Cable Loss
2.The emission levels of other frequencies are very lower than the limit and not show in test report.
3.The test data shows only the worst case GFSK mode(Low Channel:2402MHz).

1GHz~25GHz

GFSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804.00	58.33	30.55	5.77	24.66	58.21	74	-15.79	Pk
V	4804.00	43.53	30.55	5.77	24.66	43.41	54	-10.59	AV
V	7206.00	59.66	30.33	6.32	24.55	60.2	74	-13.8	Pk
V	7206.00	44.25	30.33	6.32	24.55	44.79	54	-9.21	AV
V	9608.00	55.53	30.55	5.77	24.66	55.41	74	-18.59	Pk
V	9608.00	44.34	30.55	5.77	24.66	44.22	54	-9.78	AV
V	12010.00	59.02	30.33	6.32	24.55	59.56	74	-14.44	Pk
V	12010.00	44.76	30.33	6.32	24.55	45.3	54	-8.7	AV
H	4804.00	56.47	30.55	5.77	24.66	56.35	74	-17.65	Pk
H	4804.00	41.32	30.55	5.77	24.66	41.2	54	-12.8	AV
H	7206.00	58.68	30.33	6.32	24.55	59.22	74	-14.78	Pk
H	7206.00	41.51	30.33	6.32	24.55	42.05	54	-11.95	AV
H	9608.00	57.9	30.55	5.77	24.66	57.78	74	-16.22	Pk
H	9608.00	41.31	30.55	5.77	24.66	41.19	54	-12.81	AV
H	12010.00	59.29	30.33	6.32	24.55	59.83	74	-14.17	Pk
H	12010.00	41.16	30.33	6.32	24.55	41.7	54	-12.3	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2441MHz									
V	4882.00	59.39	30.55	5.77	24.66	59.27	74	-14.73	Pk
V	4882.00	41.95	30.55	5.77	24.66	41.83	54	-12.17	AV
V	7323.00	57.83	30.33	6.32	24.55	58.37	74	-15.63	Pk
V	7323.00	44.08	30.33	6.32	24.55	44.62	54	-9.38	AV
V	9764.00	55.96	30.55	5.77	24.66	55.84	74	-18.16	Pk
V	9764.00	41.47	30.55	5.77	24.66	41.35	54	-12.65	AV
V	12205.00	59.1	30.33	6.32	24.55	59.64	74	-14.36	Pk
V	12205.00	44.16	30.33	6.32	24.55	44.7	54	-9.3	AV
H	4882.00	57.79	30.55	5.77	24.66	57.67	74	-16.33	Pk
H	4882.00	43.4	30.55	5.77	24.66	43.28	54	-10.72	AV
H	7323.00	59.41	30.33	6.32	24.55	59.95	74	-14.05	Pk
H	7323.00	44.27	30.33	6.32	24.55	44.81	54	-9.19	AV
H	9764.00	57.47	30.55	5.77	24.66	57.35	74	-16.65	Pk
H	9764.00	44.15	30.55	5.77	24.66	44.03	54	-9.97	AV
H	12205.00	59.63	30.33	6.32	24.55	60.17	74	-13.83	Pk
H	12205.00	42.79	30.33	6.32	24.55	43.33	54	-10.67	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2480MHz									
V	4960.00	56.73	30.55	5.77	24.66	56.61	74	-17.39	Pk
V	4960.00	41.74	30.55	5.77	24.66	41.62	54	-12.38	AV
V	7440.00	57.62	30.33	6.32	24.55	58.16	74	-15.84	Pk
V	7440.00	41.42	30.33	6.32	24.55	41.96	54	-12.04	AV
V	9920.00	59.54	30.55	5.77	24.66	59.42	74	-14.58	Pk
V	9920.00	41.13	30.55	5.77	24.66	41.01	54	-12.99	AV
V	12400.00	58.96	30.33	6.32	24.55	59.5	74	-14.5	Pk
V	12400.00	41.03	30.33	6.32	24.55	41.57	54	-12.43	AV
H	4960.00	56.47	30.55	5.77	24.66	56.35	74	-17.65	Pk
H	4960.00	41.68	30.55	5.77	24.66	41.56	54	-12.44	AV
H	7440.00	58.78	30.33	6.32	24.55	59.32	74	-14.68	Pk
H	7440.00	42.78	30.33	6.32	24.55	43.32	54	-10.68	AV
H	9920.00	57.36	30.55	5.77	24.66	57.24	74	-16.76	Pk
H	9920.00	42.98	30.55	5.77	24.66	42.86	54	-11.14	AV
H	12400.00	55.15	30.33	6.32	24.55	55.69	74	-18.31	Pk
H	12400.00	42.09	30.33	6.32	24.55	42.63	54	-11.37	AV

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

π/4DQPSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804.00	55.88	30.55	5.77	24.66	55.76	74	-18.24	Pk
V	4804.00	43.64	30.55	5.77	24.66	43.52	54	-10.48	AV
V	7206.00	55.56	30.33	6.32	24.55	56.1	74	-17.9	Pk
V	7206.00	42.28	30.33	6.32	24.55	42.82	54	-11.18	AV
V	9608.00	55.05	30.55	5.77	24.66	54.93	74	-19.07	Pk
V	9608.00	41.46	30.55	5.77	24.66	41.34	54	-12.66	AV
V	12010.00	56.47	30.33	6.32	24.55	57.01	74	-16.99	Pk
V	12010.00	43.36	30.33	6.32	24.55	43.9	54	-10.1	AV
H	4804.00	55.35	30.55	5.77	24.66	55.23	74	-18.77	Pk
H	4804.00	41.5	30.55	5.77	24.66	41.38	54	-12.62	AV
H	7206.00	56.27	30.33	6.32	24.55	56.81	74	-17.19	Pk
H	7206.00	44.3	30.33	6.32	24.55	44.84	54	-9.16	AV
H	9608.00	58.12	30.55	5.77	24.66	58	74	-16	Pk
H	9608.00	41.08	30.55	5.77	24.66	40.96	54	-13.04	AV
H	12010.00	58.89	30.33	6.32	24.55	59.43	74	-14.57	Pk
H	12010.00	41.35	30.33	6.32	24.55	41.89	54	-12.11	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2441MHz									
V	4882.00	57.12	30.55	5.77	24.66	57	74	-17	Pk
V	4882.00	41.97	30.55	5.77	24.66	41.85	54	-12.15	AV
V	7323.00	58.21	30.33	6.32	24.55	58.75	74	-15.25	Pk
V	7323.00	41.29	30.33	6.32	24.55	41.83	54	-12.17	AV
V	9764.00	58.54	30.55	5.77	24.66	58.42	74	-15.58	Pk
V	9764.00	42.95	30.55	5.77	24.66	42.83	54	-11.17	AV
V	12205.00	57.56	30.33	6.32	24.55	58.1	74	-15.9	Pk
V	12205.00	41.56	30.33	6.32	24.55	42.1	54	-11.9	AV
H	4882.00	58.21	30.55	5.77	24.66	58.09	74	-15.91	Pk
H	4882.00	42.11	30.55	5.77	24.66	41.99	54	-12.01	AV
H	7323.00	57.62	30.33	6.32	24.55	58.16	74	-15.84	Pk
H	7323.00	41.79	30.33	6.32	24.55	42.33	54	-11.67	AV
H	9764.00	57.39	30.55	5.77	24.66	57.27	74	-16.73	Pk
H	9764.00	43.6	30.55	5.77	24.66	43.48	54	-10.52	AV
H	12205.00	55.14	30.33	6.32	24.55	55.68	74	-18.32	Pk
H	12205.00	41.68	30.33	6.32	24.55	42.22	54	-11.78	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2480MHz									
V	4960.00	58.87	30.55	5.77	24.66	58.75	74	-15.25	Pk
V	4960.00	41.5	30.55	5.77	24.66	41.38	54	-12.62	AV
V	7440.00	58.46	30.33	6.32	24.55	59	74	-15	Pk
V	7440.00	43.61	30.33	6.32	24.55	44.15	54	-9.85	AV
V	9920.00	59.43	30.55	5.77	24.66	59.31	74	-14.69	Pk
V	9920.00	41.29	30.55	5.77	24.66	41.17	54	-12.83	AV
V	12400.00	55.31	30.33	6.32	24.55	55.85	74	-18.15	Pk
V	12400.00	41.85	30.33	6.32	24.55	42.39	54	-11.61	AV
H	4960.00	55.94	30.55	5.77	24.66	55.82	74	-18.18	Pk
H	4960.00	41.01	30.55	5.77	24.66	40.89	54	-13.11	AV
H	7440.00	58.39	30.33	6.32	24.55	58.93	74	-15.07	Pk
H	7440.00	41.34	30.33	6.32	24.55	41.88	54	-12.12	AV
H	9920.00	58.87	30.55	5.77	24.66	58.75	74	-15.25	Pk
H	9920.00	43.38	30.55	5.77	24.66	43.26	54	-10.74	AV
H	12400.00	55.42	30.33	6.32	24.55	55.96	74	-18.04	Pk
H	12400.00	41.43	30.33	6.32	24.55	41.97	54	-12.03	AV

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

8DPSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804.00	58.82	30.55	5.77	24.66	58.7	74	-15.3	Pk
V	4804.00	42.72	30.55	5.77	24.66	42.6	54	-11.4	AV
V	7206.00	58.49	30.33	6.32	24.55	59.03	74	-14.97	Pk
V	7206.00	42.9	30.33	6.32	24.55	43.44	54	-10.56	AV
V	9608.00	55.23	30.55	5.77	24.66	55.11	74	-18.89	Pk
V	9608.00	41.59	30.55	5.77	24.66	41.47	54	-12.53	AV
V	12010.00	57.12	30.33	6.32	24.55	57.66	74	-16.34	Pk
V	12010.00	42.27	30.33	6.32	24.55	42.81	54	-11.19	AV
H	4804.00	55.2	30.55	5.77	24.66	55.08	74	-18.92	Pk
H	4804.00	41.83	30.55	5.77	24.66	41.71	54	-12.29	AV
H	7206.00	58.3	30.33	6.32	24.55	58.84	74	-15.16	Pk
H	7206.00	43.8	30.33	6.32	24.55	44.34	54	-9.66	AV
H	9608.00	59.03	30.55	5.77	24.66	58.91	74	-15.09	Pk
H	9608.00	41.17	30.55	5.77	24.66	41.05	54	-12.95	AV
H	12010.00	56.88	30.33	6.32	24.55	57.42	74	-16.58	Pk
H	12010.00	41.88	30.33	6.32	24.55	42.42	54	-11.58	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2441MHz									
V	4882.00	55.55	30.55	5.77	24.66	55.43	74	-18.57	Pk
V	4882.00	41.62	30.55	5.77	24.66	41.5	54	-12.5	AV
V	7323.00	59.34	30.33	6.32	24.55	59.88	74	-14.12	Pk
V	7323.00	43.26	30.33	6.32	24.55	43.8	54	-10.2	AV
V	9764.00	55.53	30.55	5.77	24.66	55.41	74	-18.59	Pk
V	9764.00	42.93	30.55	5.77	24.66	42.81	54	-11.19	AV
V	12205.00	55.65	30.33	6.32	24.55	56.19	74	-17.81	Pk
V	12205.00	44.93	30.33	6.32	24.55	45.47	54	-8.53	AV
H	4882.00	59.71	30.55	5.77	24.66	59.59	74	-14.41	Pk
H	4882.00	43.24	30.55	5.77	24.66	43.12	54	-10.88	AV
H	7323.00	59.53	30.33	6.32	24.55	60.07	74	-13.93	Pk
H	7323.00	44.71	30.33	6.32	24.55	45.25	54	-8.75	AV
H	9764.00	58.15	30.55	5.77	24.66	58.03	74	-15.97	Pk
H	9764.00	42.73	30.55	5.77	24.66	42.61	54	-11.39	AV
H	12205.00	55.01	30.33	6.32	24.55	55.55	74	-18.45	Pk
H	12205.00	43.64	30.33	6.32	24.55	44.18	54	-9.82	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2480MHz									
V	4960.00	59.69	30.55	5.77	24.66	59.57	74	-14.43	Pk
V	4960.00	41.46	30.55	5.77	24.66	41.34	54	-12.66	AV
V	7440.00	57.76	30.33	6.32	24.55	58.3	74	-15.7	Pk
V	7440.00	44.46	30.33	6.32	24.55	45	54	-9	AV
V	9920.00	56.43	30.55	5.77	24.66	56.31	74	-17.69	Pk
V	9920.00	41.05	30.55	5.77	24.66	40.93	54	-13.07	AV
V	12400.00	57.31	30.33	6.32	24.55	57.85	74	-16.15	Pk
V	12400.00	41.2	30.33	6.32	24.55	41.74	54	-12.26	AV
H	4960.00	55.48	30.55	5.77	24.66	55.36	74	-18.64	Pk
H	4960.00	41.1	30.55	5.77	24.66	40.98	54	-13.02	AV
H	7440.00	58.62	30.33	6.32	24.55	59.16	74	-14.84	Pk
H	7440.00	41.09	30.33	6.32	24.55	41.63	54	-12.37	AV
H	9920.00	59.25	30.55	5.77	24.66	59.13	74	-14.87	Pk
H	9920.00	44.35	30.55	5.77	24.66	44.23	54	-9.77	AV
H	12400.00	55.72	30.33	6.32	24.55	56.26	74	-17.74	Pk
H	12400.00	44.24	30.33	6.32	24.55	44.78	54	-9.22	AV

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

5. RADIATED BAND EMISSION MEASUREMENT

5.1 Test Requirement:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205, RSS-Gen 8.9, RSS-Gen 8.10
Test Method:	ANSI C63.10: 2013
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.
Test site:	Measurement Distance: 3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Value
Above 1GHz	Peak	1MHz	3MHz	Peak
	Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

g. Test the EUT in the lowest channel,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULT

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
GFSK	Low Channel: 2402MHz										
	H	2390.00	59.73	30.22	4.85	23.98	58.34	74.00	-15.66	PK	PASS
	H	2390.00	46.18	30.22	4.85	23.98	44.79	54.00	-9.21	AV	PASS
	H	2400.00	62.91	30.22	4.85	23.98	61.52	74.00	-12.48	PK	PASS
	H	2400.00	47.71	30.22	4.85	23.98	46.32	54.00	-7.68	AV	PASS
	V	2390.00	62.22	30.22	4.85	23.98	60.83	74.00	-13.17	PK	PASS
	V	2390.00	48.35	30.22	4.85	23.98	46.96	54.00	-7.04	AV	PASS
	V	2400.00	61.57	30.22	4.85	23.98	60.18	74.00	-13.82	PK	PASS
	V	2400.00	48.69	30.22	4.85	23.98	47.30	54.00	-6.70	AV	PASS
	High Channel: 2480MHz										
	H	2483.50	61.65	30.22	4.85	23.98	60.26	74.00	-13.74	PK	PASS
	H	2483.50	47.09	30.22	4.85	23.98	45.70	54.00	-8.30	AV	PASS
	H	2500.00	59.99	30.22	4.85	23.98	58.60	74.00	-15.40	PK	PASS
	H	2500.00	47.42	30.22	4.85	23.98	46.03	54.00	-7.97	AV	PASS
	V	2483.50	59.02	30.22	4.85	23.98	57.63	74.00	-16.37	PK	PASS
	V	2483.50	47.89	30.22	4.85	23.98	46.50	54.00	-7.50	AV	PASS
	V	2500.00	61.13	30.22	4.85	23.98	59.74	74.00	-14.26	PK	PASS
	V	2500.00	48.03	30.22	4.85	23.98	46.64	54.00	-7.36	AV	PASS
π/4DQPSK	Low Channel: 2402MHz										
	H	2390.00	62.17	30.22	4.85	23.98	60.78	74.00	-13.22	PK	PASS
	H	2390.00	46.86	30.22	4.85	23.98	45.47	54.00	-8.53	AV	PASS
	H	2400.00	62.53	30.22	4.85	23.98	61.14	74.00	-12.86	PK	PASS
	H	2400.00	46.39	30.22	4.85	23.98	45.00	54.00	-9.00	AV	PASS
	V	2390.00	60.46	30.22	4.85	23.98	59.07	74.00	-14.93	PK	PASS
	V	2390.00	47.49	30.22	4.85	23.98	46.10	54.00	-7.90	AV	PASS
	V	2400.00	61.28	30.22	4.85	23.98	59.89	74.00	-14.11	PK	PASS
	V	2400.00	48.11	30.22	4.85	23.98	46.72	54.00	-7.28	AV	PASS
	High Channel: 2480MHz										
	H	2483.50	61.43	30.22	4.85	23.98	60.04	74.00	-13.96	PK	PASS
	H	2483.50	47.57	30.22	4.85	23.98	46.18	54.00	-7.82	AV	PASS
	H	2500.00	61.54	30.22	4.85	23.98	60.15	74.00	-13.85	PK	PASS
	H	2500.00	46.30	30.22	4.85	23.98	44.91	54.00	-9.09	AV	PASS
	V	2483.50	61.13	30.22	4.85	23.98	59.74	74.00	-14.26	PK	PASS
	V	2483.50	46.54	30.22	4.85	23.98	45.15	54.00	-8.85	AV	PASS
	V	2500.00	59.38	30.22	4.85	23.98	57.99	74.00	-16.01	PK	PASS
	V	2500.00	48.37	30.22	4.85	23.98	46.98	54.00	-7.02	AV	PASS

8DPSK	Low Channel: 2402MHz										
	H	2390.00	60.79	30.22	4.85	23.98	59.40	74.00	-14.60	PK	PASS
	H	2390.00	47.11	30.22	4.85	23.98	45.72	54.00	-8.28	AV	PASS
	H	2400.00	61.45	30.22	4.85	23.98	60.06	74.00	-13.94	PK	PASS
	H	2400.00	46.09	30.22	4.85	23.98	44.70	54.00	-9.30	AV	PASS
	V	2390.00	62.78	30.22	4.85	23.98	61.39	74.00	-12.61	PK	PASS
	V	2390.00	48.91	30.22	4.85	23.98	47.52	54.00	-6.48	AV	PASS
	V	2400.00	59.20	30.22	4.85	23.98	57.81	74.00	-16.19	PK	PASS
	V	2400.00	48.29	30.22	4.85	23.98	46.90	54.00	-7.10	AV	PASS
	High Channel: 2480MHz										
	H	2483.50	59.92	30.22	4.85	23.98	58.53	74.00	-15.47	PK	PASS
	H	2483.50	46.30	30.22	4.85	23.98	44.91	54.00	-9.09	AV	PASS
	H	2500.00	60.59	30.22	4.85	23.98	59.20	74.00	-14.80	PK	PASS
	H	2500.00	48.35	30.22	4.85	23.98	46.96	54.00	-7.04	AV	PASS
	V	2483.50	61.08	30.22	4.85	23.98	59.69	74.00	-14.31	PK	PASS
	V	2483.50	46.27	30.22	4.85	23.98	44.88	54.00	-9.12	AV	PASS
	V	2500.00	60.67	30.22	4.85	23.98	59.28	74.00	-14.72	PK	PASS
	V	2500.00	47.83	30.22	4.85	23.98	46.44	54.00	-7.56	AV	PASS

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d), RSS-247 5.5
Test Method:	ANSI C63.10

6.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter com-plies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

According to RSS-247§5.5 and RSS-Gen§8.9, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) or RSS-Gen is not required.

6.2 Test Setup



6.3 Test procedure

Using the following spectrum analyzer setting:
A) Set the RBW = 100KHz.
B) Set the VBW = 300KHz.
C) Sweep time = auto couple.
D) Detector function = peak.
E) Trace mode = max hold.
F) Allow trace to fully stabilize.

6.4 DEVIATION FROM STANDARD

No deviation.

6.5 Test Result

Band Edge

Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
1-DH5	2402	-51.61	-20	Pass
1-DH5	2480	-52.96	-20	Pass
2-DH5	2402	-50.26	-20	Pass
2-DH5	2480	-52.7	-20	Pass
3-DH5	2402	-52.69	-20	Pass
3-DH5	2480	-52.38	-20	Pass

Test Graphs

Band Edge NVNT 1-DH5 2402MHz Ant1 No-Hopping Ref



Band Edge NVNT 1-DH5 2402MHz Ant1 No-Hopping Emission



Band Edge NVNT 1-DH5 2480MHz Ant1 No-Hopping Ref



Band Edge NVNT 1-DH5 2480MHz Ant1 No-Hopping Emission

Band Edge NVNT 2-DH5 2402MHz Ant1 No-Hopping Ref



Band Edge NVNT 2-DH5 2402MHz Ant1 No-Hopping Emission



Band Edge NVNT 2-DH5 2480MHz Ant1 No-Hopping Ref



Band Edge NVNT 2-DH5 2480MHz Ant1 No-Hopping Emission

Band Edge NVNT 3-DH5 2402MHz Ant1 No-Hopping Ref



Band Edge NVNT 3-DH5 2402MHz Ant1 No-Hopping Emission

Band Edge NVNT 3-DH5 2480MHz Ant1 No-Hopping Ref



Band Edge NVNT 3-DH5 2480MHz Ant1 No-Hopping Emission

Band Edge(Hopping)

Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
1-DH5	2402	-52.72	-20	Pass
1-DH5	2480	-52.42	-20	Pass
2-DH5	2402	-49.78	-20	Pass
2-DH5	2480	-52.17	-20	Pass
3-DH5	2402	-53.58	-20	Pass
3-DH5	2480	-52.39	-20	Pass

Test Graphs

Band Edge(Hopping) NVNT 1-DH5 2402MHz Ant1 Hopping Ref



Band Edge(Hopping) NVNT 1-DH5 2402MHz Ant1 Hopping Emission

Band Edge(Hopping) NVNT 1-DH5 2480MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 1-DH5 2480MHz Ant1 Hopping Emission

Band Edge(Hopping) NVNT 2-DH5 2402MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 2-DH5 2402MHz Ant1 Hopping Emission

Band Edge(Hopping) NVNT 2-DH5 2480MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 2-DH5 2480MHz Ant1 Hopping Emission

Band Edge(Hopping) NVNT 3-DH5 2402MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 3-DH5 2402MHz Ant1 Hopping Emission

Band Edge(Hopping) NVNT 3-DH5 2480MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 3-DH5 2480MHz Ant1 Hopping Emission

Conducted RF Spurious Emission

Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
1-DH5	2402	-43.09	-20	Pass
1-DH5	2441	-41.75	-20	Pass
1-DH5	2480	-39.18	-20	Pass
2-DH5	2402	-43.7	-20	Pass
2-DH5	2441	-42.05	-20	Pass
2-DH5	2480	-40.72	-20	Pass
3-DH5	2402	-43.83	-20	Pass
3-DH5	2441	-40.47	-20	Pass
3-DH5	2480	-41.95	-20	Pass

Test Graphs

Tx. Spurious NVNT 1-DH5 2402MHz Ant1 Ref



Tx. Spurious NVNT 1-DH5 2402MHz Ant1 Emission

Tx. Spurious NVNT 1-DH5 2441MHz Ant1 Ref



Tx. Spurious NVNT 1-DH5 2441MHz Ant1 Emission

Tx. Spurious NVNT 1-DH5 2480MHz Ant1 Ref



Tx. Spurious NVNT 1-DH5 2480MHz Ant1 Emission



Tx. Spurious NVNT 2-DH5 2402MHz Ant1 Ref



Tx. Spurious NVNT 2-DH5 2402MHz Ant1 Emission

Tx. Spurious NVNT 2-DH5 2441MHz Ant1 Ref



Tx. Spurious NVNT 2-DH5 2441MHz Ant1 Emission

Tx. Spurious NVNT 2-DH5 2480MHz Ant1 Ref



Tx. Spurious NVNT 2-DH5 2480MHz Ant1 Emission

Tx. Spurious NVNT 3-DH5 2402MHz Ant1 Ref



Tx. Spurious NVNT 3-DH5 2402MHz Ant1 Emission

Tx. Spurious NVNT 3-DH5 2441MHz Ant1 Ref

Tx. Spurious NVNT 3-DH5 2441MHz Ant1 Emission

Tx. Spurious NVNT 3-DH5 2480MHz Ant1 Ref



Tx. Spurious NVNT 3-DH5 2480MHz Ant1 Emission



7. 20DB&99% BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.247 (a)(1), RSS 247 5.1, RSS-Gen 6.7
Test Method:	ANSI C63.10:2013

7.1 Test Setup

7.2 Limit

According to RSS-247§5.1(a)& §5.1(b), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

7.3 Test procedure

1. Set RBW = 30 kHz.
2. Set the video bandwidth (VBW) ≥ 3 x RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
8. The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30KHz RBW and 100 KHz VBW record the 99% bandwidth.

7.4 DEVIATION FROM STANDARD

No deviation.

7.5 Test Result

Mode	Test channel	20dB Emission Bandwidth (MHz)	99%Bandwidth (MHz)	Result
GFSK	Lowest	1.03	0.937	Pass
	Middle	1.04	0.958	
	Highest	1.034	0.965	
π/4DQPSK	Lowest	1.331	1.233	Pass
	Middle	1.342	1.248	
	Highest	1.34	1.241	
8DPSK	Lowest	1.312	1.224	Pass
	Middle	1.312	1.235	
	Highest	1.301	1.227	

Test Graphs

-20dB Bandwidth NVNT 1-DH5 2402MHz Ant1



-20dB Bandwidth NVNT 1-DH5 2441MHz Ant1



-20dB Bandwidth NVNT 1-DH5 2480MHz Ant1



-20dB Bandwidth NVNT 2-DH5 2402MHz Ant1



-20dB Bandwidth NVNT 2-DH5 2441MHz Ant1



-20dB Bandwidth NVNT 2-DH5 2480MHz Ant1



-20dB Bandwidth NVNT 3-DH5 2402MHz Ant1



-20dB Bandwidth NVNT 3-DH5 2441MHz Ant1



-20dB Bandwidth NVNT 3-DH5 2480MHz Ant1



OBW NVNT 1-DH5 2402MHz Ant1



OBW NVNT 1-DH5 2441MHz Ant1


Keysight Spectrum Analyzer - Occupied BW
Center Freq 2.441000000 GHz
Center Freq: 2.441000000 GHz
Trig: Free Run
#Atten: 30 dB
Avg|Hold: 100/100
Radio Std: None
Radio Device: BTS
11:27:38 AM May 30, 2024
#IFGain:Low
Ref Offset 2.04 dB
10 dB/div
Ref 22.04 dBm
Mkr1 2.4410321 GHz
-3.9543 dBm
Center 2.441 GHz
#Res BW 30 kHz
#VBW 100 kHz
Span 3 MHz
Sweep 3.333 ms
Occupied Bandwidth
958.09 kHz
Total Power 5.61 dBm
Transmit Freq Error 10.972 kHz
% of OBW Power 99.00 %
x dB Bandwidth 1.059 MHz
x dB -20.00 dB
MSG
STATUS

OBW NVNT 1-DH5 2480MHz Ant1



OBW NVNT 2-DH5 2402MHz Ant1



OBW NVNT 2-DH5 2441MHz Ant1



OBW NVNT 2-DH5 2480MHz Ant1