

SPECIFICATION

for

0dBi glue stick 2.4G WIFI antenna

Customer No.

Product No.

TX-2.4G rubber stick antenna

Author: XiaofengZeng Review: Liming

Release Date: 2024.10.08

ShenZhen Tianxing Communications Co., Ltd

1st Floor, Building 2, No. 71 Tianwan Road, Tianliao Community, Yutang Street,Guangming
District, Shenzhen

E-mail: sz_shuodian@163.com

Tel: 0755-86006322

Fax: 0755-86006323

Shenzhen Tianxing Communications Co., Ltd.

Contents

<u>SPECIFICATION.....</u>	<u>1</u>
<u>SHENZHEN TIANXING COMMUNICATIONS CO., LTD.....</u>	<u>1</u>
<u>CONTENTS</u>	<u>1</u>
<u>1. BILATERAL CONFIRMATION PAGE</u>	<u>3</u>
<u>2. GENERAL</u>	<u>4</u>
<u>3. GENERAL PRODUCT SPECIFICATIONS</u>	<u>4</u>
<u>4. SPECIFICATION DETIALS</u>	<u>5</u>
<u>4.1 MECHANICAL PROPERTIES</u>	<u>5</u>
<u>4.2 ELECTRIC PERFORMANCE</u>	<u>7</u>
<u>5. PRODUCT PACKAGING</u>	<u>9</u>
<u>6. DOCUMENT RESUME</u>	<u>9</u>

1. Bilateral Confirmation page

1.1 Customer signature

Customer:

Seapartment/post	Sign	Date
Hardware Engineer/RD		
Mechanical/MD		
Project Manager/PM		
Commercial/Puchasing		
Checker		

1.2 Signature of Tianxing Communications

Seapartment/post	Sign	Date
Antenna Engineer/RD		
Mechanical/MD		
Project Manager/PM		
QA		
Checker		

2. General

2.1 Scope of application

2.4G WIFI Antenna

2.2 Operating temperature range

Temperature range of this product: -20 ~ +65 °C

2.3 Storage temperature range:

This product is stored at - 30 ~ + 75 °C

3. General product specifications

NO.	ITEMS	DETAILS
1	Type	2.4G WIFI Antenna
2	Operating Frequency Band	2400-2500MHz
3	VSWR	≤ 2.5
4	Gain	0dBi
5	Impedance	50 Ω
6	Antenna Type	Glue stick antenna
7	Antenna composition	Glue stick
8	Entity Picture	

4. Specification Details

4.1 Mechanical Properties


4.11 Product Composition:

4.12 Apperance

Good appearance without scars 、dirts、protuberances, etc.

4.13 Antenna Picture and Structure Dimension

Product drawings:



4.2 Electric Performance


4.21 Test condition

Environment:	Equipment:
Temperature: 10℃——+30℃	Network Analyzer: KEYSIGHT E5071C
Humidity: ≤80% (+40℃)	AnechiorChamber:Multi-probe
Atmospher: 750mmkg±30mmkg	Microwave

4.22 Test Data for Electrical Performance:

4.22.1 S11 of the Antenna:


Marker (MHZ)	2400	2450	2500
Returnloss	-8.31	-10.82	-16.25
VSWR	2.21	1.75	1.30



4. 22. 2 Passive gain、 efficiency and Radiation Pattern:

Marker (MHz)	2400	2450	2500
Gain (dBi)	-0.26	0	-0.28
Efficiency (%)	54.5	57.4	55.8

2450 MHz:



5. Product Packaging

Manner of packing: Packed in self sealed bags, 200 pcs each.

6. Document Resume

Document No.	
Release Date	2024/10/08
Author	XiofengZeng
Review	LiMing

Revised History

Date	Version	Revised Record
2024/10/8	1.00	New Project