

FCC PART 15.249

TEST REPORT

For

Zhejiang Desman Intelligent Technology Co., LTD

Floor 1-3, Building 1, No.7 Jianghui South Road, Binjiang District, Hangzhou City, Zhejiang Province, China, 310051

FCC ID: 2BG5G-K140PLUS

Report Type: Amended Report	Product Name: Smart Lock
Report Number:	<u>RKSA260104001-00AM1</u>
Report Date:	<u>2026-02-02</u>
Reviewed By:	<u>Jenny Yang</u> Jenny Yang
Approved By:	<u>Kyle Xu</u> Kyle Xu
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu Province, China Tel: +86-512-86175000 Fax: +86-512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Kunshan). This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, or any agency of the U.S. Government.



TABLE OF CONTENTS

REPORT REVISION HISTORY	3
GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
JUSTIFICATION	6
EUT EXERCISE SOFTWARE	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	9
TEST EQUIPMENT LIST	10
FCC§15.203 - ANTENNA REQUIREMENT.....	12
APPLICABLE STANDARD	12
ANTENNA CONNECTOR CONSTRUCTION	12
FCC §15.207 (A) - AC LINE CONDUCTED EMISSIONS	13
APPLICABLE STANDARD	13
TEST SYSTEM SETUP.....	13
EMI TEST RECEIVER SETUP.....	13
TEST PROCEDURE	14
TEST RESULTS SUMMARY	14
TEST DATA: SEE APPENDIX	14
FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS& OUT OF BAND EMISSION.....	15
APPLICABLE STANDARD	15
TEST SYSTEM SETUP.....	15
TEST EQUIPMENT SETUP	18
TEST PROCEDURE	18
TEST RESULTS SUMMARY	19
TEST DATA: SEE APPENDIX	19
FCC §15.215(C) - 20 DB BANDWIDTH TESTING.....	20
APPLICABLE STANDARD	20
TEST PROCEDURE	20
TEST DATA: SEE APPENDIX	20
APPENDIX - TEST DATA.....	21
CONDUCTED EMISSIONS	21
RADIATED EMISSIONS	24
FUNDAMENTAL AND BAND EDGE TEST	34
20 DB BANDWIDTH TESTING	36
EUT PHOTOGRAPHS.....	37
TEST SETUP PHOTOGRAPHS	38

REPORT REVISION HISTORY

Version	Report No.	Issue Date	Description
R1V1	RKSA260104001-00A	2026-01-28	Initial Release
R1V2	RKSA260104001-00AM1	2026-02-02	1. Add CE data of power terminal 2. Update the version to ANSI C63.10-2020

Note: The amended report (Report No.: RKSA260104001-00AM1) supersedes and replaces the previous issued report (RKSA260104001-00A). Please discard or destroy the previous issued report and dispose of it accordingly.

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	Zhejiang Desman Intelligent Technology Co., LTD
Tested Model:	K140PLUS
Product Name:	Smart Lock
Power Supply:	DC 3.7V from battery or DC 5V from USB port
RF Function:	24G SRD
Operating Band/Frequency:	24.00 GHz - 24.25 GHz
Maximum Field Strength of Fundamental:	99.22 dB μ V/m @3m
Modulation Type:	FMCW
Antenna Type:	PCB Antenna
★Maximum Antenna Gain:	5.84 dBi
Sample/EUT Status:	Good condition

Note: The maximum antenna gain is provided by the applicant.

All measurement and test data in this report was gathered from production sample serial number: RKSA260104001-1 (Assigned by the BACL (Kunshan). The EUT supplied by the applicant was received on 2026-01-04)

Objective

This type approval report is prepared for *Zhejiang Desman Intelligent Technology Co., LTD* in accordance with Part 2-Subpart J, and Part 15-Subparts A and C of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209, 15.215 and 15.249 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19 dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	9 kHz~150 kHz	3.8dB
	150 kHz~30 MHz	3.4dB
	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
	40GHz ~50GHz	4.92dB
	50GHz ~75GHz	5.16dB
	75GHz ~100GHz	5.64dB
Occupied Bandwidth		0.5kHz
Temperature		1.0℃
Humidity		6%

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu Province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) is accredited in accordance with ISO/IEC 17025:2017 by NVLAP (Lab code: 600338-0), and the lab has been recognized as the FCC accredited lab under the KDB 974614 D01, the FCC Designation No.: CN5055.

SYSTEM TEST CONFIGURATION**Justification**

Operation Frequency Details:

Sweep Start Frequency (MHz)	Sweep Stop Frequency (MHz)
24010	24240
The below frequencies were tested:	
Low Channel	24010
Middle Channel	24110
High Channel	24240

EUT Exercise Software

The system was configured for testing in an engineering mode, which was provided by manufacturer Engineer Mode was used during the test.

★Power level: Default

Note: The power level was declared by the applicant.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Power on Tools Co., Ltd	Adapter	DA-00052000UL001	/
/	Power strip	/	/

External I/O Cable


Cable Description	Length (m)	From Port	To Port
Power Cable 1	1.0	EUT	Adapter
Power Cable 2	1.0	Power strip	LISN

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions(Below 1GHz):



For Radiated Emissions(Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
15.205, §15.209, §15.249	Radiated Emissions& Out of Band Emission	Compliant
§15.215 (c)	20 dB Bandwidth	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2025-04-09	2026-04-08
Sunol Sciences	Hybrid Antenna	JB3	A090314-1	2024-11-08	2027-11-07
Sonoma Instrument	Pre-amplifier	310N	171205	2025-04-09	2026-04-08
Rohde & Schwarz	Auto test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-8	008	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-9	009	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-10	010	2025-04-09	2026-04-08
BACL	Active Loop Antenna	1313-1A	4041511	2025-08-10	2028-08-09
Narda	6 dB Attenuator	773-6	10690812-2-1	2024-11-08	2027-11-07
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2025-04-09	2026-04-08
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2023-06-27	2026-06-26
ETS-LINDGREN	Horn Antenna	3116	2516	2024-12-12	2027-12-11
A.H.Systems, inc	Amplifier	PAM-0118P	512	2025-04-09	2026-04-08
SELECTOR	Amplifier	EM18G40G	60726	2025-04-09	2026-04-08
Rohde & Schwarz	Auto test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-11	011	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-12	012	2025-04-09	2026-04-08
MICRO-COAX	Coaxial Cable	Cable-13	013	2025-04-09	2026-04-08
FMI	Horn Antenna	24245-AB	51	2025-04-09	2026-04-08
HP	Harmonic Mixer	11970U	2332A00837	2025-04-09	2026-04-08
SAGE	WR-15 Rectangular Gain Horn	SAR-2408-15-S2	13563-08	2025-04-09	2026-04-08
HP	Harmonic Mixer	11970V	611	2025-04-09	2026-04-08
SAGE	Horn Antenna	SAR-2309-10-S2	15633-04	2025-04-09	2026-04-08
HP	Harmonic Mixer	11970W	2521A00535	2025-04-09	2026-04-08
Narda	Attenuator	10dB	10dB-01	2025-04-08	2026-04-07
Rohde & Schwarz	Auto test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-6	006	2025-04-09	2026-04-08

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2025-09-01	2026-08-31
Rohde & Schwarz	LISN	ENV216	101115	2025-04-08	2026-04-07
Audix	Test Software	e3	V9	N/A	N/A
Rohde & Schwarz	Pulse limiter	ESH3-Z2	100552	2025-04-08	2026-04-07
MICRO-COAX	Coaxial Cable	Cable-15	015	2025-04-08	2026-04-07

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.203 - ANTENNA REQUIREMENT

Applicable Standard

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

Antenna Connector Construction

The EUT has a PCB antenna which is permanently attached to the EUT, fulfill the requirement of this section, please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

Test System Setup



The measurement procedure of EUT setup is according with ANSI C63.10-2020. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW
150 kHz - 30 MHz	9 kHz

Test Procedure

ANSI C63.10-2020 clause 6.2

During the conducted emission test, the EUT was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

If the maximum peak value of the emissions is below the average limit, the QP value and average value measurement will not need to be performed and only record the maximum peak measured value to meet the requirements.

Level & Over Limit Calculation

The Level is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation from the Meter Reading. The basic equation is as follows:

Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)

Level (dBμV) = Read level (dBμV) + Factor (dB)

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7 dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

Over Limit (dB) = Level (dBμV) - Limit (dBμV)

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data: See Appendix

FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS& OUT OF BAND EMISSION

Applicable Standard

As per FCC§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:


Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24GHz-24.25GHz	250	2500

As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.


(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Test System Setup


9 kHz - 30 MHz:





30 MHz - 1 GHz:



1 GHz - 18 GHz:



18 GHz - 40 GHz:**40 GHz - 100 GHz:**

The radiated emission and out of band emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15.209/15.205 and FCC 15.249 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

Test Equipment Setup

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	VBW	IF B/W	Detector	Measurement
9 kHz - 150 kHz	200 Hz	1 kHz	200 Hz	QP/Peak/Average	QP/Peak/Average
150 kHz - 30 MHz	9 kHz	30 kHz	9 kHz	QP/Peak/Average	QP/Peak/Average
30 MHz - 1000 MHz	100 kHz	300 kHz	/	Peak	Peak
	/	/	120 kHz	QP	QP
1 GHz-40 GHz	1MHz	3 MHz	/	Peak	Peak
	1MHz	3 MHz	/	Average	Average
40 GHz-100 GHz	1MHz	3 MHz	/	Peak	Peak
	1MHz	10Hz	/	Peak	Average

Note: If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform a QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

If the measured peak level of the emissions that the measuring receiver reading level plus corrected factor is at least 10 dB below the QP emission limit, there's no need to record the measured QP level of the emissions in the report.

For 9 kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude (dBμV/m) = Meter Reading (dBμV) + Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

Note: The QuasiPeak (dBμV/m), MaxPeak (dBμV/m), Average (dBμV/m) which shown in the data table are all Corrected Amplitude.

The “**Margin/ Over Limit**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)
Over Limit (dB) = Level (dBμV/m) - Limit (dBμV/m)

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209 &15.205 & 15.249.

Test Data: See Appendix

FCC §15.215(c) - 20 dB BANDWIDTH TESTING


Applicable Standard

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test System Setup



Test Data: See Appendix


APPENDIX - TEST DATA

CONDUCTED EMISSIONS**Environmental Conditions & Test Information**

Test Date:	2026-01-30
Temperature:	15.9°C
Relative Humidity:	31 %
ATM Pressure:	103.0 kPa
Test Result:	Pass
Test Engineer:	Carto Sun

Line:

Date: 2026-01-30



Trace: 1

Site : CE

Condition : limit\FCC PART 15.207\FCC 15.207 QP.csv Line

Project No. : RKSA260104001

Model : K140PLUS

Phase : L

Voltage : 120V/60Hz

Mode : SRD

Test Equipment : ENV216,ESR3

Receiver Setting : RBW: 9 kHz, Sweep Time: Auto

Temperature : 15.9°C

Humidity : 31%


Atmospheric pressure: 103.0kPa

Test Engineer : Jack He

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.429	11.00	20.29	31.29	47.26	-15.97	Average
2	0.429	17.90	20.29	38.19	57.26	-19.07	QP
3	0.504	11.10	20.17	31.27	46.00	-14.73	Average
4	0.504	17.30	20.17	37.47	56.00	-18.53	QP
5	0.672	10.10	20.25	30.35	46.00	-15.65	Average
6	0.672	14.80	20.25	35.05	56.00	-20.95	QP
7	2.557	9.40	20.27	29.67	46.00	-16.33	Average
8	2.557	14.30	20.27	34.57	56.00	-21.43	QP
9	3.297	10.10	20.23	30.33	46.00	-15.67	Average
10	3.297	14.90	20.23	35.13	56.00	-20.87	QP
11	28.827	12.90	20.70	33.60	50.00	-16.40	Average
12	28.827	17.90	20.70	38.60	60.00	-21.40	QP

Neutral:

Date: 2026-01-30



Trace: 1

Site : CE
 Condition : limit\FCC PART 15.207\FCC 15.207 QP.csv Neutral
 : DET:Peak
 Project No. : RKSA260104001
 Model : K140PLUS
 Phase : N
 Voltage : 120V/60Hz
 Mode : SRD
 Test Equipment : ENV216,ESR3
 Receiver Setting : RBW: 9 kHz, Sweep Time: Auto
 Temperature : 15.9°C
 Humidity : 31%
 Atmospheric pressure: 103.0kPa
 Test Engineer : Jack He

	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.693	9.30	20.24	29.54	46.00	-16.46	Average
2	0.693	15.00	20.24	35.24	56.00	-20.76	QP
3	0.968	9.40	20.19	29.59	46.00	-16.41	Average
4	0.968	15.20	20.19	35.39	56.00	-20.61	QP
5	1.795	9.10	20.26	29.36	46.00	-16.64	Average
6	1.795	14.20	20.26	34.46	56.00	-21.54	QP
7	4.792	11.00	20.17	31.17	46.00	-14.83	Average
8	4.792	15.80	20.17	35.97	56.00	-20.03	QP
9	22.807	11.60	20.61	32.21	50.00	-17.79	Average
10	22.807	16.80	20.61	37.41	60.00	-22.59	QP
11	29.116	13.40	20.70	34.10	50.00	-15.90	Average
12	29.116	18.70	20.70	39.40	60.00	-20.60	QP

RADIATED EMISSIONS**Environmental Conditions & Test Information**

Test Item:	RADIATED EMISSIONS				
	9kHz - 30MHz	30MHz - 1 GHz	1 GHz - 18 GHz	18 GHz - 40 GHz	40 GHz - 100 GHz
Test Date:	2026-01-13	2026-01-13	2026-01-12	2026-01-12 to 2026-01-26	2026-01-12 to 2026-01-26
Temperature:	15.3 °C	15.3 °C	16.1 °C	16.1-21.6 °C	16.1-21.6 °C
Relative Humidity:	39 %	39 %	41 %	41-51%	41-51%
ATM Pressure:	102.1 kPa	102.1 kPa	102.5 kPa	102.5-102.6. kPa	102.5-102.6. kPa
Test Result:	Pass	Pass	Pass	Pass	Pass
Test Engineer:	Scarf Yang	Scarf Yang	Destine Hu	Hugh Wu	Hugh Wu


Test Item:	RADIATED EMISSIONS				
	Fundamental and band edge Test	/	/	/	/
Test Date:	2026-01-21 to 2026-01-26	/	/	/	/
Temperature:	20.6-21.6°C	/	/	/	/
Relative Humidity:	47-51 %	/	/	/	/
ATM Pressure:	101.4-102.6 kPa	/	/	/	/
Test Result:	Pass	/	/	/	/
Test Engineer:	Hugh Wu	/	/	/	/

Test Result: Compliant*EUT operation mode: Transmitting**After pre-scan in the X, Y and Z axes of orientation, the worst case X axes is below:*


9 kHz-30MHz: (Transmitting in maximum output power channel (High channel))

Parallel (worst case):

9 kHz-150 kHz



150 kHz -30 MHz



Project No. RKSA260104001
Date: 13.JAN.2026 16:54:44

Tester: Scarf Yang

Project No. RKSA260104001
Date: 13.JAN.2026 16:54:44

Tester: Scarf Yang

9 kHz-150 kHz:


Frequency (MHz)	Corrected Amplitude (dBμV/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dBμV/m @ 3m)	Margin (dB)
0.010128	46.53	PK	-0.51	127.49	80.96
0.025356	50.52	PK	-0.59	119.52	69.00
0.029586	46.18	PK	-0.61	118.18	72.00
0.034662	46.42	PK	-1.36	116.81	70.39

150 kHz-30 MHz:

Frequency (MHz)	Corrected Amplitude (dBμV/m) @3m	Detector PK/QP/Ave.	Corrected Factor (dB/m)	Limit (dBμV/m @ 3m)	Margin (dB)
0.150000	49.08	PK	-11.34	104.08	55.00
1.344000	41.29	PK	-28.75	65.04	23.75
4.388700	39.74	PK	-31.97	69.54	29.80
14.179500	30.94	PK	-33.12	69.54	38.60

30 MHz - 1 GHz: (Transmitting in maximum output power channel (High channel))**Common Information**

Project No: RKSA260104001
EUT Model: K140PLUS
Test Mode: Transmitting in SRD mode
Standard: FCC Part 15.249
Test Equipment: ESCI, JB3, 310N
Receiver Setting: RBW: 100 kHz, VBW: 300 kHz, Sweep Time: Auto
Temperature: 15.3°C
Humidity: 39%
Barometric Pressure: 102.1kPa
Test Engineer: Scarf Yang
Test Date: 2026/1/13

**Critical_Freqs**

Frequency (MHz)	MaxPeak (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
30.363750	28.40	40.00	11.60	H	-5.0
60.918750	17.81	40.00	22.19	V	-17.1
121.058750	23.14	43.50	20.36	V	-10.9
180.835000	24.77	43.50	18.73	H	-13.0
494.872500	28.59	46.00	17.41	H	-5.5
896.210000	35.33	46.00	10.67	V	1.0


1 GHz - 18 GHz

Low Channel

Common Information

Project No.: RKSA260104001
EUT Model: K140PLUS
Test Mode: Transmitting
Standard: FCC Part 15.249& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 16.1℃
Humidity: 41%
Atmospheric Pressure: 102.5kPa
Test Engineer: Destine Hu
Test Date: 2026/1/12

Full Spectrum



Critical_Freqs


Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2139.000000	---	20.11	54.00	33.89	H	-9.9
2139.000000	31.03	---	74.00	42.97	H	-9.9
5950.400000	---	36.14	54.00	17.86	V	-0.7
5950.400000	47.65	---	74.00	26.35	V	-0.7
8595.600000	---	42.03	54.00	11.97	V	4.7
8595.600000	52.75	---	74.00	21.25	V	4.7
13988.000000	---	45.62	54.00	8.38	H	11.1
13988.000000	57.16	---	74.00	16.84	H	11.1
14447.000000	---	47.02	54.00	6.98	H	11.9
14447.000000	56.45	---	74.00	17.55	H	11.9
17762.000000	52.61	---	74.00	21.39	V	11.1
17762.000000	---	46.12	54.00	7.88	V	11.1

Middle Channel

Common Information

Project No.: RKSA260104001
EUT Model: K140PLUS
Test Mode: Transmitting
Standard: FCC Part 15.249& FCC Part 15.205& FCC Part 15.209
Test Equipment: ESU40,3115,PAM-0118P
Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
Temperature: 16.1°C
Humidity: 41%
Atmospheric Pressure: 102.5kPa
Test Engineer: Destine Hu
Test Date: 2026/1/12

Full Spectrum



Critical_Freqs


Frequency (MHz)	MaxPeak (dB µ V/m)	Average (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Pol	Corr. (dB/m)
1394.400000	---	19.80	54.00	34.20	V	-13.8
1394.400000	30.92	---	74.00	43.08	V	-13.8
4692.400000	43.20	---	74.00	30.80	V	-3.7
4692.400000	---	32.79	54.00	21.21	V	-3.7
8667.000000	52.24	---	74.00	21.76	H	4.7
8667.000000	---	42.00	54.00	12.00	H	4.7
14946.800000	56.42	---	74.00	17.58	H	10.5
14946.800000	---	45.30	54.00	8.70	H	10.5
17031.000000	---	46.98	54.00	7.02	V	10.9
17031.000000	53.45	---	74.00	20.55	V	10.9
17830.000000	53.83	---	74.00	20.17	H	11.3
17830.000000	---	45.95	54.00	8.05	H	11.3

High Channel

Common Information

Project No.: RKSA260104001
 EUT Model: K140PLUS
 Test Mode: Transmitting
 Standard: FCC Part 15.249& FCC Part 15.205& FCC Part 15.209
 Test Equipment: ESU40,3115,PAM-0118P
 Receiver Setting: RBW: 1MHz, VBW: 3MHz, Sweep Time: Auto
 Temperature: 16.1°C
 Humidity: 41%
 Atmospheric Pressure: 102.5kPa
 Test Engineer: Destine Hu
 Test Date: 2026/1/12

Full Spectrum




Critical_Freqs

Frequency (MHz)	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Pol	Corr. (dB/m)
2856.400000	---	22.47	54.00	31.53	V	-8.5
2856.400000	34.10	---	74.00	39.90	V	-8.5
6008.200000	---	35.76	54.00	18.24	V	-0.6
6008.200000	48.16	---	74.00	25.84	V	-0.6
8537.800000	---	42.01	54.00	11.99	V	4.7
8537.800000	52.41	---	74.00	21.59	V	4.7
14181.800000	---	45.82	54.00	8.18	H	11.4
14181.800000	56.74	---	74.00	17.26	H	11.4
14521.800000	---	47.09	54.00	6.91	H	11.9
14521.800000	54.69	---	74.00	19.31	H	11.9
17850.400000	53.43	---	74.00	20.57	H	11.4
17850.400000	---	46.09	54.00	7.91	H	11.4


18 GHz - 40 GHz:

Low Channel

Horizontal



Vertical




Project No :RKSA260104001 Tester :Hugh Wu
Date: 12.JAN.2026 17:40:24


Project No :RKSA260104001 Tester :Hugh Wu
Date: 12.JAN.2026 18:14:05

Middle Channel

Horizontal



Vertical




Project No :RKSA260104001 Tester :Hugh Wu
Date: 12.JAN.2026 18:46:24


Project No :RKSA260104001 Tester :Hugh Wu
Date: 12.JAN.2026 19:20:03

High Channel

Horizontal



Vertical



Project No :RKSA260104001 Tester :Hugh Wu
Date: 26.JAN.2026 16:58:27

Project No :RKSA260104001 Tester :Hugh Wu
Date: 26.JAN.2026 16:26:02

18 GHz - 40 GHz

Frequency	MaxPeak	Average	Limit	Margin	Pol	Corr.
(GHz)	(dBμV/m)	(dBμV/m)	(dBμV/m)	(dB)		(dB/m)
Low Channel						
32.173	---	51.95	60	8.05	V	22.19
34.994	63.72	---	80	16.28	V	26.99
32.173	---	52.02	60	7.98	H	22.19
34.782	63.76	---	80	16.24	H	26.63
Middle Channel						
32.138	---	51.91	60	8.09	V	22.13
31.997	64.13	---	80	15.87	V	21.89
32.138	---	52.1	60	7.9	H	22.13
35.276	63.78	---	80	16.22	H	27.47
High Channel						
32.032	---	51.78	60	8.22	V	22.08
32.244	63.59	---	80	16.41	V	26.15
32.032	---	51.73	60	8.27	H	27.23
32.067	63.93	---	80	16.07	H	22.01

Note: Extrapolation factor of 20dB/decade from 3m to 1.5m

Distance extrapolation factor = $20 \log(\text{specific distance [3m]}/\text{test distance [1.5m]})$ dB

Limit = Specific limits(dB μ V/m) + distance extrapolation factor (6 dB)

40 GHz - 50 GHz:

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Pol	Corr. (dB)
Low Channel						
48.02	53.58	---	97.5	43.92	H	25
48.02	54.17	---	97.5	43.33	V	25
Middle Channel						
48.22	54.83	---	97.5	42.67	H	25
48.22	54.51	---	97.5	42.99	V	25
High Channel						
48.42	54.49	---	97.5	43.01	H	25
48.42	54.62	---	97.5	42.88	V	25

50 GHz - 75 GHz:

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Pol	Corr. (dB)
Low Channel						
66.13	58.43	---	83.54	25.11	H	36
66.13	58.67	---	83.54	24.87	V	36
Middle Channel						
59.58	59.03	---	83.54	24.51	H	36
59.58	58.95	---	83.54	24.59	V	36
High Channel						
61.58	58.38	---	83.54	25.16	H	36
61.58	58.42	---	83.54	25.12	V	36

Note: The limit on the peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. Therefore, when the measured peak level of the emissions is at least 20 dB below the peak emission limit, there's no need to record the measured AV level of the emissions.

Extrapolation factor of 20dB/decade from 3m to 1.0m

Distance extrapolation factor = $20 \log(\text{specific distance [3m]}/\text{test distance [1m]})$ dB

Limit = Specific limits(dBμV/m) + distance extrapolation factor (9.54dB)

75 GHz - 100 GHz:

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Pol	Corr. (dB)
Low Channel						
85.92	61.8	---	83.54	21.74	H	45
85.92	61.25	---	83.54	22.29	V	45
Middle Channel						
85.88	61.39	---	83.54	22.15	H	45
85.88	61.51	---	83.54	22.03	V	45
High Channel						
78.08	62.74	---	83.54	20.8	H	45
78.08	62.88	---	83.54	20.66	V	45

Note: The limit on the peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. Therefore, when the measured peak level of the emissions is at least 20 dB below the peak emission limit, there's no need to record the measured AV level of the emissions.

Extrapolation factor of 20dB/decade from 3m to 1.0m


Distance extrapolation factor = $20 \log(\text{specific distance [3m]}/\text{test distance [1.0m]})$ dB

Limit = Specific limits(dBμV/m) + distance extrapolation factor (9.54dB)

Fundamental and band edge Test

Fundamental


Horizontal



Low Channel

Vertical

Fundamental



Project No : RKSA260104001
Date: 21.JAN.2026 15:12:35


Tester :Hugh Wu

Project No : RKSA260104001
Date: 21.JAN.2026 15:50:08

Tester :Hugh Wu

Fundamental


Horizontal



Middle Channel

Vertical

Fundamental



Project No : RKSA260104001
Date: 21.JAN.2026 17:39:03


Tester :Hugh Wu

Project No : RKSA260104001
Date: 21.JAN.2026 18:10:15

Tester :Hugh Wu

Fundamental


Horizontal



High Channel

Vertical

Fundamental



Project No : RKSA260104001
Date: 26.JAN.2026 17:48:44

Tester :Hugh Wu

Project No : RKSA260104001
Date: 26.JAN.2026 18:20:57

Tester :Hugh Wu

Note: The unit of limit and test level are dBμV/m.

Fundamental:

Frequency (GHz)	Pol	Average Field strength of fundamental@1.5M (dBuV/m)	Peak Field strength of fundamental @1.5M (dBuV/m)	Average Field strength of fundamental@ 3M (dBuV/m)	Peak Field strength of fundamental @3M (dBuV/m)	Limit@3M (dBuV/m)	Margin
24.01	H	---	104.46	---	98.46	127.96	29.5
	H	103.96	---	97.96	---	107.96	10
	V	---	104.15	---	98.15	127.96	29.81
	V	103.54	---	97.54	---	107.96	10.42
24.11	H	---	104.48	---	98.48	127.96	29.48
	H	103.56	---	97.56	---	107.96	10.4
	V	---	105.22	---	99.22	127.96	28.74
	V	104.67	---	98.67	---	107.96	9.29
24.21	H	---	101.02	---	95.02	127.96	32.94
	H	100.45	---	94.45	---	107.96	13.51
	V	---	101.38	---	95.38	127.96	32.58
	V	100.78	---	94.78	---	107.96	13.18

Band Edge:

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Corr. (dB/m)
Low channel							
23.999	69.1	---	80	10.9	150	H	9.4
23.999	---	58.37	60	1.63	150	H	9.4
23.999	65.12	---	80	14.88	150	V	9.5
24.000	---	56.35	60	3.65	150	V	9.5
High Channel							
24.251	70.34	---	80	9.66	150	H	9.4
24.251	---	59.01	60	0.99	150	H	9.4
24.251	68.93	---	80	11.07	150	V	9.5
24.251	---	58.04	60	1.96	150	V	9.5

Note: Extrapolation factor of 20dB/decade from 3m to 1.5m

Distance extrapolation factor = $20 \log (\text{specific distance [3m]}/\text{test distance [1.5m]})$ dB

Limit = Specific limits(dBμV/m) + distance extrapolation factor (6 dB)

Maximum Field Strength of Fundamental (specific distance [3m]) = Peak Field strength of fundamental (test distance [1.5m]) - distance extrapolation factor (6 dB), So Maximum Field Strength of Fundamental is 99.22 dBμV/m at 3m.

20 dB BANDWIDTH TESTING


Environmental Conditions & Test Information

Test Date:	2026-01-26
Temperature:	21.6 °C
Relative Humidity:	51 %
ATM Pressure:	102.6 kPa
Test Result:	Pass
Test Engineer:	Hugh Wu

Test Result: Compliant.

Test Mode: Transmitting

Mode	20 dB BANDWIDTH (MHz)	F _L (GHz)	Limit (GHz)	F _H (GHz)	Limit (GHz)
Sweep	237.981	24.0071	24	24.2450	24.25



Project No :RKSA260104001 Tester :Hugh Wu
Date: 26 JAN.2026 22:05:20

EUT PHOTOGRAPHS

Please refer to the attachment EXHIBIT A - EUT EXTERNAL PHOTOGRAPHS, EXHIBIT B - EUT INTERNAL PHOTOGRAPHS.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment EXHIBIT C - TEST SETUP PHOTOGRAPHS.

Declarations

1. The laboratory is not responsible for the authenticity of any information provided by the applicant. Information from the applicant that may affect test results is marked with “★”.
2. The test data was only valid for the test sample(s).
3. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.
4. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
5. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor $k=2$ with the 95.45% confidence interval.

*******END OF REPORT*******