XbotGo Remote Controller

User Manual

Model: Xbotto-RC1
Remote Control Range: Approximately 10 meters
Quick Start Guide
Remote Control Function
Specifications

We sincerely thank you for choosing XbotGo!

To ensure your safety and maximum performance, please read this manual carefully before using and keep the manual for future reference. If you encounter any issues during use, please refer to the troubleshooting section in the manual or contact our customer service team. We will provide professional support.

- **Warning:**
  - Do not disassemble, drop, or expose the product to extreme conditions. Failure to comply may result in fire, electric shock, or other serious injuries. These forms of misuse may void warranty and cancel the factory warranty.
  - **Comply with local laws and regulations:**
    - Do not use the product in areas where the use of remote controllers, Bluetooth devices, and wireless devices is prohibited or restricted (hospitals, theaters, aircrafts, and gasoline stations), and strictly prohibited in aircrafts.

Remote Controller Specifications

Model	Xbotto-RC1
Battery Model	CR2032
Operational Frequency Range	2.4G
Temperature	0℃ - 40℃ (32℉ - 104℉)

Quick Start Guide

1. Remote Pairing: Before first use, please ensure the remaining power of the remote control is sufficient. Press and hold the pairing button on the remote control for 3 seconds to enter the pairing mode. Then, press the function button (for 5 seconds) to connect and complete the pairing.
2. OTA Updating: A green light flashes when the function button is held for 5 seconds. Release the button to initiate the OTA update process.

- Upon XbotGo APP start-up, please wait approximately 30 seconds for the Xbotto-DFM to pair. After this, connection is established. No prior connection setup is required for subsequent uses. Simply turn on the Xbotto-DFM and the remote will automatically connect.
- **Functions of the Remote Controller:**
  - Pairing: Hold the pairing button for 3 seconds to enter pairing mode. Then, press the function button (for 5 seconds) to complete the pairing. Alternatively, pairing can also be initiated via the Xbotto-DFM's function button. Refer to the Xbotto-DFM's quick start guide for more details.
  - Function Activation: Press the function button to activate the corresponding function. Refer to the Xbotto-DFM's quick start guide for more details.

Xbotto-RC1 Remote Controller

1. Power Button
2. Function Selection Button
3. Confirm Button
4. Directional Button (Up/Down/Left/Right)
5. Battery Compartment

Buttons and Functions

Buttons are used to get familiar with the remote controller.

Camera Function

Press the Camera Function button to switch to camera mode, press the confirm button to capture photos and record videos.

- **On the remote controller:**
  - Short press the Confirm button: Pressing once starts camera mode. Pressing again ends the camera mode and saves the current photo or video.
  - Long press the Confirm button: Hold for 3 seconds to enter camera mode. Release the button to end camera mode and save the current photo or video.
- **On the APP UI:**
  - Short press the Confirm button: Pressing once starts the 5-second countdown for photo capture. Pressing again ends the camera mode and saves the current photo or video.
  - Long press the Confirm button: Hold for 3 seconds to enter camera mode. Release the button to end camera mode and save the current photo or video.

Photo Function

Press the Function button twice to switch to the photo mode.

In photo mode, press the confirm button to take photos.

Steering Function

Press the Function button three times to switch to the steering mode.

Press the up, down, left, and right directional buttons to control the gimbal or the corresponding steering.

Main Function (Available only during camera function mode)

Hold down the Confirm button for 3 seconds to enter the main menu. Use the directional buttons to navigate through the menu options and the confirm button to confirm your selection.

Pressing the confirm button on the remote controller, there will be two different outcomes, depending on the current mode: If the current mode is **not** the **recording** function, it **pauses**; **the** video recording **stops**. If the current mode is the **recording** function, it **ends**; **the** video recording **stops** and **saves**.

Highlights: Link the Xbotto-Pro's Apple Watch Highlight Record Button.

Note

If the remote controller is not functioning, light flashes, the buzzer sounds, or if the APP displays errors, automatic reconnection failures, please follow the prompts on the APP to resolve the operation.

Battery

The remote controller is equipped with a CR2032 button battery.

Note:

- Ensure proper performance.
- Avoid short circuits, disassembly, or exposure to high temperatures.
- Dispose of the battery in accordance with local regulations. For more details, please consult the manufacturer's guidelines.

Battery Disposal:

- Do not dispose of the remote controller as general municipal waste. Please refer to local regulations for proper battery disposal.

Notes on Remote Controller

- The remote controller's signal range is approximately 10 meters. Ensure the device is within this range for optimal signal strength. The light will flash upon pairing completion.

RC1

XbotGo Remote Controller

遠隔操作器 ユーザーガイド

Model: Xbotto-RC1
遠隔操作範囲: 約10メートル
クイックスタートガイド
遠隔操作機能
仕様

遠隔操作器 ユーザーガイド をご購入いただきまして、誠にありがとうございます。

ご使用前に必ずこの取扱説明書をお読みいただき、安全を確保し、最大限のパフォーマンスを発揮するために、この説明書を保管してください。ご使用中に問題が発生した場合は、説明書のトラブルシューティングセクションを参照するか、カスタマーサービスにご連絡ください。当社の専門サポートをご提供いたします。

- 警告:
  - 分解、落下、または極端な環境にさらされないでください。従わない場合、火災、感電、または深刻な怪我を引き起こす可能性があります。これらの誤用は保証を無効にし、工場保証を解除する可能性があります。
  - **現地の法律および規制を遵守してください:**
    - 遠隔操作器、Bluetooth デバイス、および無線デバイスの使用が禁止または制限されている場所（病院、劇場、航空機、および給油所）、および航空機内では厳禁です。

遠隔操作器の仕様

モデル	Xbotto-RC1
ボタン電池の型番	CR2032
動作周波数帯	2.4G
動作温度	0℃ - 40℃ (32℉ - 104℉)

クイックスタートガイド

1. 遠隔ペアリング: 初回使用前に、遠隔操作器の残量が十分であることを確認してください。遠隔操作器のペアリングボタンを3秒間長押しして、ペアリングモードに入ります。次に、機能ボタンを（5秒間）押して接続を完了します。
2. 遠隔操作器の OTA アップデート: 機能ボタンを5秒間長押しすると、緑色の光が点滅します。ボタンを離すと、OTA アップデートが開始されます。

- XbotGo アプリの起動後、Xbotto-DFM のペアリングには約30秒かかります。この時間が経過すると、接続が確立されます。以降の使用では、事前の接続設定は不要です。Xbotto-DFM の電源を入れるだけで、遠隔操作器は自動的に接続されます。
- **遠隔操作器の機能:**
  - ペアリング: 遠隔操作器のペアリングボタンを3秒間長押しして、ペアリングモードに入ります。次に、機能ボタンを（5秒間）押して接続を完了します。または、Xbotto-DFM の機能ボタンを使用してペアリングを開始することもできます。詳細については、Xbotto-DFM のクイックスタートガイドを参照してください。
  - 機能アクティベーション: 機能ボタンを押して、対応する機能をアクティベートします。詳細については、Xbotto-DFM のクイックスタートガイドを参照してください。

Xbotto-RC1リモートコントローラー

1. 電源ボタン
2. 機能選択ボタン
3. 確定ボタン
4. 方向ボタン（上/下/左/右）
5. バッテリーカバーを開く

ボタンと機能

ボタンを使用して遠隔操作器に慣れてください。

カメラ機能

カメラ機能モードに切り替えるには、カメラ機能ボタンを押します。確定ボタンを押して写真を撮影したり、動画を録画したりします。

- **リモコンの場合:**
  - 短押し: 1回押すとカメラモードが開始されます。もう一度押すとカメラモードが終了し、現在の写真または動画が保存されます。
  - 長押し: 3秒間長押しするとカメラモードが開始されます。3秒間長押しすると、カメラモードが終了し、現在の写真または動画が保存されます。
- **APP UI:**
  - 短押し: 確定ボタンを短押しすると、写真撮影のための5秒カウントダウンが開始されます。もう一度押すとカメラモードが終了し、現在の写真または動画が保存されます。
  - 長押し: 確定ボタンを長押しすると、カメラモードが開始されます。3秒間長押しすると、カメラモードが終了し、現在の写真または動画が保存されます。

写真機能

機能ボタンを2回押して写真機能に切り替えます。

写真モードでは、確定ボタンを押して写真を撮影します。

操縦機能

機能ボタンを3回押して操縦モードに切り替えます。

方向ボタンを押して、ジンバルまたは対応する操縦を制御します。

メイン機能（カメラ機能モードでのみ利用可能）

確定ボタンを3秒間長押しして、メインメニューに入ります。方向ボタンを使用して機能を閲覧し、確定ボタンを押して選択します。

リモコンの確定ボタンを押すと、現在のモードによって2つの結果が発生します: 現在のモードが**録画**機能**以外**の場合、**一時停止**します。**録画**機能の場合、**終了**します。

ハイライト: XbotGo Pro の Apple Watch ハイライト記録ボタンとリンクします。

注意

リモコンが正常に作動しない場合、点滅する場合、ブザーが鳴る場合、または APP に表示されるエラーが発生した場合、自動再接続に失敗した場合、APP の指示に従って操作を解決してください。

電池

リモコンには CR2032 ボタン電池が搭載されています。

注意事項:

- 適切な動作を確保します。
- 短絡、分解、または高温への曝露を避けます。
- 廃棄については、地域の規制に従ってください。詳細については、メーカーのガイドラインを参照してください。

廃棄物処理:

- リモコンを一般廃棄物として廃棄しないでください。地域の規制を参照して適切な廃棄を行ってください。

リモコンに関する注意事項

- リモコンの信号範囲は約10メートルです。最適な信号強度を確保するには、デバイスがこの範囲内にあることを確認してください。ペアリングが完了すると、ライトが点滅します。

FCC Warnning:

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection againstharmful interference in a residential installation. This equipment generates, uses and can radiateradio frequency energy and, if not installed and used in accordance with the instructions, maycause harmful interference to radio communications. However, there is no guarantee thatinterference will not occur in a particular installation. If this equipment does cause harmfulinterference to radio or television reception, which can be determined by turning the equipmentoff and on, the user is encouraged to try to correct the interference by one or more of thefollowing measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Caution: Any changes or modifications to this device not explicitly approved by manufacturer could void your authority to operate this equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1)This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 0cm between the radiator and your body.

ISED Statement

- English: This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions:

(1) This device may not cause interference.

(2) This device must accept any interference, including interference that may cause undesired operation of the device.

- French:Cet appareil contient des émetteurs/récepteurs exempts de licence qui sont conformes aux CNR exempts de licence d'Innovation, Sciences et Développement économique Canada. Le fonctionnement est soumis aux deux conditions suivantes :

(1) Cet appareil ne doit pas causer d'interférences.

(2) Cet appareil doit accepter toute interférence, y compris les interférences susceptibles de provoquer un fonctionnement indésirable de l'appareil.

This device meets the exemption from the routine evaluation limits in section 2.5 of RSS 102 and compliance with RSS 102 RF exposure, users can obtain Canadian information on RF exposure and compliance.

cet appareil est conforme à l'exemption des limites d'évaluation courante dans la section 2.5 du cnr - 102 et conformité avec rss 102 de l'exposition aux rf, les utilisateurs peuvent obtenir des données canadiennes sur l'exposition aux champs rf et la conformité.

This equipment complies with Canada radiation exposure limits set forth for an uncontrolled environment.

This equipment should be installed and operated with minimum distance 0cm between the radiator & your body.

Cet équipement est conforme Canada limites d'exposition aux radiations dans un environnement non contrôlé.

Cet équipement doit être installé et utilisé avec une distance minimale de 0 cm entre le radiateur et votre corps.