

SPECIFICATION FOR APPROVAL

CUSTOMER :	
PART NAME :	贴片四螺旋WiFi 2.4G (3.2mm*1.6mm*0.8mm)
PART NO. :	2.4G
DZZ NO. :	D04-0876-R0A
REV. :	

	MANUFACTURERR SIGNATURE	CUSTOMER SIGNATURE
APPROVED BY:		
DATE:		

Shenzhen be-comfortable technology.co.,LTD

深圳市得自在科技有限公司

Address: No.1606,Build C6,HengFeng industrial city,xixiang
street,baoan district,Shenzhen

shanghai mengju technology co., LTD

上海市盟钜科技有限公司

103B, Build10, No.198 Zhang Heng Road , Pudong New
Area,Shanghai

CONTENTS

Item	Description	Page
1.	天线规格表.....	3
2.	修订记录	4
3.	成品图	5
4.	环境要求	6
5.	RF参数	7~10
6.	图纸.....	11
7.	包装.....	12

PCB Antenna Assembly

Specification(With housing)

1.Electrical Properties

- 1.1 Frequecy range.....2.4G~2.5G
- 1.2 Impedance.....50Ω Norminal
- 1.3 Antenna Type Monopole
- 1.4 VSWR.....<2
- 1.5 Efficiency≥50%
- 1.6 Gain(Peak).....0dBi
- 1.7 Radiation.....Omni
- 1.8 Polarization.....Linear
- 1.9 Admitted Power.....1W

2.Physical Properties

- 2.1 Dimensions.....3.2mm*1.6mm*0.8mm
- 2.2 Connector Type.....SMT
- 2.3 Working Temperature.....-20°C~+65°C
- 2.4 Storage Temperature.....-30°C~+75°C

Antenna Design for 贴片四螺旋WiFi天线


V1.00

Document Number	NDX-20200108
1st Released Date	08/01/2020
Author	Huiping Feng
Review By	Zhongyi Zhao


Revised History

[illegible]

1.1 Mechanical instruction




1.2 Antenna clearance size requirement




2. Analyzer Measurement

2.1 Ant 四螺旋wifi天线 S11







3. Gain & Patterns test results

3.1 Measurement setting






3.2 2D Patterns (2.4G)



4 3D Peak Gain & Efficiency(2.4G)

Frequency (GHz)	Efficiency (%)	Peak Gain (dBi)
2400	55.31	1.71
2410	55.52	1.63
2420	55.57	1.69
2430	56.39	1.66
2440	56.99	1.67
2450	57.78	1.68
2460	56.69	1.75
2470	55.54	1.69
2480	54.51	1.82
2490	53.26	1.79
2500	53.97	1.83



线路左右交错

备注:

1. PCB材料: 电解铜1/20Z, 双面板, FR4
2. 镀点处理: 镀金, 镀金厚度0.013um
3. 表面处理: 黑油, 尺寸: 长*宽*厚度
4. 包装方式: 载带包装
5. 丝印字体: 掏金
6. 未标公差尺寸, 模具冲出尺寸公差为±0.1, 寸公差为±0.05, 标重点的孔公差为±0.05.
7. 涂 斜线 为铜箔线路, 涂 点阵 为穿孔, 涂 黄色 的为镀点区域, 涂 白色 的为基材区域
8. 安规要求: ROHS六项
9. 品质要求按照得自在《IQC进料检验规范》执行

SHEN ZHEN Be Comfortable CO., LTD		深圳得自在科技有限公司	
四螺旋贴片天线		2020-1-8	
Project	Part Name	Date	
Part No.	N12-4878-R0A	Designed by	张小东
Material	PCB	Checked by	冯惠平
DWG No.	N12-4878-R0A	Approved by	
Unit	mm	Scale	1:1
Rev		Rev	A

产品包装规范

日期：2020.9.25

page: 1 of 1

成品名称：四壁螺旋天线	版本：A
客户：	
INSPECTION DRAWING TAKING OUT DIRECTION COVER TAPE(上带) (外加保护带) REEL (卷盘) CARRIER (下带) 前段空16PCS 中间段产品300PCS 尾部空16PCS TAKING OUT DIRECTION 三角板 物料标签 干燥剂 16盘 2000PCS 防水袋 包装长度5100CM 外箱 350 350 8 通孔胶 物料标签 长胶长度5100CM	
Notes: 1. 每卷前空16PCS, 后空16PCS, 中间包装3000PCS±2 品, 尾部用美纹胶纸封住, 美纹胶长度为18"20cm 2. 外圈再卷一圈保护带, 保护带最后重叠50MM MIN. 同样用18"20cm长美纹胶将其封住. 3. 每个卷盘上贴一张物料标签 (按 要求填写). 4. 每10卷盘装入1个外箱; 外箱角 落用三角板填充; 用透明胶将外箱封口 5. 将标签(按要求打印好的)贴在 纸箱侧表上方, 6. 尾数箱用纸壳或其它填充物填 满空间, 或将纸 箱割小至刚好表下, 7. 在搬运过程中要轻柔轻放, 8. 在运输中不可堆放过多, 不可有 重压现象. 注: 客户特殊要求请参照业务的出货资料, 以实际包装为准;	

批准：

确认 赵中义

拟制：殷正军